

# Creating a Library of React Components using Create React App

April 9th 2020

★ 67,070 reads



11

Audio Presented by plivo

Speed: 1x

Read by: D

**@aakashns**

Aakash N S



**UPDATE:** You can use the npm package `create-component-lib` to automate all the steps described in this blog post.

## create-component-lib

Create React App is easily the best tool for creating and developing React applications. With a little bit of work, it can also be used to create React components that can be published to npm and used in other React applications. Here's what you need to do:

1. Create a new project using `create-react-app` :

```
create-react-app simple-component-library
```

2. Delete all the files inside `src/`, and create a new `index.js` file with some starter code:

```
import React from "react";
import ReactDOM from "react-dom";

ReactDOM.render(<div>Hello world</div>, document.getElementById("root"));
```

3. Create a new folder `src/lib` and place your React components inside it. `src/lib` will serve as the root folder of the module published to `npm`. Write the code for an example component:

```
import React from "react";
import "./TextInput.css";

const TextInput = ({ type = "text", label, value, onChange }) => (
  <div className="simple-form-group">
    {label} && <label className="simple-text-label">{label}</label>
    <input
      type={type}
      className="simple-text-input"
      value={value}
      onChange={e => onChange} && onChange(e.target.value)}
    />
  </div>
);

export default TextInput;
```

Styling can be done inline, or in separate CSS files:

```
.simple-form-group {
  margin-bottom: 1rem;
}

.simple-text-label {
  display: block;
  color: red;
}
```




```
import React from 'react';
import { render } from "react-dom";
import { TextInput } from "../lib";

const App = () => (
  <div style={{ width: 640, margin: "15px auto" }}>
    <h1>Hello React</h1>

    <TextInput label="Email Address" placeholder="name@example.com" />
  </div>
);
```

```
    </div>
  );

  render(<App />, document.getElementById("root"));
```



Run `npm start` and navigate to `http://localhost:3000` to view the result.

It works (duh!)

Tip: Use `react-live` to create a live-editable documentation site!

5. Install `babel-cli` using the command `npm i babel-cli --save-dev` and create a file `.babelrc` in the root of the project with the following con

Discover Anything 🔍

🕒

Start Writing

Log in

🔔

☰

🕒 HACKERNOON

🔧

Creating a Library of React Components using Create React App by @aakashns

▶


📄

```
"presets": [
  ["react-app", { "absoluteRuntime": false }]
]
```

◀

6. Replace the `build` script inside `package.json` with the following:

```
"build": "rm -rf dist && NODE_ENV=production babel src/lib --out-dir dist --copy-files --ignore __tests__,spec.js,test.js,__snapshots__"
```



The command `npm run build` will now transpile the code inside `src/lib` (ignoring tests and snapshots) into the folder `dist`.

7. Remove the line `"private": true` from `package.json`. Also remove `react-scripts`, `react` and `react-dom` from dependencies, and move their `devDependencies`. Additionally, you can also add `react` and `react-dom` to `peerDependencies`.

8. To prepare for publishing, add the following lines to `package.json`:



```
"main": "dist/index.js",
"module": "dist/index.js",
"files": [ "dist", "README.md" ],
"repository": {
  "type": "git",
  "url": "URL_OF_YOUR_REPOSITORY"
}
```

9. Remove the default `README.md` file, and create a new one with some information about the library.

```
# simple-component-library
A library of React components created using `create-react-app`.## Installation
Run the following command:
`npm install simple-component-library`
```


10. Publish to `npm`!

```
npm run publish
```

And that's it! Now you can install the library with the command `npm install simple-component-library` and use it in any project created using `create-react-app`. Here's the full code for this article:

You can clone the repository and use it as a starting point to skip some of the steps. Hope it helps!

11    



by Aakash N S [@aakashns](#)

[Read my stories](#)

## TAGS

[#javascript](#)[#react](#)[#front-end-development](#)[#open-source](#)[#coding](#)[#nodejs](#)[#programming](#)[#beginners](#)

## RELATED STORIES



### Training an Image Classifier From Scratch in 15 Minutes

Published at Apr 09, 2020 by aakashns [#machine-learning](#)



### My Top 5 Best Practices for ReactJs

Published at Mar 14, 2022 by sachinchaurasiya [#javascript](#)



### Cache API Calls in JavaScript by Memoizing Promises

Published at Mar 14, 2022 by aldrinvincent [#javascript](#)




### Javascript Cheatsheet: Spread Operators


Published at Mar 14, 2022 by imsabir [#javascript](#)



### What is all the Fuss about Full Stack Developers?

Published at Mar 14, 2022 by max101 [#developer](#)





# What it Takes to Create a Simple JavaScript Table in 2022

Published at Mar 14, 2022 by matkainer #technology

## THIS ARTICLE WAS FEATURED IN...

[Daveceddia](#)[Github](#)[Npmjs](#)[Dev](#)[Stackoverflow](#)[Cometchat](#)[Qiita](#)[Hatenablog](#)

Join  
HackerNoon

Curated Stories. |

## THE HACKERNOON NEWSLETTER

Quality Weekly Reads About Technology Infiltrating Everything

Subscribe<sup>free</sup>

☐ Yes, I agree to receive emails about tech eating the world.



## ABOUT

[Careers](#)  
[Contact](#)  
[Cookies](#)  
[Emails](#)  
[Help](#)  
[Privacy](#)  
[Terms](#)

## READ

[Archive](#)  
[Leaderboard](#)  
[Noonification](#)  
[Signup](#)  
[Tech Brief](#)  
[Tech Tags](#)  
[Top Stories](#)

## WRITE

[Distribution](#)  
[Editor Tips](#)  
[Guidelines](#)  
[New Story](#)  
[Perks](#)  
[Prompts](#)  
[Why Write](#)

## SPONSOR

[Billboard](#)  
[Brand Publishing](#)  
[Case Studies](#)  
[Contests](#)  
[Niche Marketing](#)  
[Newsletter](#)  
[Writing Contests](#)