

## Numbering Rule

The numbering of footnotes can be restarted either on each page, each section or never. This behavior is determined by the document's attribute FootnoteNumberingRule.

### Restart each Page

The footnote numbering can be restarted on each page. This is the default behavior.

```
\document
[
  FootnoteNumberingRule = RestartPage
]
{
  ...
}
```

### Restart each Section

The footnote numbering can be restarted at each section.

```
\document
[
  FootnoteNumberingRule = RestartSection
]
{
  ...
}
```

### Continuous Numbering

The footnote numbering can be continuous over the whole document.

```
\document
[
  FootnoteNumberingRule = RestartContinuous
]
{
  ...
}
```

## Number Style

The number style of the footnote's reference symbols can be altered. This Behavior is determined by the document's attribute FootnoteNumberStyle.

### Arabic Numbers

The footnotes' numbers can be arabic numbers (1, 2, 3, ...), as done in this document. This is the default behavior.

```
\document
[
FootnoteNumberStyle = Arabic
]
{
...
}
```

### Letters

The footnotes' numbers can be lower case letters (a, b, c, ...) or uppercase letters (A, B, C, ...).

```
\document
[
//Lower case letters for the footnote numbers (a, b, c, ...).
FootnoteNumberStyle = LowercaseLetter

//Use this to achieve upper case letters for the footnote numbers (A, B, C, ...).
//FootnoteNumberStyle = UppercaseLetter
]
{
...
}
```

### Roman Numbers

The footnotes' numbers can be roman numbers written with lower case letters (i, ii, iii, ...) or upper case letters (I, II, III, ...).

```
\document
[
//Lower case roman numbers for the footnotes (i, ii, iii, ...).
FootnoteNumberStyle = LowercaseRoman

//Use this to achieve upper case roman numbers for the footnotes (I, II, III, ...).
//FootnoteNumberStyle = UppercaseRoman
]
{
...
}
```

## Reference Symbol

The footnote's reference symbols can be altered for each footnote or the document's global footnote attributes can be used.

### Using the Document's Footnote Numbering

By default, the reference symbol is defined by the document's attributes described above.

```
\paragraph
{
  This is a footnote using the document's footnote numbering.
  \footnote{Text within the footnote.}
}
```

This is a footnote using the document's footnote attributes <sup>1</sup>.

### Custom Symbol

Each Footnote can use its own Reference symbol. Note that this procedure will not influence footnote counting over the document.

Unlike the sample, you should either always define an individual reference symbol, or never.

```
\paragraph
{
  This is a footnote with an individual symbol
  \footnote[Reference = "*"]{Text within the footnote.}
}
\paragraph
{
  This is a footnote using the document's footnote numbering.
  \footnote{Text within the footnote.}
}
```

This is a footnote with an individual symbol <sup>\*</sup>.

This is a footnote using the document's footnote numbering <sup>3</sup>.

---

<sup>1</sup>Text within the footnote.

<sup>\*</sup>Text within the footnote.

<sup>3</sup>Text within the footnote.

## Location

Footnotes can be placed either at the bottom of the page or directly beneath the page content.

### Bottom of Page

You can place the footnotes at the bottom of the page. This is the default behavior.

```
\documentclass
[
  FootnoteLocation = BottomOfPage
]
{
  ...
}
```

### Beneath Text

You can place the footnotes directly beneath the page content, as done in this document.

```
\documentclass
[
  FootnoteLocation = BeneathText
]
{
  ...
}
```