Table 1 – vLCD_PRINT_STRING Test Plan

TD 4 X	¥7 •4	Table I – VLCD_PKIN I	_STRING	Test Fiai	<u>l</u>	
Test Writer:		Boyd Dilley				
Test Case Name:		LCD Print String	Test ID			Driver Test
		Test	#:			
Description:		Verify operation of	Type:			White Box
		Print String function			X	Black Box
		with LCD display				
Tester Information						
Name of Tester:			Date:			
Hardware Ver:		1.0	Time:			
Setu		Connect STK600 Port_K_ to the LCD board input pins				
p:						
Test	(Test Variable)	Expected Result	Pass	Fail	N/A	Comments
1	Top line	Hello should print on	X			
	Print "Hello"	the top line				
2	Text Wrap Enabled	Should print the	X			
	Print	whole string using				
	"ABCDEFGHIJKL	both the top and				
	MNOPQRSTUVWX	bottom lines				
	YZ"					
3	Text Wrap Disabled	Should print	X			
	Print	Everything except Y				
	"ABCDEFGHIJKL	and Z.				
	MNOPQRSTUVWX					
4	YZ"	TT 11 1 11 1 1	37			
4	Bottom line	Hello should print on	X			
	Print "hello"	the bottom line				
5	Top line	Hello should print on	X			
	Print "Hello"	the top line; and				
	Bottom line	World should print				
	Print "world"	on the bottom line				
6	Print "A"	Should take to	X			
1	Test time	print a single				
		character.			1	
Overall Test Result:			X			Function tested as
						expected, all results
						are a pass