

From Rubbish to Resource: Waste-Stream-Specific Scenario Narratives for the Future of Secondary Raw Material Recovery in the EU

Stewart Charles McDowall^{a*}, Nathalie Körf^b, Carlos Felipe Blanco^{a, c}, and Stefano Cucurachi^a

^a*Institute of Environmental Sciences (CML), Leiden University, P.O. Box 9518, Leiden, 2300RA, South Holland, The Netherlands*

^b*Chair of Circular Economy and Recycling Technology at Technische Universität Berlin, Straße des 17. Juni 135, 10623 Berlin, Germany*

^c*Netherlands Organisation for Applied Scientific Research (TNO), Princetonlaan 6, 3584 CB, Utrecht, The Netherlands*

* Corresponding author: s.c.mcdowall@cml.leidenuniv.nl

Abstract

Securing the future supply of raw materials—particularly critical raw materials (CRMs)—is essential to promoting and sustaining economic and societal well-being. Effective forecasting of this supply requires consideration of secondary raw materials (2RMs) contained in diverse waste streams, alongside primary raw materials (1RMs) extracted from the environment. Given the deep uncertainty inherent in long-term forecasting, it is prudent to methodically explore a broad range of possible developments.

This paper presents the narrative construction phase of a scenario development process that explored future pathways for waste management and material recovery up to 2050. These storylines were developed within the Horizon Europe-funded project FutuRaM, which aims to establish methodology, reporting, and guidance to strengthen the raw materials knowledge base within the EU and beyond.

Three scenarios—Business as Usual (BAU), Recovery (REC), and Circularity (CIR)—were constructed to reflect divergent societal, political, economic, and technological trajectories. Each scenario consists of an overarching narrative, complemented by detailed qualitative projections regarding the future composition and volume of six specific waste categories. The scenario development process employed a structured approach integrating forecasting and backcasting techniques, identification of key drivers and uncertainties, extensive stakeholder engagement, and the creation of coherent narrative storylines grounded in current trends, stated policy goals, and published forecasts.

These scenario narratives can directly inform strategic decision-making, policy formulation, and long-term planning by clarifying plausible futures, trade-offs, and key intervention levers in waste and resource systems. Their utility can be further enhanced by using them as a structured foundation for quantitative modelling, in

which qualitative assumptions are translated into scenario parameters and explored with system models to compare pathways, test sensitivities, and assess system-wide implications.

Keywords

Circular Economy, Scenario Development, Storyline Narratives, Backcasting and Forecasting, Waste and Resource Management, Secondary Raw Materials, Critical Raw Materials, Stakeholder Engagement

List of abbreviations

35	1RM	Primary Raw Material
36	2RM	Secondary Raw Material
37	BATT	Waste Batteries (waste stream name)
38	BAU	Business-as-usual (scenario name)
39	CDW	Construction and Demolition Waste (waste stream name)
40	CE	Circular Economy
41	CIR	Circularity (scenario name)
42	CRM	Critical Raw Material
43	EEE	Electrical and Electronic Equipment
44	ELV	End-of-Life Vehicles (waste stream name)
45	EoL	End-of-Life
46	EoU	End-of-Use
47	EoW	End-of-Waste
48	EPR	Extended Producer Responsibility
49	EU	European Union
50	EU27+4	EU + Iceland, Norway, Switzerland, and the UK
51	EV	Electric Vehicle
52	FutuRaM	Future of Raw Materials (EU Horizon 2020 project)
53	GDP	Gross Domestic Product
54	IAM	Integrated Assessment Model
55	ICE	Internal Combustion Engine
56	IEA	International Energy Agency
57	IRTC	International Round Table on Materials Criticality
58	LCA	Life Cycle Assessment
59	LIB	Lithium-ion Battery

60	LMT	Light Means of Transport
61	MFA	Material Flow Analysis
62	MIN	Mining Waste (waste stream name)
63	NIMBY	Not In My Backyard (parochial protectionism)
64	RCP	Representative Concentration Pathway
65	REC	Recovery (scenario name)
66	REE	Rare Earth Elements
67	re-X	A broad set of circular economy strategies (“reduce”, “reuse”, “repair”, “recycle” etc.)
68	SLASH	Slags and Ashes (waste stream name)
69	SRM	Strategic Raw Material
70	SSP	Shared Socioeconomic Pathway
71	TRL	Technology Readiness Level
72	UK	The United Kingdom of Great Britain and Northern Ireland
73	UN	United Nations
74	UNFC	United Nations Framework Classification for Resources
75	WEEE	Waste Electrical and Electronic Equipment (waste stream name)
76	WFD	Waste Framework Directive

1. Introduction

1.1. Context and motivation

Europe's material economy depends on a secure and sustainable supply of raw materials. Primary raw materials (IRMs) extracted from virgin resources underpin manufacturing, energy, mobility, and digital infrastructure, but their extraction and processing can entail significant environmental and social impacts (Mononen et al., 2022). Additionally, the EU's reliance on foreign imports for many of these materials results in a high level of exposure to geopolitical risks and global market volatility (Carrara et al., 2023). Secondary raw materials (2RMs)—materials recovered from products, components, and residues at their end-of-life—offer a complementary source that can reduce dependence on IRMs, lower life-cycle burdens, and support circular-economy objectives (European Commission et al., 2021). Within the broader category of raw materials, critical raw materials (CRMs) are those with high economic importance and elevated supply risk; ensuring their availability is central to decarbonisation and digitalisation strategies in the EU (European Commission et al., 2023; International Energy Agency (IEA), 2023a).

The availability and recoverability of 2RMs depend on dynamic, interlinked drivers: product design and durability; collection, sorting, and recycling infrastructure; market acceptance and quality of secondary outputs; energy systems; trade and industrial policy; and consumer behaviour (Huisman et al., 2017; Li et al., 2022). These factors evolve under uncertainty on multi-decadal time horizons and interact across sectors and policy domains. As a result, decision-makers require forward-looking analyses that can systematically explore alternative futures, illuminate trade-offs, and test the implications of policy and technology choices (Amer et al., 2013; Mahmoud et al., 2009).

Scenario analysis provides such a lens and is widely used in environmental and resource domains to investigate long-term developments under uncertainty. Numerous scenario sets exist for energy systems and mobility transitions at national, EU, and global scales (Commission et al., 2021; International Energy Agency (IEA), 2023c, 2023b; OECD, 2012; Skea et al., 2021). By contrast, relatively few scenario sets centre explicitly on 2RM/CRM recovery systems and the waste streams that supply them. Where they do exist, they are often sector-specific (e.g., e-waste (Parajuly et al., 2019), traction batteries (Abdelbaky et al., 2020)) or more narrowly focussed CRM outlook reports (Buisson et al., 2024; International Energy Agency (IEA), 2025). Thus, there remains a gap in comprehensive, multi-stream perspectives on future 2RM supply supported by robust, transparent data.

1.2. FutuRaM's aim and scope

Addressing this, the Horizon Europe project FutuRaM develops the knowledge base on the availability and recoverability of 2RMs within the EU—with particular attention to critical raw materials (CRMs)—to support

evidence-based decisions by industry, investors, and policy-makers (FutuRaM consortium & European Commission, 2023; FutuRaM consortium, 2022).

FutuRaM focusses on the EU-27 plus Iceland, Norway, Switzerland, and the UK (EU27+4) over 2025–2050 and targets six waste streams with significant 2RM and CRM potential: batteries (BATT), waste electrical and electronic equipment (WEEE), end-of-life vehicles (ELV), construction and demolition waste (CDW), mining residues (MIN), and slags and ashes (SLASH). The project integrates material stock-flow information; considers economic, technological, regulatory, social, environmental, and geopolitical drivers and interactions with manufacturing, energy, and transport systems; and aligns outputs, where appropriate, with the United Nations Framework Classification for Resources (UNFC) (United Nations Economic Commission for Europe (UNECE), 2023).

Within this programme, Work Package 2 (WP2) develops a set of plausible, internally consistent scenarios that (i) characterise future 2RM supply from the six waste streams, (ii) identify key drivers and uncertainties, and (iii) provide a structured basis for subsequent quantification and model coupling. The scenarios are intended to inform public and private decisions by enabling systematic assessment of policy and technology options and their implications for 2RM/CRM availability and related environmental–economic outcomes. Within this scope, we develop scenario narratives to structure and inform subsequent quantification.

1.3. Policy context for 2RM/CRM scenarios

Government strategies and legislation at the local, state, and EU levels provide both direction and constraints for 2RM/CRM systems. The European Green Deal sets the overarching objective of climate neutrality by 2050 and promotes resilient, sustainable industrial value chains (European Commission, 2019). The Circular Economy Action Plan outlines measures to improve resource efficiency, product durability and repairability, waste prevention, and high-quality recycling, with close links to the EU Industrial Strategy (European Commission, 2020). Together, these frameworks create strong signals favouring design for circularity, increased recovery rates, and market development for 2RMs.

The Critical Raw Materials Act introduces specific supply-security benchmarks: by 2030, not more than 65% of annual EU consumption of each strategic raw material should stem from a single non-EU country; within the EU, capacities should be sufficient to extract $\geq 10\%$, process $\geq 40\%$, and recycle $\geq 15\%$ of annual consumption (European Commission, 2023). These benchmarks inform the REC and CIR scenarios, which examine the technology- and system-level changes needed to approach them via domestic recovery and circularity measures.

Waste-stream-specific legislation is also pertinent. BATT, ELV, and WEEE are governed by dedicated directives and regulations that set collection, treatment, and recycling requirements (European Commission, 2012, 2023b, 2023a, 2023c). These instruments shape the feasible ranges of collection rates, treatment

efficiencies, and design obligations used in the scenarios. Notably, several statutory targets—particularly in batteries—are ambitious to the point that meeting them would require rapid structural reforms and performance improvements across the recovery chain. Accordingly, BAU does not assume full attainment of these targets within the study horizon, whereas REC and CIR explore pathways that deliberately mobilise technological and systemic measures to meet or approach them.

A non-exhaustive list of relevant policies that were considered in this study are presented in appendix A3

1.4. Scenario types and their use in this study

In futures studies, scenario exercises are commonly grouped into three families that address different questions (Börjeson et al., 2005, 2006; Cordova-Pozo & Rouwette, 2023; Dreborg, 1996; Skea et al., 2021)

- **Predictive** — *What will happen?* These scenarios explore likely developments given current conditions and stated policies, typically using forecasting assumptions. They are informative for baseline planning but are contingent on assumptions and may under-represent low-probability disruptions.
- **Explorative** — *What could happen?* These map a space of plausible futures by varying external drivers and internal responses. They support preparedness across a range of outcomes without attaching probabilities or preferences.
- **Normative** — *How can a specified target be reached?* These work backwards from desired end-states (e.g., policy targets) to identify feasible pathways and enabling measures. They are purpose-oriented and depend on the choice of goals.

In practice, robust scenario work often combines these families and integrates qualitative narratives with quantitative parameters (Amer et al., 2013; Bishop et al., 2007). This study adopts a mixed-method scenario approach—integrating forecasting and backcasting—tailored to 2RM/CRM systems. The three scenarios are internally consistent and comparable across the six waste streams. They are specified at a level that provides a robust foundation for subsequent quantification—sufficiently detailed to support parameterisation and model-based analysis using methods such as material flow analysis (MFA) and life cycle assessment (LCA).

1.5. Contribution of this paper

This paper documents the narrative construction phase of FutuRaM’s scenario development. It:

1. develops three internally consistent, cross-comparable scenario storylines—BAU, REC), and CIR—covering six waste streams;
2. synthesises policy targets, technology trajectories, market developments, and expert judgement to identify key drivers, constraints, and uncertainties for 2RM/CRM recovery;
3. specifies transparent assumptions and traceable logic chains that map qualitative storyline elements to

scenario parameters, thereby providing a structured basis for subsequent quantification and model coupling within FutuRaM; and

4. clarifies the treatment of EU targets and benchmarks across scenarios, distinguishing baseline (BAU) assumptions from deliberate policy/technology mobilisation in REC and CIR.

The remainder of the paper describes the scenario method, presents the BAU/REC/CIR narratives by waste stream, and discusses implications for strategy and policy.

2. Methodology

This section outlines the scenario development workflow applied in FutuRaM (Figure 1). Herein is detailed Steps 1–6; parameterisation of scenario variables (Step 7) is reported in Appendix 6, quantitative modelling and implementation (Steps 8–9) fall outside the scope of this study. Selected outputs from Step 4 are presented in the Results (subsection 3.1) and supporting appendices (A5).

2.1. Step 1: Establish framework and scope

Framework. Scenarios were designed to ensure scientific rigour, transparency, and policy relevance. They are (i) evidence-based and methodologically robust; (ii) coherent and internally consistent while spanning a range of plausible futures and key uncertainties; (iii) decision-oriented, clarifying potential consequences of alternative choices; (iv) participatory, drawing on domain experts and stakeholders; (v) transparent and well documented to enable replication and open dissemination; (vi) adaptive, with provisions for periodic updating; (vii) systems-oriented, capturing interconnections among sectors, waste streams, and policy domains; (viii) long-term in perspective; (ix) integrative of quantitative modelling and qualitative narratives; and (x) communicated clearly to support both practitioner uptake and scholarly contribution. To facilitate consistent communication, a shared vocabulary was established at the outset (Appendix A1).

Scope. The scenarios examine plausible futures for waste management, resource recovery, and the circular economy across the EU-27 plus Iceland, Norway, Switzerland, and the UK (EU27+4) over 2025–2050, with projection years at 2025, 2030, 2035, 2040, 2045, and 2050. Temporal granularity was limited to avoid spurious precision given long-term uncertainty. The analysis centres on six FutuRaM waste streams—WEEE, ELV, BAT, CDW, MIN, and SLASH—together with interfaces to manufacturing, energy, and transport systems, and the relevant environmental, economic, social, technological, and geopolitical policy domains.

2.2. Step 2: Determine methodology

Selection criteria and methods considered. We identified methods and tools suited to FutuRaM’s objectives using criteria of relevance and applicability to context; feasibility (time, budget, expertise, data); transparency and documentation; flexibility to incorporate new evidence; accessibility for non-experts; effectiveness and efficiency; and stakeholder acceptability. Candidate methods are summarised in Appendix A2.

Core scenario set and candidate dimensions. The grant proposal defined three core scenarios—Business as Usual (BAU), Recovery (REC), and Circularity (CIR)—to explore how secondary raw material (2RM) availability is shaped by the evolution of 2RM recovery systems and re-X strategies. During scoping, additional dimensions were considered, notably supply-chain security and the pace of the energy transition. Their inclusion was tested using the procedures below. The reasons for ultimately not adopting further dimensions are discussed in Section 4.

Multi-criteria and cross-impact analysis. To avoid uncontrolled growth in scenario variants, we applied a matrix-based multi-criteria and cross-impact analysis to evaluate internal consistency and plausibility of combinations (Steubing et al., 2016). For instance, “low” progress in the energy transition was judged inconsistent with “high” progress in recycling/circularity indicators and could be excluded. By contrast, supply-chain security varied more independently, but credible geopolitical speculation was not feasible; incorporating it as a scenario dimension would introduce excessive uncertainty. Instead, potential supply constraints will be analysed via sensitivity tests and, where appropriate, explorative multi-objective optimisation to address questions such as: *What happens to the 2RM system if element x is constrained, and what responses are optimal?* Additional rationale is provided in the Section 4.

Delphi process. Early stages of scenario building were supported by a Delphi process to aggregate expert judgement across waste streams and recovery-system domains (Hsu & Sandford, 2019). Steps included expert selection, initial questionnaires, iterative rounds with controlled feedback, and convergence toward consensus.

2.3. Step 3: Marker-scenario mapping

We conducted a structured literature review to identify and analyse marker scenarios relevant to FutuRaM. This mapping served to (i) build on established knowledge; (ii) benchmark assumptions, drivers, and methodological approaches; (iii) identify gaps; and (iv) enhance comparability and credibility of our scenarios. Insights from marker scenarios informed the selection of drivers, the structuring of storylines, and the alignment of projection years and sectoral linkages. The consulted marker scenarios are listed in Appendix A4.

2.4. Step 4: Identify key drivers and select scenario elements

Purpose and approach. This step identified the social, economic, technological, environmental, and policy factors that shape the waste-management system over time. The process combined literature review, internal expert elicitation, and stakeholder engagement to assess trends, uncertainties, and emerging issues. It was iterative, with feedback loops to ensure coverage of the most influential drivers and to maintain consistency with scope and objectives.

Sub-method and workflow. Figure 2 depicts the sub-method for identifying and defining scenario elements:

- **Preliminary collection and screening.** Candidate elements were compiled from peer-reviewed literature, statistics, policy documents, and project datasets, then screened against predefined criteria for relevance, reliability, plausibility, and model utility. Overlapping items were consolidated (e.g., recyclability mandates with design-for-recyclability), and elements judged irrelevant, non-modellable, or unreliable (e.g., corruption, data protection, supply-chain conflict) were excluded.
- **Assessment and categorisation.** Retained items were organised by thematic relevance and characteristics, yielding 21 key elements (Table 1). While CIR and REC share many elements, they

differ in how targets are achieved: CIR emphasises re-X strategies (reduce, reuse, repair, remanufacture, recycle), whereas REC prioritises advances in recovery technology and infrastructure—an important distinction for subsequent quantitative modelling.

- **Scope classification.** Each element was classified according to its relationship to the waste-management system: **internal** (within scope for detailed research and modelling, e.g., composition and design changes), **external** (included in storylines, varying over time but constant across scenarios, e.g., population, GDP), or **outside** (excluded from scenarios but, where relevant, examined in sensitivity analysis, e.g., supply constraints).

Selected Step-4 outputs are presented in the Results (subsection 3.1) and the appendices (A5 and A6). The validated element set informed the design of storyline themes (Step 5) and the drafting of narratives (Step 6).

2.5. Step 5: Develop storyline themes

The overarching scenario themes were guided by the FutuRaM charter and the grant proposal's core scenario set. Themes focus on how 2RM availability evolves under different combinations of recovery-system development and re-X strategies. The three scenarios are:

- **Business as Usual (BAU)** — *Predictive*: projects outcomes if current policies and trajectories persist, assuming continuity in waste management and resource recovery systems.
- **Recovery (REC)** — *Normative*: prioritises technological and infrastructural improvements in recovery systems to meet EU material-use and recovery targets.
- **Circularity (CIR)** — *Normative and explorative*: aligns with the EU Circular Economy Action Plan (European Commission, 2020), examining systemic adoption of re-X strategies to achieve targets and reduce dependence on primary resources.

A graphical depiction of the scenarios is provided in Figure 3. The rationale for not expanding the scenario set with additional dimensions is discussed in Section 4.

2.6. Step 6: Develop qualitative narrative storylines


Narratives were constructed through an iterative process that combined systematic evidence gathering with structured consultation. Data on trends, targets, policies, and marker scenarios were collated to define candidate drivers and elements. These inputs were scrutinised in workshops and Delphi-style rounds with consortium experts and, where appropriate, external stakeholders, to test plausibility, resolve inconsistencies, and prioritise influential factors. Draft narratives for BAU, REC, and CIR were reviewed for internal coherence and alignment with the agreed scope, then refined through successive feedback cycles.

Each storyline integrates qualitative insights with model-ready descriptors to enable later parameterisation.

Assumptions, causal links, and uncertainty ranges were documented to support transparency and to flag items for sensitivity analysis. The outputs of Step 6 thus provide: (i) coherent narratives that explain how and why system trajectories diverge across scenarios; (ii) a traceable mapping from qualitative drivers to quantitative variables; and (iii) an auditable record of literature sources, expert judgements, and decisions.

The main outcome of this study, the scenario storyline narratives are presented in the Results (subsection 3.2). More details about the waste-stream-specific impacts of the scenarios is presented in Appendix A7.

Forward link to Step 7. Parameter values and time paths for model variables (e.g., technology performance, collection and sorting rates, design and composition shifts) are to be quantified in Step 7 using trends and forecasts, subject to the consistency constraints defined in Steps 2–6. These parameters were analysed in preparation for quantification and reported in Appendix A6. **Steps 8–9** (quantitative modelling and implementation) are outside the scope of this study.






Figure 2. An illustration of the methodology used for identifying, defining, screening, and integrating the key elements of the scenarios developed in FutuRaM

3. Results

3.1. Scenario element selection

Results from the preliminary collection of scenario elements are summarised in Appendix A5. Table 1 lists the drivers and factors retained after the screening process. Appendix A6 presents the final, categorised set of scenario elements and indicates which are carried forward for parameterisation and subsequent modelling. Elements were excluded when judged out of scope, insufficiently specific to the focal waste streams, or infeasible to quantify.

Table 1. Scenario drivers and factors retained after screening. Items were omitted if they were out of scope, not sufficiently specific to the waste streams, or infeasible to quantify. “Scenario variances” denote a qualitative stakeholder assessment of the expected trend for each driver/factor in the three scenarios—Business as Usual (BAU), Recovery (REC), and Circularity (CIR).

Domain	Factor/Driver	Scenario variance		
		BAU	REC	CIR
Economic	CO ₂ market price	I	I	I
Economic	Economic growth	I	I	I
Economic	Energy prices	I	I	I
Economic	Market saturation of (electronic) products	I	I	II
Economic	Raw material vs 2RM prices	I	I	I
Economic	Re-industrialisation of EU	I	I	I
Environmental	Climate change impacts	I	I	I
Environmental	Climate change mitigation efforts	I	I	I
Environmental	Increased drive for environmental protection	I	III	III
Environmental	Resource shortages	I	I	I
Legal/Political	Ecodesign/re-X mandates	I	II	III
Legal/Political	Governance: corruption vs compliance	I	I	I
Legal/Political	International trade and co-operation (vs. autarky)	I	I	I
Legal/Political	Product information transparency	I	III	III
Legal/Political	Progress toward renewable energy targets	I	I	I
Legal/Political	Stricter environmental regulations	I	III	III
Legal/Political	Subsidies/taxation to promote circularity	I	I	I
Legal/Political	Supply chain due diligence laws	I	II	III
Social	Hoarding of end-of-life consumer products	III	II	II
Social	NIMBY attitudes toward projects	I	I	I
Social	Participation in re-X activities	I	II	III
Social	Population change	I	I	I
Social	Urbanisation	I	I	I
Technical	Digitisation	I	I	I
Technical	2RM system integration	I	III	III

Technical	Product technology (design for re-X)	I	III	III
Technical	Recovery technology (recycling system)	I	III	III

3.2. Qualitative narrative development: The scenario storylines

This subsection presents abbreviated qualitative storylines for the three scenarios—Business as Usual (BAU), Recovery (REC), and Circularity (CIR)—summarising their system-wide logic and expected trajectories. Figure 3 illustrates the distinct economic logic embodied by each scenario: trend continuation in BAU, technology-led improvements in recovery systems in REC, and systemic adoption of re-X strategies in CIR. More detailed information about the waste-stream-specific impacts of each scenario is given in appendix A7.




Figure 3. A schematic representation of the three discrete economic models embodied by the three scenarios developed in FutuRaM: a) Business-as-usual (BAU), b) Recovery (REC), c) Circularity (CIR). Adapted from Government of the Netherlands (2016).

3.2.1 Scenario I: Business-as-usual (BAU)

The BAU scenario projects present trends through to 2050 with minimal deviation in consumption patterns and in the organisation of the secondary raw material (2RM) system. While incremental gains occur—e.g., moderate resource-efficiency improvements, gradual advances in recovery technology, and a steady energy transition—transformational change is constrained by economic pressures, social preferences, political inertia, and entrenched interests. Primary extraction remains the dominant source meeting the EU's growing material

demand.

System trajectory and assumptions

BAU is a forecasting-led pathway: it extrapolates current drivers and institutions, assuming today's policy ambition and enforcement largely persist. Minor efficiency gains are absorbed by rising demand, leaving overall material throughput closely coupled to GDP growth. The linear take–make–dispose model continues to shape production and consumption, and the 2RM system improves only at the margin.

Material demand and supply

Material demand remains tightly linked to economic activity, so total consumption increases over time. Primary mining and extraction continue as the leading supply sources, reinforcing reliance on traditional extraction methods. Base metals benefit from established markets and economies of scale and are comparatively well recycled; by contrast, many rare and specialty metals are still lost because technologies and economics limit their recovery. EU mining remains limited and geographically concentrated in a few member states; known domestic potentials—e.g., lithium (PT, FR, UK) and rare earths (SE)—are not realised. Import dependency therefore escalates, increasing exposure to supply disruptions and market volatility.

Waste management and recovery performance

Recycling and recovery rates remain **low** relative to potential, with persistent losses of critical raw materials. Producer responsibility schemes and data availability improve only incrementally; collection performance and contamination continue to limit output quality and value. Investments in sorting, pre-treatment, and recovery capacity are selective and insufficient to change system-level outcomes. As a result, significant 2RM opportunities are missed, and landfilling or low-value outlets remain prevalent in several streams.

Policy and governance

Many EU targets for ecodesign, recycling, recovery, and waste prevention are not met. Regulatory tightening is constrained and uneven across member states, providing weak incentives for high-quality recyclates or design changes. Where policies advance, implementation and monitoring gaps blunt impact. Without stronger and more consistent measures, innovation remains patchy and the cost of secondary outputs often fails to match primary alternatives at required specifications.

Environmental and socio-economic outcomes

Environmental pressures from extraction persist, contributing to ecosystem degradation, biodiversity loss, and climate impacts. Relative to pathways with stronger circular measures, BAU exhibits higher cumulative energy and material footprints. At the same time, heightened import reliance exposes EU industry to price spikes and supply shocks, increasing planning uncertainty and potentially delaying investment in new recovery technologies. Industrial priorities emphasise short-term cost efficiency over long-term resilience and sustainability. Transitions to renewable energy and e-mobility proceed, but at the present pace rather than on an

accelerated trajectory.

Dependencies and risks

Key vulnerabilities include: (i) persistent coupling of demand and GDP; (ii) limited progress on design-for-circularity and product information, which constrains high-quality recovery; (iii) under-investment in 2RM technologies and infrastructure; and (iv) import-related exposure to geopolitical and market risks. These factors reinforce lock-in to linear practices, making it harder to realise future gains without stronger policy and market signals.

Positioning relative to other scenarios

BAU serves as a reference against which the Recovery (REC) and Circularity (CIR) scenarios can be evaluated. Compared with REC, BAU exhibits lower recovery performance, weaker output quality, and higher landfilling; compared with CIR, it lacks the upstream design, use-phase, and sufficiency levers needed to decouple services from primary extraction. In short, BAU represents the lower-bound pathway where incremental improvements occur but the structure of the system—and its associated risks—largely persists.

3.2.2 Scenario II: Recovery (REC)

The recovery scenario centres on harnessing pre-consumer and post-consumer waste as a significant source of secondary raw materials (2RMs). It moves decisively beyond the status quo by upgrading recovery performance and infrastructure, yet overall material throughput continues to track growing demand rather than absolute reductions. The modelling approach combines backcasting for dimensions governed by policy targets with forecasting for areas without binding targets, linking desired outcomes to present conditions and projecting feasible pathways from current baselines.

System focus and technological change

Waste treatment is the pivotal actor. The emphasis is on rolling out and optimising advanced recovery technologies to improve sorting fidelity, material purity, and process efficiency. Digitalisation—spanning artificial intelligence, automation, robotics, and enhanced process control—raises plant productivity and stabilises quality, allowing higher-value recyclates to re-enter manufacturing. Investments concentrate on upgrading sorting, pre-treatment, and recovery facilities, and on data systems that disclose product composition and design attributes, which in turn enable better characterisation and targeted recovery. Producer responsibility schemes mature, driving higher take-back and collection across key streams and reinforcing steady feedstock to recyclers.

Policy, governance, and market organisation

EU targets for recycling and recovery are reached due to a more expansive, efficient, and effective waste management system. Regulatory instruments are tightened to promote high-quality outputs (e.g., contamination limits, de-risked offtake), improving the economics of recovery. Standardisation and clearer guidance support

365 EU-wide implementation and compliance; cross-border coordination and knowledge transfer help diffuse good
366 practice. Alongside regulation, public investment and R&D programmes crowd in private capital for plant
367 upgrades and process innovation, while transparency requirements expand the availability of product and
368 material data relevant to recovery planning.

369 **Material supply and risk profile**

370 Higher domestic recovery partially mitigates supply risk by reducing exposure to volatile global markets;
371 nonetheless, import dependence persists for several critical inputs where domestic end-of-life stocks, technology
372 readiness, or economics remain constraining. Urban mining and recovery from selected waste streams and
373 tailings are explored more systematically, with pilots scaling where yields and costs are favourable. Industrial
374 actors increase the share of secondary inputs where price–quality conditions permit, but adoption varies across
375 sectors and member states.

376 **Environmental and socio-economic outcomes**

377 Relative to business-as-usual (BAU), environmental burdens decline due to higher recovery rates and lower
378 landfilling. However, upstream pressures linked to aggregate consumption growth remain significant—this is a
379 system that recovers more, not one that uses less. Employment expands in recycling, recovery, and associated
380 services as collection improves and plants scale. Cost efficiency in 2RM production improves through learning
381 and quality gains, further reinforcing uptake in manufacturing where specifications can be met.

382 **Diffusion dynamics and behavioural dimensions**

383 Innovation diffusion is uneven. Frontrunner regions and sectors demonstrate higher yields and faster quality
384 improvements; laggards remain closer to BAU performance. Public awareness of recycling improves, but
385 behaviour change is still concentrated at the end-of-pipe (separating and returning products) rather than
386 sufficiency (avoiding or reducing consumption). As a result, the system attains higher circular recovery without
387 fully addressing demand-side drivers.

388 **Dependencies and implementation risks**

389 Realising the scenario’s gains depends on sustained investment in recovery infrastructure and digital capabilities;
390 robust enforcement of quality standards; and continued maturation of producer responsibility schemes. Key risks
391 include: (i) inconsistent implementation and monitoring across member states; (ii) quality shortfalls that depress
392 secondary material prices or restrict their use in high-specification applications; and (iii) slower-than-expected
393 technology learning, which would limit cost and performance improvements. These risks are partially offset by
394 clearer regulatory signals, improved data availability on product composition and design, and public
395 procurement practices that accept certified secondary content.

396 **Positioning relative to other scenarios**

397 Compared with BAU, REC delivers higher recovery, lower landfilling, and better-quality secondary outputs

through technology, standards, and organisation. In contrast with a full circularity pathway, REC places most of its leverage at end-of-life rather than at design and use; it moderates—but does not decouple—material demand. Consequently, import reliance is reduced only partially, and remains material for certain critical inputs.

3.2.3 *Scenario III: Circularity (CIR)*

System trajectory and assumptions

CIR deploys waste prevention, ecodesign, reuse, repair, remanufacturing, and high-quality recycling to the maximum feasible extent, with the explicit aim of decoupling material services from primary resource extraction. The modelling approach combines backcasting for factors with binding targets and forecasting for factors without them, linking desired outcomes to present conditions and defining consistent pathways from now to 2050.

Material demand and supply (towards decoupling)

Relative to BAU and REC, total material throughput is moderated by upstream measures (design for longevity, sharing and service models) and higher 2RM use. 2RM recycling and recovery rates rise markedly; secondary materials gain wider acceptance in production as standards and data improve. Reliance on imports declines as domestic circular flows expand, although strategic procurement remains important in specific value chains. Renewable energy and cleaner process technologies are applied throughout 2RM production and use to support a low-carbon trajectory.

Waste management and recovery performance

End-of-life systems shift from volume handling to quality-focused recovery. Standardised collection, advanced sorting, and traceable feedstocks (e.g., product passports, waste tracking) raise output purity and value, enabling high-quality, loop-closing recycling. Reuse, repair, refurbishment, and remanufacture absorb a larger share of post-consumer inflows; residual fractions are more readily segregated and recovered at high efficiency. Investments prioritise design-compatible recovery, contamination control, and certification that unlock secondary inputs for high-specification applications.

Policy and governance

EU targets for recycling, recovery, ecodesign, and waste prevention are met, supported by stricter product-design guidelines, robust implementation, and monitoring. Regulatory instruments reward durability, reparability, standardisation, and disassembly; producer responsibility schemes are extended to drive high collection and take-back. Digital information requirements (e.g., product passports) become baseline practice across value chains, improving planning and verification. New business models—product-service systems, leasing, and take-back—scale and moderate traditional consumption patterns. Fiscal reform complements regulation (e.g., shifting taxation from labour to resource depletion; flexible VAT rates for repair), while phasing out environmentally harmful subsidies. Member States implement EU measures and tailor complementary regional initiatives;

international coordination supports alignment with broader commitments.

Mechanisms of resource efficiency

CIR enhances resource efficiency via four complementary strategies:

1. **Narrowing** material flows through reduced or shared product use and improved manufacturing efficiency;
2. **Slowing** flows by extending product and component lifetimes via reuse, repair, refurbishment, and remanufacture;
3. **Closing** loops through high-quality recycling that reduces landfilling and incineration and lowers demand for primary inputs;
4. **Substituting** finite inputs with renewable or lower-impact alternatives where feasible.

Design, behaviour, and information

Re-X strategies are embedded from the design phase onward (repairability, remanufacturability, standardised components, easy disassembly). Predictive maintenance and monitoring extend service life in sectors such as transport and manufacturing. Transparency tools—digital product passports and waste tracking—standardise information on composition, durability, and repairability, enabling efficient disassembly, reuse, and high-quality recycling, and fostering collaboration along value chains. Public awareness and education increase participation in repair, reuse, and service models, reinforcing demand for long-lived, upgradable products.

Environmental and socio-economic outcomes

CIR retains product, material, and resource value in the economy for longer while minimising waste generation, consistent with a sustainable, low-carbon, resource-efficient, and competitive EU economy. Anticipated effects include:

- **Economic:** greater resilience to resource scarcity and price volatility; emergence of efficient production and consumption models; new business opportunities; diversified employment in circular activities.
- **Environmental:** lower cumulative energy use and mitigation of irreversible ecological damages across climate, biodiversity, and pollution pressures.
- **Social:** broader participation in repair, reuse, and service models; enhanced inclusion via local circular enterprises and skills development.

Dependencies and enablers

Delivery depends on: (i) sustained investment in design-compatible recovery infrastructure and digital information systems; (ii) consistent enforcement of product-design and recovery standards; (iii) mature producer

responsibility with verified performance; (iv) stable market pull for certified secondary content (including public procurement); and social/consumer engagement. These enablers reduce quality risk, improve economics for 2RMs, and support continued diffusion of circular practices.

Positioning relative to other scenarios

Compared with BAU, CIR achieves substantially higher recovery quality and volume and moderates demand via upstream design and behavioural levers. Compared with REC, CIR shifts the centre of gravity upstream—placing design, durability, and service models alongside end-of-life performance. The CIR scenario is, thereby, advancing from “recover more” to “use better and less,” with stronger progress towards decoupling economic growth from 1RM consumption.

4. Discussion

What this study adds

This paper addresses a clear gap: while many scenario sets exist for energy and mobility, few centre on the waste-derived supply of raw materials and its implications for critical raw materials (CRMs). We contribute a transparent, EU27+4-focused scenario framework with three internally consistent storylines—Business as Usual (BAU), Recovery (REC), and Circularity (CIR)—that are explicitly grounded in waste-stream realities. The narratives integrate qualitative evidence (policies, technology trajectories, market drivers) with model-ready descriptors, creating a traceable bridge from storylines to subsequent parameterisation and quantitative modelling.

Interpreting the three storylines

BAU offers a predictive baseline of incremental change, useful as a reference for policy appraisal. REC is a normative pathway that concentrates on technology and infrastructure in collection, sorting, and processing to raise recovery performance and approach statutory targets for 2RMs relevant to CRMs. CIR is a normative/explorative pathway that layers demand-side and design-side levers—re-X strategies such as reduce, reuse, repair, remanufacture, recycle—on top of improved recovery, aiming to decouple material services from 1RM extraction. Taken together, the trio delineates a wide but decision-relevant envelope of futures for 2RM supply, enabling systematic testing of how policy and technology choices propagate through the resource-recovery system.

Policy relevance: focusing on controllable levers

A key design choice was to prioritise variables that decision-makers can influence (“policy knobs”), including: product design requirements (durability, reparability, standardisation), collection and sorting performance, recycling yields and quality, end-market development for 2RMs, and enabling governance (standards, reporting, extended producer responsibility). By structuring the scenarios around these levers, the narratives remain directly interpretable for regulators, industry, and investors and are well suited to downstream tools such as life cycle assessment and material flow analysis.

The authors considered adding explicit axes for supply-chain security and the pace of the energy transition. Both are highly salient for CRMs but proved problematic as core scenario dimensions. Credible trajectories for supply-chain security would require geopolitical forecasting beyond the evidence base and would inflate uncertainty and scenario count without commensurate insight. Similarly, varying the energy transition orthogonally to BAU/REC/CIR created internal inconsistencies (e.g., “low transition–high circularity” combinations) and a combinatorial expansion that diluted the focus on waste-system levers. Instead, these influences can be explored through targeted sensitivity analysis and optional module coupling. For example, exogenous supply constraints can be imposed in shock tests, and simplified price modules can probe how

alternative 1RM–2RM price paths shape collection and processing responses. This approach preserves clarity and decision usefulness while acknowledging real-world volatility.

Strengths of the approach

Methodologically, three features strengthen credibility and transferability. First, we used marker-scenario mapping to align assumptions and highlight gaps relative to established scenario families, improving comparability. Second, cross-impact and multi-criteria checks were applied to test internal consistency and to reduce false-plausible combinations before narrative drafting. Third, structured expert elicitation (Delphi-style) and stakeholder workshops were used to challenge assumptions, surface disagreements, and converge on the most influential drivers. The result is a set of storylines that are both transparent—assumptions and rationales are documented—and practicable—parameters and projection years are specified to enable quantification.

Limitations and caveats

Several limitations merit attention. The geographical focus (EU27+4) supports policy relevance but constrains generalisability to other institutional contexts; transfer will require careful adaptation of drivers and policy instruments. The time horizon (2025–2050) and discrete projection years balance tractability and detail but cannot capture short-term shocks or continuous dynamics; we caution against over-interpreting mid-point values. Data gaps persist for some waste streams and sub-components (e.g., informal flows, secondary output quality), and expert judgement was necessary in places; while triangulated, expert elicitation carries bias risk. Finally, the present contribution covers narrative construction; full insight into performance trade-offs depends on subsequent parameterisation (Step 7) and quantitative modelling (Steps 8–9), which are outside this paper's scope.

Implications for modelling and evidence needs

The narratives provide clear cues for model coupling. REC and CIR, in particular, specify parameter families (collection rates, sorting efficiencies, process yields, design shifts) and boundary conditions (policy targets, technology readiness) that can be translated into time paths and tested against constraints. Two priorities emerge: (i) systematic sensitivity analyses for supply constraints, price dynamics, and technology learning rates; and (ii) selective coupling to market and trade modules to capture feedbacks that materially affect 2RM uptake. Progress also depends on improving evidence for product composition, durability, and design trends, and on better quality metrics for secondary outputs—areas where targeted data collection would materially reduce uncertainty.

Outlook and use

We view the narratives as living artefacts. They can be updated as legislation, technology, and markets evolve, while preserving a consistent backbone for tracking change. Practically, the storylines support three near-term uses: (1) screening of policy packages for internal coherence (e.g., aligning design mandates with recovery infrastructure timelines); (2) investment planning for collection, sorting, and high-quality recycling capacity; and

536 (3) prioritisation of R&D on recovery technologies and circular-design practices most consequential for CRM-
537 relevant 2RMs. By keeping the scenarios centred on controllable levers and by documenting assumptions
538 transparently, the framework aims to enable robust, evidence-informed decisions amid persistent uncertainty.

5. Conclusions

This paper has developed three internally consistent narrative scenarios—Business as Usual (BAU), Recovery (REC), and Circularity (CIR)—to explore how waste management and recovery systems could shape the availability of secondary raw materials (2RMs) relevant to critical raw materials (CRMs) in the EU27+4 to 2050. The storylines integrate policy, technology, and market evidence with structured expert input, marker-scenario mapping, and cross-impact checks, yielding transparent, model-ready descriptors and projection years suitable for subsequent quantification.

A deliberate design choice was to centre the scenarios on levers that decision-makers can influence—product design and standards, collection and sorting performance, recycling yields and quality, and end-market development for 2RMs—rather than on highly exogenous axes. Proposed dimensions such as supply-chain security and the pace of the energy transition were therefore not adopted as core axes; instead, they will be addressed through sensitivity analysis and optional coupling to market/trade and optimisation modules. This preserves interpretability while acknowledging genuine sources of volatility.

The narratives now provide a concrete basis for parameterisation and for the development and testing of quantitative models. Priority tasks include (i) translating storyline cues into time paths for collection, sorting, process efficiency, and design shifts; (ii) systematic sensitivity tests for supply constraints and 1RM–2RM price dynamics; and (iii) targeted data improvements on product composition, durability, and secondary-output quality.

While results are scoped to the EU27+4 and a 2025–2050 horizon, the framework is transferable with appropriate localisation. By focusing on controllable levers and documenting assumptions clearly, the scenarios are intended to support evidence-informed policy and investment decisions under deep uncertainty.

Supplementary Material

The supplementary material supplied in the appendices of this manuscript contain the following sections:

- A1. Terminology definitions
- A2. Scenario development methods
- A3. Overview of relevant policy instruments
- A4. Overview of marker scenarios
- A5. Scenario elements after screening and categorisation for quantification
- A6. Drivers and factors identified in the screening phase
- A7. Waste-stream-specific scenario impacts

Data availability

All publicly available data related to the development of the scenarios and the composition of this manuscript is available in online repositories hosted by Zenodo (<https://doi.org/10.5281/zenodo.16882850>) and Github (<https://GitHub.com/Stew-McD/scenario-development>)

Acknowledgements

This research project was financially supported by the European Union's Horizon 2020 research and innovation programme under the grant agreement No. 101058522 (project FutuRaM — futuram.eu). The authors would like to acknowledge the many FutuRaM consortium members and stakeholders who contributed to the development of the scenarios presented in this study. The authors would also like to thank the reviewers for their valuable comments and suggestions.

CRedit authorship contribution statement

Stewart Charles McDowall: Conceptualisation, Methodology, Investigation, Data curation, Formal analysis, Validation, Visualisation, Writing: original draft, Writing: review & editing, Visualisation.

Nathalie Körf: Conceptualisation, Methodology, Investigation, Data curation, Writing: review & editing

Carlos Felipe Blanco: Conceptualisation, Methodology, Validation, Writing: review & editing, Funding acquisition, Supervision.

Stefano Cucurachi: Conceptualisation, Methodology, Validation, Writing: review & editing, Funding acquisition, Supervision.



Figure 4: CRediT authorship visualisation

Declarations

Competing interests

The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

Open access

This article is licensed under a Creative Commons Attribution 4.0 International Licence, which permits use, sharing, adaptation, distribution, and reproduction in any medium or format, as long as you give appropriate credit to the original author(s) and the source, provide a link to the Creative Commons licence, and indicate if changes were made. The images or other third party material in this article are included in the article's Creative Commons licence, unless indicated otherwise in a credit line to the material. If material is not included in the article's Creative Commons licence and your intended use is not permitted by statutory regulation or exceeds the permitted use, you will need to obtain permission directly from the copyright holder. To view a copy of this licence, visit <http://creativecommons.org/licenses/by/4.0/>.

Use of artificial intelligence

The authors declare that no generative artificial intelligence tools were used in the generation of the research data or results reported in this paper. Generative AI was used solely to assist in the editing and refinement of the manuscript text, with all content reviewed and approved by the authors.

References

- Abdelbaky, M., Peeters, J. R., Duflou, J. R., & Dewulf, W. (2020). Forecasting the EU recycling potential for batteries from electric vehicles. *Procedia CIRP*. <https://doi.org/10.1016/j.procir.2020.01.109>
- Amer, M., Daim, T. U., & Jetter, A. (2013). A review of scenario planning. *Futures*. <https://doi.org/10.1016/j.futures.2012.10.003>
- Bishop, P., Hines, A., & Collins, T. (2007). The current state of scenario development: An overview of techniques. *Foresight - The Journal of Future Studies*. <https://doi.org/10.1108/14636680710727516>
- Börjeson, L., Höjer, M., Dreborg, K.-H., Ekvall, T., & Finnveden, G. (2005). *Towards a user's guide to scenarios—A report on scenario types and scenario techniques*. Royal Inst. of Technology, Stockholm (Sweden). Environmental Strategies Research - fms. <https://www.osti.gov/etdeweb/biblio/20688312>
- Börjeson, L., Höjer, M., Dreborg, K.-H., Ekvall, T., & Finnveden, G. (2006). Scenario types and techniques: Towards a user's guide. *Futures*. <https://doi.org/10.1016/j.futures.2005.12.002>
- Boulos, S., Sousanoglou, A., Evans, L., Lee, J., King, N., Facheris, C., & Donelli, M. (2015). The durability of products: Standard assessment for the circular economy under the Eco-Innovation Action Plan. *Report for European Commission, DG Environment*.
- Buisson, E., Dhir, S., Hegarty, A., Hwang, G., Kim, Y. Y., Michaels, K., Bredariol, T. de O., Pospiech, R., & Raboca, J. (2024). *Recycling of critical minerals: Strategies to scale up recycling and urban mining*. International Energy Agency (IEA). <https://iea.blob.core.windows.net/assets/6987d251-bf8b-44a2-ab34-835e0321b793/RecyclingofCriticalMinerals.pdf>
- Carrara, S., Bobba, S., Blagoeva, D., Alves Dias, P., Cavalli, A., Georgitzikis, K., Grohol, M., Itul, A., Kuzov, T., Latunussa, C., Lyons, L., Malano, G., Maury, T., Prior Arce, A., Somers, J., Telsnig, T., Veeh, C., Wittmer, D., Black, C., ... Christou, M. (2023). *Supply chain analysis and material demand forecast in strategic technologies and sectors in the EU – A foresight study*. Publications Office of the European Union. <https://doi.org/10.2760/334074>
- Center for Climate Change Adaption Science at the University of Arizona. (2023). *Glossary—Scenario Planning for the Institute of the Environment*. <https://www.adaptationscenarios.org/glossary>
- Commission, E., Action, D.-G. for C., Energy, D.-G. for, Mobility, D.-G. for, Transport, De Vita, A., Capros, P., Paroussos, L., Fragkiadakis, K., Karkatsoulis, P., Höglund-Isaksson, L., Winiwarter, W., Purohit, P., Gómez-Sanabria, A., Rafaj, P., Warnecke, L., Deppermann, A., Gusti, M., Frank, S., ... Kalokyris, T. (2021). *EU reference scenario 2020 – Energy, transport and GHG emissions – Trends to 2050*. Publications Office. <https://doi.org/doi/10.2833/35750>
- Cordova-Pozo, K., & Rouwette, E. A. J. A. (2023). Types of scenario planning and their effectiveness: A review of reviews. *Futures*. <https://doi.org/10.1016/j.futures.2023.103153>
- Dreborg, K. H. (1996). Essence of backcasting. *Futures*. [https://doi.org/10.1016/s0016-3287\(96\)00044-4](https://doi.org/10.1016/s0016-3287(96)00044-4)
- European Commission. (2012). *Directive 2012/19/EU of the European Parliament and of the council of 4 July 2012 on waste electrical and electronic equipment (WEEE) (recast)*. European Commission. <https://eur-lex.europa.eu/legal-content/EN/TXT/?uri=CELEX:32012L0019>
- European Commission. (2019). *The European Green Deal*. European Commission. <https://eur-lex.europa.eu/legal-content/EN/TXT/?uri=COM:2019:640:FIN>
- European Commission. (2020). *A New Circular Economy Action Plan For a Cleaner and More Competitive Europe*. European Commission. <https://doi.org/10.2779/05068>

- European Commission. (2023a). *Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC*. European Commission. <http://data.europa.eu/eli/dir/2014/53/2023-10-01>
- European Commission. (2023b). *End-of-life vehicles Regulation*. European Commission. https://environment.ec.europa.eu/topics/waste-and-recycling/end-life-vehicles/end-life-vehicles-regulation_en
- European Commission. (2023). *European Critical Raw Materials Act*. European Commission. https://single-market-economy.ec.europa.eu/publications/european-critical-raw-materials-act_en
- European Commission. (2023c). *Regulation (EU) 2023/1542 of the European Parliament and of the Council of 12 July 2023 concerning batteries and waste batteries, amending Directive 2008/98/EC and Regulation (EU) 2019/1020 and repealing Directive 2006/66/EC*. European Commission. <https://eur-lex.europa.eu/eli/reg/2023/1542/oj>
- European Commission, Directorate-General for Internal Market, E., Industry, & SMEs. (2021). *3rd Raw Materials Scoreboard – European innovation partnership on raw materials*. Publications Office. <https://doi.org/doi/10.2873/567799>
- European Commission, Directorate-General for Internal Market, E., Industry, SMEs, Grohol, M., & Veeh, C. (2023). *Study on the critical raw materials for the EU 2023 — Final report*. Publications Office of the European Union. <https://doi.org/10.2873/725585>
- FutuRaM consortium. (2022). *Consortium Agreement—Project 101058522—FutuRaM*.
- FutuRaM consortium & European Commission. (2023). *Grant Agreement—Project 101058522—FutuRaM*. <https://doi.org/10.3030/101058522>
- Hsu, C.-C., & Sandford, B. A. (2019). The Delphi Technique: Making Sense of Consensus. *Practical Assessment, Research, and Evaluation*. <https://doi.org/10.7275/pdz9-th90>
- Huisman, J., Leroy, P., Tertre, F., Söderman, M. L., Chancerel, P., Cassard, D., Løvik, A. N., Wäger, P., Kushnir, D., Rotter, V. S., Mähltitz, P., Herreras, L., Emmerich, J., Hallberg, A., Hina Habib, Wagner, M., & Downes, S. (2017). *Prospecting Secondary Raw Materials in the Urban Mine and mining wastes (ProSUM) —Final Report*. <https://doi.org/10.13140/RG.2.2.10451.89125>
- Intergovernmental Panel on Climate Change (IPCC). (2022). *Climate Change and Land*. Cambridge University Press. <https://doi.org/10.1017/9781009157988>
- International Energy Agency (IEA). (2022). *World Energy Outlook 2022*. International Energy Agency (IEA). <https://iea.blob.core.windows.net/assets/830fe099-5530-48f2-a7c1-11f35d510983/WorldEnergyOutlook2022.pdf>
- International Energy Agency (IEA). (2023a). *Critical Minerals Market Review 2023*. International Energy Agency (IEA). <https://www.iea.org/reports/critical-minerals-market-review-2023>
- International Energy Agency (IEA). (2023b). *Energy Technology Perspectives 2023*. <https://doi.org/10.1787/7c6b23db-en>
- International Energy Agency (IEA). (2023c). *Global Energy and Climate Model*. International Energy Agency (IEA). <https://www.iea.org/reports/global-energy-and-climate-model>
- International Energy Agency (IEA). (2025). *Global Critical Minerals Outlook 2025*. International Energy Agency (IEA). <https://www.iea.org/reports/global-critical-minerals-outlook-2025>

- Li, F.-Q., Wang, P., Chen, W., Chen, W.-Q., Wen, B., & Dai, T. (2022). Exploring recycling potential of rare, scarce, and scattered metals: Present status and future directions. *Sustainable Production and Consumption*. <https://doi.org/10.1016/j.spc.2022.01.018>
- Mahmoud, M., Liu, Y., Hartmann, H., Stewart, S., Wagener, T., Semmens, D., Stewart, R., Gupta, H., Dominguez, D., Dominguez, F., Hulse, D., Letcher, R., Rashleigh, B., Smith, C., Street, R., Ticehurst, J., Twery, M., Delden, H. van, Waldick, R., ... Winter, L. (2009). A formal framework for scenario development in support of environmental decision-making. *Environmental Modelling & Software*. <https://doi.org/10.1016/j.envsoft.2008.11.010>
- Mancini, L., De Camillis, C., & Pennington, D. (2013). *Security of supply and scarcity of raw materials: Towards a methodological framework for sustainability assessment*. European Commission. <https://doi.org/10.2788/94926>
- Mononen, T., Kivinen, S., Kotilainen, J. M., & others. (2022). *Social and Environmental Impacts of Mining Activities in the EU*. European Commission. [https://www.europarl.europa.eu/thinktank/en/document/IPOL_STU\(2022\)729156](https://www.europarl.europa.eu/thinktank/en/document/IPOL_STU(2022)729156)
- OECD. (2012). OECD Environmental Outlook to 2050. In *OECD Environmental Outlook*. OECD. <https://doi.org/10.1787/9789264122246-en>
- Parajuly, K., Kuehr, R., Awasthi, A. K., & others. (2019). *Future E-waste Scenarios*. United Nations Environment Programme (UNEP), International Environmental Technology Centre (IETC), United Nations University (UNU), United Nations Institute for Training and Research (UNITAR). <https://www.unep.org/ietc/resources/publication/future-e-waste-scenarios>
- Pardo, R., & Schweitzer, J. P. (2018). *A Long-term Strategy for a European Circular Economy – Setting the Course for Success* [Policy Paper]. Think2030.
- Singhal, D., Tripathy, S., & Jena, S. K. (2020). Remanufacturing for the circular economy: Study and evaluation of critical factors. *Resources, Conservation and Recycling*. <https://doi.org/10.1016/j.resconrec.2020.104681>
- Skea, J., van Diemen, R., Portugal-Pereira, J., & others. (2021). Outlooks, explorations and normative scenarios: Approaches to global energy futures compared. *Technological Forecasting and Social Change*. <http://dx.doi.org/10.1016/j.techfore.2021.120736>
- Steubing, B., Mutel, C., Suter, F., & others. (2016). Streamlining scenario analysis and optimization of key choices in value chains using a modular LCA approach. *The International Journal of Life Cycle Assessment*.
- United Nations Economic Commission for Europe (UNECE). (2023). *United Nations Framework Classification for Resources (UNFC)*. United Nations Economic Commission for Europe (UNECE). <https://unece.org/sustainable-energy/sustainable-resource-management/united-nations-framework-classification>

Appendices

A1. Terminology definitions

Table A1. To promote clarity in the scenario development process, the following set of terminology was defined for use in discussions, reports, and other stakeholder interactions. This glossary was modelled on that of Skea (2021), with additional definitions sourced from Arizona (2023).

Term	Meaning	Context level	Also called	Source
Scenario	An outline or model of an expected or supposed sequence of events. Plausible descriptions of how the future may develop based on a coherent and internally consistent set of assumptions about key driving forces. Plausible futures of a system under different conditions; “scenario” as a “hypothetical sequence of events constructed for the purpose of focusing attention on causal processes and decision points.	Highest level	Pathway, future typology	Arizona, 2023
Normative scenario	Goal-oriented scenario: identify decisions and investments that must be made to achieve desired future outcomes. Example: Constraining cumulative emissions.	Scenario type	Backcasting	Skea, 2021
Exploratory scenario	Exploration of plausible alternative developments to test whether decision-making is robust against different outcomes. Generally, involving a qualitative storyline about a possible future, complemented by quantitative analysis. Example: Socio-economic scenarios.	Scenario type	Plausible scenarios	Skea, 2021
Outlook	To provide a most likely estimate of future trends as a guide for decision-making.	Scenario type	Forecast, projection	Skea, 2021
Scenario characteristics	A combination of the vague attributes that make up the qualitative storyline for a scenario. For example, in WEC (2019) the scenario titled Modern Jazz is described as: “A market-led, digitally disrupted world with faster-paced and more uneven economic growth. Recent signals suggest that this entrepreneurial future might accelerate clean energy access on both global and local scales, whilst presenting new systems’ integration, cybersecurity, and data privacy challenges”.	Scenario description	Qualitative storyline descriptors	Skea, 2021
Scenario scale	Description of the spatial extent or temporal extent of a scenario. For us, mostly EU toward 2050.	Scenario component		Arizona, 2023
Scenario dimensions	Uncertainties around which scenarios are constructed, represented as axes	Scenario component		Arizona, 2023

Term	Meaning	Context level	Also called	Source
	in some methods. In our case they might end up being, level of circularity, free-trade/autarky, progress in energy transition.			
Scenario literature	Journal articles, grey literature, etc., from which data is sourced that can be used to justify decisions in scenario development.	Scenario component		Skea, 2021
Scenario logics	Methods for structuring the relationships between different drivers and assumptions in scenarios	Scenario component		Arizona, 2023
Time horizon	End date of the scenario's forecast	Scenario attribute		Skea, 2021
Snapshot	The position of scenario/s at a particular point of time	Scenario attribute		Skea, 2021
Storyline and simulation	Combination of qualitative narrative development and quantitative modelling	Scenario component		Arizona, 2023
Marker scenario	Generally, a widely accepted scenario which can be used a guide or to provide background information. E.g., SSP1-5, and the GEC models from the IEA. If applicable, these can be extended upon or combined to help build our models.	Scenario description	Basis scenario	Skea, 2021
SSP	Shared Social Pathways. They “describe plausible major global developments that together would lead in the future to different challenges for mitigation and adaptation to climate change. The SSPs are based on five narratives describing alternative socio-economic developments, including sustainable development, regional rivalry, inequality, fossil-fuelled development, and middle-of-the-road development. The long-term demographic and economic projections of the SSPs depict a wide uncertainty range consistent with the scenario literature.”	Marker scenario examples		(Intergovernmental Panel on Climate Change (IPCC), 2022)
Drivers	Underlying causes of system change that are external from the system of analysis. They come from higher scales and are not affected by what happens within the system.	Scenario component	Factors	Arizona, 2023
Factors	Causes of system change that are internal from the system of analysis. Can be (hopefully) quantified, or at least estimated	Scenario component (internal)		Skea, 2021
Factor variables	Discrete elements which are subject to change and have effects on one or more factors	Factor component		Skea, 2021

Term	Meaning	Context level	Also called	Source
Factor parameters	Discrete elements which are NOT subject to change (possibly based on assumptions and simplifications) and have effects on one or more factors	Factor component		Skea, 2021
Trends	An inclination in a particular direction	Attribute of drivers or factors	System development	Skea, 2021
Likelihood	The likelihood of an occurrence, an outcome, or a result, where this can be estimated probabilistically	Attribute of drivers or factors	Probability	Arizona, 2023
Virtually certain	>99/% probability of occurrence	Attribute of drivers or factors	Probability	Arizona, 2023
Very likely	>90%	Attribute of drivers or factors	Probability	Arizona, 2023
Likely	>66%	Attribute of drivers or factors	Probability	Arizona, 2023
More likely than not	>50%	Attribute of drivers or factors	Probability	Arizona, 2023
About as likely as not	33–66%	Attribute of drivers or factors	Probability	Arizona, 2023
Unlikely	<33%	Attribute of drivers or factors	Probability	Arizona, 2023
Very unlikely	<10%	Attribute of drivers or factors	Probability	Arizona, 2023
Exceptionally unlikely	<1%	Attribute of drivers or factors	Probability	Arizona, 2023

A2. Scenario development methods

Table A2. A summary of the methods and tools considered, including a brief description of each and its relevance to the specific context and objectives of the FutuRaM scenario development process.

Method	Description	Key Characteristics
Delphi	Structured expert consultation to gather and distil knowledge and judgments	Iterative rounds of surveys/questionnaires,

Method	Description	Key Characteristics
MCA	Decision-support technique to evaluate and rank scenarios based on criteria	Expert consensus building Consideration of multiple dimensions in quantifying qualitative factors
Forecasting	Use of historical data and statistical methods to predict future trends	Reliance on quantitative models, Time series analysis
Backcasting	Working backward from a desired future vision to identify necessary steps	Focus on desired outcomes and future targets, Identification of necessary actions
Scenario Planning	Development of multiple future scenarios to understand the range of possibilities	Identification of key drivers and uncertainties, Narrative construction for each scenario
Morphological Analysis	Exploration of different combinations of variables/factors	Matrix-based exploration of variables and combinations
Cross-Impact Analysis	Analysis of interdependencies and interactions between variables/factors	Identification of relationships and cross-impacts
Morphological Box	Systematic exploration of the potential combinations of different components	Identification of component options and combinations
Gausemeier approach	A scenario development method involving the identification of future developments, evaluation of influencing factors, and determination of desired and undesired developments	Systematic analysis of future developments and factors
Schwartz' 8-Step Scenario Model	Scenario building model consisting of eight steps: identify the focal issue, determine the key forces, construct the scenario framework, identify driving forces, assess the uncertainties, develop the scenarios, analyse the scenarios, and monitor and adjust the scenarios	Systematic progression through stages of scenario development
Schoemaker's 10-Step Scenario Model	Scenario building model consisting of ten steps: identify the focal issue, determine the scope, identify the key driving forces, develop the scenarios, define the scenario logic, assess the scenarios, refine the scenarios, examine implications, formulate actions, and communicate results	Emphasis on thorough analysis and evaluation of scenarios

A3. Overview of relevant policy documents

Table A3. An overview of policy actions identified as relevant to the future supply of secondary raw materials (2RMs) in the EU

Policy	Country	Year	Status	Jurisdiction
EU Directive 2006/66/EC Battery Directive	EU	2006	In force	International
Royal Decree 975/2009 about environmental protection and extractive industries	Spain	2009	In force	National
Finland's Minerals Strategy	Finland	2010	In force	National
Resource Security Action Plan	UK	2012	In force	National
Supply of Mineral Resources (SoS MinErals)	UK	2012	In force	National
Horizon 2020: Climate action, environment resource efficiency, and raw materials	EU	2013	Ended	International
National Strategy for Energy Research	France	2016	In force	National
European Battery Alliance	EU	2017	In force	National
Resources for France Plan	France	2018	In force	National
Battery fund: 3.2 billion euros for research and innovation	EU	2019	In force	International
EU Sustainable Batteries Regulation	EU	2020	Announced	Regional
Green Deal: Circular Economy Action Plan	EU	2020	In force	International
Circular Economy Action Plan	Spain	2021	In force	National
Horizon Europe Strategic Plan (2021 – 2024)	EU	2021	In force	International
National Battery Strategy 2025	Finland	2021	In force	National
National Planning Policy Framework	UK	2021	In force	National
Minerals Security Partnership	EU	2022	Announced	International
Resilience for the future: The UK's critical minerals strategy	UK	2022	In force	National
European Institute of Innovation and Technology: Raw Materials Project Call	EU	2023	Announced	International

A4. Overview of marker scenarios

Table A4. An overview of marker scenarios identified as relevant to the future supply of secondary raw materials (2RMs) in the EU

Literature	Type	Waste Stream	Temporal Coverage	Location	Number of scenarios	Link
The Shared Socioeconomic Pathways (SSPs) and their energy, land use, and greenhouse gas emissions implications: An overview	Academic	All	Scenario to 2100	Global	5 SSPs	∞

Literature	Type	Waste Stream	Temporal Coverage	Location	Number of scenarios	Link
Environmental Impacts of Global Offshore Wind Energy Development until 2040	Academic	CDW	Scenario: 2019–2040	Global	4 (based on IEA)	∞
Global greenhouse gas emissions from residential and commercial building materials and mitigation strategies to 2060	Academic	CDW	Scenario: 2020–2060	Global	2 (based on SSP2)	∞
Modelling global material stocks and flows for residential and service sector buildings towards 2050	Academic	CDW	Scenario: 2020–2060	Global	1 (SSP2)	∞
The evolution and future perspectives of energy intensity in the global building sector 1971–2060	Academic	CDW	Scenario: 2020–2060	Global	1 (SSP2)	∞
Tracking Construction Material over Space and Time Prospective and Geo-referenced modelling of Building Stocks and Construction Material Flows	Academic	CDW	Scenario to 2060	Global	6	∞
Global construction materials database and stock analysis of residential buildings between 1970–2050	Academic	CDW	Scenario to 2060	Global	1 (SSP2)	∞
A comprehensive set of global scenarios of housing, mobility, and material efficiency for material cycles and energy systems modelling	Academic	CDW	Scenario to 2060	Global	Low energy demand, SSP1, SSP2	∞
Global scenarios of resource and emission savings from material efficiency in residential buildings and cars	Academic	CDW, ELV	Scenarios to 2050	Global	SSP1, SSP2	∞
Matching global cobalt demand under different scenarios for co-production and mining attractiveness	Academic	BAT	2050	Global	5	∞
Copper at the crossroads: Assessment of the interactions between low-carbon energy transition and supply limitations	Academic	Copper	2050	Global	2: 2 °C and 4 °C	∞
The impact of climate policy implementation on lithium, cobalt and nickel demand: The case of the Dutch automotive sector up to 2040	Academic	ELV, Batteries	Scenario: 2019–2040	NL	2 (Based on policies)	∞
The rise of electric vehicles—2020 status and future expectations	Academic	ELV, BAT	up to 2050	Global	various	∞
Scenarios for the Return of Lithium-ion Batteries out of Electric Cars for Recycling	Academic	ELV, Battery	Scenario to 2050	Global	2	∞
The dynamic equilibrium mechanism of regional lithium flow for	Academic	ELV, BAT	Scenario to 2050	Global	1 (projection)	∞

Literature	Type	Waste Stream	Temporal Coverage	Location	Number of scenarios	Link
transportation electrification						
Future material demand for automotive lithium-based batteries	Academic	ELV, BAT	Scenario to 2050	Global	4 (based on IEA)	∞
Analysis of the Li-ion battery industry in light of the global transition to electric passenger light-duty vehicles until 2050	Academic	ELV, BAT	Scenario to 2050	Global	Combination of SSPs and RCPs	∞
Circular economy strategies for electric vehicle batteries reduce reliance on raw materials	Academic	ELV, BAT	Scenario to 2050	Global	Reference + 4 technologies	∞
Summary and critical review of the International Energy Agency's special report: The role of critical minerals in clean energy transitions	Academic	Energy	2050	Global	n/a	∞
Review of critical metal dynamics to 2050 for 48 elements	Academic	Energy	Scenario to 2050	Global	1 compiled from various renewable technologies	∞
Major metals demand, supply, and environmental impacts to 2100: A critical review	Academic	Energy	Scenario to 2100	Global	1 review of 197 studies	∞
Requirements for Minerals and Metals for 100% Renewable Scenarios	Academic	Energy	Scenario to 2050	Global	1.5 degree scenario	∞
The 3-machines energy transition model: Exploring the energy frontiers for restoring a habitable climate	Academic	Energy	2100	Global	20, rapid transition stabler 1.5 °C and return to 350 ppm	∞
Modelling the demand and access of mineral resources in a changing world	Academic	Energy, Construction	2060	Global	RTS, BD2S IEA	∞
Rare earths in the energy transition: what threats are there for the 'vitamins of modern society'?	Academic	Rare earths	2050	Global	2: 2°C and 4°C	∞
A slag prediction model in an electric arc furnace process for special	Academic	SLASH	None	Global	n/a	∞

Literature	Type	Waste Stream	Temporal Coverage	Location	Number of scenarios	Link
steel production						
Decarbonising the iron and steel sector for a 2°C target using inherent waste streams	Academic	SLASH	Scenario to 2050	Global	1 (2 degree climate goal)	∞
Environmental Implications of Future Demand Scenarios for Metals: Methodology and Application to the Case of Seven Major Metals	Academic	Various	Scenario to 2050	Global	4 (UN GEO-4)	∞
Resource Demand Scenarios for the Major Metals	Academic	Various	Scenario to 2050	Global	4 (UN GEO-4)	∞
Raw material depletion and scenario assessment in European Union – A circular economy approach	Academic	Various	None	EU	n/a	∞
Material bottlenecks in the future development of green technologies	Academic	Various	Scenario to 2050	Global	1 (BAU)	∞
Reuse assessment of WEEE: Systematic review of emerging themes and research directions	Academic	WEEE	None	Global	n/a	∞
A systematic literature review on the circular economy initiatives in the European Union	Academic	Circularity	None	EU	Circular strategies	∞
Material Flow Accounting: Measuring Global Material Use for Sustainable Development	Academic	Various	Scenario to 2100	Global	1 (BAU)	∞
Circular Economy Action Plan	Action plan	Various	Scenario to 2050	EU	35 actions to climate neutrality	∞
Construction and demolition waste: challenges and opportunities in a circular economy	Report	CDW	None	EU	n/a	∞
IEA world energy model	Report	Energy	Scenario to 2050	Global	4	∞
Bloomberg scenarios	Report	Energy	Scenario to 2050	Global	3	∞
The Role of Critical Minerals in Clean Energy Transitions	Report	Energy	None	Global	n/a	∞
Transitions to 2050 decide now act for climate	Report	Energy	Scenario to 2050	France	4 to reach 2.1C by 2100	∞
Raw materials demand for wind and solar PV technologies in the	Report	Energy	Scenario to 2050	EU	low and high	∞

Literature	Type	Waste Stream	Temporal Coverage	Location	Number of scenarios	Link
transition towards a decarbonised energy system					material demand scenarios	
Inventaires des besoins en matière, énergie, eau et sols des technologies de la transition énergétique	Report	Energy	Scenario to 2050	France	1	∞
Minerals in the future of Europe	Report	MinW	Scenario to 2050	EU	3 (2050 net-zero, digital, circular)	∞
Minerals, Critical Minerals and the US Economy	Report	MinW	None	US	n/a	∞
Minéraux stratégiques — État des lieux et propositions pour une vision partagée	Report	MinW	None	FR	n/a	∞
The Critical Raw Materials (CRM) initiative – Underpinning the strategic approach to the EU’s raw materials policy	Report	MinW	None	EU	n/a	∞
Towards the Circular Economy: Accelerating the scale-up across global supply chains	Report	Circularity	None	Global	n/a	∞
The Circular Economy in Europe	Report	Circularity	None	EU	n/a	∞
Global material flows and resource productivity: Forty years of evidence	Report	Circularity	None	Global	n/a	∞
The circular economy concept: contextualisation and multiple perspectives	Report	Circularity	None	Global	n/a	∞
Global material flows database	Database	Various	None	Global	n/a	∞
International Resource Panel	Reports	Various	None	Global	n/a	∞
World Business Council for Sustainable Development	Reports	Various	None	Global	n/a	∞
Ellen MacArthur Foundation	Reports	Various	None	Global	n/a	∞
European Environment Agency	Reports	Various	None	EU	n/a	∞
International Energy Agency	Reports	Energy	None	Global	n/a	∞
United Nations Environment Programme	Reports	Various	None	Global	n/a	∞

Literature	Type	Waste Stream	Temporal Coverage	Location	Number of scenarios	Link
United Nations Industrial Development Reports	Reports	Various	None	Global	n/a	∞
World Bank	Reports	Various	None	Global	n/a	∞
World Economic Forum	Reports	Various	None	Global	n/a	∞

A5. Scenario elements identified in the initial collection phase

Table A5. A list of scenario elements identified in the initial phase of driver/factor collection by FutuRaM stakeholders

Driver	Definition
Accessibility	Ease of access to goods, services, or infrastructure
Accessibility/Infrastructure	Availability and adequacy of infrastructure to support accessibility
Availability of recovery technologies	Existence and accessibility of technologies for material recovery
Change of products in the scope WEEE directive	Inclusion or exclusion of certain products within the scope of the WEEE directive
Climate change impacts (flooding, etc.)	Consequences of climate change, such as increased flooding or extreme events
Climate change mitigation efforts	Actions taken to reduce greenhouse gas emissions and combat climate change
CO ₂ market	Trading system for carbon emissions permits or credits
Compliance with rules	Adherence to regulations, guidelines, or standards
Composition change	Alteration or modification of the composition of materials or products
Conflict in supply chain	Disputes or conflicts within the supply chain of raw materials or products
Corruption	Dishonest or unethical behaviour, typically involving misuse of power
Cultural values / Consciousness	Beliefs, attitudes, and awareness of individuals and society
Data protection	Safeguarding personal data and ensuring privacy
Digital product passports	Digital documentation providing information about a product's lifecycle
Digitalization	Integration and adoption of digital technologies and processes
Ecodesign	Designing products with consideration for their environmental impact
Education level	Level of education attained by individuals or the overall population

Driver	Definition
Electricity price	Cost of electricity for consumers or businesses
Employment rates	Percentage of the working-age population that is employed
Energy efficiency of buildings	Performance and efficiency of energy consumption in buildings
Exchange rates	Value of one currency relative to another currency
Gasoline/petrol price	Cost of gasoline/petrol for vehicles
GDP/PPP	Gross Domestic Product (GDP) adjusted for purchasing power parity (PPP)
Improved durability	Enhanced longevity and resistance of products or materials
Improved recyclability	Increased ability of products or materials to be recycled or reused
Improved repairability	Enhanced ability to repair and maintain products or equipment
Increased intrinsic drive for environmental protection	Growing internal motivation to protect and conserve the environment
Industrialization of Europe	Development and growth of industrial activities in European countries
Inflation	Increase in the general price level of goods and services over time
Infrastructure	Physical structures and facilities necessary for the functioning of society
Intellectual property issues	Legal rights and protections for intellectual creations and innovations
Interest rates	Cost of borrowing money or the return on investment
Land rights	Legal rights to ownership, use, or access to land
Material efficiency	Effective use and management of materials to minimize waste and loss
Miniaturization	Process of making products or components smaller and more compact
New mines in rich EU countries?	Establishment of new mines in economically prosperous European countries
NIMBY to projects	Not-In-My-Backyard opposition to the location of certain projects
Obligatory recycling standards for treatment facilities	Mandatory standards for recycling processes in treatment facilities
Obligatory removal of CRMs from waste	Required removal or extraction of critical raw materials from waste streams
Obsolescence	State of being outdated or no longer in use or demand
Population	Total number of people in a given area or region
Product prices	Prices of goods or products in the market
Raw material prices	Prices of primary materials used in production processes

Driver	Definition
Recyclability mandates	Requirements or regulations promoting the recyclability of products
Reduced consumerism	Shift towards decreased consumption and a more sustainable lifestyle
Redundancy	Availability of backup systems or alternative options
Renewable energy targets	Set goals or objectives for increasing the use of renewable energy sources
Repairability mandates	Requirements or regulations promoting the repairability of products
Resource shortage	Insufficient availability or scarcity of natural resources
Sharing economy	Economic system based on sharing resources and services
2RM prices	Prices of secondary raw materials or recycled materials
Stricter environmental regulations	Increased regulations and policies aimed at reducing environmental impact
Subsidies	Financial support or incentives provided by governments or organizations
Supply chain due diligence laws	Regulations or laws requiring companies to assess and manage supply chain risks
Target enforcement	Implementation and enforcement of specific targets or goals
Taxation (raw materials, landfill)	Imposition of taxes on raw materials or landfill activities
Trade barriers	Barriers or restrictions to international trade or commerce
Transparency	Openness, accountability, and information accessibility
Treatment cost	Cost of waste treatment, disposal, or recycling processes
Urbanisation	Increase in the population living in urban areas
Volunteering	Engagement in unpaid activities for the benefit of others
Water supply constraints	Limitations on the availability or access to freshwater resources
Work-life balance	Equilibrium between work and personal life

611

A6. Scenario drivers and factors categorised for quantification in subsequent modelling

Table A6. A list of the scenario elements categorised for quantification. The Roman numerals in the columns BAU, REC, and CIR represent the magnitude of the future trend for the element in the scenario. Internal, external, and outside refer to the classification type of the scenario element.

Domain	Element	Internal	External	Outside	BAU	REC	CIR	Model Parameters Affected
Economic	Subsidies and taxation to promote circular strategies	✓			I	I	III	Demand, waste generation, lifetimes, sharing, collection,
Political	Targets and enforcement to promote circular strategies	✓			I	I	III	Demand, waste generation, lifetimes, sharing, collection
Society	Participation in re-X activities	✓			I	I	III	Demand, waste generation, lifetimes, sharing, collection,
Economic	Subsidies and taxation to promote recovery strategies	✓			I	III	I	Recycling rates, recovery capacity, recovery impacts, collection
Political	Targets and enforcement to promote recovery strategies	✓			I	III	I	Recycling rates, recovery rates, capacity
Political	Supply chain due diligence laws	✓			I	III	III	Composition, export
Political	Stricter environmental regulations	✓			I	III	III	Composition, waste generation, lifetimes, export, recovery rates, recovery capacity, recovery impacts
Political	Stricter waste management regulations	✓			I	III	III	Composition, waste generation, lifetimes, export, recovery rates, recovery capacity, recovery impacts
Technology	Product technology	✓			I	III	III	Lifetimes, recovery rates, recovery impacts
Technology	Recovery technology	✓			I	III	III	Recovery rates, recovery capacity, recovery impacts
Technology	Integration of 2RM recovery system across Europe	✓			I	III	III	Recycling rates, recovery rates, recovery capacity, recovery impacts
Economic	Progress toward renewable energy targets		✓		stable	stable	stable	Composition, demand, waste generation, recovery impacts
Economic	Economic growth		✓		stable	stable	stable	Composition, demand, waste generation
Society	Population		✓		stable	stable	stable	Demand, waste generation

Domain	Element	Internal	External	Outside	BAU	REC	CIR	Model Parameters Affected
Economic	Primary vs. secondary raw material prices		✓		n/a	n/a	n/a	Considered in sensitivity analysis
Economic	Energy prices		✓		n/a	n/a	n/a	Considered in sensitivity analysis
Economic	Carbon price		✓		n/a	n/a	n/a	Considered in sensitivity analysis
Environment	Resource supply constraints		✓		n/a	n/a	n/a	Considered in sensitivity analysis:
Economic	International trade and co-operation (vs. autarky)			✓	n/a	n/a	n/a	Not model input (resource supply constraints is a proxy)
Economic	Re-industrialisation of EU			✓	n/a	n/a	n/a	Not model input
Society	Resistance to recovery projects (NIMBY)			✓	n/a	n/a	n/a	Not model input (considered in NFC assessments)

A7. Waste-stream-specific scenario impacts

5.1.1 Scenario I: Business-as-usual (BAU)

Batteries (BATT)

In the BAU scenario, the management of end-of-life batteries remains largely unchanged. The lack of technological innovation and regulatory incentives leads to continued low recovery rates of valuable materials from battery waste.

- A growing volume of battery waste due to the increased use of electronic transport and renewable energy storage systems.
- Lack of technological innovation and regulatory incentives lead to low recovery rates for certain battery types and certain elements.
- Collection systems for battery waste remain sporadic and unstandardised.
- Primary extraction remains the dominant source of battery materials.
- Share of LIB will increase (EV, LMT, Industrial LIB uptake).
- LIB battery chemistries will change, and new LIB technologies will enter the market, though not with a focus on recycling and recovery.
- Larger portable batteries: shift towards lithium-ion batteries.

- 624 • Small format batteries in EEE: no significant change in battery chemistry.
 - 625 • Use of critical resources continues but is already decreasing (BATT chemistry already changing towards less CRM content).
 - 626 • Large-scale reuse of batteries is minimal.
 - 627 • Collection rates do not fulfil the EU targets.
 - 628 • Recycling efficiencies do not fulfil the EU targets.
 - 629 • Recovery rates do not fulfil the EU targets.
-

630 **End-of-life Vehicles (ELV)**

631 The BAU scenario maintains the current approach to end-of-life vehicles, with minimal improvements in the recovery and recycling process. The absence of effective
632 technologies and regulatory incentives results in low recovery rates of valuable materials from ELVs.

- 633 • Legislation banning new internal combustion engine vehicles from 2035.
 - 634 • Current recovery technologies are unable to significantly improve the extraction of valuable materials from ELVs.
 - 635 • Consumer demand continues to drive high production of new vehicles.
 - 636 • ELV collection systems remain at their current efficiency.
 - 637 • A significant proportion of vehicle components continue to end up as waste.
 - 638 • Gradual and slow improvement of recycling chain technology efficiency.
 - 639 • No new legislation to improve recovery and support circular strategies compared to 2023.
-

Waste Electrical and Electronic Equipment (WEEE)

In the BAU scenario, the treatment of WEEE does not significantly change. The lack of technological progress and effective regulation results in low recovery rates of valuable materials from WEEE.

- Limited improvements in the recovery of valuable materials from WEEE.
- High consumer demand for new electronics continues to drive high WEEE generation.
- Ineffective collection systems and lack of public interest result in significant amounts of WEEE ending up in landfills.
- No significant growth in collaboration between government and industry for WEEE recovery.
- The majority of WEEE continues to be treated with common domestic waste, with low recycling rates.
- No groundbreaking technologies and practices to improve recovery and circularity.
- Reuse of products and components is not widely utilised.
- Changes in legislation (e.g., circular economy and product design targets, targets for collection and recycling) are not strictly implemented.
- The BAU and REC scenarios are similar from the put-on-market perspective (production and consumption remain the same), but the recovery stage makes the difference.

Mining Waste (MIN)

The BAU scenario sees the continuation of current practices in mining waste management. The absence of advanced recovery technologies and regulatory incentives leads to low recovery rates of valuable materials from mining waste.

- Limited technological advancements lead to static recovery rates of valuable materials from mining waste.
- Continued reliance on primary extraction as the dominant source of raw materials.
- Minimal advances in collaboration between government and industry for mining waste recovery.

- Low levels of traceability and management of mining waste.
 - Mining waste remains a significant environmental challenge.
 - Mining waste recovery projects remain too expensive.
 - Little incentive for the private sector and public sector, except for monitoring environmental risks of existing deposits.
-

Construction and Demolition Waste (CDW)

In the BAU scenario, the management of CDW remains largely unchanged.

- Focus on new construction to meet demand, no changes in CDW generation rate.
 - No increase in refurbishment or renovation activities relative to new construction rates.
 - Continue meeting the 2020 EU target from the Waste Directive of 70% CDW recovery (including preparation for re-use, recycling, and other material recovery, including backfilling).
 - Recovery of metals remains at already high levels (>90%).
 - Recovery of minerals remains at already high levels (>70%) by using them as aggregates in road construction and backfilling.
 - Recycling of wind turbines stays around 85% (mainly metals); permanent magnets continue to be recycled as part of the metal fractions.
 - Base metals are recovered as before, with limited improvements in recovery technologies and regulatory incentives.
 - Repowering trends for wind turbines persist.
 - Excluding wind turbines, there is no particular focus on the recovery of CRMs from CDW, where they constitute only a small fraction of the total mass (e.g., embedded in scrap steel).
-

Slags, Ashes, and Other Residues (SLASH)

In the BAU scenario, SLASH continues to be treated as low- or negative-value waste. The absence of economically profitable recovery technologies or regulatory mandates leads to low improvements in the recovery rates of CRMs from SLASH.

Slags

Slags are waste products from the metallurgical industry, containing mainly minerals with some metals that could not be recovered during the metallurgical process.

Reasons for non-recovery include:

1. Current technology does not allow further recovery.
 2. The metals are not of economic interest.
- More than 90% of slags are minerals; slags that meet environmental criteria (end-of-waste criteria) are valorised as aggregates for the construction industry or as SCM (cement replacement materials).
 - Slags containing high concentrations of heavy metals are landfilled.
 - The volume of slags will stay stable. From 2013 to 2023, metal production was stable, resulting in stable slag production.
 - Due to the energy transition, slags from “classic” furnaces will decrease, while slags from electric arc furnaces will increase.
 - Limited facilities exist to recover CRMs/2RMs; metallurgical companies recover as much metal as is economically viable.

Ashes

Ashes are waste products from the incineration of fossil fuels, biomass, or waste. Two main types exist: fly ashes and bottom ashes.

- Coal fly ashes are used to replace cement up to 30%.
- Biomass ashes (bottom and fly) are used as fertiliser or landfilled, depending on composition.

- Fly ashes from waste incineration are landfilled; bottom ashes are further treated in some EU countries.

From bottom ashes, fractions rich in Fe, Al, Cu, and Zn are separated for reuse in industry; Cu-rich fractions also yield PGMs, Ag, and Au. The mineral aggregates portion is used in construction if it meets environmental criteria; untreated ashes are landfilled.

- In the last 10–20 years, some EU countries shifted from landfilling to incineration, increasing ash volumes from waste incineration.
- Coal use declined, reducing coal ash volumes; further decline is expected.
- Biomass incineration increased; future trends uncertain due to land use pressures.
- Almost all coal fly ashes are used as SCM (high-value stream up to €80/ton).
- Biomass fly ashes lack sorting facilities; waste incineration bottom ashes have sorting facilities in some countries, but coverage is incomplete, leaving room for improvement.

5.1.2 Scenario II: Recovery (REC)

Batteries (BATT)

Under the recovery scenario, end-of-life batteries become a crucial source of secondary raw materials, primarily due to the increased adoption of electric vehicles and renewable energy storage systems. Technological innovation drives the recovery and recycling process, ensuring valuable materials are extracted from waste batteries for reuse.

- Increase in end-of-life batteries due to the growth of electric vehicles and renewable energy storage.
- Advanced recovery technologies facilitate the efficient extraction of valuable materials from battery waste.
- Standardised collection systems enhance the quantity and quality of battery waste available for recovery.
- Collaboration between industry and government lead to investments in research and development of battery recovery technologies.

- 712 • Battery passports have a strong impact on collection, material recovery rates and recycling rates.
- 713 • Collection:
 - 714 • Portable battery collection increases according to the trend seen in the WEEE waste stream.
 - 715 • Improved collection of light means of transport batteries.
 - 716 • Improved regulation and collection of industrial batteries.
- 717 • Material recovery:
 - 718 • Improved recycling technologies.
 - 719 • Battery Pass will improve material recovery.
 - 720 • Higher recovery rate for lithium.
 - 721 • Increase in recycling by average weight.
 - 722 • Recycling of plastics.
- 723 • Ambitious goals of recycling/recovery rates compete with reuse, so reuse remains low.
- 724 • Improved public awareness means fewer batteries end up in the municipal waste stream and less hoarding.
- 725 • There is competition for the batteries from the reuse vs. recycling market.
- 726 • Design for recycling:
 - 727 • Material and composition selection for recycling.
 - 728 • Higher requirements on design for disassembly.
 - 729 • Information available to promote efficient recovery.

End-of-life Vehicles (ELV)

The recovery scenario envisions a more effective and technology-driven end-of-life vehicle treatment process. Advancements in recovery technologies allow for improved extraction of valuable materials from vehicles at their end of life, although consumerism still drives high demand for new vehicles.

- Innovations in recovery technologies allow for a higher recovery rate of CRM-containing materials from ELVs.
- The total number of vehicles produced remains high due to consumer demand.
- Improved systems for ELV collection are established, ensuring efficient management of ELV waste.
- Increased collaboration between the government and industry leads to investments in ELV recovery technologies.
- Focus on managing the end-of-life of vehicles.
- EU recovery targets are reached (current and proposed targets, including increased and new targets).
- Common/bulk materials (Fe, non-Fe, plastics) and precious metals (Au, Ag, Pd, Pt) reach high mass recycling rates and high element recycling rates. Other CRMs currently not recovered reach a moderate level of recovery.
- For instance:
 - More advanced dismantling and processing steps (e.g., components and materials).
 - More specialised recovery of certain components and materials (e.g., electric motors including permanent magnets and embedded REE) as suggested in the proposal for a revised ELV directive.
 - More public and private interest in developing recycling chains.
 - Increased collection rate due to greater public and business participation, driven by target-based incentives with strong regulations and monitoring.
- Design for recycling:
 - Higher requirements on design for disassembly.

- Information available to enable recovery.

Waste Electrical and Electronic Equipment (WEEE)

Under the recovery scenario, WEEE becomes a significant resource for secondary raw materials. Technological advancements in the sector improve the efficiency of WEEE treatment, although the consumerism-driven demand for new electronics remains high.

- Advanced technologies enable higher recovery rates of valuable materials from WEEE.
- Despite advancements in design for recyclability, WEEE generation remains high due to consumer demand for new electronics.
- Standardised and segregated collection systems for WEEE are implemented, improving the supply of materials for recovery.
- Increased industry-government collaboration leads to further development in WEEE recovery technologies.
- Consumer behaviour remains a significant hurdle for more efficient WEEE management.
- Higher recycling rates — making full use of disposed parts. For instance:
 - More automation of the dismantling and processing steps (e.g., AI).
 - Recycling technology improvements (e.g., small component recovery).
 - More effective collection infrastructure.
 - Financial support provided to recyclers/operators.
 - Bans on WEEE exports push for increased domestic recycling.
- **Design for recovery:** Ecodesign mandates changes in weight and composition of EEE to reduce complexity and improve recoverability.
- Higher public awareness and participation in WEEE management.
- Higher compliance from the public, producers, and businesses.

- Strong regulations and monitoring with higher collection and recycling targets; fines imposed for non-compliance.
- Greater focus on end-of-life management of WEEE.

Mining Waste (MIN)

Under the recovery scenario, technological advancements enable the extraction of residual valuable materials from mining waste, transforming it into a more valuable resource.

- Technological advancements facilitate the extraction of valuable materials from mining waste.
- Despite progress in recovery technologies, primary extraction remains the dominant source of raw materials due to high consumer demand.
- Government and industry collaboration supports the development of technologies for recovering materials from mining waste.
- Increased traceability and management of mining waste through digitalisation.
- Mining waste remains a significant environmental challenge.

Construction and Demolition Waste (CDW)

Sources: (eu2008wastedirective)

Under the recovery scenario, Construction and Demolition Waste (CDW) becomes an important resource for secondary raw materials, though mostly base metals and aggregates. Despite some progress in eco-design and material efficiency, the construction industry continues to generate significant amounts of waste or ‘downcycled’ materials.

- Focus on new construction to meet demand, no change in CDW generation rate.
- No increase in refurbishment or renovation activities.

- Enhancement of recycling quality to recover materials at higher value.
- Increased investment and an enhanced regulatory system in waste management, contributing to higher recovery rates.
- Creation of new waste recovery infrastructure to improve recovery.
- Widespread application of selective demolition and strict on-site waste sorting, increasing recovery of waste.
- Recovery of minerals is intensified with a stronger focus on closed-loop recycling (e.g., cement and aggregate are separated, aggregate is used, but cement is not treated).
- Recovery of other materials such as glass, plastics, and wood is also intensified.
- Better separation of waste at source leads to higher quality secondary raw materials.
- Repowering trends for wind turbines stay the same.
- Improved recycling of wind turbine blades, especially regarding plastics; permanent magnets are recycled at a functional level.

Slags, Ashes, and Other Residues (SLASH)

In the recovery scenario, SLASH is recognised as a potential resource for secondary raw materials. Advances in recovery technologies enable the extraction of valuable metals from SLASH; however, the total volume of CRMs recovered from this material remains low, except in cases of supply constraint.

- Digital solutions enhance the traceability and management of SLASH.
- More functional collection infrastructure.
- Financial support provided to recyclers/operators.
- Introduction of 2RM/CRM recovery targets (e.g., recovery of P from biomass ash for fertiliser).
- Higher awareness and participation of relevant sectors in SLASH issues and management.

- Strong regulations and monitoring with higher collection and recycling targets.

Slags

- Advanced recovery technologies allow for the extraction of valuable metals and minerals from slags.
- New recovery technologies are installed in the metallurgical industry.
- All metals are recovered from the slags; slag itself contains only minerals or trace metal elements.
- Due to low metal content, slags are ideal resources for the construction industry.

Ashes

- New recovery technologies are installed in the incineration industry.
- A shift in the volume and quality of ashes is expected.
- Coal fly ash volumes decrease over time to almost zero.
- Biomass ash volumes and quality remain stable.
- Waste incineration ashes: in the recovery scenario, there is a shift from landfill/incineration towards recycling, reuse, and repair.
 - In high-landfill countries, this will increase ash volumes.
 - In low-landfill, high-incineration countries, ash volumes decrease, and composition changes, with less CRM content due to better pre-sorting.

5.1.3 *Scenario III: Circularity*

Batteries (BATT)

In the circularity scenario, battery waste treatment undergoes a massive transformation. The shift towards electric vehicles and renewable energy storage significantly increases the quantity of end-of-life batteries. However, thanks to new regulations, technological advancements, and business models, the majority of battery components

are recycled or reused.

- Massive increase in end-of-life batteries due to the shift to electric vehicles and renewable energy storage.
- New regulations incentivise battery manufacturers to design for recycling.
- Battery recycling technologies improve, enabling higher recovery rates of valuable metals.
- Standardised collection systems for battery waste are established, improving recycling efficiency.
- Service-based business models such as leasing ensure manufacturers retain ownership of batteries, promoting circularity.
- Greater transparency through digital product passports aids in effective battery waste management.
- Battery passport and publicly accessible information from the new Battery Regulation provided by the economic operator placing the battery on the market enables high re-use rates.
- Increased repairability/modularity.
- Reduced demand from the sharing economy and more sustainable transport choices.
- New emerging technologies better suited for reuse/repair.
- Ambitious targets set by business and public policy.

End-of-life Vehicles (ELV)

For ELVs, the circular economy model affects vehicle design, use, and disposal. Emphasising extended vehicle life through repair and remanufacturing, this scenario also focuses on recovering materials from vehicles at the end of their life.

- Vehicle design shifts towards repairability, upgradability, and recyclability, increasing vehicle lifespan.
- Standardised ELV collection systems are established, ensuring efficient waste management.

- Innovative technologies enable higher recovery rates of metals and other valuable materials from ELVs.
- Service-based models such as vehicle leasing and sharing reduce the total number of vehicles produced.
- Digital product passports provide component information to aid recycling or reuse.
- Focus on managing the use phase of vehicles.
- Circular strategies take place before material recovery, delaying recovery.
- Information is available to enable these strategies.
- EU vehicle policy influences materials in vehicles through lightweighting and downsizing:
 - Increase in average occupancy and vehicle-kilometres per trip.
 - Decrease in average lifetime (in years) as utilisation factors increase.
- Increased circular strategies from greater public and business participation, driven by target-based incentives and strong regulations.

Waste Electrical and Electronic Equipment (WEEE)

In the circularity scenario, WEEE becomes a valuable resource instead of a disposal challenge. Through product design changes and advanced recovery technologies, a significant share of WEEE materials is reclaimed and fed back into production.

- Electronic products are designed for longevity, repairability, upgradability, and recyclability.
- Advanced technologies enable higher recovery rates of precious metals from WEEE.
- Improved WEEE collection systems ensure a steady material supply for recovery.
- Digitalisation and data use enhance traceability and efficiency in WEEE management.
- Service-based models promote product-as-a-service instead of ownership, reducing WEEE generation

- 856 • Increased durability and lifespans.
- 857 • Increased repairability.
- 858 • More sharing and product-service systems, with some equipment having reduced lifetime.
- 859 • Expanded second-hand market.
- 860 • Less hoarding.
- 861 • Higher formal collection and recycling rates.
- 862 • Focus is more on production and use phases than end-of-life.
- 863 • Design for circularity: Ecodesign mandates repairability, durability, no obsolescence, modularity, and continual software upgrades
- 864 • Chargers and batteries are interoperable across products and easily disassembled.
- 865 • Strong regulations and monitoring with higher reuse and circular targets, and fines for non-compliance.
- 866 • Support and infrastructure for circular strategies (e.g., repair shops, spare parts access).
- 867 • Greater use of connected products, smart tech, and IoT to monitor and extend product life.

868 **Mining Waste (MIN)**

869 In this scenario, mining waste impacts are two-fold: primary mining demand drops due to efficiency and recovery rates, and mining waste itself becomes a valuable
870 resource.

- 871 • Decrease in primary mining reduces mining waste generation.
- 872 • Advanced technologies extract valuable materials from mining waste.
- 873 • Policies and regulations incentivise mining waste reuse.

- Digital solutions improve tracking and management of mining waste.
- Stakeholder collaboration promotes circular practices in mining.

Construction and Demolition Waste (CDW)

In the circularity scenario, CDW generation is reduced, and material recovery is improved.

- Less demolition and new construction lowers CDW volumes.
- Buildings designed for disassembly and reuse extend material life and reduce waste.
- Longer lifetimes for buildings and wind turbines (less repowering).
- Wind turbine blades refurbished/repaired for reuse.
- Improved recycling technologies reduce downcycling.
- Policies and regulations incentivise recycled material use in construction.
- Improved CDW collection and separation systems.
- Digital tools improve resource management in construction and renovation.
- Selective deconstruction allows reuse of individual construction components.

Slags, Ashes, and Other Residues (SLASH)

In the circularity scenario, SLASH is recognised as a potential resource for secondary raw materials. Recovery conditions are similar to the recovery scenario, but overall waste generation decreases.

- Digital solutions enhance traceability and management.

- 891 • More functional collection infrastructure.
- 892 • Financial support to recyclers/operators.
- 893 • 2RM/CRM recovery targets (e.g., P from biomass ash for fertiliser).
- 894 • Higher awareness and sector participation in SLASH management.
- 895 • Strong regulations and monitoring with higher collection/recycling targets.

896 **Slags**

- 897 • Advanced recovery technologies extract valuable metals and minerals.
- 898 • New recovery technologies are installed in metallurgical industries.
- 899 • All metals are recovered; slag contains only minerals or trace metals.
- 900 • Slags become ideal resources for the construction industry.

901 **Ashes**

- 902 • New recovery technologies are installed in incineration plants.
- 903 • Shift in ash volumes and quality is expected.
- 904 • Coal fly ash declines to almost zero.
- 905 • Biomass ash volumes and quality remain stable.
- 906 • Waste incineration ashes:
 - 907 • In high-landfill countries, increased volumes due to diversion from landfill.
 - 908 • In low-landfill, high-incineration countries, reduced volumes and less CRM content due to better pre-sorting.