Robotics

Stewart Nash

February 14, 2025

Contents

Chapter 1

Dynamics

1.1 Kinematics

Take a vector with components $\mathbf{P} = (a_x, b_y, c_z)$. A scale factor w can be added (to the matrix form) to give

$$\mathbf{P} = \begin{bmatrix} P_x \\ P_y \\ P_z \\ w \end{bmatrix} \tag{1.1}$$

where $(a_x, b_y, c_z) = (P_x/w, P_y/w, P_z/w)$. A direction vector can be represented by a scale factor of zero ($w = 0$).

A universe reference frame is represented by $F_{x,y,z}$ and a moving frame is represented by $F_{n,o,a}$ where the letters n, o, and a come from the words normal, orientation and approach. Relative to the gripper, the z-axis is the approach axis by which the gripper approaches an object. The orientation with which the gripper frame approaches the part is the orientation axis. The normal-axis or x-axis is normal to both. A fourth vector which gives the location of a frame relative to a reference frame can be added to the vectors representing the components of the n-, o-, and a-axes to give a homogeneous matrix representation of this relative frame

$$F = \begin{bmatrix} 1 & 0 & 0 & d_x \\ 0 & 1 & 0 & d_y \\ 0 & 0 & 1 & d_z \\ 0 & 0 & 0 & 1 \end{bmatrix} \tag{1.2}$$

Pre-multiplying the frame matrix by the transformation matrix will yield the new location of the frame.

Rotation matrices about the x-, y- and z-axes are given by

$$\text{rot}(x, \theta) = \begin{bmatrix} 1 & 0 & 0 \\ 0 & \cos\theta & \sin\theta \\ 0 & \sin\theta & \cos\theta \end{bmatrix}$$

$$\text{rot}(y, \theta) = \begin{bmatrix} \cos\theta & 0 & \sin\theta \\ 0 & 1 & 0 \\ -\sin\theta & 0 & \cos\theta \end{bmatrix} \tag{1.3}$$

$$\text{rot}(z, \theta) = \begin{bmatrix} \cos\theta & -\sin\theta & 0 \\ \sin\theta & \cos\theta & 0 \\ 0 & 0 & 1 \end{bmatrix}$$

Denoting the transformation of frame R relative to frame U (universe) as $^{U}T_R$, denoting the p relative to the frame R as $^{R}p = p_{noa}$, and denoting p relative to frame U as $^{U}p = p_{xyz}$ we have

$$^{U}p = {^{U}T_R} \times {^{R}p} \tag{1.4}$$

1.2   Differential Motion

1.3   Dynamic Analysis

1.4   Trajectory Planning

Chapter 2

Controls

2.1 State Variable Representation

Powerful tools from matrix algebra can be used to solve sets of first-order differential equations. That is why it is sometimes helpful to transform a system described by nth-order differential equations into a system of first-order differential equations.

2.1.1 Systems Modeled by Linear Differential Equations

Consider a system represented by a nth-order, single-input linear constant coefficient differential equation

$$\sum_{i=0}^{n} a_i \frac{d^i y}{dt^i} = u \tag{2.1}$$

This equation can be replaced by n first-order differential equations

$$\begin{cases} \dfrac{dx_k}{dt} = x_{k+1},\ 1 < k < n \\ \dfrac{dx_n}{dt} = \dfrac{1}{a_n}\left[\displaystyle\sum_{k=0}^{n-1} a_k x_{k+1}\right] + \dfrac{1}{a_n}u \end{cases} \tag{2.2}$$

where $x_1 \equiv y$ and $i, k \in \mathbb{W}$. This can be written as a matrix equation

$$\begin{bmatrix} \frac{dx_1}{dt} \\ \frac{dx_2}{dt} \\ \vdots \\ \frac{dx_n}{dt} \end{bmatrix} \begin{bmatrix} 0 & 1 & 0 & \cdots & 0 \\ 0 & 0 & 1 & \cdots & 0 \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ -\frac{a_0}{a_n} & -\frac{a_1}{a_n} & -\frac{a_2}{a_n} & \cdots & -\frac{a_{n-1}}{a_n} \end{bmatrix} \begin{bmatrix} x_1 \\ x_2 \\ \vdots \\ x_n \end{bmatrix} + \begin{bmatrix} 0 \\ 0 \\ \vdots \\ 0 \\ \frac{1}{a_n} \end{bmatrix} u \tag{2.3}$$

3

or

$$\frac{d\mathbf{x}}{dt} = A\mathbf{x} + \mathbf{b}u \tag{2.4}$$

A multi-input-multi-output (MIMO) system can be represented by

$$\begin{bmatrix} \frac{dx_1}{dt} \\ \frac{dx_2}{dt} \\ \vdots \\ \frac{dx_n}{dt} \end{bmatrix} \begin{bmatrix} a_{11} & a_{12} & \cdots & a_{1n} \\ a_{21} & a_{22} & \cdots & a_{2n} \\ \vdots & \vdots & \ddots & \vdots \\ a_{n1} & a_{n2} & \cdots & a_{nn} \end{bmatrix} \begin{bmatrix} x_1 \\ x_2 \\ \vdots \\ x_n \end{bmatrix} + \begin{bmatrix} b_{11} & b_{12} & \cdots & b_{1r} \\ b_{21} & b_{22} & \cdots & b_{2r} \\ \vdots & \vdots & \ddots & \vdots \\ b_{n1} & b_{n2} & \cdots & b_{nr} \end{bmatrix} \begin{bmatrix} u_1 \\ u_2 \\ \vdots \\ u_r \end{bmatrix} \tag{2.5}$$

or

$$\frac{d\mathbf{x}}{dt} = A\mathbf{x} + B\mathbf{u} \tag{2.6}$$

where $\mathbf{u}$ is an r-vector of input functions.

Let $\boldsymbol{\Phi}$ be the $n \times n$ *transition matrix* of the differential equation given above which is described by the matrix equation

$$\frac{d\boldsymbol{\Phi}}{dt} = A\boldsymbol{\Phi} \tag{2.7}$$

2.1.2   Systems Modeled by Constant Coefficient Linear Difference Equations

2.2   Signal Flow Graphs

2.3   Nyquist Analysis and Design

2.4   Root Locus Analysis and Design

2.5   Bode Analysis and Design

Chapter 3

Image Processing