```
1 0.000000
                     192.168.1.109
                                         192.168.1.255
                                                              UDP
                                                                      305
                                                                            54915 → 54915 Len=263
Frame 1: 305 bytes on wire (2440 bits), 305 bytes captured (2440 bits) on interface 0
Ethernet II, Src: Micro-St 2b:94:62 (8c:89:a5:2b:94:62), Dst: Broadcast (ff:ff:ff:ff:ff:ff)
Internet Protocol Version 4, Src: 192.168.1.109, Dst: 192.168.1.255
   0100 .... = Version: 4
   .... 0101 = Header Length: 20 bytes (5)
   Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
   Total Length: 291
   Identification: 0x3f99 (16281)
   Flags: 0x00
   Fragment offset: 0
   Time to live: 128
   Protocol: UDP (17)
   Header checksum: 0x0000 [validation disabled]
   [Header checksum status: Unverified]
   Source: 192.168.1.109
   Destination: 192.168.1.255
   [Source GeoIP: Unknown]
    [Destination GeoIP: Unknown]
User Datagram Protocol, Src Port: 54915, Dst Port: 54915
Data (263 bytes)
0000 00 53 54 49 41 4e 2d 50 43 00 84 17 46 02 00 00
                                                   .STIAN-PC...F...
0010 90 b6 1f 50 b8 00 00 00 00 00 00 00 00 00 00 00
                                                    ...P......
                                                   3'....P..F...
0020 33 27 00 00 00 00 00 00 e0 50 84 17 46 02 00 00
0030 00 a0 75 17 46 02 00 00 80 ce 3b 18 46 02 00 00
                                                    ..u.F....;.F...
0040 00 00 00 00 00 00 00 7c 6a 14 56 00 00 00 00
                                                    .....|j.V....
0050 48 a5 97 55 00 00 00 00 c9 ba 1f 50 b8 00 00 00
                                                   H..U.....P....
0060 00 00 00 00 00 00 00 00 e0 96 75 17 46 02 00 00
                                                   ....u.F...
0070 14 b7 1f 50 b8 00 00 00 30 b7 1f 50 b8 00 00 00
                                                    ...P....0..P....
0080 18 d5 28 7b 34 39 66 37 64 65 61 33 2d 32 62 63
                                                    ..({49f7dea3-2bc
0090
     62 2d 34 34 65 37 2d 39 30 61 63 2d 37 63 31 65
                                                    b-44e7-90ac-7c1e
     38 32 35 61 36 66 34 39 7d 00 00 00 00 00 00 00
                                                    825a6f49}.....
00a0
00b0 01 00 00 00 00 00 00 10 b7 1f 50 b8 00 00 00
                                                    ....P....
. . . . . . . . . . . . . . . .
. . . . . . . . . . . . . . . .
. . . . . . . . . . . . . . . .
. . . . . . . . . . . . . . . . . . .
0100 00 00 00 35 48 c3 1f
                                                    ...5H..
   Data: 00535449414e2d50430084174602000090b61f50b8000000...
    [Length: 263]
                                                                            Who has 192.168.1.65? Tell 192.168.1.254
     2 0.291501
                     ArrisGro_15:6a:b1
                                         Broadcast
                                                              ARP
Frame 2: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface 0
Ethernet II, Src: ArrisGro_15:6a:b1 (d4:b2:7a:15:6a:b1), Dst: Broadcast (ff:ff:ff:ff:ff)
Address Resolution Protocol (request)
```