

HTMLWriter (Writerw, HTMLDocumentdoc, int pos, int len)

javax.swing.text.html. HTMLWriter

HTMLWriter (Writer w, HTMLDocument doc)

Methods declared in supertypes are hidden in subtypes

AbstractWriter (Writer w, Document doc, int pos, int len) # AbstractWriter (Writer w, Element root, int pos, int len) # AbstractWriter (Writer w, Document doc) # AbstractWriter (Writer w, Element root)

void output (char[] content, int start, int length) \$\func\$ void text (Element elem) \$\bullet\$ int get / setCurrentLineLength() String getText (Elementelem) 🎉 boolean get / setCanWrapLines () String get / setLineSeparator() int getStartOffset() boolean inRange (Element next) int getIndentLevel()
int get / setIndentSpace() int get / setLineLength() # ElementIterator getElementIterator() Document getDocument() int getEndOffset() boolean isLineEmpty () void decrIndent() void incrIndent() Writer getWriter() void indent ()

void endTag (Elementelem) \ # boolean matchNameAttribute (AttributeSetattr, HTML.Tag tag) void closeOutUnwantedEmbeddedTags(AttributeSet attr) void writeEmbeddedTags (AttributeSetattr) 4 # boolean synthesizedElement(Element elem) void textAreaContent (AttributeSet attr) void selectContent(AttributeSetattr) 14 void writeOption (Option option) # boolean isBlockTag (AttributeSet attr) void emptyTag (Element elem) 🕻 void comment (Element elem) & void startTag (Element elem) &

javax.swing.text.html. MinimalHTMLWriter

MinimalHTMLWriter (Writer w, StyledDocument doc)
MinimalHTMLWriter (Writer w, StyledDocument doc, int bos, int len)

void startFontTag (String style) 1 # boolean isText (Element elem) void endFontTag() # boolean inFontTag()

void writeBody () 🔖

void writeComponent (Element elem) & void writeContent (Element elem, boolean needsIndenting) & void writeContent (Element elem, boolean needsIndenting) writeHTMLTags (AttributeSet attr) writeEndTag (String endTag) 🕴 writeImage (Element elem) 14 writeLeaf (Element elem) void writeEndParagraph() & void writeHeader() 🎉 void Void

writeNonHTMLAttributes (AttributeSet attr) & void writeStartParagraph(Element elem) & void writeStartTag(String tag) & writeStyles () Void

void write (String content) \(\begin{align*} \quad \text{v} \\ \text{void write} \quad \text{charl] chars, int startIndex, int length) \(\begin{align*} \begin{align*} \quad \text{v} \\ \text{void write} \quad \text{charl] chars, int startIndex, int length) \(\begin{align*} \begin{align*} \quad \text{v} \\ \text{void} \quad \text{write} \\ \text{charl} \\ \text{

void write (char ch) &

void write () 🔥