javax.naming.spi.*

InitialContextFactory *(spi)*
Context **getInitialContext** (Hashtable environment)

InitialContextFactoryBuilder *(spi)*
InitialContextFactory **createInitialContextFactory** (Hashtable environment)

ObjectFactoryBuilder *(spi)*
ObjectFactory **createObjectFactory** (Object obj, Hashtable environment)

ObjectFactory *(spi)*
Object **getObjectInstance** (Object obj, Name name, Context nameCtx, Hashtable environment)

DirObjectFactory *(spi)*
Object **getObjectInstance** (Object obj, Name name, Context nameCtx, Hashtable environment, Attributes attrs)

StateFactory *(spi)*
Object **getStateToBind** (Object obj, Name name, Context nameCtx, Hashtable environment)

DirStateFactory *(spi)*
Result **getStateToBind** (Object obj, Name name, Context nameCtx, Hashtable environment, Attributes inAttrs)
class **Result**

DirStateFactory.Result
Result (Object obj, Attributes outAttrs)
Attributes **getAttributes** ()
Object **getObject** ()

NamingManager *(spi)*
Context **getContinuationContext** (CannotProceedException cpe)
Context **getInitialContext** (Hashtable env)
Object **getObjectInstance** (Object refInfo, Name name, Context nameCtx, Hashtable environment)
Object **getStateToBind** (Object obj, Name name, Context nameCtx, Hashtable environment)
Context **getURLContext** (String scheme, Hashtable environment)
boolean **hasInitialContextFactoryBuilder** ()
void **setInitialContextFactoryBuilder** (InitialContextFactoryBuilder builder)
void **setObjectFactoryBuilder** (ObjectFactoryBuilder builder)

String CPE

DirectoryManager *(spi)*
DirContext **getContinuationDirContext** (CannotProceedException cpe)
Object **getObjectInstance** (Object refInfo, Name name, Context nameCtx, Hashtable environment, Attributes attrs)
DirStateFactory.Result **getStateToBind** (Object obj, Name name, Context nameCtx, Hashtable environment, Attributes attrs)

Serializable

ResolveResult *(spi)*
ResolveResult ()
ResolveResult (Object robj, String rcomp)
ResolveResult (Object robj, Name rname)
Name get / setRemainingName ()
Object get / setResolvedObj ()
void appendRemainingComponent (String name)
void appendRemainingName (Name name)

Resolver *(spi)*
ResolveResult **resolveToClass** (Name name, Class contextType)
ResolveResult **resolveToClass** (String name, Class contextType)