

Methods declared in supertypes are hidden in subtypes



void columnAdded (TableColumnModelEvente) void columnMarginChanged(ChangeEvente)

void columnMoved (TableColumnModelEvente) void columnRemoved (TableColumnModelEvente)

void columnSelectionChanged(ListSelectionEvente)



JTableHeader (TableColumnModelcm) JTableHeader JTableHeader ()

int get / setDraggedDistance() TableCellRenderer get / setDefaultRenderer() TableColumn get / setDraggedColumn() TableColumnModel get / setColumnModel ()

boolean get / setReorderingAllowed() TableColumn get / setResizingColumn() boolean get / setResizingAllowed()

Rectangle getHeaderRect (int column)

boolean get / setUpdateTableInRealTime() JTable get / setTable () TableHeaderUI get / setUI ()

int columnAtPoint (Point point) void resizeAndRepaint()

TableColumnModel createDefaultColumnModel() # TableCellRenderer createDefaultRenderer() void initializeLocalVars()



Serializable

TableColumn

TableColumn (int modelIndex) TableColumn ()

TableColumn (int modelIndex, int width)

TableColumn (int modelIndex, int width, TableCellRenderer cellRenderer, TableCellEditor cellEditor)

TableCellRenderer get / setHeaderRenderer() TableCellRenderer get / setCellRenderer() TableCellEditor get / setCellEditor ()

Object get / setHeaderValue() Object get / setIdentifier ()

int get / setMaxWidth ()
int get / setMinWidth ()
int get / setModelIndex ()
int get / setPreferredWidth ()

boolean get / setResizable () int get / setWidth ()

void add / removePropertyChangeListener(PropertyChangeListener) PropertyChangeListener[] getPropertyChangeListeners()

TableCellRenderer createDefaultHeaderRenderer() void sizeWidthToFit ()

HEADER_RENDERER_PROPERTY, CELL_RENDERER_PROPERTY String COLUMN_WIDTH_PROPERTY, HEADER_VALUE_PROPERTY,