



URL

Methods declared in supertypes are hidden in subtypes

Serializable

SocketAddress

InetSocketAddress

```
InetSocketAddress (int port)
InetSocketAddress (InetAddress addr, int port)
InetSocketAddress (String hostname, int port)
```

Accessors

```
InetAddress getAddress ()
String getHostName ()
int getPort ()
boolean isUnresolved ()
```

Object

```
boolean equals (Object obj)
int hashCode ()
String toString ()
```

NetworkInterface

Static Methods

```
NetworkInterface getByInetAddress (InetAddress addr)
NetworkInterface getByName (String name)
Enumeration getNetworkInterfaces ()
```

Accessors

```
String getDisplayName ()
Enumeration getInetAddresses ()
String getName ()
```

Object

```
boolean equals (Object obj)
int hashCode ()
String toString ()
```



Serializable

InetAddress

Static Methods

```
InetAddress[] getAllByName (String host)
InetAddress getByAddress (byte[] addr)
InetAddress getByAddress (String host, byte[] addr)
InetAddress getByHost (String host)
InetAddress getLocalHost ()
```

Accessors

```
byte[] getAddress ()
String getCanonicalHostName ()
String getHostAddress ()
String getHostByAddr (byte[] addr)
String getHostName ()
```

```
boolean isAnyLocalAddress ()
boolean isLinkLocalAddress ()
boolean isLoopbackAddress ()
boolean isMulticastAddress ()
boolean isMCGlobal ()
boolean isMCLinkLocal ()
boolean isMCNodeLocal ()
boolean isMCOrgLocal ()
boolean isMCSitelocal ()
boolean isMulticastAddress ()
boolean isSiteLocalAddress ()
```

Object

```
boolean equals (Object obj)
int hashCode ()
String toString ()
```

Other Public Methods

```
byte[] lookupAllHostAddr (String host)
Object run ()
```



InetAddress

InetAddress

boolean isIPv4CompatibleAddress ()