java.beans.*
EventSupport

Methods declared in supertypes are hidden in subtypes

Serializable

PropertyChangeSupport (Object sourceBean)

PropertyChangeSupport (Object sourceBean)

```
void  add / removePropertyChangeListener (PropertyChangeListener listener)
void  add / removePropertyChangeListener (String propertyName,  PropertyChangeListener listener)
void  firePropertyChange (PropertyChangeEvent evt)
void  firePropertyChange (String propertyName,   Object oldValue,  Object newValue)
void  firePropertyChange (String propertyName,   int oldValue, int newValue)
void  firePropertyChange (String propertyName,   boolean oldValue, boolean newValue)
PropertyChangeListener[]  getPropertyChangeListeners ()
PropertyChangeListener[]  getPropertyChangeListeners (String propertyName)
boolean  hasListeners (String propertyName)
```

---

javax.swing.event. **SwingPropertyChangeSupport**

SwingPropertyChangeSupport (Object sourceBean)

Serializable

VetoableChangeSupport (Object sourceBean)

VetoableChangeSupport (Object sourceBean)

```
void  add / removeVetoableChangeListener (VetoableChangeListener listener)
void  add / removeVetoableChangeListener (String propertyName,  VetoableChangeListener listener)
void  fireVetoableChange (PropertyChangeEvent evt)
void  fireVetoableChange (String propertyName,   Object oldValue,  Object newValue)
void  fireVetoableChange (String propertyName,   int oldValue, int newValue)
void  fireVetoableChange (String propertyName,   boolean oldValue, boolean newValue)
VetoableChangeListener[]  getVetoableChangeListeners ()
VetoableChangeListener[]  getVetoableChangeListeners (String propertyName)
boolean  hasListeners (String propertyName)
```

---

java.lang.reflect. **InvocationHandler**

Object invoke (Object proxy, Method method, Object[] args)

EventHandler

EventHandler (Object target,   String action,   String eventPropertyName,   String listenerMethodName)

Static Methods
```
Object  create  (Class listenerInterface,    Object target,    String action)
Object  create  (Class listenerInterface,    Object target,    String action,   String eventPropertyName)
Object  create  (Class listenerInterface,    Object target,    String action,   String eventPropertyName,    String listenerMethodName)
```
Accessors
```
String  getAction ()
Object  getTarget ()
```
Event Methods
```
String  getEventPropertyName ()
String  getListenerMethodName ()
```