



java.beans.* BeanInfo

Methods declared in supertypes are hidden in subtypes



BeanInfo

Accessors

```
BeanInfo() getAdditionalBeanInfo()  
BeanDescriptor getBeanDescriptor()  
int getDefaultPropertyIndex()  
java.awt.Image getIcon (int iconKind)  
MethodDescriptor[] getMethodDescriptors()  
PropertyDescriptor[] getPropertyDescriptors()  
Event Methods  
int getDefaultEventIndex()  
EventSetDescriptor[] getEventSetDescriptors()  
  
int ICON_COLOR_16x16  
ICON_COLOR_32x32  
ICON_MONO_16x16  
ICON_MONO_32x32
```



BeanContextServiceProviderBeanInfo

```
java.beans.beancontext.  
BeanInfo[] getServicesBeanInfo ()
```



SimpleBeanInfo

```
java.awt.Image loadImage (String resourceName)
```

Introspector

```
String decapitalize (String name)  
void flushCaches ()  
void flushFromCaches (Class clz)  
BeanInfo getBeanInfo (Class beanClass) ⚡  
BeanInfo getBeanInfo (Class beanClass, int flags) ⚡  
BeanInfo getBeanInfo (Class beanClass, Class stopClass) ⚡  
String[] getBeanInfoSearchPath ()  
void setBeanInfoSearchPath (String path[])  
  
int USE_ALL_BEANINFO, IGNORE_IMMEDIATE_BEANINFO,  
IGNORE_ALL_BEANINFO
```



Beans

```
Object get / isInstanceOf (Object bean, Class targetType)  
Object instantiate (ClassLoader ds, String beanName) ⚡  
Object instantiate (ClassLoader ds, String beanName, BeanContext beanContext) ⚡  
Object instantiate (ClassLoader ds, String beanName, BeanContext beanContext, AppletInitializer) ⚡  
boolean isDesignTime ()  
boolean isGuiAvailable ()  
void setDesignTime (boolean isDesignTime) ⚡  
void setGuiAvailable (boolean isGuiAvailable) ⚡
```



AppletInitializer

```
void activate (Applet newApplet)  
void initialize (Applet newAppletBean, BeanContext bCtxt)
```