# java.awt.image.* Miscellaneous

## BufferStrategy

Accessors
BufferCapabilities getCapabilities ()
Graphics getDrawGraphics ()
Other Public Methods
boolean contentsLost ()
boolean contentsRestored ()
void show ()

## ImageObserver

boolean imageUpdate (Image img, int infoflags, int x, int y, int width, int height)

int WIDTH, HEIGHT, PROPERTIES, SOMEBITS, FRAMEBITS, ALLBITS, ERROR, ABORT

## java.awt. Component

## Cloneable — java.awt. BufferCapabilities

BufferCapabilities (ImageCapabilities frontCaps, ImageCapabilities backCaps, FlipContents flipContents)

Accessors
ImageCapabilities getBackBufferCapabilities ()
FlipContents getFlipContents ()
ImageCapabilities getFrontBufferCapabilities ()
boolean isFullScreenRequired ()
boolean isMultiBufferAvailable ()
boolean isPageFlipping ()
Object
Object clone ()

class FlipContents

## java.awt. BufferCapabilities.FlipContents

FlipContents UNDEFINED, BACKGROUND, PRIOR, COPIED

## TileObserver

void tileUpdate (WritableRenderedImage source, int tileX, int tileY, boolean willBeWritable)

## Cloneable — java.awt. ImageCapabilities

ImageCapabilities (boolean accelerated)

Accessors
boolean isAccelerated ()
boolean isTrueVolatile ()
Object
Object clone ()

## Serializable — java.awt. MediaTracker

MediaTracker (Component comp)

Accessors
Object[] getErrorsAny ()
Object[] getErrorsID (int id)
boolean isErrorAny ()
boolean isErrorID (int id)
Collectors
void add / removeImage (Image image, int id)
void add / removeImage (Image image, int id, int w, int h)
void removeImage (Image image)
Other Public Methods
boolean checkAll ()
boolean checkAll (boolean load)
boolean checkID (int id)
boolean checkID (int id, boolean load)
int statusAll (boolean load)
int statusID (int id, boolean load)
void waitForAll ()
boolean waitForAll (long ms)
void waitForID (int id)
boolean waitForID (int id, long ms)

int LOADING, ABORTED, ERRORED, COMPLETE