



URL

Methods declared in supertypes are hidden in subtypes

Serializable



SocketAddress



InetSocketAddress

```
InetSocketAddress (int port)
InetSocketAddress (InetAddress addr, int port)
InetSocketAddress (String hostname, int port)
```

Accessors

```
InetAddress getAddress ()
String getHostName ()
int getPort ()
boolean isUnresolved ()
Object
boolean equals (Object obj)
int hashCode ()
String toString ()
```



NetworkInterface

```
Static Methods
NetworkInterface getByInetAddress (InetAddress addr)
NetworkInterface getByName (String name)
Enumeration getNetworkInterfaces ()
```

Accessors

```
String getDisplayName ()
Enumeration getInetAddresses ()
String getName ()
Object
boolean equals (Object obj)
int hashCode ()
String toString ()
```



Serializable



InetAddress

```
Static Methods
InetAddress[] getAllByName (String host)
InetAddress getByAddress (byte[] addr)
InetAddress getByAddress (String host, byte[] addr)
InetAddress getByName (String host)
InetAddress getLocalHost ()
```

Accessors

```
byte[] getAddress ()
String getCanonicalHostName ()
String getHostAddress ()
String getHostByAddr (byte[] addr)
String getHostName ()
boolean isAnyLocalAddress ()
boolean isLinkLocalAddress ()
boolean isLoopbackAddress ()
boolean isMulticastAddress ()
boolean isMCGlobal ()
boolean isMCLinkLocal ()
boolean isMCNodeLocal ()
boolean isMCOrgLocal ()
boolean isMCSitelocal ()
boolean isMulticastAddress ()
boolean isSiteLocalAddress ()
Object
boolean equals (Object obj)
int hashCode ()
String toString ()
Other Public Methods
byte[] lookupAllHostAddr (String host)
Object run ()
```



Inet4Address



Inet6Address

```
boolean isIPv4CompatibleAddress ()
```