# ▼ javax.swing.text.\*

AttributeSet

# Methods declared in supertypes are hidden in subtypes

### T AttributeSet

void setResolveParent (AttributeSet parent)
void addAttribute (Object name. Object value)
void add / removeAttributes (AttributeSet attributes)
void removeAttribute (Object name)

T MutableAttributeSet

void removeAttributes (Enumeration names)

Object getAttribute (Object key) int getAttributeCount()

boolean isDefined (Object attrName) Enumeration getAttributeNames () AttributeSet getResolveParent ()

boolean isEqual (AttributeSet attr)

boolean containsAttribute (Object name, Object value) boolean containsAttributes (AttributeSet attributes) AttributeSet copyAttributes () Other Public Methods

Object NameAttribute, ResolveAttribute

interface CharacterAttribute interface ColorAttribute interface FontAttribute

interface ParagraphAttribute

## T StyleContext.SmallAttributeSet

SmallAttributeSet (Object[] attributes) SmallAttributeSet (AttributeSet attrs)

boolean equals (Object obj) int hashCode () Object clone ()

String toString ()

int getElementIndex (int offset) Element getElement (int index) int getElementCount() Document getDocument() AttributeSet getAttributes ()

Element getParentElement () int getEndOffset () String getName ()

void dump (PrintStream psOut, int indentAmount)

Other Public Methods

# void finalize ()

int getStartOffset () boolean isLeaf ()

### iavax.swing.tree. TreeNode

int getIndex (TreeNode node) TreeNode getChildAt (int childIndex) boolean getAllowsChildren () int getChildCount () TreeNode getParent () boolean isLeaf () Other Public Methods

Enumeration children ()



String getName ()

Event Methods
void add / removeChangeListener (ChangeListener I)

# void fireStateChanged ()
ChangeListenerf] getChangeListeners ()
EventListenerf] getListeners (Class listenerType)

**Event Methods** 

String toString ()

T StyleContext.NamedStyle NamedStyle ()
NamedStyle (Style parent)
NamedStyle (String name, Style parent)

Serializable



Serializable

### T SimpleAttributeSet SimpleAttributeSet

SimpleAttributeSet (AttributeSet source)

boolean is Empty () Accessors Object

Object clone () boolean equals (Object obj) int hashCode () String toString ()

AttributeSet EMPTY

# T AbstractDocument.BranchElement

BranchElement (Element parent, AttributeSet a)

String toString ()
Other Public Methods
Element positionToElement (int pos)
void replace (int offset, int length, Element[] elems)

Serializable

T AbstractDocument.AbstractElement

AbstractElement (Element parent, AttributeSet a)

Javax.swing.text.html. HTMLDocument.BlockElement BlockElement (Element parent, AttributeSet a)

# T AbstractDocument.LeafElement

LeafElement (Element parent, AttributeSet a, int offs0, int offs1)

String toString ()

Javax. swing.text.html. HTMLDocument.RunElement

RunElement (Element parent, AttributeSeta, int offs0, int offs1)

T AttributeSet.CharacterAttribute

### T StyleConstants

int getAlignment (AttributeSeta)

Color getBackground (AttributeSet a) int getBidiLevel (AttributeSet a)

float getFirstLineIndent (AttributeSet a) Component getComponent (AttributeSet a)

String getFontFamily (AttributeSet a) int getFontSize (AttributeSeta)

Color getForeground (AttributeSet a)

Icon geticon (AttributeSet a)
float getLineSpacing (AttributeSet a)
float getLineSpacing (AttributeSet a)
float getRightIndent (AttributeSet a)
float getSpaceAbove (AttributeSet a)

float getSpaceBelow (AttributeSeta) TabSet getTabSet (AttributeSeta) ooolean isBold (AttributeSet a)

boolean isStrikeThrough (AttributeSet a) boolean isSubscript (AttributeSet a) boolean isItalic (AttributeSet a)

poolean isSuperscript (AttributeSet a) boolean isUnderline (AttributeSet a)

void **setAlignment** (MutableAttributeSeta, int align) void **setBackground** (MutableAttributeSeta, Color fg)

void setBold (MutableAttributeSet a, boolean b) void setBidiLevel (MutableAttributeSet a, int o)

void setComponent (MutableAttributeSet a, Component c) void setFirstLineIndent (MutableAttributeSet a, float i) void setFontFamily (MutableAttributeSet a, String fam)

void setFontSize (MutableAttributeSet a, int s)

void setForeground (MutableAttributeSet a, Color fg)

void settalic (MutableAttributeSet a, boolean b) void settcon (MutableAttributeSet a, Icon c)

void setLeftIndent (MutableAttributeSet a, float i) void setLineSpacing (MutableAttributeSet a, float i) void setRightIndent (MutableAttributeSet a, float i)

void setStrikeThrough (MutableAttributeSet a, boolean b) void setSubscript (MutableAttributeSet a, boolean b) void setSpaceAbove (MutableAttributeSet a, float i) void setSpaceBelow (MutableAttributeSet a, float i)

void setSuperscript (MutableAttributeSet a, boolean b) void setTabSet (MutableAttributeSet a, TabSet tabs) void setUnderline (MutableAttributeSet a, boolean b)

Object

String toString ()

String ComponentElementName, IconElementName

FontFamily, FontSize, Bold, Italic, Underline, StrikeThrough, Superscript, Subscript, Foreground, Background, ComponentAttribute, IconAttribute, ComposedTextAttribute, Object NameAttribute, ResolveAttribute, ModelAttribute, BidiLevel, FirstLineIndent, LeftIndent, RightIndent, LineSpacing, SpaceAbove, SpaceBelow, Alignment, TabSet, Orientation

int ALIGN\_LEFT, ALIGN\_CENTER, ALIGN\_RIGHT,

ALIGN\_JUSTIFIED

class CharacterConstants

class ColorConstants class FontConstants

class ParagraphConstants

T StyleConstants.CharacterConstants Object Underline, StrikeThrough, Superscript, Subscript, ComponentAttribute, IconAttribute, BidilLevel,

Family, Size, Bold, Italic, Foreground, Background

T AttributeSet.ColorAttribute

T StyleConstants.ColorConstants

Object Foreground, Background

T AttributeSet.FontAttribute

**StyleConstants.FontConstants** 

Object Family, Size, Bold, Italic

T AttributeSet.ParagraphAttribute

T StyleConstants.ParagraphConstants

LineSpacing, SpaceAbove, SpaceBelow, Alignment, TabSet, Orientation Object FirstLineIndent, LeftIndent, RightIndent,

www.falkhausen.de Version 0.8 Copyright 2002 by Markus Falkhausen. All rights reserved.