



java.beans.* Persistence

Methods declared in supertypes are hidden in subtypes

**XMLDecoder**


XMLDecoder (InputStream in)
XMLDecoder (InputStream in, Object owner)
XMLDecoder (InputStream in, Object owner, ExceptionListener exceptionListener)

Accessors
Object get / setOwner ()
Event Methods
ExceptionListener get / setExceptionListener ()
Other Public Methods
void close ()
Object readObject ()

**XMLEncoder**


XMLEncoder (OutputStream out)

Accessors
Object get / setOwner ()
Other Public Methods
void close ()
void flush ()


**Encoder**

Accessors + Collectors
Object get (Object oldInstance)
PersistenceDelegate get / setPersistenceDelegate (Class type)
Object remove (Object oldInstance)
Event Methods
ExceptionListener get / setExceptionListener ()
Other Methods
void writeExpression (Expression oldExp)
void writeStatement (Statement oldStm)
void writeObject (Object o)

#


**ExceptionListener**

void exceptionThrown (Exception e)

**Expression**

Expression (Object target, String methodName, Object[] arguments)
Expression (Object value, Object target, String methodName, Object[] arguments)

Accessors
Object getvalue () ↴
void setValue (Object value)
Object
String toString ()

**Statement**


Statement (Object target, String methodName, Object[] arguments)

Accessors
Object[] getArguments ()
String getMethodName ()
Object getTarget ()
Object
String toString ()
Other Public Methods
void execute () ↴

**DefaultPersistenceDelegate**

DefaultPersistenceDelegate ()
DefaultPersistenceDelegate (String[] constructorPropertyNames)

www.falkhausen.de Version 0.8 Copyright 2002 by Markus Falkhausen. All rights reserved.

**PersistenceDelegate**

void writeObject (Object oldInstance, Encoder out)
void initialize (Class type, Object oldInstance, Object newInstance, Encoder out)
Expression instantiate (Object oldInstance, Encoder out)
boolean mutatesTo (Object oldInstance, Object newInstance)