



java.beans.* BeanInfo

Methods declared in supertypes are hidden in subtypes



BeanInfo

Accessors

```
BeanInfo[] getAdditionalBeanInfo()  
BeanDescriptor getBeanDescriptor()  
int getDefaultPropertyIndex()  
java.awt.Image getIcon (int iconKind)  
MethodDescriptor[] getMethodDescriptors()  
PropertyDescriptor[] getPropertyDescriptors()  
Event Methods  
int getDefaultEventIndex()  
EventSetDescriptor[] getEventSetDescriptors()
```

```
int ICON_COLOR_16x16  
ICON_COLOR_32x32  
ICON_MONO_16x16  
ICON_MONO_32x32
```



java.beans.beancontext.
BeanInfo[] getServicesBeanInfo()

BeanContextServiceProviderBeanInfo



SimpleBeanInfo

```
java.awt.Image loadImage (String resourceName)
```



Introspector

```
String decapitalize (String name)  
void flushCaches ()  
void flushFromCaches (Class clz)  
BeanInfo getBeanInfo (Class beanClass) ↵  
BeanInfo getBeanInfo (Class beanClass, int flags) ↵  
BeanInfo getBeanInfo (Class beanClass, Class stopClass)  
String[] getBeanInfoSearchPath ()  
void setBeanInfoSearchPath (String path[])
```

```
int USE_ALL_BEANINFO, IGNORE_IMMEDIATE_BEANINFO,  
IGNORE_ALL_BEANINFO
```



Beans

```
Object get / isInstanceOf (Object bean, Class targetType)  
Object instantiate (ClassLoadercls, String beanName) ↵  
Object instantiate (ClassLoadercls, String beanName, BeanContext beanContext) ↵  
Object instantiate (ClassLoadercls, String beanName, BeanContext beanContext, AppletInitializer initialized) ↵  
boolean isDesignTime ()  
boolean isGuiAvailable ()  
void setDesignTime (boolean isDesignTime) ↵  
void setGuiAvailable (boolean isGuiAvailable) ↵
```



AppletInitializer

```
void activate (Applet newApplet)  
void initialize (Applet newAppletBean, BeanContext bCtxt)
```