



**Faculty of Engineering and Architectural Science,
Department of Electrical, Computer and Biomedical Engineering**

Lab Manual

COE892

Distributed and Cloud Computing

Dr. Muhammad Jaseemuddin

TAs: Amirhossein Razavi, Deepu Sasi, Mahdiyar Alavi and Rendel Abrasia

Winter 2026

Lab Schedule

Labs	Title	Tentative Due Weeks	Marks
Lab 1	Concurrency vs. Parallelism	Week 5	4
Lab 2	gRPC	Week 8	4
Lab 3	RabbitMQ	Week 9	4
Lab 4-5	FastAPI and Containers	Week 12	8

Pre-Lab

Software Environment

Following software environment is recommended and supported:

Ubuntu 22.04 LTS (<https://ubuntu.com/download/desktop>)

Python 3.0 or higher

PyCharm Community Edition (<https://www.jetbrains.com/pycharm/>)

gRPC (<https://grpc.io/>)

RabbitMQ (<https://www.rabbitmq.com/>)

FastAPI (<https://fastapi.tiangolo.com/>)

Virtual Machine Setup and Verification

A pre-configured VirtualBox virtual machine running Ubuntu 20.04 LTS is available for download that can be used for the labs. The VM includes all required software (FastAPI, gRPC, RabbitMQ, Wireshark, and Python dependencies).

Step 1: Install VirtualBox

1. Download and install VirtualBox from:
<https://www.virtualbox.org/wiki/Downloads>
2. Select Windows hosts (or macOS hosts if applicable).
3. Complete the installation using default settings.

Step 2: Download the COE892 Virtual Machine

1. Download the COE892 VirtualBox image from the course Google Drive link:
COE892vm_12262022.ova
2. The file size is approximately 6.4 GB.

Step 3: Import the VM

1. Open VirtualBox.
2. Select File → Import Appliance.
3. Browse to and select COE892vm_12262022.ova.
4. Assign at least 4 GB RAM and 2 CPUs.
5. Click Import.

Step 4: Start the VM

1. Start the imported VM.
2. The system logs in automatically as:
3. Username: bob
4. Password: letbobin

Step 5: Verify Installed Packages

- Open a terminal and run the following example tests.
- FastAPI Test

```
cd ~/Examples/fastapi-Example  
./testit.sh
```

- Open Firefox inside the VM and navigate to:

<http://127.0.0.1:8000>

A response such as {"Hello":"World"} confirms FastAPI is working.

- gRPC Test

```
cd ~/Examples/gRPC-Example  
./testit.sh
```

- RabbitMQ Test

```
cd ~/Examples/rabbitmq-Example  
./testit.sh
```

Successful execution confirms the environment is correctly set up.

Lab Submission and Grading Policy

- You must submit lab individually
- Your submission includes a one-page note about your implementation illustrating main data structures and functions and screenshots of your test run
- A random sample of students will be called for demonstration for each lab
- Late submission will be accepted up to three days subject to the mark attrition rate of 10% per day of late submission

Lab 1: Concurrency vs Parallelism

Due Date: **February 6, 2026**

Objective

In this lab you will write two programs in Python using Python threading and multiprocessing modules to process data of several Land Mine Detector Robots.

Description

Consider the model of a land space as a 2D array of zeros and non-zeros where a positive value of (i, j)th element indicates that there is a mine at that location. You get the map.txt file where the first line has 2 numbers divided by space, the first one represents the number of rows of the land, and the second number indicates the number of columns. Then the rest of the file specifies the state of each cell in the land.

Part 1: Drawing the path of the Rovers

For this part, first you need to write a program which reads the map. The program can get the data of 10 rovers from the public API provided below: <https://coe892.reev.dev/lab1/rover/:number>
Alternatively, you can launch the API server by following the procedure outline in **Appendix A**.

Where the “:**number**” represents the rover’s ID (ranging from 1 to 10). The response is a string containing all the commands that were sent to the rover. **List of the commands are:**

Commands	Meaning
L	Turn left
R	Turn right
M	Move forward
D	Dig

For example, the response could be “**RMLMMMMDLMMRMD**”.

1. Write a sequential program that gets the commands of each robot and calculates the path of that robot (consider robots at point (0,0) facing south at the initial state). Create a file "**path_i.txt**" where **i** is the rover number and draw the path by using "*" on the map, indicating the rover has been on that cell or 0 for the rest of the map. (You should consider if the rover hits a mine and it doesn't dig it and move, the mine will explode, and the rest of the commands should be ignored). Using the time module, show how long it took to write all the path files.
Note that if a Move Forward command is called when the rover is facing an edge, the command can be ignored.
2. Modify the program to take advantage of the Python Threading module to make the functions run in parallel. Record the total processing time and then compare it to the sequential approach and calculate the difference of their computation times. You should use Locks, if necessary.

Part 2: Digging mines

In this part, we want rover #1 to start digging and disarming any mine it comes across, upon receiving the digging (D) command.

To achieve this, write a program that reads the **mines.txt** file and considers the mine your rover is on in the file and their serial number. You can use a specific hash value to simulate the digging and disarming process.

To disarm a mine, you need to find a valid PIN by considering the following:

1. A selected **PIN** gets concatenated with the **serial number** of the mine, as a **prefix**, and results in a value we call **Temporary Mine Key**
2. The Temporary Mine Key is then hashed using the [sha256](#) hash function, and a value is determined
3. If the determined hashed has at least **six leading zeros** (e.g. 00000A12B...), the PIN is **valid**

Please note that there may be more than one valid pin for the mines. To find a valid PIN by following the above procedure, you should use brute-force and start with any arbitrary string.

Your task is first to write a code for the above-mentioned process using a sequential approach in Python and record its time to disarm all the mines in the field. Then, write the same process but use Python

Threading module to run the functions in parallel. Record the total processing time and then compare it to the sequential approach and calculate their differences.

Lab Submission

You need to create a report file for the lab that would describe all the steps taken in each part. The report should include an introduction and conclusion section, as well. Please make sure all your files are compressed in a ZIP file (RAR is not accepted). The name of the file should be your last name (e.g. "xyz.zip"). Only one D2L submission per individual is accepted. All reports should be contained in the ZIP file and in PDF format (Docs is not accepted).

Lab 2: gRPC

Due Date: **March 6, 2026**

Objective

In this lab, you will write two programs in Python using gRPC to simulate the communication of several rovers with ground control, as an extension of Lab 1.

Description

Consider a gRPC server (the ground control) and 10 clients (the rovers) that are supposed to communicate using the gRPC protocol. Each rover implements the following methods:

1. Get map (e.g., "The 2D land array")
2. Get a stream of commands (e.g., "RMLMMMMMDLMMRMD")
3. Get a mine serial number
4. Let the server know if they have executed all commands successfully, or not (a mine might explode with a wrong series of commands)
5. Share a mine PIN with the server

For the sake of simplicity, note that each rover works independently; that is upon reaching a mine, a rover must disarm the mine irrespective to it being disarmed previously by another rover.

Part 1: Create the Proto Buffer Files

For this part, you need to create the *.proto* files required for the gRPC communication of the 5 methods mentioned in the description. You should describe the service, methods, messages and... required for the gRPC communication.

Part 2: Create the Server

In part 2, you need to create the gRPC server (the ground control) utilizes the 2D map files (as used in Lab 1), rovers command files containing the commands given to each rover (client) and a mine serial number file (similar to mines.txt seen in Lab 1). The server should be created based on the *.proto* files

generated in Part 1 of the lab and should implement at least the above 5 methods as mentioned in the description.

Part 3: Create the Client Side

In part 3, you need to create the gRPC client (the rovers) that should implement at least the above 5 methods mentioned in the description. This Python file should accept a CLI argument which indicates the rover number (1-10), which is expected when being executed. The rover (client) would retrieve the map upon running and store it in a suitable data structure. It would then retrieve the stream of commands and start executing them in order. This process does not need to use Python Threading and could be implemented sequentially. The client then needs to get the mine serial number, if it contacts a mine in need of disarming and share the mine PIN with the server, afterwards. Finally, the client needs to notify the server after executing all the commands successfully.

Lab Submission

You need to create a report file for the lab that would describe all the steps taken in each part. The report should include introduction and conclusion sections. Please make sure all your files are compressed in a ZIP file (RAR is not accepted). Submit the ZIP file to D2L. All reports should be included in the ZIP file and in the PDF format (Docs is not accepted).

Lab 3: RabbitMQ

Due Date: **March 13, 2026**

Objective

In this lab, you will write three programs in Python using gRPC and RabbitMQ to simulate the communication of a few rovers, the deminers and ground control together, as a continuation of Lab 2.

Description

In this lab, like the previous lab, the ground control relies on three files, the miners' serial number, the 2D map array, and the commands list. However, the rovers no longer perform the digging command. They only explore the land and request the gRPC server upon finding a mine to retrieve the mine serial number and publish a demining task using RabbitMQ. The entity of deminers, introduced in this lab, then use the queue to get coordinates of found mines, their ID, and their serial numbers. The deminers then start disarming the discovered mines, if not busy, one by one. Once a deminer had done, it would publish the PIN of the mine over another RabbitMQ channel, where the ground control is considered the consumer.

Part 1: Create the RabbitMQ server

In the first part, create the RabbitMQ server. You can create the server in different ways depending upon your environment. You can follow the instructions to download and install RabbitMQ server (and clients) given at [Downloading and Installing RabbitMQ — RabbitMQ](#)

Docker: Install docker on your machine, and then launch the server using the following command:

```
docker run --name mqserver -p 5672:5672 rabbitmq
```

This command creates a container from the **rabbitmq** image, named **mqserver**, and maps the port **5672** of the machine to the port **5672** of the container.

Part 2: Create the Ground Control

In this part, you need to create the server (the ground control) that takes advantage of the 2D map files (as used in Lab 1 and 2), rover command files containing the commands (excluding the digging command) given to each rover (client) and a mine serial number file (like mines.txt used in Lab 1 and 2). The server should be created based on the *.porto* files created in Part 1 of Lab 2, however we only require methods #1 to #3 (*Get map*, *Get command stream*, and *Get mine serial number*). The server should also subscribe to the **Defused-Mines** channel and either display the defused mine on a STD output file or log it to a file.

Part 3: Create the Rovers

In part 3, you need to create the gRPC client (the rovers) and implement the required methods mentioned in the description. This Python file should accept a CLI argument that indicates the rover number (1-10), which is expected when being executed. Upon running, the rover retrieves the map and stores it in a suitable data structure. It then retrieves the stream of commands and starts exploring the map. This process does not need to use Python Threading and could be implemented sequentially. The client then gets the mine's serial number, if it contacts a mine in need of disarming and publish the mine's coordinates, ID, and serial number to the **Demine-Queue** channel of RabbitMQ server.

Part 4: Create the Deminers

In this last part, you need to create a Python file for deminers. This Python file should accept a CLI argument that indicates the deminer number (1 or 2), which is expected when being executed. The deminers subscribe to the **Demine-Queue** channel of RabbitMQ server and then proceed to demine the assigned mine, if not busy. They then publish the PIN of the mine on the **Defused-Mines** channel of RabbitMQ server.

Lab Submission

Write a report for the lab that describes all the steps taken in each part. The report should include an introduction and conclusion section. Please make sure all your files are compressed in a ZIP file (RAR is not accepted). All reports should be contained in the ZIP file and in PDF format (Docs is not accepted).