

Smart meter consumption time-series forecasting

Ir. Stijn Staring

Thesis submitted for the degree of
Master of Science in Artificial
Intelligence, eg

Thesis supervisor:

Prof. dr. ir. Bart De Moor

Assessors:

Prof. dr. ir. Unknown

Prof. dr. ir. Unknown

Mentor:

Ir. Lola Botman

© Copyright KU Leuven

Without written permission of the thesis supervisor and the author it is forbidden to reproduce or adapt in any form or by any means any part of this publication. Requests for obtaining the right to reproduce or utilize parts of this publication should be addressed to the Departement Computerwetenschappen, Celestijnenlaan 200A bus 2402, B-3001 Heverlee, +32-16-327700 or by email info@cs.kuleuven.be.

A written permission of the thesis supervisor is also required to use the methods, products, schematics and programmes described in this work for industrial or commercial use, and for submitting this publication in scientific contests.

Preface

I would like to thank everybody who kept me busy the last year, especially my promoter and my assistants. I would also like to thank the jury for reading the text. My sincere gratitude also goes to my wife and the rest of my family.

Ir. Stijn Staring

Contents

Preface	i
Abstract	iv
Abstract	v
List of Figures and Tables	vi
List of Abbreviations and Symbols	viii
1 Introduction	1
1.1 Importance of topic	1
1.2 Problem formulation and link with previous studies	1
1.3 Thesis objective and structure	1
2 Data analysis	3
2.1 Introduction to dataset	3
2.2 Preprocessing	4
2.3 Analysis	8
2.4 Baseline model	13
2.5 Conclusion	14
3 State of the art short-term residential load forecasting techniques	15
3.1 Introduction to Neural Networks	15
3.2 Short-Term residential electrical load forecasting	18
3.3 Tables	24
3.4 Conclusion	24
4 Clustering of the load profiles	27
4.1 The First Topic of this Chapter	27
4.2 The Second Topic	28
4.3 Conclusion	28
5 Forecasting of time-series	31
5.1 The First Topic of this Chapter	31
5.2 Conclusion	31
6 Evaluating results	33
6.1 The First Topic of this Chapter	33
6.2 The Second Topic	34
6.3 Conclusion	35

7 Conclusion	37
A Introduction to the dataset	41
A.1 Introduction to the dataset	41
A.2 Missing values	42
A.3 Daily filter	42
B Old things	47
B.1 ARIMA	47
Bibliography	49

Abstract

The **abstract** environment contains a more extensive overview of the work. But it should be limited to one page.

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Abstract

In dit **abstract** environment wordt een al dan niet uitgebreide Nederlandse samenvatting van het werk gegeven. Wanneer de tekst voor een Nederlandstalige master in het Engels wordt geschreven, wordt hier normaal een uitgebreide samenvatting verwacht, bijvoorbeeld een tiental bladzijden.

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

List of Figures and Tables

List of Figures

2.1	Resulting month of March after substitution of the missing values by the mean value of the measurements.	5
2.2	One of the 9 identified meters with multiple zero daily consumptions . .	6
2.3	The maximum differences between the minimum and maximum weekly rolling averages for all the different time-series.	7
2.4	Figure that shows the seasonality of the electrical load during the week. The blue line shows the average week over all weeks in 2017.	9
2.5	Relation between consumption and temperature.	10
2.6	Figure with the comparison between holidays and business days.	12
2.7	Figure with the comparison of the different dwelling types.	13
3.1	Figure of a MLP (source [9]).	16
3.2	Figure of the logical flow of a vanilla RNN with a hidden state (source [9]).	17
3.3	Exponential decrease of the gradient size of a simple RNN (red) or a LSTM (blue) (source [8]).	19
3.4	Results obtained in paper [7] using the PDRNN method.	21
3.5	Influence of the number of layers and the pooling method used in [7]. . .	22
3.6	Different approaches tried in [4] and their averaged performance of 29,808 individual forecasts of half an hour individual loads.	23
3.7	The importance of the different inputs as based on the average class activation score. (source [3])	24
3.8	Comparison between LSTM and CNN-LSTM. source([3])	25
A.1	The amount of NaN values in all the 3248 smart meters.	41
A.2	Resulting month of March after substitution of the missing values by the mean value of the measurements.	43
A.3	Resulting month of March after substitution of the missing values by the mean value of the same moment on the next and previous day.	44
A.4	The time-serie with the original maximum difference between the minimum and maximum weekly rolling averages.	45
A.5	The time-serie with the new maximum difference between the minimum and maximum weekly rolling averages.	45

A.6	Figure that shows the seasonality of the electrical load during the day. .	46
B.1	Z-scores calculated from the yearly consumptions.	48

List of Tables

2.1	Table with information about the characteristics of the available datasets.	4
A.1	Amount of response on the voluntary questionnaires.	42

List of Abbreviations and Symbols

Abbreviations

LoG	Laplacian-of-Gaussian
MSE	Mean Square error
PSNR	Peak Signal-to-Noise ratio

Symbols

42	“The Answer to the Ultimate Question of Life, the Universe, and Everything” according to [?]
c	Speed of light
E	Energy
m	Mass
π	The number pi

Chapter 1

Introduction

The first contains a general introduction to the work. The goals are defined and the modus operandi is explained.

1.1 Importance of topic

Customer is better informed what the bill is going to be at the end of the month/year. Energy producer can build a better trust with its customer by sending reliable bills. (Providing good service) Producent can better estimate the energy demand of the whole customer population. This will lead to cheaper electricity production because a better planning is possible where there is less need of the more flexible but more expensive electricity installations e.g. diesel engines.

1.2 Problem formulation and link with previous studies

Now going to forecast individual houses, not aggregated signals.

1.3 Thesis objective and structure

The goal of this thesis is to do short-term load forecasting for individual households. A forecast of the electrical load of a household for 24 hours.

Chapter 2

Data analysis

In this chapter details of the dataset are introduced and an analysis is performed. Things discussed about the dataset concern assessing missing data, removing zero days, normalizing the data and removing time-series with identified fundamental changes. The analysis looks at the seasonality, influence of temperature, comparing weekdays with weekends, impact of holidays and the driving households characteristics. Finally the definition of a suitable baseline model is given, which will be used during the evaluation with more elaborate models in chapter 6.

2.1 Introduction to dataset

update pictures The data that is used in this thesis is made available for the **IEEE-CIS technical challenge on energy prediction from smart data**. It consists out of data from smart meters about the 1/2 hour granulated electricity consumption of 3248 households located in the United Kingdom in the year 2017. The definition of a household are all the people who occupy a single housing unit, regardless of their relationship to one another. Each smart meter collected thus a total of 17520 measurements that are performed by the the leading international energy provider, E.ON UK plc. Not all the 3248 smart meters consist of full data as can be seen in Figure A.1 in appendix A. It can be clearly seen that there are 12 steps in the amount of missing values. This is because the available data ranges from one month (only December) to a full year of data. This acknowledges that customers may have joined at different times during the year. Additionally, missing values are introduced due to errors in sending/receiving from smart meters.

Next to the electricity consumption of the different households, also information is available about the average, minimum and maximum temperature of the day on the location of the smart meter. This data is available at a daily resolution. Also, through voluntary surveys, incomplete information is collected about 2143 smart meters. This concerns e.g. dwelling type, number of occupants, number of bedrooms etc. Table A.1 displays all the attributes in appendix A.

Because of the additional information about the attributes that are summed up in

2. DATA ANALYSIS

consumption.csv		weather.csv	
# households	3248	information	average temperature
information	electric load		max temperature
measurements	17520		min temperature
granularity	$\frac{1}{2}$ hour	granularity	daily
timespan	year 2017	addInfo.csv	
location	UK	# households	2143

TABLE 2.1: Table with information about the characteristics of the available datasets.

Table A.1, it can be better understood what kind of households are included in the consumption.csv. It is assumed that all the loads are measured from households of the type listed below and each household is made up of maximum four persons and has a maximum of five bedrooms. industrial loads or small businesses, a bakery for example, are not considered.

- flat
- bungalow
- detached house
- semi-detached house
- terraced house

2.2 Preprocessing

Following steps discuss the preprocessing done on the consumption time-series containing measurements for the entire year.

2.2.1 Missing data

As discussed above the consumption dataset contains additionally to the missing months also missing data due to sending/receiving errors of the smart meters. When this happens the data of the whole day is lost. It should be emphasized that a missing value should not always directly be seen as an error. It can be that the smart meter was put off because the inhabitants were on a holiday for example. The nan values then also gives information about the consumption behaviour, namely that it is possible that the inhabitants go on vacation and the electrical load will in this case normally correspond to a constant base load. However, the assumption is made that in the case of the “consumption.csv” missing data corresponds to a sending/receiving error of the smart meter. This assumption is valid because when full year data is assessed, the missing values always perfectly correspond to a day of missing values. It is therefore highly likely that the organizers of the competition manually deleted days in the consumption to increase the difficulty of the forecasting and to model sending/receiving errors of the smart meters. That the missing values correspond to

sending/receiving errors is also stated in the data description of the competition.

Two methods to impute the missing values are compared. Method one substitutes the missing values of a time-series by the mean of all the measurements done by the meter. Method two replaces the missing values by the mean consumption value of the same moment on the next and previous day. If the next or previous day is also missing, the closest known day is used. The resulting signals can be seen in Figure A.2 and Figure A.3 in appendix A.

In order to ascertain which method of the two performs the best, a reference dataset is needed in order to compare the estimated with the true values of the missing measurements. From the original dataset which contain 3248 meters it was found that for 181 meters the month March was given without missing data. These 181 complete signals of the month March are used as reference dataset. In order to create the test data in each of the 181 meter signals 7 random days of the month March were removed and estimated by the earlier two methods. The normalized mean square errors, MSE_{AN} and MSE_{mean} given by $\sum_{i=1}^D e_i^2$ and normalized by MSE_{mean} are given in Figure 2.1.




FIGURE 2.1: Resulting month of March after substitution of the missing values by the mean value of the measurements.

From Figure 2.1 it can be seen that using method 2 which estimates the missing values by the mean consumption value of the same moment on the next and previous day, outperforms method 1 which takes the mean of the signal. Therefore, all the missing values in the consumption dataset are estimated using method 2 with the only exception the first of January and thirty-one December. If one of these two days are missing, the method 1 is used because of the absence of two neighbouring days.

2.2.2 Zero days

When processing the consumption data, some untraditional meter measurements were identified. For example there were 9 meters that had multiple days with zero day consumption measurements. Because it is unlikely that a household produces exactly zero kWh on a day all these 9 meters were removed. The consumption time-serie of one of the meters is displayed in Figure 2.2 in appendix A.




FIGURE 2.2: One of the 9 identified meters with multiple zero daily consumptions

Also, there has been looked if there were fundamental changes in the electricity consumption of certain meters. This is further discussed in section ??.

2.2.3 Normalization of the data

Normalization is necessary because while absolute consumption differs, relative patterns of human behaviour are more similar [5]. The patterns in the human behaviour is what a forecasting model is trying to predict and normalization contributes by avoiding the disturbance of different magnitudes in which this human pattern may occur. Every individual household time-serie is normalized based on its yearly consumption as was done in [5]. The advantage of using the yearly consumption to normalize in comparison of the minimum and maximum values, is the robustness against measurements out shooters and every smart meter has a total consumption of one at the end of the year.

$$normalized \ value = \frac{consumption_i}{\sum_{n=1}^{17520} consumption_i} \quad (2.1)$$

As discussed in section 2.3 the average is taken over all the normalized time-series to obtain a single signal.

2.2.4 Removing of fundamental changes in the consumption load

maybe have to remove this section. After normalization of all the individual time-series it is looked for fundamental changes in the consumption load due for example when an extra person lives in the house or when systems are installed that use a lot of electricity, during the year. An example of such a time-series can be seen in Figure A.4 in appendix A. These changes are identified by looking at the maximum difference of the minimum and maximum rolling mean consumption over 7 days for each individual meter. If this difference can not anymore be explained by the dependency on the temperature and previous present appliances, it is assumed that a fundamental change in electricity consumption took place. It is desired that the mean consumption doesn't change much during the year. This is because the model that later will be used expects the household situation to be the same for the entire year and the time-series with a fundamental change can thus lead to a disturbance when it is kept in the training data. Figure 2.3 shows all the maximum differences between the minimum and maximum weekly rolling averages. The red line on 0.00125 shows the cutoff and the smart meters above this line are removed. This cut off value chosen on sight. In total 239 smart meters remain. In Figure A.5 in appendix A the time-series with the new maximum difference between the minimum and maximum weekly rolling averages is given.




FIGURE 2.3: The maximum differences between the minimum and maximum weekly rolling averages for all the different time-series.

2.3 Analysis

Finally, the average is taken over all the remaining ... time-series to obtain a single signal. This is done to investigate the dependency of the smart meters on seasonality, temperature, weekends and holidays. At the end of this chapter a baseline forecasting will be discussed that will be used as null-hypothesis in chapter 6 to assess if the developed models lead to an improvement.

2.3.1 Seasonality

In this section the seasonality of the consumption data is discussed. In [2] it was concluded that all the forecasting algorithms that were considered, produced more accurate forecasts when they were combined with a preprocessing stage that extracted the seasonality before forecasting, compared to applying the same algorithms directly on raw data. The forecasting model is left with the task of modelling the deviation of the template consumption instead which is less challenging than performing a forecast out of the blue. These templates or filter are extracted from the consumption dataset by the use of equations 2.2 and 2.3. D and W gives respectively the number of days and weeks in the dataset. \bar{y}_i and \bar{y}_j gives the consumption of half an hour, averaged over respectively all days and weeks. **read paper again...**

$$\bar{y}_i = \frac{1}{D} \sum_{d=1}^D y_{di} i \in [1, 48] \quad (2.2)$$

$$\bar{y}_j = \frac{1}{W} \sum_{w=1}^W y_{wj} j \in [1, 336] \quad (2.3)$$

Figure A.6 shows the daily filter in appendix A. Figure 2.4 shows the weekly filter. In the daily and weekly filters there can clearly be seen a consumption peak after midnight. This is due to heat storage systems that use electricity in the hours of low tariff and that release heat during high electricity tariffs.

2.3.2 Influence of temperature

In following section the correlation between the temperature and the electricity consumption is discussed.

Pearson correlation

The Pearson correlation is a measurement of the linear dependency between two variables which is based on the covariance variable. A Pearson correlation values gives information concerning the magnitude of the association and the corresponding direction of it. A Pearson value of one and minus one give respectively a perfect positive and negative linear relation between the variables. A value of zero, corresponds




FIGURE 2.4: Figure that shows the seasonality of the electrical load during the week. The blue line shows the average week over all weeks in 2017.

to independent behaviour. Following formula is used when calculating the Pearson correlation.

$$\rho_{X,Y} = \frac{\sigma_{x,y}}{\sigma_x \sigma_y} \quad (2.4)$$

Assumptions concerning Pearson correlation are that samples used for the correlation should be independent, normal distributed and linear related to each other. Also, homoscedasticity is assumed. Homoscedasticity is important when performing linear regression and assumes that σ_x and σ_y are constant and not in function of each other. This final assumption is validated by making use of Figure 2.5.

This figure shows the classic cone-shaped pattern of heteroscedasticity. On days when it is warm there is overall similar human behaviour in lowering the electricity consumption. However, on colder days the variation in consumption is higher. Because the assumptions of the Pearson correlation are not fulfilled, care should be taken with its output.

Applying the Pearson correlation on Figure 2.5 gives a correlation value of -0.87 . This means there is a reasonable linearly decreasing relation.

Spearman correlation

Spearman correlation is a “Rank correlation”. This means that the ordering of the




FIGURE 2.5: Relation between consumption and temperature.

consumption and temperature in a sample are each compared in their corresponding array of measurements. When the ordering of both variables in a sample are similar, correlation is strong and positive. If the ordering is reversed, correlation is strong and negative. There is a perfect positive ordering if larger consumption always corresponds to a higher temperature. Notice that for a perfect ordering, no linear relation of the variables is necessary. The Spearman correlation coefficient is calculated using equation 2.4, but takes into account the rank of a variable in all the measurements of this variable instead of the measurement value itself.

In order to use the spearman correlation data has to be ordinal, which means that it can be ordered. The spearman correlation gives information about the monotonicity relation between the variables. $\rho = 1$ corresponds to a monotonically increasing relation.

Applying the Spearman correlation gives a correlation value of -0.89 , which means there is a reasonable negative monotonicity relation.

Kendal correlation The “Kendal correlation” is also a rank based correlation. Here it is looked at the pairs of observation that are concordant, discordant or neither. A correlation coefficient close to one occurs when both variables have the same ranking and similar a coefficient close to minus one occurs when rankings in one variable are the reverse of the other. Equation 2.5 gives the equation to calculate the “Kendal

correlation coefficient”.

$$\tau = \frac{n^+ - n^-}{\sqrt{(n^+ + n^- + n^x)(n^+ + n^- + n^y)}} \quad (2.5)$$

- n^+ is the number of concordant pairs
- n^- is the number of discordant pairs
- n^x is the number of ties only in x
- n^y is the number of ties only in y
- concordant $\rightarrow (x_i > x_j)$ and $(y_i > y_j)$ or $(x_i < x_j)$ and $(y_i < y_j)$
- discordant $\rightarrow (x_i > x_j)$ and $(y_i < y_j)$ or $(x_i < x_j)$ and $(y_i > y_j)$
- neither $\rightarrow (x_i = x_j)$ or $(y_i = y_j)$
- if both $(x_i = x_j)$ and $(y_i = y_j) \rightarrow$ not included in either n^x or n^y

Applying the Kendal correlation gives a correlation value of -0.67 , which means there is a reasonable negative monotonicity relation.

2.3.3 Comparing weekdays with weekends

Weekdays vs weekends can be compared with the help of Figure 2.4. The reader is reminded that in order to get this graph, all the remaining household loads after preprocessing are averaged after which all the weeks are again averaged. It can be seen that the consumption of the average business day is similar to a weekend day concerning the two main peaks during the day and the sharp peak at midnight. However, it can be seen that the first peak during the day is higher and goes less down again. This effect can be seen both during a sunday and saturday, but is most visible during a sunday. To proof previous statements similarity is measured by calculating the hourly difference of the 21 combinations that can be made of two different days. Figure ?? shows in red the error of combinations between business days or weekends and in blue the error of combinations between a business day and weekend day. **Put figure**

2.3.4 Impact of holidays

In order to look at the impact of a holiday, all the holidays of the English and welsh holiday calendar are identified for the year 2017. For each of the 8 holidays a corresponding business day is selected with an as close as possible average temperature of the day. This is done to mitigate the temperature dependency. The resulting average holiday and business day is given in Figure 2.6. It can be seen that the consumption of a holiday behaves similar as a weekend day. Figure shows the average error between a holiday vs business day and a holiday vs weekend day. The error

is calculated as discussed in section 2.3.3. **Check again if the legend is not swapped.**




FIGURE 2.6: Figure with the comparison between holidays and business days.

2.3.5 Identification of driving attributes

In this section the influence of the extra knowledge about the kind of household where the smart meter is located, is investigated. This is not done by using a single averaged signal as was the case in the previous analysis sections. Now, every meter with additional information is considered. In Figure 2.7 the monthly consumption of the month December in function of dwelling type is shown. The month December is chosen, because this month is known for every smart meter. Missing values of the smart meters are substituted by method two, as discussed in section 2.2.1. The amount of meters used for every visualization can be seen in Table A.1.

Similar as was done in Figure 2.7 is also done for the other characteristics of the smart meters. The conclusions are listed below. As can be seen in Table A.1, some characteristics have not much data or the data is not much distribute over the different options of a characteristic. If this is the case, no reliable conclusions could be drawn. **Add concrete numbers!!**

- There is a lot of variance in the monthly consumption of a detached house, but it has mostly a higher consumption than other dwelling types




FIGURE 2.7: Figure with the comparison of the different dwelling types.

- A “real” house (detached, semi-detached or terraced) tends to have higher monthly consumptions than a flat or bungalow.
- The order of monthly consumption according to the mean and median values: Flat < Bungalow < Semi-detached < Terraced < Detached
- More occupants means more monthly consumption
- More rooms in the house means more monthly consumption
- Almost all houses use gas as heating fuel
- Almost all houses use gas as hot water fuel
- The age of the boiler has no clear effect on the monthly consumption
- The vast majority of the lofts are insulated
- The majority of walls are insulated
- The vast majority heats till a temperature between 18 and 20 degrees
- The majority of people has an efficient lighting percentage between 75% and 100%

2.4 Baseline model

A naive baseline 24 hour forecasting model that is chosen is using the last 24 hour as prediction.

2.5 Conclusion

The final section of the chapter gives an overview of the important results of this chapter. This implies that the introductory chapter and the concluding chapter don't need a conclusion.

Chapter 3

State of the art short-term residential load forecasting techniques

Forecasting the electrical load of the different individual households has a couple of challenges. There should be dealt with the missing values, as discussed in section 2.2.1. Also, the different time-series are influenced by exogenous factors as weather conditions and the day of the year. The dependency on exogenous variables can be a very non-linear relation and can have different effects on different households. For example depending on a house has solar panels, the consumption could be altered much. Only three indications of the temperature are given on a daily basis. Some additional information is know of certain households, but this data is very incomplete. Next, the individual load series have a high volatility and uncertainty with respect to a load signal on transmission level which shows more consistent seasonality and straight forward dependency on weather and calendar variables. This is because the contingency of the individual load data is mitigated due to averaging out of the uncertainty. Ofcourse, the obvious disadvantage is that only forecasts on this aggregated level can be made which is not the goal of our investigation. To tackle the high non-linearity that is inherent to residential load forecasting in literature often “Neural Networks” to deal with this. **See also paper TA2 -> aggregated vs individual forecasting.**

3.1 Introduction to Neural Networks

A standard multilayer feedforward neuralnetwork with locally bounded piecewise continuous activation function can approximate any continuous function to any degree of accuracy if and only if the network’s activation function is not a polynomial, as stated by **Leshno et al** in **1993**. This theorem proofs that a “universal approximator” exists for continuous functions, but it lacks the recipe to construct it. In [6] it is shown that a feedforward network with a single layer is enough to approximate any function by a specified accuracy if the hidden layer has the possibility to add an

unlimited amount of hidden neurons in its layer. It is discussed that when a function is discontinuous, which means that it makes sudden, sharp jumps, it is not possible to approximate the function by any prescribed accuracy. However, in practise a continuous approximation is often good enough.

Neural networks are suitable of learning very non-linear mappings between inputs and outputs. The difference between “Deep Neural Networks” and “Shallow Neural Networks” is the amount of layers of neurons are used inside the network. These layers of neurons, that are not inputs or outputs are called “hidden neurons”. Because a “Deep Neural Network” has a hierarchical layout of the different hidden layers, it not only learning features from the non-linear combinations of inputs, but uses other layers to learn features of combinations of features learned in lower hidden layers. This is possible because higher hidden layers get the outputs of lower hidden layers as input. As discussed in [7] due to this characteristic, deep learning is suitable to learn multiple uncertainties with differing sharing levels over different households e.g. the amount of sunshine. However, because of the higher expressiveness (and often the amount of the to learn parameters), a “Deep Neural Network” with respect to a “Shallow Neural Network”, suffers more of overfitting as is discussed in section 3.1.4.

3.1.1 MLP

The simplest configuration of deep networks are multilayer perceptrons and they are made up out of multiple fully connected layers of neurons. Figure 3.1 shows a MLP with one hidden layer.




FIGURE 3.1: Figure of a MLP (source [9]).

All layers are connected to the next layer by the means of an affine function together with a non-linear activation function represented by sigma as shown by equation 3.1 with $\mathbf{L}^{(N)}$ the vector with outputs of the Nth layer, $\mathbf{W}^{(N)}$ the Nth weight matrix and $\mathbf{b}^{(N)}$ the Nth bias.

$$\mathbf{L}^{N+1} = \sigma(\mathbf{W}^{(N)}\mathbf{L}^N + \mathbf{b}^{(N)}) \quad (3.1)$$

3.1.2 CNN

See oneNote

3.1.3 RNN

A recurrent Neural Network is a specialized neural network to better deal with sequential information. While traditional deep neural networks assume that inputs and outputs are independent of each other, the output of recurrent neural networks depend on the prior elements within the sequence. In order to take past information from previous inputs into account, a hidden variable h_t is used. By making use of this variable which makes a summary of the previous seen information, an exponential increase in the number of model parameters is avoided. Equation 3.2 shows how the previous hidden state and the current information are merged in the next hidden state with $\mathbf{X}^t \in \mathbb{R}^{d \times 1}$, $\mathbf{H}^t \in \mathbb{R}^{h \times 1}$, $\mathbf{W}_1 \in \mathbb{R}^{h \times d}$, $\mathbf{W}_2 \in \mathbb{R}^{h \times h}$ and $\mathbf{b} \in \mathbb{R}^{h \times 1}$.

$$\mathbf{H}^{t+1} = \sigma(\mathbf{W}_1 \mathbf{X}^t + \mathbf{W}_2 \mathbf{H}^t + \mathbf{b}) \quad (3.2)$$

The this equation \mathbf{X}^t corresponds to one example at time step t with dimensionality d . Also a deep RNN is possible, where multiple hidden state per time step are used.

The mapping from the hidden state to an output is executed by making use of Equation 3.3 with $\mathbf{O}^t \in \mathbb{R}^{q \times 1}$, $\mathbf{H}^t \in \mathbb{R}^{h \times 1}$, $\mathbf{W}_3 \in \mathbb{R}^{q \times h}$ and $\mathbf{b} \in \mathbb{R}^{q \times 1}$.

$$\mathbf{O}^t = \mathbf{W}_3 \mathbf{H}^t + \mathbf{b} \quad (3.3)$$




FIGURE 3.2: Figure of the logical flow of a vanilla RNN with a hidden state (source [9]).

3.1.4 Difficulties & Solutions of neural networks

Neural Networks have a high expressiveness but comes at the cost of overfitting and a vanishing gradient. when the NN is learning from training data, every epoch the error between the input and output of the training examples is reduced. In the beginning the generalization error reduces simultaneously with the training error. The generalization error is the error that the model makes on data that is not in the training set. However, on a certain point during the training the generalization error increases while the training error still decreases. This means that the model is no longer learning “intelligent” general rules and patterns in the data, but is just remembering the training data and will therefore not apply in general. This is often the case in a model with high expressiveness because the model is less pushed to make generalizations and has the ability to just to remember the training data. Solutions to overfitting can be regularization which includes the parameter norms as a cost in the objective function. Typical choices for resembling the size of a parameter are the L_1 and the L_2 norms. Other methods that can be used are: early stopping, dropout and pruning.

It should also be noted that the gradient can increase very much, which in literature is called gradient explosion. The solution strategy for this is applying gradient clipping.

The second problem is the vanishing gradient problem which originates because while using the backpropagation algorithm to calculate the gradient which is used in different update methods of the weights, the gradient is calculated at the end of the NN and propagated back using every time the previous calculated gradient values who exponentially decrease. Therefore at the first layers of the network, the gradient has become so small that the weights are almost not updated anymore. In a RNN setting this corresponds to having a short term memory which means that initial inputs that were presented to the NN are being forgotten. Mitigation strategies often proposed in literature are LSTM and GRU. Both techniques have in common that they can learn which data in the sequence is important and should be retained and which information can be thrown away. It is important to state that LSTM and GRU are not solving the vanishing gradient problem as explained in [8]. The gradient is still exponentially decreasing, but the effect is less pronounced as can be seen for LSTM in Figure 3.3. τ gives the number of epochs.

3.2 Short-Term residential electrical load forecasting

Pooling paper Classical ways to deal with uncertainty.

Residential electrical load series have a high amount of volatility and uncertainty due to the contingency of the electrical consumption. Classical ways to deal with this are discussed in [7] and listed as follows:

1. Clustering to group similar houses based on historic load or exogenous consumption driving variables. Because the load or driving variables are similar in




FIGURE 3.3: Exponential decrease of the gradient size of a simple RNN (red) or a LSTM (blue) (source [8]).

a cluster, the variance of uncertainty is also decreased. However, performance is very dependent of the dataset.

2. Aggregating the residential loads to cancel out the uncertainties. The aggregated signal will show more regular patterns which means that is easier to predict. The downside is that the aggregated forecast will do a poor job of serving as forecast for a household
3. A spectral analysis e.g. wavelet analysis, Fourier transforms and empirical mode decomposition aim at separating a load serie into a regular pattern, an uncertain signal and noise. Because the amount of regularity is low in a residential load serie, this method is infeasible.

In this paper [7] a novel pooling-based deep recurrent neural network is proposed which collects load profiles of neighbouring houses into a pool of training inputs. Pooling of neighbouring households historical loads to serve as input of the “Deep Recurrent Neural Network”, is proposed to increase the data volume and diversity of load forecasting, which mitigates the effect of overfitting present in a DRNN. The idea is as quoted by [7] to use the interconnected spacial information to compensate insufficient temporal information. Thereby, the pool of data allows to learn the correlations between neighbouring households and the shared uncertainties coming from external factors e.g. temperature. Also, due to the pooling of different households during training the DRNN is able to learn common uncertainties. In paper [7] pools consisting of 10 households are used. From the pool of inputs every epoch a randomly chosen batch of load signals are fed to the network. LSTM is applied to mitigate the short term memory of the RNN. Additionally, there is been made use of early stopping to further avoid overfitting. To implement early stopping there has been looked at the “MSE” for k iterations, obtained by cross-validation. When the variance of this sequence gets smaller than a specified variable, training stops. When the training ends, performance is tested on each household by using the learned

3. STATE OF THE ART SHORT-TERM RESIDENTIAL LOAD FORECASTING TECHNIQUES

network to perform a feed-forward prediction of the electrical load.

An overview of the different steps that were done during the proposed method are: data cleaning and preprocessing → data pooling → data sampling → data training → benchmarking.

Performance of the proposed method was finally evaluated based on a test set of the last 30 days and consisting out of :

1. performance of the proposed method with respect to Vanilla RNN, SVR and DRNN (without pooling)
2. the effect of the neural network depth and pooling

The proposed DRNN with pooling outperforms all other four methods based on following three metrics:

$$RMSE = \sqrt{\frac{\sum_{t=1}^N (\hat{y}_t - y_t)^2}{N}} \quad (3.4)$$

$$NRMSE = \frac{RMSE}{y_{max} - y_{min}} \quad (3.5)$$

$$MAE = \frac{\sum_{t=1}^N |\hat{y}_t - y_t|}{N} \quad (3.6)$$

The amount of which the PDRNN outperformed the other methods can be seen in Table ?? . The effect of the depth of the DRNN and the pooling method is depicted in Figure 3.5. It can be seen that without the pooling method the DRNN only benefits from extra layers till three are used. This is because from that point, overfitting will reduce the generalization capacity of the DRNN. With the pooling technique, extra layers stays beneficial. It can thus be concluded that introducing extra hidden layers is a good choice to model the non-linear relations, but this can only be done efficiently when overfitting is mitigated by the use of a pooling strategy. The RNN with pooling used for benchmarking consisted out of five layers and thirty hidden units in each layer.

GRU (Gated Reset Update) or LSTM (Long Short Term Memory) can be implemented. They are both enhancements of the vanilla RNN which suffers from a vanishing gradient which causes it to behave without a long term memory. In practise to know which one works often both are tried [8]. Stochastic gradient descent means that the approximated gradient is calculated from a random subset of the available data instead from the entire dataset.

Short-term Residential load forecasting based on LSTM RNN paper

In [4] it is chosen for a LSTM approach to forecast the complex temporal consumption pattern which characterises a single household electricity load. It is discussed that the diversity in the aggregated level of the individual electrical loads, smooths the

<i>Network Architecture</i>	<i>RMSE (kWh)</i>	<i>NRMSE (kWh)</i>	<i>MAE (kWh)</i>
<i>ARIMA</i>	0.5593	0.1132	0.2998
<i>RNN</i>	0.5280	0.1076	0.2913
<i>SVR</i>	0.5180	0.1048	0.2855
<i>DRNN</i>	0.4815	0.0974	0.2698
<i>PDRNN</i>	0.4505	0.0912	0.2510
<i>Improvement from DRNN to PDRNN</i>	6.45%		6.96%
<i>Improvement from ARIMA to PDRNN</i>	19.46%		16.28%

FIGURE 3.4: Results obtained in paper [7] using the PDRNN method.

daily load profile. This has as effect that the aggregated electrical load time-series becomes more predictable, while a single household electrical load is more dependent on the human behaviour of its residents. This is substantiated by making use of a density based clustering technique where it was shown that the different daily consumptions of the aggregated signal could be described by one cluster and no outliers. An outlier means that a daily consumption could not be assigned to a cluster. On the other hand for individual time series the amount of outliers could range to over 80. To compare the consistency of different individual load signals the amount of outliers could therefore be used.

Because the residents daily routine is characterizing the household load so much, this is tried to be learned directly inside the LSTM RNN.

Inputs that are given to the LSTM are k past half hour load measurements, the time of when this measurements were taken, the day of the week of the measurements and if this day is a holiday or not. In table 3.6 the results are shown of the LSTM RNN method in comparison with other forecasting techniques. It can be noted that the proposed technique outperforms the rest based on the average performance of 29,808 individual forecasts of half an hour individual loads. Forecasting was performed on 69 different electrical loads coming from households in Australia. However, for individual load series forecasting the MAPE minimization is also remarkable when considering its simplicity in comparison with LSTM. Next, it was concluded that learning methods that had good performance on aggregated time-series e.g. IS-HF

3. STATE OF THE ART SHORT-TERM RESIDENTIAL LOAD FORECASTING TECHNIQUES




FIGURE 3.5: Influence of the number of layers and the pooling method used in [7].

and KNN, perform much worse when predicting individual loads.

Further, by making use of a regression technique in function of the amount of outliers it is shown that LSTM and BPNN (Back-Propagation Neural Network) perform similar for, as previously discussed, consistent individual loads. The LSTM only starts to differentiate in performance when inconsistency grows. To conclude things that lack in [4] are practical useful forecasts of a timespan of 24h instead of only half an hour and making use of a rule of thumb when parameter tuning. Hyperparameters that can be tuned in LSTM are: learning rate, lag variable, amount of hidden layers and the amount of hidden nodes.

CNN-LSTM paper

In [3] a novel technique is proposed which makes use of a convolutional neural network from which the outputs are given to a LSTM recurrent network after which a fully connected neural network is used to produce the outputs. The purpose of the CNN is to extract the features that are the main drivers of energy consumption and to

<i>Method/Scenario</i>	<i>Avg. MAPE individual forecasts</i>	<i>Avg. MAPE Aggregating forecasts</i>	<i>Avg. MAPE forecasting the aggregate</i>
LSTM/2 time steps	44.39 %	8.18%	9.14%
LSTM/6 time steps	44.31%	8.39%	8.95%
LSTM/12 time steps	44.06%	8.64%	8.58%
Empirical mean	136.46%	32.54%	32.54%
MAPE minimisation	46.00%	34.91%	27.28%
BPNN-D/1 day	80.02%	11.69%	14.50%
BPNN-D/2 days	75.28%	11.67%	14.48%
BPNN-D/3 days	74.10%	11.66%	14.42%
BPNN-T/2 time steps	49.62%	8.37%	9.54%
BPNN-T/6 time steps	49.04%	8.29%	9.55%
BPNN-T/12 time steps	49.49%	8.36%	9.17%
KNN/2 time steps	74.83%	15.37%	11.23%
KNN/6 time steps	71.19%	14.61%	12.10%
KNN/12 time steps	81.13%	15.23%	15.30%
ELM/2 time steps	122.90%	33.68%	Not tested
ELM/6 time steps	136.49%	35.35%	Not tested
ELM/12 time steps	123.45%	30.05%	Not tested
IS-HF	96.76%	20.43%	32.09%

FIGURE 3.6: Different approaches tried in [4] and their averaged performance of 29,808 individual forecasts of half an hour individual loads.

remove the noise that comes initially together with the raw inputs. The CNN is made up out of convolution layers and pooling layers and makes use of the “ReLU” activation function. The main purpose of a convolution layer is to extract features while the pooling layer reduces the number of parameters by making use of the “max pooling principle”. Using the “max pooling principle” means taking the max value of each neuron cluster of the previous layer. As discussed in paper [4] LSTM is suitable to alleviate the problem of a vanishing or exploding gradient which characterized a simple RNN. LSTM is able to preserve long-term memory by making use of memory states that is used in the calculation of hidden states. It is therefore suitable to remembering the irregular trend of the electrical load time-serie. Finally, a fully connected time-serie predicts the load forecast.

Paper [3] further showed superiority with respect to only making use of the LSTM layers as can be seen in Table ?? . The Inputs that were used to forecast the household load which is located in France are: three submeters with historical loads, global intensity, voltage, global reactive power, global active power, time, data and month. At last, also an analysis is performed to investigate the influence of the different inputs by calculating the average class activation score over the inputs. The results

3. STATE OF THE ART SHORT-TERM RESIDENTIAL LOAD FORECASTING TECHNIQUES

are shown in Figure ???. It can be seen that especially “Sub metering 3” has a big influence on the final forecasts. This sub meter corresponds to the the electric water heater and air conditioner of the house. As was shown in Section A.1 the dataset used in this thesis gives only information about the presence of a hot water heater. Discussed limitations in the paper are the definition of the hyper parameters that were set by trail and error instead of using an automated method e.g. a genetic algorithm. A further limitation is the lack of household characteristics e.g. the amount of residents living in the house. It has previously been shown by **C. Beckel et al.** that household occupancy is one of the primarily drivers of electrical consumption in a household.




FIGURE 3.7: The importance of the different inputs as based on the average class activation score. (source [3])

CNN-GRU paper

3.3 Tables

Tables are used to present data neatly arranged. A table is normally not a spreadsheet! Compare Table ?? en Table ??: which table do you prefer?

3.4 Conclusion

The final section of the chapter gives an overview of the important results of this chapter. This implies that the introductory chapter and the concluding chapter don't need a conclusion.

Prediction performance with time resolution change.

Method	Resolution	MSE	RMSE	MAE	MAPE
Linear Regression	Minutely	0.4046	0.6361	0.4176	74.52
	Hourly	0.4247	0.6517	0.5022	83.74
	Daily	0.2526	0.5026	0.3915	52.69
	Weekly	0.1480	0.3847	0.3199	41.33
LSTM	Minutely	0.7480	0.8649	0.6278	51.45
	Hourly	0.5145	0.7173	0.5260	44.37
	Daily	0.2406	0.4905	0.4125	38.72
	Weekly	0.1049	0.3239	0.2438	35.78
CNN-LSTM	Minutely	0.3738	0.6114	0.3493	34.84
	Hourly	0.3549	0.5957	0.3317	32.83
	Daily	0.1037	0.3221	0.2569	31.83
	Weekly	0.0952	0.3085	0.2382	31.84

FIGURE 3.8: Comparison between LSTM and CNN-LSTM. source([3])

Chapter 4

Clustering of the load profiles

Do a literature study about forecasting. What is the current state of the art methods to do forecasting.

4.1 The First Topic of this Chapter

4.1.1 Item 1

Sub-item 1

Nunc velit augue, scelerisque dignissim, lobortis et, aliquam in, risus. In eu eros. Vestibulum ante ipsum primis in faucibus orci luctus et ultrices posuere cubilia Curae; Curabitur vulputate elit viverra augue. Mauris fringilla, tortor sit amet malesuada mollis, sapien mi dapibus odio, ac imperdiet ligula enim eget nisl. Quisque vitae pede a pede aliquet suscipit. Phasellus tellus pede, viverra vestibulum, gravida id, laoreet in, justo. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Integer commodo luctus lectus. Mauris justo. Duis varius eros. Sed quam. Cras lacus eros, rutrum eget, varius quis, convallis iaculis, velit. Mauris imperdiet, metus at tristique venenatis, purus neque pellentesque mauris, a ultrices elit lacus nec tortor. Class aptent taciti sociosqu ad litora torquent per conubia nostra, per inceptos hymenaeos. Praesent malesuada. Nam lacus lectus, auctor sit amet, malesuada vel, elementum eget, metus. Duis neque pede, facilisis eget, egestas elementum, nonummy id, neque.

Sub-item 2

Proin non sem. Donec nec erat. Proin libero. Aliquam viverra arcu. Donec vitae purus. Donec felis mi, semper id, scelerisque porta, sollicitudin sed, turpis. Nulla in urna. Integer varius wisi non elit. Etiam nec sem. Mauris consequat, risus nec congue condimentum, ligula ligula suscipit urna, vitae porta odio erat quis sapien. Proin luctus leo id erat. Etiam massa metus, accumsan pellentesque, sagittis sit amet, venenatis nec, mauris. Praesent urna eros, ornare nec, vulputate eget, cursus

sed, justo. Phasellus nec lorem. Nullam ligula ligula, mollis sit amet, faucibus vel, eleifend ac, dui. Aliquam erat volutpat.

4.1.2 Item 2

Fusce vehicula, tortor et gravida porttitor, metus nibh congue lorem, ut tempus purus mauris a pede. Integer tincidunt orci sit amet turpis. Aenean a metus. Aliquam vestibulum lobortis felis. Donec gravida. Sed sed urna. Mauris et orci. Integer ultrices feugiat ligula. Sed dignissim nibh a massa. Donec orci dui, tempor sed, tincidunt nonummy, viverra sit amet, turpis. Quisque lobortis. Proin venenatis tortor nec wisi. Vestibulum placerat. In hac habitasse platea dictumst. Aliquam porta mi quis risus. Donec sagittis luctus diam. Nam ipsum elit, imperdiet vitae, faucibus nec, fringilla eget, leo. Etiam quis dolor in sapien porttitor imperdiet.

4.2 The Second Topic

Cras pretium. Nulla malesuada ipsum ut libero. Suspendisse gravida hendrerit tellus. Maecenas quis lacus. Morbi fringilla. Vestibulum odio turpis, tempor vitae, scelerisque a, dictum non, massa. Praesent erat felis, porta sit amet, condimentum sit amet, placerat et, turpis. Praesent placerat lacus a enim. Vestibulum non eros. Ut congue. Donec tristique varius tortor. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Nam dictum dictum urna. Phasellus vestibulum orci vel mauris. Fusce quam leo, adipiscing ac, pulvinar eget, molestie sit amet, erat. Sed diam. Suspendisse eros leo, tempus eget, dapibus sit amet, tempus eu, arcu. Vestibulum wisi metus, dapibus vel, luctus sit amet, condimentum quis, leo. Suspendisse molestie. Duis in ante. Ut sodales sem sit amet mauris. Suspendisse ornare pretium orci. Fusce tristique enim eget mi. Vestibulum eros elit, gravida ac, pharetra sed, lobortis in, massa. Proin at dolor. Duis accumsan accumsan pede. Nullam blandit elit in magna lacinia hendrerit. Ut nonummy luctus eros. Fusce eget tortor.

Ut sit amet magna. Cras a ligula eu urna dignissim viverra. Nullam tempor leo porta ipsum. Praesent purus. Nullam consequat. Mauris dictum sagittis dui. Vestibulum sollicitudin consectetur wisi. In sit amet diam. Nullam malesuada pharetra risus. Proin lacus arcu, eleifend sed, vehicula at, congue sit amet, sem. Sed sagittis pede a nisl. Sed tincidunt odio a pede. Sed dui. Nam eu enim. Aliquam sagittis lacus eget libero. Pellentesque diam sem, sagittis molestie, tristique et, fermentum ornare, nibh. Nulla et tellus non felis imperdiet mattis. Aliquam erat volutpat.

4.3 Conclusion

Vestibulum sodales ipsum id augue. Integer ipsum pede, convallis sit amet, tristique vitae, tempor ut, nunc. Nam non ligula non lorem convallis hendrerit. Maecenas hendrerit. Sed magna odio, aliquam imperdiet, porta ac, aliquet eget, mi. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus.

Vestibulum nisl sem, dignissim vel, euismod quis, egestas ut, orci. Nunc vitae risus vel metus euismod laoreet. Cras sit amet neque a turpis lobortis auctor. Sed aliquam sem ac elit. Cras velit lectus, facilisis id, dictum sed, porta rutrum, nisl. Nam hendrerit ipsum sed augue. Nullam scelerisque hendrerit wisi. Vivamus egestas arcu sed purus. Ut ornare lectus sed eros. Suspendisse potenti. Mauris sollicitudin pede vel velit. In hac habitasse platea dictumst.

Suspendisse erat mauris, nonummy eget, pretium eget, consequat vel, justo. Pellentesque consectetur erat sed lacus. Nullam egestas nulla ac dui. Donec cursus rhoncus ipsum. Nunc et sem eu magna egestas malesuada. Vivamus dictum massa at dolor. Morbi est nulla, faucibus ac, posuere in, interdum ut, sapien. Proin consectetur pretium urna. Donec sit amet nibh nec purus dignissim mattis. Phasellus vehicula elit at lacus. Nulla facilisi. Cras ut arcu. Sed consectetur. Integer tristique elit quis felis consectetur eleifend. Cras et lectus.

Ut congue malesuada justo. Curabitur congue, felis at hendrerit faucibus, mauris lacus porttitor pede, nec aliquam turpis diam feugiat arcu. Nullam rhoncus ipsum at risus. Vestibulum a dolor sed dolor fermentum vulputate. Sed nec ipsum dapibus urna bibendum lobortis. Vestibulum elit. Nam ligula arcu, volutpat eget, lacinia eu, lobortis ac, urna. Nam mollis ultrices nulla. Cras vulputate. Suspendisse at risus at metus pulvinar malesuada. Nullam lacus. Aliquam tempus magna. Aliquam ut purus. Proin tellus.

Chapter 5

Forecasting of time-series

Typical variables used in a forecasting model are: past electricity consumption loads, weather information, calendar information and error-correction terms [\[1\]](#).

5.1 The First Topic of this Chapter

5.1.1 Item 1

5.2 Conclusion

Chapter 6

Evaluating results

Morbi malesuada hendrerit dui. Nunc mauris leo, dapibus sit amet, vestibulum et, commodo id, est. Pellentesque purus. Pellentesque tristique, nunc ac pulvinar adipiscing, justo eros consequat lectus, sit amet posuere lectus neque vel augue. Cras consectetur libero ac eros. Ut eget massa. Fusce sit amet enim eleifend sem dictum auctor. In eget risus luctus wisi convallis pulvinar. Vivamus sapien risus, tempor in, viverra in, aliquet pellentesque, eros. Aliquam euismod libero a sem.

6.1 The First Topic of this Chapter

6.1.1 Item 1

Sub-item 1

Nunc velit augue, scelerisque dignissim, lobortis et, aliquam in, risus. In eu eros. Vestibulum ante ipsum primis in faucibus orci luctus et ultrices posuere cubilia Curae; Curabitur vulputate elit viverra augue. Mauris fringilla, tortor sit amet malesuada mollis, sapien mi dapibus odio, ac imperdiet ligula enim eget nisl. Quisque vitae pede a pede aliquet suscipit. Phasellus tellus pede, viverra vestibulum, gravida id, laoreet in, justo. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Integer commodo luctus lectus. Mauris justo. Duis varius eros. Sed quam. Cras lacus eros, rutrum eget, varius quis, convallis iaculis, velit. Mauris imperdiet, metus at tristique venenatis, purus neque pellentesque mauris, a ultrices elit lacus nec tortor. Class aptent taciti sociosqu ad litora torquent per conubia nostra, per inceptos hymenaeos. Praesent malesuada. Nam lacus lectus, auctor sit amet, malesuada vel, elementum eget, metus. Duis neque pede, facilisis eget, egestas elementum, nonummy id, neque.

Sub-item 2

Proin non sem. Donec nec erat. Proin libero. Aliquam viverra arcu. Donec vitae purus. Donec felis mi, semper id, scelerisque porta, sollicitudin sed, turpis. Nulla in urna. Integer varius wisi non elit. Etiam nec sem. Mauris consequat, risus nec

congue condimentum, ligula ligula suscipit urna, vitae porta odio erat quis sapien. Proin luctus leo id erat. Etiam massa metus, accumsan pellentesque, sagittis sit amet, venenatis nec, mauris. Praesent urna eros, ornare nec, vulputate eget, cursus sed, justo. Phasellus nec lorem. Nullam ligula ligula, mollis sit amet, faucibus vel, eleifend ac, dui. Aliquam erat volutpat.

6.1.2 Item 2

Fusce vehicula, tortor et gravida porttitor, metus nibh congue lorem, ut tempus purus mauris a pede. Integer tincidunt orci sit amet turpis. Aenean a metus. Aliquam vestibulum lobortis felis. Donec gravida. Sed sed urna. Mauris et orci. Integer ultrices feugiat ligula. Sed dignissim nibh a massa. Donec orci dui, tempor sed, tincidunt nonummy, viverra sit amet, turpis. Quisque lobortis. Proin venenatis tortor nec wisi. Vestibulum placerat. In hac habitasse platea dictumst. Aliquam porta mi quis risus. Donec sagittis luctus diam. Nam ipsum elit, imperdiet vitae, faucibus nec, fringilla eget, leo. Etiam quis dolor in sapien porttitor imperdiet.

6.2 The Second Topic

Cras pretium. Nulla malesuada ipsum ut libero. Suspendisse gravida hendrerit tellus. Maecenas quis lacus. Morbi fringilla. Vestibulum odio turpis, tempor vitae, scelerisque a, dictum non, massa. Praesent erat felis, porta sit amet, condimentum sit amet, placerat et, turpis. Praesent placerat lacus a enim. Vestibulum non eros. Ut congue. Donec tristique varius tortor. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Nam dictum dictum urna.

Phasellus vestibulum orci vel mauris. Fusce quam leo, adipiscing ac, pulvinar eget, molestie sit amet, erat. Sed diam. Suspendisse eros leo, tempus eget, dapibus sit amet, tempus eu, arcu. Vestibulum wisi metus, dapibus vel, luctus sit amet, condimentum quis, leo. Suspendisse molestie. Duis in ante. Ut sodales sem sit amet mauris. Suspendisse ornare pretium orci. Fusce tristique enim eget mi. Vestibulum eros elit, gravida ac, pharetra sed, lobortis in, massa. Proin at dolor. Duis accumsan accumsan pede. Nullam blandit elit in magna lacinia hendrerit. Ut nonummy luctus eros. Fusce eget tortor.

Ut sit amet magna. Cras a ligula eu urna dignissim viverra. Nullam tempor leo porta ipsum. Praesent purus. Nullam consequat. Mauris dictum sagittis dui. Vestibulum sollicitudin consectetur wisi. In sit amet diam. Nullam malesuada pharetra risus. Proin lacus arcu, eleifend sed, vehicula at, congue sit amet, sem. Sed sagittis pede a nisl. Sed tincidunt odio a pede. Sed dui. Nam eu enim. Aliquam sagittis lacus eget libero. Pellentesque diam sem, sagittis molestie, tristique et, fermentum ornare, nibh. Nulla et tellus non felis imperdiet mattis. Aliquam erat volutpat.

6.3 Conclusion

Vestibulum sodales ipsum id augue. Integer ipsum pede, convallis sit amet, tristique vitae, tempor ut, nunc. Nam non ligula non lorem convallis hendrerit. Maecenas hendrerit. Sed magna odio, aliquam imperdiet, porta ac, aliquet eget, mi. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Vestibulum nisl sem, dignissim vel, euismod quis, egestas ut, orci. Nunc vitae risus vel metus euismod laoreet. Cras sit amet neque a turpis lobortis auctor. Sed aliquam sem ac elit. Cras velit lectus, facilisis id, dictum sed, porta rutrum, nisl. Nam hendrerit ipsum sed augue. Nullam scelerisque hendrerit wisi. Vivamus egestas arcu sed purus. Ut ornare lectus sed eros. Suspendisse potenti. Mauris sollicitudin pede vel velit. In hac habitasse platea dictumst.

Suspendisse erat mauris, nonummy eget, pretium eget, consequat vel, justo. Pellentesque consectetur erat sed lacus. Nullam egestas nulla ac dui. Donec cursus rhoncus ipsum. Nunc et sem eu magna egestas malesuada. Vivamus dictum massa at dolor. Morbi est nulla, faucibus ac, posuere in, interdum ut, sapien. Proin consectetur pretium urna. Donec sit amet nibh nec purus dignissim mattis. Phasellus vehicula elit at lacus. Nulla facilisi. Cras ut arcu. Sed consectetur. Integer tristique elit quis felis consectetur eleifend. Cras et lectus.

Ut congue malesuada justo. Curabitur congue, felis at hendrerit faucibus, mauris lacus porttitor pede, nec aliquam turpis diam feugiat arcu. Nullam rhoncus ipsum at risus. Vestibulum a dolor sed dolor fermentum vulputate. Sed nec ipsum dapibus urna bibendum lobortis. Vestibulum elit. Nam ligula arcu, volutpat eget, lacinia eu, lobortis ac, urna. Nam mollis ultrices nulla. Cras vulputate. Suspendisse at risus at metus pulvinar malesuada. Nullam lacus. Aliquam tempus magna. Aliquam ut purus. Proin tellus.

Chapter 7

Conclusion

The final chapter contains the overall conclusion. It also contains suggestions for future work and industrial applications.

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hac habitasse

platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

Fusce mauris. Vestibulum luctus nibh at lectus. Sed bibendum, nulla a faucibus semper, leo velit ultricies tellus, ac venenatis arcu wisi vel nisl. Vestibulum diam. Aliquam pellentesque, augue quis sagittis posuere, turpis lacus congue quam, in hendrerit risus eros eget felis. Maecenas eget erat in sapien mattis porttitor. Vestibulum porttitor. Nulla facilisi. Sed a turpis eu lacus commodo facilisis. Morbi fringilla, wisi in dignissim interdum, justo lectus sagittis dui, et vehicula libero dui cursus dui. Mauris tempor ligula sed lacus. Duis cursus enim ut augue. Cras ac magna. Cras nulla. Nulla egestas. Curabitur a leo. Quisque egestas wisi eget nunc. Nam feugiat lacus vel est. Curabitur consectetur.

Suspendisse vel felis. Ut lorem lorem, interdum eu, tincidunt sit amet, laoreet vitae, arcu. Aenean faucibus pede eu ante. Praesent enim elit, rutrum at, molestie non, nonummy vel, nisl. Ut lectus eros, malesuada sit amet, fermentum eu, sodales cursus, magna. Donec eu purus. Quisque vehicula, urna sed ultricies auctor, pede lorem egestas dui, et convallis elit erat sed nulla. Donec luctus. Curabitur et nunc. Aliquam dolor odio, commodo pretium, ultricies non, pharetra in, velit. Integer arcu est, nonummy in, fermentum faucibus, egestas vel, odio.

Sed commodo posuere pede. Mauris ut est. Ut quis purus. Sed ac odio. Sed vehicula hendrerit sem. Duis non odio. Morbi ut dui. Sed accumsan risus eget odio. In hac habitasse platea dictumst. Pellentesque non elit. Fusce sed justo eu urna porta tincidunt. Mauris felis odio, sollicitudin sed, volutpat a, ornare ac, erat. Morbi quis dolor. Donec pellentesque, erat ac sagittis semper, nunc dui lobortis purus, quis congue purus metus ultricies tellus. Proin et quam. Class aptent taciti sociosqu ad litora torquent per conubia nostra, per inceptos hymenaeos. Praesent sapien turpis, fermentum vel, eleifend faucibus, vehicula eu, lacus.

Appendices

Appendix A

Introduction to the dataset

Appendices hold useful data which is not essential to understand the work done in the master's thesis. An example is a (program) source. An appendix can also have sections as well as figures and references[?].

A.1 Introduction to the dataset




FIGURE A.1: The amount of NaN values in all the 3248 smart meters.

Attribute	Filled places
Dwelling type (5 cat.)	1702
# Occupants (max 4)	74
# Bedrooms (max 5)	1859
Heating fuel (4 cat.)	78
Hot water fuel (3 cat.)	76
Boiler age (2 cat.)	74
Loft insulation (2 cat.)	75
Wall insulation (5 cat.)	75
Heating temperature (4 cat.)	74
Efficient lighting percentage (4 cat.)	73
Dishwasher (0,1,2)	76
Freezer (0,1,2)	70
Fridge freezer (0,1,2)	70
Refrigerator (0,1,2)	73
Tumble Dryer (0,1,2)	76
Washing machine (0,1,2)	76
Game console (0,1,2,3)	72
Laptop (0,1,2,3,4)	70
Pc (0,1,2,3)	70
Router (0,1,2)	69
Set top box (0,1,2,3)	70
Tablet (0,1,2,3,4)	70
Tv (0,1,2,3,4)	75

TABLE A.1: Amount of response on the voluntary questionnaires.

A.2 Missing values

A.2.1 Fundamental change

A.3 Daily filter




FIGURE A.2: Resulting month of March after substitution of the missing values by the mean value of the measurements.




FIGURE A.3: Resulting month of March after substitution of the missing values by the mean value of the same moment on the next and previous day.




FIGURE A.4: The time-series with the original maximum difference between the minimum and maximum weekly rolling averages.




FIGURE A.5: The time-series with the new maximum difference between the minimum and maximum weekly rolling averages.




FIGURE A.6: Figure that shows the seasonality of the electrical load during the day.

Appendix B

Old things

B.0.1 Removing outliers

After the missing values are replaced by estimations, the outliers of the electricity consumption signals are identified. This is done by looking at the z-scores of the yearly consumptions. A z-score is calculated using equation ?? and assumes that the yearly consumptions are normally distributed around the average consumption. Consumptions that have a very low probability to occur are removed by imposing that $|z - score| < 3$.

$$z - score = \frac{x - \mu}{\sigma} \quad (B.1)$$

Figure B.1 gives the obtained z-values. It can be seen that 6 meters with an unlikely high or low consumption are removed.

B.0.2 Normalization of the data

Normalization is necessary because while absolute consumption differs, relative patterns of human behaviour are more similar [5]. The patterns in the human behaviour is what a forecasting model is trying to predict and normalization contributes by avoiding the disturbance of different magnitudes in which this human pattern may occur. Every individual household time-series is normalized based on its maximum and minimum value according to equation B.2.

$$normalizedvalue = \frac{x - x_{min}}{x_{max} - x_{min}} \quad (B.2)$$

As discussed in section ?? the average is taken over all the normalized time-series to obtain a single signal. **Ask if this is good??** Because the maximum is taken into account during the normalization, measurement out shooters have an influence on the normalization.

B.1 ARIMA

What is ARIMA. Assumptions of ARIMA...




FIGURE B.1: Z-scores calculated from the yearly consumptions.

Stationarity

<https://machinelearningmastery.com/remove-trends-seasonality-difference-transform-python/> When data is modelled it is assumed that the statistics of the data are consistent or stationary. This means the mean and standard deviation is not changing in time. However, because time series are often subdued to a trend or seasonality this assumption of stationarity is violated. In order to model not stationary observations by a stationary model as ARIMA, trends and seasonal effects should be removed. A way to check the stationarity of your observations, the “Dickey-Fuller test” can be used. A way to remove non-stationarity is by using “Difference Transform”. Here the trend and seasonality is subtracted from the observations leaving behind a stationary dataset.

Bibliography

- [1] M. Espinoza, J. Suykens, R. Belmans, and B. De Moor. Electric Load Forecasting. *IEEE control systems magazine*, (October 2007):43–57, 2007.
- [2] B. A. Hoverstad, A. Tiedemann, H. Langseth, and P. Ozturk. Short-Term Load Forecasting With Seasonal Decomposition Using Evolution for Parameter Tuning. *IEEE Transactions on Smart Grid*, 6(4):1904–1913, 2015.
- [3] T. Y. Kim and S. B. Cho. Predicting residential energy consumption using CNN-LSTM neural networks. *Energy*, 182:72–81, 2019.
- [4] W. Kong, Z. Y. Dong, Y. Jia, D. J. Hill, Y. Xu, and Y. Zhang. Short-Term Residential Load Forecasting Based on LSTM Recurrent Neural Network. *IEEE Transactions on Smart Grid*, 10(1):841–851, 2019.
- [5] J. Lago. A ratios and clustering based approach to forecast electricity consumption, 2020.
- [6] M. A. Nielsen. *Neural Networks and Deep Learning*, 2015.
- [7] H. Shi, M. Xu, and R. Li. Deep Learning for Household Load Forecasting-A Novel Pooling Deep RNN. *IEEE Transactions on Smart Grid*, 9(5):5271–5280, 2018.
- [8] J. Teuwen and N. Moriakov. *Convolutional neural networks*. Elsevier Inc., 2019.
- [9] M. Zhang, Aston Lipton, Zachary Li and A. Smola. *Dive Into Deep Learning*, volume 17. 2020.