

Exercises: Introduction to Hibernate

This document defines the exercise assignments for the [“Spring Data” course @ SoftUni](#).

1. Setup

Use the **provided skeleton** to create **soft_uni** database.

1. Change the **port**, **username** and **password** accordingly to your settings.

```
<?xml version="1.0" encoding="UTF-8"?>
<persistence xmlns="http://java.sun.com/xml/ns/persistence"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://java.sun.com/xml/ns/persistence
    http://java.sun.com/xml/ns/persistence/persistence_2_0.xsd"
  version="2.0">

  <persistence-unit name="soft_uni">
    <properties>
      <property name="hibernate.connection.url"
        value="jdbc:mysql://localhost:3306/soft_uni?createDatabaseIfNotExist=true&useSSL=false"/>
      <property name="hibernate.connection.driver_class" value="com.mysql.jdbc.Driver" />
      <property name="hibernate.hbm2ddl.auto" value="update"/>
      <property name="hibernate.connection.username" value="" />
      <property name="hibernate.connection.password" value="" />
    </properties>
  </persistence-unit>
</persistence>
```

2. Create EntityManagerFactory and run your program.

```
EntityManagerFactory factory =
    Persistence.createEntityManagerFactory( persistenceUnitName: "soft_uni");
EntityManager em = factory.createEntityManager();
```

3. Fill the database into **Workbench** or **IntelliJ** by **executing** the provided **.sql** script.

2. Change casing

Use the **soft_uni** database. Persist **all towns** from the database. Detach those whose name length is **more than 5 symbols**. Then transform the **names** of all attached towns to **uppercase** and **save them to the database**.

3. Contains Employee

Use the **soft_uni** database. Write a program that checks if a given employee name is **contained in the database**.

Example

Input	Output
Svetlin Nakov	Yes
John Doe	No

4. Employees with Salary Over 50 000

Write a program that gets the first name of all employees who have salary over **50 000**.

Example:

Output
Terri
Jean
Ken
...

5. Employees from Department

Extract all employees from the **Research and Development** department. Order them by **salary** (in ascending order), then by **id** (in **ascending** order). Print only their **first name**, **last name**, **department name** and **salary**.

Example:

Output
Diane Margheim from Research and Development - \$40900.00
Gigi Matthew from Research and Development - \$40900.00
Michael Raheem from Research and Development - \$42500.00
Svetlin Nakov from Research and Development - \$48000.00
Martin Kulov from Research and Development - \$48000.00
George Denchev from Research and Development - \$48000.00
Dylan Miller from Research and Development - \$50500.00

6. Adding a New Address and Updating Employee

Create a new address with **text** "Vitoshka 15". Set that address to an **employee** with a **last name**, given as an input.

7. Addresses with Employee Count

Find all addresses, **ordered** by the **number of employees** who live there (**descending**).

Take only the **first 10 addresses** and print their **address text**, **town name** and **employee count**.

Example

Output
163 Nishava Str, ent A, apt. 1, Sofia - 3 employees
7726 Driftwood Drive, Monroe - 2 employees
...

8. Get Employee with Project

Get an **employee by his/her id**. Print only his/her **first name**, **last name**, **job title** and **projects** (only their names). The projects should be **ordered by name** (ascending). The output should be printed in the format given in the example.

Example

Input	Output
147	Linda Randall - Production Technician HL Touring Handlebars ML Road Rear Wheel

	Patch kit Touring-1000
83	John Evans - Production Technician Half-Finger Gloves LL Mountain Handlebars Racing Socks Women's Tights

9. Find Latest 10 Projects

Write a program that prints the **last 10 started projects**. Print **their name, description, start and end date** and **sort them by name** lexicographically. For the output, check the format from the example.

Example

Output
Project name: All-Purpose Bike Stand Project Description: Research, design and development of ... Project Start Date:2005-09-01 00:00:00.0 Project End Date: null
Project name: Bike Wash Project Description: Research, design and development of ... Project Start Date:2005-08-01 00:00:00.0 Project End Date: null
Project name: HL Touring Frame Project Description: Research, design and development of ... Project Start Date:2005-05-16 16:34:00.0 Project End Date: null
...

10. Increase Salaries

Write a program that increases the salaries of all employees, who are in the **Engineering, Tool Design, Marketing or Information Services** departments by **12%**. Then **print the first name, the last name and the salary** for the employees, whose salary was increased.

Example

Output
Roberto Tamburello (\$48496.00) Gail Erickson (\$36624.00) Jossef Goldberg (\$36624.00) Terri Duffy (\$71120.00) ...

11. Find Employees by First Name

Write a program that finds **all employees**, whose **first name starts with a pattern** given as an input from the console. Print their **first and last names**, their **job title** and **salary** in the format given in the example below.

- Hint: The expected results of next exercises are with update of salaries in ex 10.

Example

Input	Output
SA	Sariya Harnpadoungsataya - Marketing Specialist - (\$16128.00) Sandra Reategui Alayo - Production Technician - (\$9500.00) Sairaj Uddin - Scheduling Assistant - (\$16000.00)

	Samantha Smith - Production Technician - (\$14000.00)
	Sameer Tejani - Production Technician - (\$11000.00)
	Sandeep Kaliyath - Production Technician - (\$15000.00)

12. Employees Maximum Salaries

Write a program that finds the **max salary** for each **department**. Filter the departments, which max salaries **are not in the range** between 30000 and 70000.

Example

Output
Engineering 71120.00
Sales 72100.00
Marketing 16128.00
Production 84100.00
...

13. Remove Towns

Write a program that **deletes a town**, which name is given as an input. The program should **delete all addresses** that are in the given town. Print on the console the **number of addresses** that were **deleted**. Check the example for the output format.

Example

Input	Output
Sofia	1 address in Sofia deleted
Seattle	44 addresses in Seattle deleted