测试:


```java
public static void main(String[] args) {
    ApplicationContext context = new ClassPathXmlApplicationContext( confi
    TestBean testBean = context.getBean( name: "testBean", TestBean.class)
    ResourceLoader resourceLoader = testBean.getResourceLoader();
    System.out.println(context == resourceLoader);
  }
}
```

```
D:\java\jdk-17.0.5\bin\java.exe ...
true
Process finished with exit code 0
```

File Edit View Navigate Code Refactor Build Run Tools Git Window Help

spring6 > spring6-resources > src > main > java > com > atguigu > spring6 > resourceloaderaware > TestDemo

```java
package com.atguigu.spring6.resourceloaderaware;

import org.springframework.context.ApplicationContext;
import org.springframework.context.support.ClassPathXmlApplicationContext;
import org.springframework.core.io.ResourceLoader;


public class TestDemo {

    public static void main(String[] args) {
        ApplicationContext context = new ClassPathXmlApplicationContext(configLocation: "bean.xml");
        TestBean testBean = context.getBean(name: "testBean",TestBean.class);
        ResourceLoader resourceLoader = testBean.getResourceLoader();
        System.out.println(context==resourceLoader);
    }
}
```

Microsoft Defender configuration: The IDE has detected Microsoft Defender with Real-Time Protection enabled. It might severely degrade IDE performance. It is recommend... (today 16:)   7:14   CRLF   UTF-8   4 spaces   main