# EngageNet: Bounded Engagement Regression with State-Space Models, and Why Modality Order and Test-Time Adaptation Do Not Matter

Lado Turmanidze
Georgian Artificial Intelligence Association (GAIA)
Tbilisi, Georgia
StochasticBatman@proton.me

Philipp Müller
Max Planck Institute for Intelligent Systems
Stuttgart, Germany
phmueller@is.mpg.de

Beso Mikaberidze
Muskhelishvili Institute of Computational Mathematics (MICM)
Georgian Technical University
Tbilisi, Georgia
beso.mikaberidze@gmail.com

October 28, 2026

**Abstract**

EngageNet estimates continuous engagement in $[0, 1]$, frame by frame and for both participants of expert-novice video calls. Bidirectional selective state-space models (BiMamba) encode each feature stream over time, a second BiMamba fuses the streams by scanning across them in a learned order, and Beta regression heads output a bounded prediction with a predictive variance. A temporal block after fusion and longer training windows improve the validation Concordance Correlation Coefficient (CCC). We applied a learned modality ordering (Gumbel-Sinkhorn) to choose the order in which the streams are fused, and an unsupervised test-time adaptation driven by the predictive variance to adapt the model to unseen data, and found that neither improves the scores: the order of the modality scan does not matter, so the learned ordering does no better than a fixed one.

## 1. Introduction

Engagement, how attentive and involved a person is in a conversation, is a central signal for systems that observe or mediate human interaction. The MultiMediate challenge [13] asks for a continuous engagement score in $[0, 1]$ for every frame and for each participant of screen-mediated expert-novice conversations, recorded in Europe (NoXi [17]) and in Japan (NoXi+J [18]), and scores predictions by the concordance correlation coefficient (CCC). The task combines many heterogeneous feature streams per person, two interacting people, a bounded target, and corpora that differ in language, culture and in how the annotators used the scale. EngageNet encodes each feature stream of each person with a bidirectional selective state-space model (BiMamba) [1] over time, fuses the streams with a second BiMamba that scans across them in a learned order, and predicts a Beta distribution per frame, so that every prediction lies in $[0, 1]$ and comes with a variance that drives an unsupervised test-time adaptation. Section 2 describes the architecture, including the ordering layer and the evaluation metric, and Section 3 the experiments; Section 4 summarises the contributions and limitations, and further details and negative results are in the appendices.

## 2. Architecture

### 2.1. Input

Let $x = \{x_1, \ldots, x_M\}$ with $x_i \in \mathbb{R}^{C_i \times L}$ for all $i \in \{1, \ldots, M\}$, where $C_i$ is the number of acquisition channels for the $i$-th modality and $L$ represents the number of time steps of the input signal. The feature streams are delivered at different sampling rates (most at 25 Hz, some at 40 Hz), so every stream is first resampled to a common 25 Hz by linear interpolation and then cut into windows of $L$ frames, consecutive windows overlapping by half. All $M$ inputs therefore share the same $L$; we use $L = 250$ frames, i.e. 10 s.

#### 2.1.1. Dyadic Structure and Role Streams

Each session in the NoXi [17] family of corpora - including the NoXi+J extension [18] - is a screen-mediated dyadic interaction between an *expert* and a *novice*, recorded independently (separate cameras, separate microphones). Every feature type therefore arrives as two parallel streams, one per role, and both carry their own frame-wise engagement annotation.

We denote by $\mathcal{F}$ the set of features and by $\mathcal{R} = \{\text{expert}, \text{novice}\}$ the set of roles. The index $i$ in $x_i$

ranges over the Cartesian product $\mathcal{F} \times \mathcal{R}$, so that

$$M = |\mathcal{F}| \times |\mathcal{R}| = 2|\mathcal{F}|.$$

The feature types we use are introduced in Section 3.1. Every subsequent occurrence of $M$ in this document - including the modality-ordering permutation of Section 2.4 - refers to these role-feature pairs, not to feature types alone.

**Target.** Write $y_t^e$ and $y_t^n$ for the engagement annotations of the expert and the novice at frame $t$, each in $[0, 1]$. The challenge asks for both separately [13], and we predict both, with one output head per role. Every input channel is standardised with training-split statistics. Appendix A gives the reasons and details.

## 2.2. Output

For each frame $t$ of the encoded sequence the network emits two strictly positive shape parameters $(\alpha_t, \beta_t)$ that define a Beta predictive density over the bounded engagement scale,

$$p(y_t \mid x) = \mathrm{Beta}\big(\alpha_t(x),\, \beta_t(x)\big), \qquad y_t \in [0, 1].$$

The scalar point prediction is the predictive mean:

$$\hat{y}_t = \hat{\mu}_t = \frac{\alpha_t}{\alpha_t + \beta_t} \in (0, 1),$$

while the predictive variance supplies the uncertainty signal consumed by the test-time adaptation filter (Section 2.6). In contrast to [1], where $y$ is a discrete class label represented as a one-hot vector $p(y|x) \in \mathbb{R}^N$ over $N$ categories, engagement estimation is a *continuous bounded regression* problem: there is no category axis, and the network output for a window of length $L'$ has shape $(L', 2)$ rather than $(L', N)$.

**Unimodal and multimodal heads.** Both kinds of head are the two-layer perceptron of Section 2.5 and emit a Beta distribution per frame; they differ in what they read. A *unimodal* head reads the intra-modal representation $u_i \in \mathbb{R}^{L' \times C'}$ of a single stream $i$ (Section 2.3.1), before any fusion, and predicts $(\alpha_i, \beta_i)$ from that stream alone. One unimodal head is instantiated per feature type and shared by the two roles, so $|\mathcal{F}|$ heads give $M$ unimodal predictions per frame. They are never submitted: they provide deep supervision during training (Section 2.8) and act as students of the multimodal head in test-time adaptation (Sections 2.6 and 2.9).

The *multimodal* heads produce EngageNet's predictions. There is one per role, giving $\big(\alpha_t^r, \beta_t^r\big)$ for each $r \in \mathcal{R}$, and both read the fused representation $H \in \mathbb{R}^{L' \times MC'}$ of the inter-modal module (Section 2.3.2), in which all $M$ streams of both participants have exchanged information. The expert's prediction can therefore draw on the novice's streams as well as on the expert's own.

## 2.3. Inner Workings

The network consists of two modules: the intra-modal BiMamba module models each modality independently, and the inter-modal BiMamba module fuses them.

### 2.3.1. Intra-modal BiMamba Module

First, an initial encoder $h_i = \mathrm{InitEncoder}_i(\tilde{x}_i) \in \mathbb{R}^{L' \times C'}$ for all $i \in \{1, \ldots, M\}$ is used to extract shallow features from a specific modality, where $C'$ is the number of output channels and $L'$ is the feature length of the output signal; we use $C' = 128$ and $L' = L$ for every stream (Appendix B). The transposition of dimensions from $C_i \times L$ to $L' \times C'$ physically aligns the data structure with the sequence-first requirement of autoregressive models.

**InitEncoder internals.** Each InitEncoder is a shallow three-stage block applied to the standardised input:

$$h_i = \mathrm{InitEncoder}_i(\tilde{x}_i) = f_i\Big(\sigma\big(\mathrm{BN}\big(\mathrm{Conv1D}_i(\tilde{x}_i^\top)\big)\big)\Big),$$

where $\mathrm{Conv1D}_i$ is a temporal convolution mapping $C_i \to C_i'$ channels: every output channel at frame $t$ is a learned weighted sum over *all* input channels and a short window of neighbouring frames. BN is batch normalisation [16], $\sigma$ the SiLU activation and $f_i$ the uniform channel projection $C_i' \to C'$ (Appendix G); Appendix B gives the details.

The BiMamba module operates on $h_i$ as follows.

1. **Pre-normalisation:** $\bar{h}_i = \mathrm{LN}(h_i) \in \mathbb{R}^{L' \times C'}$, where LN is layer normalisation [15].
2. **Gate:** $g_i = \sigma(W_i^g \bar{h}_i + b_i^g)$, with weight matrix $W_i^g$, bias $b_i^g$ and SiLU $\sigma$.
3. **Bidirectional scan:** with $\hat{h}_i = W_i^h \bar{h}_i + b_i^h$ and $\Phi_d(x) = \mathrm{SSM}_d\big(\sigma(\mathrm{DWConv1D}_d(x))\big)$ for $d \in \{\rightarrow, \leftarrow\}$, the forward and backward representations of the $i$-th modality are

$$h_i^{\rightarrow} = g_i \odot \Phi_{\rightarrow}(\hat{h}_i),$$
$$h_i^{\leftarrow} = g_i \odot \mathrm{Rev}_t\big(\Phi_{\leftarrow}(\mathrm{Rev}_t(\hat{h}_i))\big),$$

   both in $\mathbb{R}^{L' \times C'}$. $\mathrm{Rev}_t(\cdot)$ flips the time axis, $\odot$ is the Hadamard product, $W_i^h$ and $b_i^h$ are a weight matrix and a bias, $\mathrm{DWConv1D}(\cdot)$ is a depthwise temporal convolution, and SSM is the selective state-space model of Mamba [2], a discretised linear recurrence whose parameters depend on the input. Appendix C gives the details.
4. **Output:** a linear projection and a residual connection give the output of the intra-modal module for the $i$-th modality,

$$u_i = h_i + \left(W_i^o \left(\frac{h_i^{\rightarrow} + h_i^{\leftarrow}}{2}\right) + b_i^o\right) \in \mathbb{R}^{L' \times C'},$$

   with weight matrix $W_i^o$ and bias $b_i^o$.

#### 2.3.2. Inter-modal BiMamba Module

The inter-modal module lets the $M$ intra-modal representations $u_i \in \mathbb{R}^{L' \times C'}$ exchange information by treating the list of modalities as the sequence, each modality taking one position; other arrangements, and why they fail, are described in Appendix F. At every time step $t$, one BiMamba block with shared weights scans the streams in the order chosen by the learned ordering of Section 2.4, $\tilde{u}_1^{(t)}, \ldots, \tilde{u}_M^{(t)}$:

$$H^{(t)} = \mathrm{BiMamba}_{\mathrm{modality}}\big(\tilde{u}_1^{(t)}, \ldots, \tilde{u}_M^{(t)}\big) \in \mathbb{R}^{M \times C'}.$$

Time is modelled only by the intra-modal module. Adjacent modalities are separated by a single decay $\bar{A}$ instead of the $\bar{A}^{C'}$ of a scan over the channels (Appendix F), and averaging the forward and backward scans lets every modality see all the others.

### 2.4. Learned Modality Ordering

The ordering of the $M$ positions of the inter-modal scan is chosen arbitrarily, and selective state-space models are order-sensitive (Appendix G). We therefore replace the fixed concatenation order with a *learned, input-dependent permutation* computed differentiably via the Gumbel-Sinkhorn operator [3].

**Score matrix.** Each modality representation is first summarised by temporal mean-pooling, $\bar{u}_i = \frac{1}{L'} \sum_{t=1}^{L'} u_i^{(t)} \in \mathbb{R}^{C'}$. A bias-free projection into a score-embedding space of dimension $d_s$ turns each summary into a key, and each *position* has its own learned query vector:

$$k_j = W_K\, \bar{u}_j \in \mathbb{R}^{d_s}, \qquad p_i \in \mathbb{R}^{d_s},$$

where $W_K \in \mathbb{R}^{d_s \times C'}$ is shared across modalities and $p_1, \ldots, p_M$ are free parameters. The score of placing modality $j$ at sequence position $i$ is the scaled dot product

$$Z_{ij} = \frac{p_i^\top k_j}{\sqrt{d_s}}.$$

This is the corrected layer of Appendix O; all other reported models, including those behind our test predictions, use the first formulation, with data-dependent queries $q_i = W_Q\, \bar{u}_i$, unscaled scores $Z_{ij} = q_i^\top k_j$, 10 Sinkhorn iterations and no unsorting (Appendix F).

**Gumbel-Sinkhorn.** During training the score matrix is perturbed with i.i.d. standard Gumbel noise and scaled by a temperature $\tau > 0$,

$$\tilde{Z}_{ij} = \frac{Z_{ij} + G_{ij}}{\tau},$$
$$G_{ij} = -\ln(-\ln U_{ij}), \quad U_{ij} \overset{\text{i.i.d.}}{\sim} \mathrm{Uniform}(0,1).$$

where $\tau$ is annealed at each epoch $t$ via $\tau_t = \max(\tau_\infty, \tau_0 \cdot \gamma^t)$, from an initial temperature $\tau_0$ with decay rate $\gamma \in (0,1)$ down to $\tau_\infty$ (Appendix M). The doubly-stochastic matrix $P$ is obtained by the Sinkhorn-Knopp algorithm [3], which alternates row and column normalisation of $\exp(\tilde{Z})$. We carry it out in log-space, with $\mathrm{logsumexp}_j\, x_j = \log \sum_j \exp(x_j)$:

$$\log P^{(0)} = \tilde{Z},$$
$$\log Q_{ij}^{(k)} = \log P_{ij}^{(k)} - \operatorname*{logsumexp}_{j'} \log P_{ij'}^{(k)},$$
$$\log P_{ij}^{(k+1)} = \log Q_{ij}^{(k)} - \operatorname*{logsumexp}_{i'} \log Q_{i'j}^{(k)},$$

for $k = 0, \ldots, n_{\mathrm{iter}} - 1$, with $P = \exp\big(\log P^{(n_{\mathrm{iter}})}\big)$ and $n_{\mathrm{iter}} = 50$.

**Soft reordering.** Position $i$ of the inter-modal sequence receives

$$\tilde{u}_i = \sum_{j=1}^{M} P_{ij}\, u_j \in \mathbb{R}^{L' \times C'}, \qquad i \in \{1, \ldots, M\}.$$

and at every time step $t$ the inter-modal BiMamba processes $\big(\tilde{u}_1^{(t)}, \ldots, \tilde{u}_M^{(t)}\big)$ (Section 2.3.2). At test time, Gumbel noise is suppressed ($G_{ij} = 0$). $P$ is never rounded to a hard permutation matrix, neither during training nor at inference.

### 2.5. Beta Regression Framework

To adapt the entropy-based selection mechanism of BiMamba-TTA for continuous engagement regression, we transition from Shannon entropy to **differential entropy**:

$$H(y) = -\int_{\mathcal{Y}} p(y) \ln p(y)\, dy$$

for a predictive density $p(y)$. Engagement is bounded in $[0,1]$, which rules out a Gaussian density (Appendix I), so we model the predictive distribution using a **Beta distribution**:

$$p(y|\alpha,\beta) = \frac{y^{\alpha-1}(1-y)^{\beta-1}}{B(\alpha,\beta)}, \quad B(\alpha,\beta) = \frac{\Gamma(\alpha)\Gamma(\beta)}{\Gamma(\alpha+\beta)}$$

**Head architecture.** Each Beta head is a two-layer perceptron. For the representation $r \in \mathbb{R}^{L' \times d_{\mathrm{in}}}$ entering the head,

$$v = \sigma\big(W^{(1)} r + b^{(1)}\big) \in \mathbb{R}^{L' \times d_h},$$

with $W^{(1)} \in \mathbb{R}^{d_h \times d_{\mathrm{in}}}$, $b^{(1)} \in \mathbb{R}^{d_h}$, SiLU $\sigma$ and head width $d_h$. Two separate linear read-outs of the same $v$ give

$$z_\alpha = W^{(\alpha)} v + b^{(\alpha)}, \qquad z_\beta = W^{(\beta)} v + b^{(\beta)},$$
$$W^{(\alpha)}, W^{(\beta)} \in \mathbb{R}^{1 \times d_h}$$

and the shape parameters $\alpha = \mathrm{softplus}(z_\alpha) + 1$ and $\beta = \mathrm{softplus}(z_\beta) + 1$, with $\mathrm{softplus}(z) = \ln(1 + e^z)$, so that $\alpha, \beta > 1$ (Appendix I). The predictive mean $\hat{\mu}$ and aleatoric uncertainty $\mathrm{Var}[y]$ are:

$$\hat{\mu} = \frac{\alpha}{\alpha+\beta}, \quad \mathrm{Var}[y] = \frac{\alpha\beta}{(\alpha+\beta)^2(\alpha+\beta+1)}$$

Targets are clipped to $[\varepsilon, 1-\varepsilon]$ with $\varepsilon = 10^{-6}$, because the log-likelihood contains $\ln y$ and $\ln(1-y)$, which diverge at annotations of exactly 0 and 1.

## 2.6. Test-Time Adaptation (TTA) and Uncertainty

Following the differential-entropy principle of the original BiMamba-TTA paper [1], we replace Shannon entropy with a regression-compatible uncertainty proxy.

For the Beta predictive distribution $p(y \mid x) = \mathrm{Beta}(\hat{\alpha}(x), \hat{\beta}(x))$ that respects the support $y \in [0, 1]$, we define

$$U(x) := \mathrm{Var}[y] = \frac{\hat{\alpha}(x)\hat{\beta}(x)}{(\hat{\alpha}(x) + \hat{\beta}(x))^2(\hat{\alpha}(x) + \hat{\beta}(x) + 1)}$$

A sample is selected for the TTA backward pass if the multimodal prediction is confident (low uncertainty) but the unimodal branches are uncertain (high uncertainty), i.e.,

$$S(x) = \mathbb{I}\Big\{U_{\text{multi}}(x) < \gamma_m \wedge \frac{1}{M}\sum_{i=1}^{M} U_i(x) > \gamma_u\Big\}.$$

Here $x$ is one window, and every $U$ is the per-frame predictive variance averaged over the window's frames; $U_{\text{multi}}$ is additionally averaged over the two role heads, and the unimodal average runs over all $M$ role-feature streams with equal weights. The thresholds $\gamma_m$ and $\gamma_u$ are quantiles of these two uncertainties within each inference batch, with $q_m = 0.3$ and $q_u = 0.7$ (Appendix J).

**Uncertainty measures.** Two measures are used for $U$; Appendix J describes what kind of uncertainty each captures, and a third measure.

1. **Parametric Beta (Aleatoric Uncertainty):** the predictive variance $U(x)$ above. Because the variance is computed analytically from the learned shape parameters, it is the fastest and default choice for the TTA filter, used in every run without dropout.
2. **Total Uncertainty (Hybrid):** We keep dropout active at inference and draw $T$ stochastic forward passes. For each pass $t$ we obtain a Beta distribution with parameters $(\hat{\alpha}^{(t)}, \hat{\beta}^{(t)})$ and corresponding mean $\hat{\mu}^{(t)}$, and $\bar{\mu}(x) = \frac{1}{T}\sum_{t=1}^{T}\hat{\mu}^{(t)}(x)$. Using the law of total variance, the full predictive uncertainty decomposes as

$$U_{\text{total}}(x) = \underbrace{\frac{1}{T}\sum_{t=1}^{T}\mathrm{Var}\big[\mathrm{Beta}(\hat{\alpha}^{(t)}, \hat{\beta}^{(t)})\big]}_{\text{aleatoric (data)}} + \underbrace{\frac{1}{T}\sum_{t=1}^{T}\big(\hat{\mu}^{(t)}(x) - \bar{\mu}(x)\big)^2}_{\text{epistemic (model)}}.$$

   The filter uses it when the model is trained with dropout and run with MC dropout.

The systems that produce our test predictions use no adaptation and therefore neither measure.

## 2.7. Concordance Correlation Coefficient (CCC)

The primary evaluation metric is the Concordance Correlation Coefficient [12], which measures agreement between predicted and ground-truth engagement trajectories:

$$\mathrm{CCC}(\hat{y}, y) = \frac{2\rho\,\sigma_{\hat{y}}\,\sigma_y}{\sigma_{\hat{y}}^2 + \sigma_y^2 + (\mu_{\hat{y}} - \mu_y)^2},$$

where $\rho$ is the Pearson correlation between predictions $\hat{y}$ and targets $y$, $\sigma_{\hat{y}}, \sigma_y$ are their standard deviations, and $\mu_{\hat{y}}, \mu_y$ are their means. CCC $\in [-1, 1]$, with 1 indicating perfect concordance. Unlike Pearson correlation alone, CCC penalises both scale and location shifts.

**The correlation ceiling.** CCC can be decomposed into two factors. Define the scale ratio and the normalised mean offset

$$\varphi := \frac{\sigma_{\hat{y}}}{\sigma_y} > 0, \qquad \omega := \frac{\mu_{\hat{y}} - \mu_y}{\sqrt{\sigma_{\hat{y}}\sigma_y}},$$

and divide numerator and denominator of the CCC by $\sigma_{\hat{y}}\sigma_y$:

$$\frac{2\rho}{\frac{\sigma_{\hat{y}}}{\sigma_y} + \frac{\sigma_y}{\sigma_{\hat{y}}} + \frac{(\mu_{\hat{y}} - \mu_y)^2}{\sigma_{\hat{y}}\sigma_y}} = \rho \cdot C_b,$$
$$C_b := \frac{2}{\varphi + \varphi^{-1} + \omega^2}.$$

Here $\rho$ is the Pearson correlation, which, following [12], we term the *precision* of the predictor, and $C_b$ the bias-correction factor, its *accuracy*.

**Proposition.** $\mathrm{CCC}(\hat{y}, y) \le \rho$, with equality iff $\sigma_{\hat{y}} = \sigma_y$ and $\mu_{\hat{y}} = \mu_y$.

*Proof.* For any $\varphi > 0$ the arithmetic-geometric mean inequality gives $\varphi + \varphi^{-1} \ge 2\sqrt{\varphi \cdot \varphi^{-1}} = 2$, with equality if and only if $\varphi = \varphi^{-1}$ ($\varphi = 1$). Since also $\omega^2 \ge 0$ with equality if and only if $\mu_{\hat{y}} = \mu_y$, the denominator of $C_b$ satisfies $\varphi + \varphi^{-1} + \omega^2 \ge 2$, hence $C_b \le 1$ and $\mathrm{CCC} = \rho\, C_b \le \rho$. Both equality conditions hold simultaneously precisely when $\sigma_{\hat{y}} = \sigma_y$ and $\mu_{\hat{y}} = \mu_y$. □

## 2.8. Training Objective

The likelihood we train on and the metric we are scored by ask different questions. The Beta negative log-likelihood looks at one frame at a time and asks whether the predicted distribution is right there. CCC looks at all frames together and asks whether the predictions rise and fall in the same pattern as the targets. A model can therefore place a sensible distribution on every frame and still order the frames badly (Appendix

L). We therefore add three terms to the likelihood,

$$\mathcal{L} = \underbrace{\frac{1}{|\mathcal{R}|}\sum_{r\in\mathcal{R}} \mathcal{L}^{w}_{\mathrm{NLL}}\big(\alpha^r, \beta^r, y^r\big)}_{\text{per-frame fit}} + \underbrace{\lambda_c\big(1-\widehat{\mathrm{CCC}}\big)}_{\text{ordering}}$$
$$+ \underbrace{\frac{\lambda_u}{M}\sum_{i=1}^{M} \mathcal{L}^{w}_{\mathrm{NLL}}\big(\alpha_i, \beta_i, y^{r(i)}\big)}_{\text{per-modality supervision}} + \underbrace{\lambda_f\, \mathcal{L}_{\mathrm{fair}}}_{\text{fairness}},$$

where $r(i)$ denotes the role of stream $i$, and $\lambda_c, \lambda_u, \lambda_f \geq 0$ set how much each term counts.

**Reweighting the likelihood.** The gradient of the Beta negative log-likelihood with respect to the mean is proportional to the precision $\kappa = \alpha + \beta$ (Appendix L), so frames the model is already sure about push hardest - a known failure of likelihood training with predicted uncertainty [21]. We fix it by scaling each frame's loss by $w_t = \kappa_t^{-\beta_w}$, giving $\mathcal{L}^{w}_{\mathrm{NLL}} = \sum_t w_t \mathcal{L}_{\mathrm{NLL},t} / \sum_t w_t$, with $\beta_w = 0.5$; $w_t$ is computed from the current $\alpha_t, \beta_t$ but treated as a fixed number when derivatives are taken, so no gradient flows back through it.

**Ordering term.** $\widehat{\mathrm{CCC}}$ is the sample concordance coefficient of Section 2.7 computed on the predicted means and the targets of the current minibatch, pooled across both roles and all frames in it. Batches are assembled from windows drawn at random from all sessions of the training split; Section 3.2 shows how much this matters.

**Per-modality supervision.** Each auxiliary head is trained on the target of the role whose stream it reads. Dividing by $M$ keeps this contribution from growing with the number of streams.

**Fairness term.** The Conditional Demographic Disparity of Appendix K is built from differences of group averages inside strata of the ground truth, and every step is differentiable, so it can be trained against rather than only measured. Splitting the batch into $n_b$ quantile bins $\mathcal{B}_1, \ldots, \mathcal{B}_{n_b}$ of the target, and writing $\overline{\hat{\mu}}_b^{\,A}$ and $\overline{\hat{\mu}}_b^{\,B}$ for each group's mean prediction inside bin $b$, we penalise

$$\mathcal{L}_{\mathrm{fair}} = \frac{\sum_{b=1}^{n_b} |\mathcal{B}_b| \left(\overline{\hat{\mu}}_b^{\,A} - \overline{\hat{\mu}}_b^{\,B}\right)^2}{\sum_{b=1}^{n_b} |\mathcal{B}_b|},$$

with bins missing either group left out of both sums.

## 2.9. Test-Time Loss

The TTA objective enforces consistency between the unimodal student heads and the multimodal teacher while still supervising the students toward the multimodal prediction. We define the **Mutual Information Sharing (MIS) loss** as the KL divergence that pushes each unimodal Beta distribution toward the multimodal one:

$$\mathcal{L}_{\mathrm{mis}} = \sum_{i=1}^{M} D_{KL}\big(\mathrm{Beta}(\alpha_i, \beta_i) \parallel \mathrm{Beta}(\alpha_{\mathrm{multi}}, \beta_{\mathrm{multi}})\big),$$

with the closed-form Beta KL divergence of Appendix J.

The final TTA loss combines the MIS consistency term with a supervision term that treats the multimodal mean as a pseudo-target for each unimodal head:

$$\mathcal{L}_{TTA} = \mathcal{L}_{\mathrm{mis}} + \lambda \sum_{i=1}^{M} \mathrm{NLL}_{\mathrm{Beta}}\big(\hat{\mu}_{\mathrm{multi}},\, \alpha_i, \beta_i\big).$$

Here $\lambda > 0$ is a hyperparameter that controls the relative importance of the two terms, and $\mathrm{NLL}_{\mathrm{Beta}}(\hat{\mu}_{\mathrm{multi}}, \alpha_i, \beta_i)$ is the Beta negative log-likelihood evaluated at the multimodal mean $\hat{\mu}_{\mathrm{multi}}$ (treated as a pseudo-label) with the unimodal shape parameters.

## 2.10. Surgical Fine-Tuning

We only update specific surgical layers to prevent catastrophic forgetting:

- BatchNorm layers inside every InitEncoder.
- First convolution in InitEncoder.
- First FC layer in Inter-modal BiMamba.

All remaining parameters receive exactly zero update. Appendix J explains the choice of layers and its relation to the Variance Starvation Problem.

# 3. Experimental Findings

## 3.1. Protocol

All numbers in this section are CCC values on the validation splits of NoXi (10 sessions, 577,176 frames over both roles) and NoXi+J (10 sessions, 400,896 frames); test annotations are not available to us. MPIIGroupInteraction, the fourth test set of the combined score (Appendix K), is not addressed in this work. Unless stated otherwise, models are trained with the configuration of Appendix M, separately per corpus. The models start from four core feature types (eGeMAPS v2, W2v-BERT 2.0, OpenFace2, OpenPose), which give $M = 8$ input streams. The challenge release provides ten feature types; we tested adding the remaining six in groups (Section 3.3), and only the XLM-RoBERTa embedding of the transcript improved the results. The final configuration therefore uses $|\mathcal{F}| = 5$ feature types and $M = 10$ streams.

Training is stochastic: the initial weights, the order of training sessions and the Gumbel noise all depend on a random seed. Every configuration below was trained with at least three seeds (95, 1, 2; the two configurations that decide the final input set also 3, 4, 5), and we report the mean and the sample standard deviation. The seed-to-seed standard deviation lies between 0.01 and 0.05 (Appendix N), so with three seeds only differences of roughly 0.04 or more are detectable. Two groups of seed scores are compared with a two-sided Welch $t$-test [22], with the Holm correction [23] when

several comparisons are made at once, and we call a difference significant when $p < 0.05$.

**Scoring.** Window predictions are reassembled into one sequence per session and role by overlap-add, and CCC is computed exactly as in the official MultiMediate'26 scoring script, with all sessions and both roles of a dataset concatenated into one sequence (Appendix N).

## 3.2. Batch Composition and Training Objective

The windows of a training batch were originally taken in order from the data stream, so practically every batch came from a single session, which contains exactly two people. We therefore draw every batch from a random permutation of all windows of all training sessions, re-shuffled each epoch. Mixing sessions raises the CCC on NoXi+J from $0.529 \pm 0.020$ to $0.599 \pm 0.029$ ($p = 0.03$) and on NoXi from $0.709 \pm 0.009$ to $0.724 \pm 0.008$ ($p = 0.10$); all results from here on use mixed batches. An ablation of the training objective (Appendix N) shows that the batch scheme also decides which loss terms matter: with single-session batches, removing the ordering term lowers NoXi+J from 0.529 to 0.396, the only individually significant effect, whereas with mixed batches no term is shown to help or hurt after the Holm correction. The value of a loss term therefore cannot be judged independently of how the batches it is computed on are composed. We keep the full objective.

## 3.3. Input Features

All ten feature types of the challenge release are available for every split of both corpora, test included. We added them in groups to the core set: text (the XLM-RoBERTa embedding of the transcript), image embeddings (DINO, ImageBind, Swin), video embeddings (VideoMAE, CLIP), and all ten together (Appendix N).

The text stream is the only addition that helps, and on NoXi+J it does so significantly (0.593 to 0.641, $p = 0.003$). The two input sets that contain it are the two best on NoXi+J, and all three sets without it are at or below the core set; adding all ten streams brings nothing over text alone and takes about 2.5 times longer to train. On NoXi the text stream is neutral (+0.005). The image embeddings add nothing, and the video embeddings significantly harm NoXi+J ($-0.084$, $p = 0.03$). We adopt core plus text as the final input set.

## 3.4. Where the Remaining Error Lies

The pooled CCC rewards two things: placing each person's overall level of engagement correctly relative to the other people, and following the changes within each person's session. To see which of the two limits the final models, we split the prediction for each person (one role in one session, 20 people per corpus) into its mean and the deviations from that mean, and replace one part at a time by the truth. *True level* keeps our deviations but shifts each person's prediction to the true mean; *true dynamics* keeps our mean but uses the true deviations; *level only* predicts each person's true mean as a constant.

The level is largely right (Appendix N): the predicted person means correlate at 0.90 with the true ones, and a perfect level would add only 0.04 to 0.05. With perfect dynamics the CCC would reach 0.95. Within a person, however, the prediction correlates with the annotation at only 0.47 on NoXi and 0.60 on NoXi+J. The remaining error therefore lies in following engagement within a session, not in its overall level. A delay of the annotators or noise in the predictions does not explain the gap (Appendix N); it is a matter of modelling.

To see which timescales are missed, we split each person's deviation from their mean with centred moving averages of 2, 10 and 60 s into four bands that add up to the deviation exactly:

Most of the within-person variance, 73% on NoXi and 81% on NoXi+J, changes more slowly than the 10 s window, and these bands also hold most of the missing score: the very slow band alone would add 0.11 on NoXi, where the model follows it worst ($r = 0.45$), and the slow band 0.15 on NoXi+J. Every window starts from a zero state, so a change slower than the window has to be inferred anew from 10 s of evidence in each window. The bands below 10 s hold little variance and would add at most 0.07.

## 3.5. Temporal Modelling after Fusion

In the architecture of Sections 2.3.2 and 2.4, time is modelled only within each stream: the intra-modal BiMamba scans each feature of each person over time, and the inter-modal block fuses the $M$ streams frame by frame. The fused state of the two people is never modelled over time. We therefore add one BiMamba block over time on the fused representation,

$$z = \mathrm{BiMamba}(HW_z) \in \mathbb{R}^{L' \times C'}, \qquad W_z \in \mathbb{R}^{MC' \times C'},$$

with the structure and initialisation of the intra-modal block (convolution width 4), and let both multimodal heads read the concatenation $[H, z]$, so that the frame-wise path is unchanged. This adds 0.26M parameters (2.06M to 2.33M). Six seeds each are compared with the final models of Section 3.3 (Appendix N).

On NoXi+J the temporal block raises the CCC by 0.043, from $0.641 \pm 0.018$ to $0.684 \pm 0.024$; the difference stays significant after the Holm correction over the two corpora ($p = 0.012$), and each of the six seeds scores higher than the final model with the same seed. The gain comes from where the previous subsection located the error: the within-person correlation rises from 0.69 to 0.75. The mean of the six models reaches 0.729 without rescaling, above the earlier rescaled ensemble

| | NoXi | | | NoXi+J | | |
|---|---|---|---|---|---|---|
| **Band** | **Variance** | $r$ | **CCC if true** | **Variance** | $r$ | **CCC if true** |
| Fast, < 2 s | 2.6% | 0.06 | 0.749 | 1.2% | 0.00 | 0.665 |
| Mid, 2 to 10 s | 10.0% | 0.37 | 0.781 | 5.5% | 0.20 | 0.711 |
| Slow, 10 to 60 s | 32.0% | 0.58 | 0.813 | 32.1% | 0.55 | **0.794** |
| Very slow, > 60 s | 40.6% | 0.45 | **0.844** | 48.5% | 0.78 | 0.764 |

**Table 1:** Error by timescale, final models. Each person's deviation from their mean is split into four bands: share of the within-person label variance in each band, Pearson $r$ between predicted and true band (higher is better), and the validation CCC if that band alone were predicted perfectly. The variance shares do not add up to 100% because the moving-average bands are not exactly uncorrelated. The gains of different bands overlap and do not add up either.

(0.714). On NoXi the block has no effect ($-0.007$, $p = 0.53$). This fits the variance split above: on NoXi+J three quarters of the label variance lie within a person, on NoXi only half. The ensembles and the new test predictions use the longer windows of Section 3.6 instead.

## 3.6. Longer Windows

Section 3.4 found most of the within-person variance, and most of the missing score, in changes slower than the 10 s window. We therefore lengthen the window. Memory grows with the number of frames per batch, so the batch shrinks from 8 to 4 windows (2 for 120 s). All runs keep the temporal block after fusion (Section 3.5). A control with 10 s windows and batches of 4 separates the effect of the window from that of the smaller batch.

On NoXi+J the 60 s window raises the CCC by 0.044 over 10 s windows ($p = 0.005$, Welch; $p = 0.0003$ paired by seed), and each of the six seeds scores higher. The smaller batch explains little of it: on the same three seeds the control with batches of 4 stays 0.036 below the 60 s windows (paired $p = 0.012$). Doubling the window to 120 s gives the same score ($-0.001$ on the same seeds).

Repeating the analysis of Section 3.4 (Appendix P) shows that both parts improve: each person's level is placed better (Pearson $r$ of the person means 0.86 to 0.89), and within a person the prediction follows the label more closely (0.68 to 0.72), mainly in the very slow band, while the slow band from 10 to 60 s, which Section 3.4 singled out, barely changes. Presumably a 60 s window gives each window more evidence for the person's current level, and the overlapping windows, half a minute apart, then follow that level as it drifts over the session. Given longer windows at inference only, the models stay stable but do not use context they were not trained on (Appendix P).

**NoXi.** On NoXi longer windows do not help. With 60 s windows the scores of the seeds range from 0.65 to 0.73 and some seeds are unstable (Appendix P), and 30 s windows are stable but no better than 10 s ones. The control with 10 s windows and batches of 4 is the best NoXi configuration so far: +0.022 over batches of 8 ($p = 0.010$, six seeds each, every seed higher) and +0.015 over the final model ($p = 0.14$). We have no explanation for the difference between the corpora; the bands of Section 3.4 would have predicted a gain on NoXi as well, where the very slow band is followed worst.

Two further attempts at long context, a whole-session path at a low rate (NoXi $-0.040$, NoXi+J $+0.001$) and a within-person loss term (NoXi $\pm 0.000$, NoXi+J $-0.004$), did not help (Appendix P).

Longer windows are the largest single gain on NoXi+J: 0.728 against 0.641 for the final model ($+0.087$, $p < 10^{-5}$), and the mean of the six models reaches 0.775 without rescaling, against 0.714 for the earlier rescaled ensemble. The new test predictions use the rescaled six-seed ensembles of the 60 s models on NoXi+J (0.787 on validation, against 0.714 before) and of the 10 s, batch 4 models on NoXi (0.766, against 0.758).

## 3.7. Learned versus Fixed Modality Ordering

The ordering layer of Section 2.4 is a contribution only if it does better than a fixed order. It does not. Four fixed orders of the $M = 10$ streams, three seeds each, score $0.712 \pm 0.014$ on NoXi and $0.666 \pm 0.018$ on NoXi+J, against $0.731 \pm 0.020$ and $0.641 \pm 0.018$ for the learned ordering (six seeds); after the Holm correction no single fixed order differs from the learned one, and a corrected version of the layer (0.717 and 0.642) does not change this. Equivalence tests show that the scan order does not matter within $\pm 0.02$ CCC, except at training time on NoXi+J, where they exclude only differences above about 0.025 (Appendix O). The trained block decays slowly enough to be nearly order-equivariant, so a learned ordering has nothing to exploit, which explains why neither version of the layer did better than a fixed order.

## 3.8. Cross-Corpus Transfer: a Shift in Label Scale

The analyses of this and the next subsection were made with models trained on single-session batches and core features (Sections 3.2 and 3.3); we have not repeated them in the final setting, but nothing in them depends on those choices. A model trained on one corpus and

| Window, batch | NoXi Seeds | NoXi CCC | NoXi+J Seeds | NoXi+J CCC |
|---|---|---|---|---|
| 10 s, 8 (Section 3.5) | 6 | $0.724 \pm 0.014$ | 6 | $0.684 \pm 0.024$ |
| 10 s, 4 | 6 | $\mathbf{0.746 \pm 0.008}$ | 3 | $0.700 \pm 0.012$ |
| 30 s, 4 | 3 | $0.733 \pm 0.004$ | | |
| 60 s, 4 | 3 | $0.693 \pm 0.044$ | 6 | $\mathbf{0.728 \pm 0.016}$ |
| 60 s, 4, gradient norm clipped at 1 | 3 | $0.697 \pm 0.065$ | | |
| 120 s, 2 | | | 3 | $0.735 \pm 0.025$ |

**Table 2:** Window length and batch size. Validation CCC (mean ± sd over the given number of seeds; higher is better) for windows of 10 to 120 s and batches of 2 to 8 windows, all with the temporal block after fusion. Empty cells were not run.

evaluated on the other scores close to zero. The decomposition CCC = $\rho C_b$ of Section 2.7 shows where the loss arises:

Across corpora the correlation stays at 0.42 to 0.45, against 0.53 to 0.70 within a corpus: the models still order frames reasonably well on unseen data. What collapses is the accuracy factor $C_b$, and the reason is visible in the means. The NoXi+J annotations average 0.834, the NoXi annotations 0.570, and each model continues to predict at the level of the corpus it was trained on; for the NoXi model on NoXi+J this offset alone pulls $C_b$ down to about 0.22 (Appendix N). The two corpora therefore differ mainly in the *scale* of their engagement labels - a shift in the label distribution, not in the input features. Our data cannot tell whether this reflects genuinely more engaged participants or a different use of the rating scale by the annotators of the two corpora.

Two consequences follow. First, by the proposition of Section 2.7, an affine recalibration of the predictions to the target's mean and standard deviation would raise the cross-corpus CCC to $\rho$, that is to about 0.42 and 0.45, but no further; it would require knowing the target corpus's label statistics, which a deployed model does not. In practice, corpus-specific models are therefore required, which is also the protocol of the official baseline. Second, the shift is invisible to the test-time adaptation of Section 2.6: its objective compares the model's heads with each other on unlabelled data and contains no information about the target corpus's label scale.

## 3.9. Test-Time Adaptation

Test-time adaptation was evaluated with the implementation of Section 2.6, in the cross-corpus setting it was designed for (NoXi model on NoXi+J) and in-corpus (NoXi+J model on NoXi+J), with four settings of the quantiles $(q_m, q_u)$ and the learning rate $\eta_{\mathrm{TTA}}$ (Appendix Q).

Without adaptation the model reaches 0.53 within NoXi+J and fails across corpora (0.09), for the label-scale reason of the previous subsection. Adaptation does not change this picture: no setting changes the cross-corpus score by more than 0.004, and in-corpus the smaller learning rate is neutral within seed noise (+0.004) and the larger one is harmful (−0.05 to −0.11). At the design quantiles $(0.3, 0.7)$ the filter selects only 2 to 6% of the windows, far below the 9% that two independent conditions of 30% each would give. The result is a clear negative one: in its current form the adaptation neither closes the cross-corpus gap, which lies in the label scale, nor improves in-corpus predictions. All other results in this document are obtained without it.

Adapting to a single person instead of a whole session (−0.002 on NoXi and −0.001 on NoXi+J at the design setting, harmful with a larger learning rate) and filtering with the total uncertainty of MC dropout (−0.002 and −0.000) do not change this result (Appendix Q).

## 3.10. Ensembling

For each corpus we average, frame by frame, the predictions of the six seeds of the final configuration (core features plus text, mixed batches, full objective, 10 s windows). Every member is trained on the training split only, and all six are used; no member is chosen by its validation score, since selecting the best single run would mostly select the luckiest seed.

**Label-free rescaling.** Averaging cancels the members' independent errors, but it also flattens the prediction: on NoXi+J the members' predictions have a standard deviation of 0.086 on average, the ensemble's only 0.078, against 0.102 for the annotations, and this too-small spread lowers $C_b$. We therefore stretch the ensemble's curve vertically around its own mean until its standard deviation equals the average standard deviation of the members (Appendix N). Only predictions enter this transformation, never annotations, so it applies unchanged to the test split. Being affine, it leaves $\rho$ untouched and can only move $C_b$.

The ensemble raises the CCC from 0.731 to 0.756 on NoXi and from 0.641 to 0.696 on NoXi+J, and the rescaling to 0.758 and 0.714. Ensembling raises the correlation itself, which is precisely the factor that the correlation ceiling of Section 2.7 identifies as the only remaining margin; the rescaling then recovers part of the accuracy lost to averaging. On NoXi+J a gap in $C_b$ remains, almost entirely from the level: the ensemble predicts 0.812 on average against 0.834 in the annotations. Two caveats apply: the decision to rescale was made on the validation split, so the final numbers are slightly optimistic; and an ensemble is

| Trained on | Evaluated on | CCC | $\rho$ | $C_b$ | mean $\hat{y}$ | mean $y$ |
|---|---|---|---|---|---|---|
| NoXi | NoXi | **0.699** | **0.703** | 0.995 | 0.584 | 0.570 |
| NoXi | NoXi+J | 0.092 | 0.422 | 0.219 | 0.577 | 0.834 |
| NoXi+J | NoXi+J | 0.530 | 0.530 | **0.999** | 0.838 | 0.834 |
| NoXi+J$^\dagger$ | NoXi | 0.143 | 0.445 | 0.321 | 0.815 | 0.570 |

**Table 3:** Cross-corpus transfer. Validation CCC (higher is better), its decomposition into the correlation $\rho$ and the bias correction $C_b$ (both at most 1; CCC $= \rho\, C_b$), and the mean prediction $\hat{y}$ and mean label $y$. Single-session batches, core features. $^\dagger$ An earlier NoXi+J model, trained with learning rate $5 \times 10^{-4}$.

| Validation CCC | NoXi | NoXi+J |
|---|---|---|
| Single model, single-session batches, core features (3 seeds) | 0.709 | 0.529 |
| + mixed-session batches (Section 3.2, 3 seeds) | 0.724 | 0.599 |
| + text stream (Section 3.3, 6 seeds) | 0.731 | 0.641 |
| + temporal block after fusion (Section 3.5, 6 seeds) | 0.724 | 0.684 |
| + NoXi: batches of 4; NoXi+J: 60 s windows (Section 3.6) | 0.746 | 0.728 |
| Six-seed ensemble of row 3, rescaled (earlier system) | 0.758 | 0.714 |
| Six-seed ensemble of row 5, rescaled (current system) | **0.766** | **0.787** |
| *For reference, MultiMediate'26 test leaderboard* | | |
| Official baseline | 0.55 | 0.31 |
| Best entry | 0.82 | 0.66 |

**Table 4:** Summary. Validation CCC (higher is better) of single models (mean over seeds) as each change is added, of the two rescaled six-seed ensembles that produce our test predictions, and, for reference, the test-split CCC of the official baseline and the best entry of the MultiMediate'26 leaderboard.

a statement about the best system we can build, not about the method. We therefore report the single-model mean over seeds as the estimate of the method and the rescaled six-seed ensemble as the system that produces the test predictions.

### 3.11. Summary

Our numbers are on the validation split and the leaderboard's on the test split, so the comparison is indicative only. The test predictions of each system (NoXi test-base and test-additional, NoXi+J test) are produced by the corresponding rescaled six-seed ensemble.

## 4. Conclusion

**Results.** EngageNet predicts continuous engagement with Beta regression heads on bidirectional state-space models. On the validation splits the best single models reach 0.746 CCC on NoXi and 0.728 on NoXi+J, and rescaled six-seed ensembles reach 0.766 and 0.787. What helped was modelling time after fusion and, on NoXi+J, training on longer windows; both act on the slow within-person changes that hold most of the remaining error.

**Contributions.** We contribute a Beta regression framework for bounded engagement, which keeps every prediction in $[0, 1]$ and provides a predictive variance at no extra cost. We also contribute a set of analyses, each over several seeds with appropriate statistical tests, of what does and does not help. Equivalence tests show that the order in which the fusion block scans the modalities does not matter within $\pm 0.02$ CCC: the trained block forgets slowly along the modality axis, so a learned ordering has nothing to exploit. Test-time adaptation does not help, whether per session, per person or with Monte Carlo dropout, and the cross-corpus failure is a shift in label scale that adaptation without labels cannot observe. Finally, separating each person's level from their changes over time locates most of the remaining error in slow within-person dynamics. This guided the temporal block after fusion and the longer windows, which raised the single-model CCC on NoXi+J from 0.641 to 0.728.

**Limitations.** All numbers are on the validation splits, since test labels are not available, and with a seed-to-seed spread of 0.01 to 0.03 only differences of about 0.04 are detectable with three seeds. Within-person dynamics remain the main gap: on NoXi the prediction follows a person's changes with a correlation of only about 0.5, while perfect within-person dynamics would raise the CCC to 0.95. Across corpora, corpus-specific models remain necessary unless the target corpus's label statistics are known.

# References


[1] Ziyu Jia et al., *A Multimodal BiMamba Network with Test-Time Adaptation for Emotion Recognition Based on Physiological Signals*, 39th Conference on Neural Information Processing Systems (NeurIPS 2025).

[2] Albert Gu and Tri Dao, *Mamba: Linear-Time Sequence Modeling with Selective State Spaces*, arXiv preprint arXiv:2312.00752 (2024).

[3] Gonzalo Mena et al., *Learning Latent Permutations with Gumbel-Sinkhorn Networks*, International Conference on Learning Representations (ICLR 2018).

[4] Eric Jang, Shixiang Gu, and Ben Poole, *Categorical Reparameterization with Gumbel-Softmax*, International Conference on Learning Representations (ICLR 2017).

[5] Emil Julius Gumbel, *Statistical Theory of Extreme Values and Some Practical Applications*, National Bureau of Standards Applied Mathematics Series, 33 (1954).

[6] Garrett Birkhoff, *Tres observaciones sobre el algebra lineal*, Universidad Nacional de Tucumán, Revista, Serie A, 5:147–151 (1946).

[7] Aitchison, J., & Shen, S. M. (1980). *Logistic-normal distributions: Some properties and uses.* Biometrika, 67(2), 261–272.

[8] P. Kumaraswamy, *A generalized probability density function for double-bounded random processes*, Journal of Hydrology, 46, 79–88 (1980).

[9] Guilherme Pumi, Cleber Rauber, and Fabio M. Bayer, *Kumaraswamy regression model with Aranda-Ordaz link function*, TEST: An Official Journal of the Spanish Society of Statistics and Operations Research, Springer;Sociedad de Estadística e Investigación Operativa, 29(4), 1051–1071, December (2020).

[10] Yaniv Romano, Evan Patterson, and Emmanuel J. Candès, *Conformalized Quantile Regression*, Advances in Neural Information Processing Systems (NeurIPS 2019), 32 (2019).

[11] Isaac Gibbs and Emmanuel Candès, *Adaptive Conformal Inference Under Distribution Shift*, Advances in Neural Information Processing Systems (NeurIPS 2021), 34, 1660–1672 (2021).

[12] Lawrence I-Kuei Lin, *A Concordance Correlation Coefficient to Evaluate Reproducibility*, Biometrics, 45(1), 255–268 (1989).

[13] Daksitha Withanage Don, Marius Funk, Michal Balazia, Huajian Qiu, Shogo Okada, François Brémond, Jan Alexandersson, Andreas Bulling, Elisabeth André, and Philipp Müller, *MultiMediate '25: Cross-cultural Multi-domain Engagement Estimation*, Proceedings of the 33rd ACM International Conference on Multimedia (MM '25), 14150–14155 (2025). doi:10.1145/3746027.3762076.

[14] Sandra Wachter, Brent Mittelstadt, and Chris Russell, *Why fairness cannot be automated: Bridging the gap between EU non-discrimination law and AI*, Computer Law and Security Review, 41, 105567 (2021). doi:10.1016/j.clsr.2021.105567.

[15] Jimmy Lei Ba, Jamie Ryan Kiros, and Geoffrey E. Hinton, *Layer Normalization*, arXiv preprint arXiv:1607.06450 (2016).

[16] Sergey Ioffe and Christian Szegedy, *Batch Normalization: Accelerating Deep Network Training by Reducing Internal Covariate Shift*, International Conference on Machine Learning (ICML 2015), 448–456.

[17] Angelo Cafaro, Johannes Wagner, Tobias Baur, Soumia Dermouche, Mercedes Torres Torres, Catherine Pelachaud, Elisabeth André, and Michel F. Valstar, *The NoXi Database: Multimodal Recordings of Mediated Novice-Expert Interactions*, Proceedings of the 19th ACM International Conference on Multimodal Interaction, 350–359 (2017). doi:10.1145/3136755.3136780.

[18] Marius Funk, Shogo Okada, and Elisabeth André, *Multilingual Dyadic Interaction Corpus NoXi+J: Toward Understanding Asian-European Non-verbal Cultural Characteristics and their Influences on Engagement*, Proceedings of the ACM International Conference on Multimodal Interaction, 224–233 (2024). doi:10.1145/3678957.3685757.

[19] Albert Gu, Ankit Gupta, Karan Goel, and Christopher Ré, *On the Parameterization and Initialization of Diagonal State Space Models*, Advances in Neural Information Processing Systems (NeurIPS 2022), 35, 35971–35983.

[20] Alan V. Oppenheim, Alan S. Willsky, and S. Hamid Nawab, *Signals and Systems*, 2nd edition, Prentice Hall (1997).

[21] Maximilian Seitzer, Arash Tavakoli, Dimitrije Antic, and Georg Martius, *On the Pitfalls of Heteroscedastic Uncertainty Estimation with Probabilistic Neural Networks*, International Conference on Learning Representations (ICLR 2022).

[22] B. L. Welch, *The Generalization of "Student's" Problem when Several Different Population Variances are Involved*, Biometrika, 34(1–2), 28–35 (1947).

[23] Sture Holm, *A Simple Sequentially Rejective Multiple Test Procedure*, Scandinavian Journal of Statistics, 6(2), 65–70 (1979).

# Appendix A Roles, Targets and Input Standardisation

**Weight sharing across roles.** The two roles observe the same physical signal semantics (an eGeMAPS vector means the same thing whether it was extracted from the expert's or the novice's microphone). Accordingly, the InitEncoder, the uniform channel projection, the intra-modal BiMamba block, and the unimodal Beta head are instantiated *once per feature type* and applied to both roles. Only the inter-modal stage distinguishes the roles, since the permutation is learned over all $M$ role-feature pairs jointly. This halves the parameter count relative to per-role encoders and forces the shared representation to be role-agnostic.

**Target construction.** With $y_t^e$ and $y_t^n$ as in Section 2, consider the averaged target $\bar{y}_t = \frac{1}{2}(y_t^e + y_t^n)$. Suppose both annotations have the same variance $\sigma^2$ and correlation $r$ with each other. Scaling a random variable by $\frac{1}{2}$ scales its variance by $\frac{1}{4}$, and the variance of a sum is the sum of the variances plus twice the covariance, so

$$\begin{aligned}\mathrm{Var}(\bar{y}) &= \tfrac{1}{4}\left[\mathrm{Var}(y^e) + \mathrm{Var}(y^n) + 2\,\mathrm{Cov}(y^e, y^n)\right] \\ &= \tfrac{1}{4}\left[\sigma^2 + \sigma^2 + 2r\sigma^2\right] = \frac{\sigma^2(1+r)}{2}\end{aligned}$$

using $\mathrm{Cov}(y^e, y^n) = r\sigma^2$. The corpus paper [18] measures exactly this correlation and finds it to be small and, in three of four language sets, negative: $r = -0.19$ for German, $-0.07$ for English, $-0.05$ for French, and $+0.51$ for Japanese, the last attributed to a stronger tendency toward interpersonal harmony. Substituting these values, the averaged target retains only 41%, 47% and 48% of the variance in the European sets respectively, and 76% in the Japanese set - so on most of the corpus more than half the signal is destroyed before training begins. Since CCC is normalised by the variance of the target (Section 2.7), what is flattened away here cannot be recovered later.

Predicting both roles needs no new machinery, because the two participants are never mixed on the way in: their recordings enter as separate streams and stay separately indexed throughout. The network therefore ends with one output head per role rather than one shared head, each producing that participant's engagement curve, and each auxiliary per-modality head is trained against the participant whose stream it reads.

**Input standardisation.** The raw feature streams occupy vastly different numerical ranges: eGeMAPS v2 $\in [-2.6 \times 10^5, 2.6 \times 10^5]$ and OpenFace2 $\in [-3 \times 10^4, 3 \times 10^4]$, while W2v-BERT 2.0 embeddings lie within $[-4, 4]$. These magnitudes compound through the encoder and state-space stages, reaching $\sim 10^{11}$ at the cross-modal block and driving the Beta shape parameters to $\sim 10^{14}$, at which point the negative log-likelihood is numerically meaningless and optimisation fails.

We therefore standardise every channel to zero mean and unit variance before it enters the network:

$$\tilde{x}_i^{(c)} = \frac{x_i^{(c)} - \mu_i^{(c)}}{\sigma_i^{(c)}}, \qquad c \in \{1, \ldots, C_i\},$$

where the per-channel statistics are accumulated in double precision over the **training split only** and reused unchanged for validation and test. Channels whose standard deviation falls below $10^{-8}$ (constant channels) are centred but not rescaled, avoiding division by zero. Because the two roles share encoder weights, they necessarily share normalisation statistics as well. The statistics are computed once per corpus.

# Appendix B Details of the InitEncoder

**Dimensions and window length.** $C' = 128$ is imposed by the uniform channel projection $f_i$ at the end of each encoder (below), which maps every stream to the same width regardless of its raw dimension $C_i$ (from 88 to 1024 channels). $L'$ follows from the window length and the encoder stride, $L' = L/s_i$; we use stride $s_i = 1$ for every stream, so no temporal downsampling takes place and $L' = L = 250$ frames (10 s at 25 Hz) for all of them. The window length is a design choice rather than a derived quantity. Ten seconds is long compared with the time engagement takes to change, which is a matter of seconds, and short compared with a session, which therefore yields more than a hundred training windows on average. Doubling it to 20 s ($L = 500$, window hop 250) made no measurable difference: over three seeds each, the NoXi mean moved from 0.709 to 0.714, and the NoXi+J mean from 0.529 to 0.560 with a seed-to-seed standard deviation of 0.054 (Section 3). We therefore kept the cheaper 10 s window.

**InitEncoder convolution.** The convolution $\mathrm{Conv1D}_i$ of the InitEncoder is

$$\big(\mathrm{Conv1D}_i(z)\big)_{t,c'} = b_{c'} + \sum_{j=0}^{k_i-1}\sum_{c=1}^{C_i} W_{j,c,c'}\; z_{t+j-p_i,\,c},$$
$$p_i = \Big\lfloor \frac{k_i-1}{2} \Big\rfloor, \qquad c' = 1,\dots,C_i',$$

where $z = \tilde{x}_i^\top \in \mathbb{R}^{L\times C_i}$, frames outside the window count as zero (`SAME` padding), and $W \in \mathbb{R}^{k_i\times C_i\times C_i'}$ and $b \in \mathbb{R}^{C_i'}$ are learned. We use the same kernel for every stream: $k_i = 5$ frames (200 ms), so $p_i = 2$ and the filter is centred on frame $t$, covering frames $t-2,\dots,t+2$. The stride is $s_i = 1$, and $C_i' = 64$ or 128 depending on the stream (Appendix M). This layer is the only place where a stream's raw channels are mixed with each other, and with $k_i C_i C_i'$ weights it is also the largest layer of the model for the wide streams: the convolutions of the widest streams alone hold about 1.6M of the final model's 2.75M parameters. Further, BN is batch normalisation [16] over the channel axis, whose running statistics are frozen at evaluation time and which later serves as a surgical adaptation target (Section 2.10); $\sigma(x) = \frac{x}{1+e^{-x}}$ is the SiLU activation function, and $f_i$ is the uniform channel projection defined in Appendix G, mapping $C_i' \to C'$ so that all modalities share a common width. Encoder weights are shared between the expert and novice streams of the same feature type.

# Appendix C Details of the BiMamba Block

**Gate.** Intuitively, the gate $g_i$ of step 2 highlights engagement-relevant information while suppressing noise and redundancy.

**Selective state-space model.** $\mathrm{SSM}(\cdot)$ represents the Selective State Space Model. Its starting point is a continuous linear time-invariant (LTI) system, defined by the state equation $\xi'(t) = A\xi(t) + Bz(t)$ and the output equation $y(t) = C\xi(t)$, where $z(t)$ is the input signal. (Throughout, we write $z$ for the input of the SSM, to keep it apart from the block output $u_i$.) To operate on discrete sequence steps, the continuous transition operator $A$ and input operator $B$ are discretised with a timestep $\Delta > 0$. Following the reference Mamba implementation [2], we use

$$\bar{A} = \exp(\Delta A), \qquad \bar{B} \approx \Delta B,$$

with a diagonal $A < 0$ (Appendix D).

Unlike traditional LTI systems, Mamba introduces *selection* by making the discretized parameters $(\bar{B}, C, \Delta)$ functions of the input $z_t$. Specifically:

$$\Delta_t = \mathrm{softplus}(s_\Delta + \mathrm{Linear}(z_t)) \in \mathbb{R}^{C'}$$
$$B_t = \mathrm{Linear}(z_t) \in \mathbb{R}^N, \quad C_t = \mathrm{Linear}(z_t) \in \mathbb{R}^N$$

where $\mathrm{softplus}(x) = \ln(1+e^x)$ and $s_\Delta \in \mathbb{R}^{C'}$ is a learned, input-independent bias term that defines the baseline timescale of the system. The inclusion of $s_\Delta$ within the *softplus* function ensures that the resulting $\Delta_t$ remains strictly positive, which is required for the stability of the discretization. This selection mechanism allows the discrete transition $\xi_t = \bar{A}_t\xi_{t-1} + \bar{B}_t z_t$ to dynamically adjust its temporal resolution. The projections producing $B_t$ and $C_t$ are bias-free.

The states are computed with a parallel associative scan (Appendix E).

**Time reversal and gating.** Note that the time reversal is applied to the backward SSM output *before* gating, so that the gate $g_i$ - which is computed once, in forward time order - modulates the feature belonging to the same time step $t$ in both branches. Applying $\mathrm{Rev}_t$ after gating would instead pair the gate at step $t$ with the feature at step $L'-t$, misaligning the two.

**Depthwise convolution.** Unlike the dense convolution of the InitEncoder, DWConv1D filters every channel separately with its own short kernel, and channels are not mixed. For an input $z \in \mathbb{R}^{L'\times C'}$, DWConv1D computes

$$\big(\mathrm{DWConv1D}(z)\big)_{t,d} = b_d + \sum_{j=0}^{D_C-1} w_{j,d}\; z_{t+j-p,\,d},$$
$$p = \Big\lfloor \frac{D_C-1}{2} \Big\rfloor, \qquad d = 1,\dots,C',$$

with learned $w \in \mathbb{R}^{D_C\times C'}$ and $b \in \mathbb{R}^{C'}$, and frames outside the window counted as zero. Each output value therefore depends only on the same channel at $D_C$ neighbouring frames: it is a learned local smoothing or differencing of every channel, applied before the state-space model. We use $D_C = 4$, as in [2], so with $p = 1$ the

filter covers frames $t-1,\dots,t+2$; the backward branch runs on the reversed sequence, where the same filter covers frames $t-2,\dots,t+1$ of the original time order. The reference Mamba implementation pads causally, so that frame $t$ sees only the past; since our model is bidirectional and processes complete windows, we use centred `SAME` padding instead. The two branches have separate convolutions. A depthwise filter has $D_C C'$ weights instead of the $D_C C'^2$ of a dense convolution, which keeps its cost linear in the channel width. In the inter-modal block, whose sequence runs over modalities instead of time, the same operator is used with $D_C = 2$, so each position is combined with the next one.

**Residual.** The residual of step 4 carries the *unnormalised* $h_i$, not $\bar{h}_i$: the layer normalisation of step 1 conditions the block's internal computation without rescaling the identity path.

# Appendix D Details of the State-Space Model

**Discretisation.** The exact discretisation yields $\bar{A} = \exp(\Delta A)$ and $\bar{B} = (\Delta A)^{-1}(\bar{A} - I)\Delta B$. The first-order (Euler) simplification $\bar{B} \approx \Delta B$ is accurate to $O(\Delta^2)$ and avoids the matrix inverse $(\Delta A)^{-1}$. Here $\exp(\cdot)$ is the matrix exponential, $\exp(X) = \sum \frac{X^k}{k!}$. Because $A$ is diagonal (see below), every power of $\Delta A$ is again diagonal, with the diagonal entries raised to that power, so the series acts on each diagonal entry separately:

$$\exp\big(\Delta \operatorname{diag}(a_1,\dots,a_N)\big) = \operatorname{diag}\big(e^{\Delta a_1},\dots,e^{\Delta a_N}\big).$$

**The SSM, exactly.** Collecting the pieces described in Section 2.3.1 and in this appendix - the diagonal state matrix, its parameterisation, and the input-dependent $\Delta_t$, $B_t$, $C_t$ of the selection mechanism - the operator applied in each branch is the following. Its input is a sequence $z = (z_1,\dots,z_{L'})$ with $z_t \in \mathbb{R}^{C'}$; in step 3, $z = \sigma(\mathrm{DWConv1D}(W_i^h \bar{h}_i + b_i^h))$. Every channel $d \in \{1,\dots,C'\}$ carries its own state $\xi_t^{(d)} \in \mathbb{R}^N$, started at $\xi_0^{(d)} = \mathbf{0}$, and

$$\xi_t^{(d)} = \exp\big(\Delta_{t,d}\, a_d\big) \odot \xi_{t-1}^{(d)} + \Delta_{t,d}\, z_{t,d}\, B_t, \qquad t = 1,\dots,L',$$

$$\big(\mathrm{SSM}(z)\big)_{t,d} = y_{t,d} = C_t^\top \xi_t^{(d)} = \sum_{n=1}^{N} C_{t,n}\, \xi_{t,n}^{(d)}.$$

Here $a_d = (a_{d,1},\dots,a_{d,N}) \in \mathbb{R}^N$ holds the (negative) decay rates of channel $d$ and the exponential is taken elementwise; $\Delta_{t,d} > 0$ is the timestep of channel $d$ at step $t$; and $B_t, C_t \in \mathbb{R}^N$ are the input and read-out vectors at step $t$, shared by all channels. The first line is the discretised state equation, with $\bar{A} = \exp(\Delta A)$ and $\bar{B} = \Delta B$; the second is the output equation. The SSM thus maps $\mathbb{R}^{L' \times C'}$ to $\mathbb{R}^{L' \times C'}$.

**Parameterisation of $A$.** The state transition matrix is not learned directly. Instead we learn $\log(-A)$ and recover

$$A = -\exp\big(A_{\log}\big) \in \mathbb{R}^{C' \times N} \quad \text{(elementwise)},$$

with $A_{\log}$ initialised by the S4D-Real scheme below. This parameterisation constrains $A < 0$ (elementwise). This guarantees $\bar{A} = \exp(\Delta A) \in (0,1)$, so the recurrence is contractive and the hidden state cannot diverge - a stability property that an unconstrained $A$ does not provide. Separate $A_{\log}$ parameters are maintained for the forward and backward directions.

**No feedthrough term.** The general state-space model has a second term in its output equation, $y(t) = C\xi(t) + Dz(t)$. This *feedthrough* is a direct path from the current input to the current output that bypasses the state. The Mamba paper writes the output equation without it, but its reference implementation does add it, as a learned vector with one entry per channel [2]; BiMamba-TTA [1] does not write out the SSM at all, so its paper gives no indication either way. Our implementation omits it, i.e. $D = 0$. This was not a deliberate design decision but a consequence of implementing the equations as written. A path around the state still exists at block level, because the residual connection of step 4 adds the block input $h_i$ to the block output; what is missing is only the narrower skip from the SSM's own input $z$ to its output. We have not tested whether adding it changes the results.

**Diagonal state transition.** Following [2], the state-space model is applied independently to each of the $C'$ channels, and the state matrix of every channel is restricted to be *diagonal*. Channel $d$ thus carries $N$ state coordinates evolving under $A^{(d)} = \operatorname{diag}(a_{d,1},\dots,a_{d,N})$, and because a diagonal matrix is fully determined by its diagonal, no $N \times N$ array is ever materialised: the entire parameter collapses to the $C' \times N$ array $A = (a_{d,n})$, one row of $N$ entries per channel. Each entry governs how quickly one state coordinate forgets, which is why we refer to these entries as decay rates. The update is then elementwise rather than a matrix product, costing $O(N)$ per channel per step instead of $O(N^2)$ and storing $C'N$ parameters instead of $C'N^2$. Diagonality is not merely an efficiency measure: it is what allows the recurrence to be evaluated by a parallel scan, as shown below.

**Temporal receptive field.** The decay rate and the timestep jointly determine how current input can influence future output. Consider a single state coordinate, which follows the recurrence

$$\xi_t = \bar{A}\,\xi_{t-1} + b_t, \qquad b_t := \bar{B}_t z_t,$$

which is *first-order*: the state at step $t$ is determined solely by the previous state $\xi_{t-1}$ and the current input alone, with no explicit dependence on $\xi_{t-2}$ or earlier. Suppose the input does not exist after step $t_0$ ($z_t = 0 \implies b_t = 0$) for $t > t_0$. Unrolling from $\xi_{t_0}$,

$$\xi_{t_0+1} = \bar{A}\,\xi_{t_0}, \qquad \xi_{t_0+2} = \bar{A}^2\xi_{t_0},$$
$$\ldots, \qquad \xi_{t_0+k} = \bar{A}^{\,k}\,\xi_{t_0}.$$

Since $\bar{A} = \exp(\Delta A) \in (0,1)$, the retained state shrinks geometrically; $\bar{A}$ is called the *decay* (or *retention*) factor. Equivalently, and this is the reading we need, the influence of an input entering at step $t_0$ on the state $k$ steps later carries the weight $\bar{A}^{\,k}$: this is exactly the accumulated multiplier that appears in the associative scan derivation of Appendix E. The *memory* of the block is described by how quickly these weights $\bar{A}^{\,1}, \bar{A}^{\,2}, \bar{A}^{\,3}, \ldots$ shrink as $k$ grows, and its *effective memory* $\tau_{\text{eff}}$ is the conventional single-number summary - the number of steps after which the weight has fallen to $e^{-1}$ of its initial value. This $e^{-1}$ convention is the standard definition of the time constant of an exponentially decaying response in linear systems theory [20], and we adopt it unchanged. Solving

$$\bar{A}^{\,\tau_{\text{eff}}} = e^{-1} \implies \tau_{\text{eff}} \ln \bar{A} = -1 \implies \tau_{\text{eff}} = \frac{-1}{\ln \bar{A}},$$

and substituting $\ln \bar{A} = \Delta A = -\Delta|A|$ (recall $A < 0$ by construction),

$$\boxed{\tau_{\text{eff}} = \frac{1}{\Delta\,|A|}}$$

measured in units of encoder output steps.

**Why the initialisation matters.** The naive choice - and the initialisation of our first implementation - is $A_{\log} = \mathbf{0}$ and $s_\Delta = \mathbf{0}$. It gives $|A| = \exp(0) = 1$ and, since the input-dependent projection contributes negligibly at initialisation, $\Delta \approx \text{softplus}(0) = \ln 2 \approx 0.693$. Hence

$$\tau_{\text{eff}} = \frac{1}{0.693 \times 1} \approx 1.44 \text{ steps}$$

The output sequence retains the input rate of 25 Hz and one step spans 1/25 s = 40 ms; the receptive field is therefore

$$1.44 \times 40\,\text{ms} \approx 58\,\text{ms}$$

A uniform $A_{\log}$ compounds the difficulty: every one of the $N$ state coordinates then carries the same decay rate, so the state dimension supplies $N$ copies of a single timescale rather than a spread of them, entirely defeating the purpose of $N > 1$.

**S4D-Real initialisation.** We therefore adopt the real-valued diagonal initialisation of [19], used in the reference Mamba implementation [2]: setting

$$A_{\log}[d,n] = \ln n \quad \to \quad a_{d,n} = -n, \qquad n = 1, \ldots, N,$$

gives every channel the decay rates $1, 2, \ldots, N$ ($N = 16$) - a ladder of distinct timescales rather than a single one. The timestep bias is initialised so that $\Delta$ is log-uniform on $[\Delta_{\min}, \Delta_{\max}] = [10^{-3}, 10^{-1}]$, obtained by inverting the softplus,

$$s_\Delta = \ln\left(e^{\Delta} - 1\right),$$

which is the exact inverse since $\text{softplus}(s_\Delta) = \ln(1 + e^{s_\Delta}) = \Delta$. The resulting receptive fields $\tau_{\text{eff}} = \frac{1}{\Delta|A|}$ span from a fraction of a step to of order $10^3$ steps - tens of seconds at 25 Hz - allowing the selection mechanism to choose an integration horizon per channel and per input rather than beginning pinned to a single very short one.

# Appendix E Parallel Evaluation via Associative Scan

This part is about speeding up the computation of the states $\xi_1, \ldots, \xi_{L'}$, which is the only expensive part of the SSM. Written for all channels at once, the states follow the recurrence introduced above,

$$\xi_t = \bar{A}_t \odot \xi_{t-1} + \bar{B}_t z_t, \qquad t = 1, \ldots, L', \qquad \xi_0 = \mathbf{0},$$

where $\xi_t$, $\bar{A}_t$ and $\bar{B}_t z_t$ are $C' \times N$ arrays with entries $\xi_{t,n}^{(d)}$, $\exp(\Delta_{t,d}\, a_{d,n})$ and $\Delta_{t,d}\, z_{t,d}\, B_{t,n}$. Once the states are known, the output $y_{t,d} = \sum_{n=1}^{N} C_{t,n}\, \xi_{t,n}^{(d)}$ is a cheap read-out at every step separately. $C_{t,n}$ is the $n$-th entry of the read-out vector $C_t = \mathrm{Linear}(z_t) \in \mathbb{R}^N$ produced by the selection mechanism: the weight with which state coordinate $n$ contributes to the output at step $t$, the same for every channel. Evaluated naively the recurrence is a loop: $\xi_t$ cannot be formed until $\xi_{t-1}$ exists, so the $L'$ steps are strictly serial. The math for each step is very simple (just a multiply-add operation on a $C' \times N$ array), so calculating it one step at a time wastes GPU time on just starting the tasks and leaves the hardware mostly idle. For a sequence of $L' = 250$, this means waiting to sequentially launch 250 separate tasks for an amount of work the GPU could otherwise process almost instantly. Ultimately, the step-by-step dependency is what slows the process down, not the calculations themselves.

Two structural facts make a parallel evaluation possible. First, because $A$ is *diagonal* in the state dimension, the update does not mix state coordinates: the vector recurrence decomposes into $n_{\text{batch}} \times C' \times N$ mutually independent *scalar* recurrences, one per (sample, channel, state) triple, all sharing the same structure. Second, each such scalar recurrence is an *affine* map of the previous state. Write the step-$t$ update as the function

$$f_t : \mathbb{R} \to \mathbb{R}, \qquad f_t(\xi) = a_t\, \xi + b_t,$$
$$a_t := \bar{A}_t, \quad b_t := \bar{B}_t z_t,$$

so that unrolling from $\xi_0 = 0$ gives $\xi_t = (f_t \circ f_{t-1} \circ \cdots \circ f_1)(0)$. The state at time $t$ is therefore nothing more than the composition of the first $t$ update maps, evaluated at zero - and computing *every* prefix of a sequence under some combining operation is precisely what a *scan* (or prefix computation) does. The archetypal example is the prefix sum, which turns $(x_1, \ldots, x_n)$ into $(x_1,\ x_1 + x_2,\ \ldots)$; a scan generalises this to any binary operator $\oplus$.

The reason this buys anything is that a scan under an *associative* $\oplus$ need not be computed left to right. Associativity means partial results may be regrouped freely, so the sequence can be reduced pairwise in a balanced binary tree: total work stays $O(L')$, but the *sequential depth* - the length of the longest chain of dependent operations - falls from $O(L')$ to $O(\log L')$. For $L' = 250$ that is roughly 8 dependent stages instead of 250, each stage saturating the device with independent work.

*Closure and the composition rule.* To scan over the update maps we must be able to represent a composed map by a finite parameter set. Affine maps in one variable are closed under composition, and the family is parameterised by exactly two numbers - a multiplier and an offset - which is why the scan carries *pairs* rather than scalars. Explicitly, for $i < j$,

$$\begin{aligned}(f_j \circ f_i)(\xi) = f_j\big(f_i(\xi)\big) &= a_j\big(a_i\xi + b_i\big) + b_j \\ &= \underbrace{(a_j a_i)}_{\text{new multiplier}}\ \xi + \underbrace{(a_j b_i + b_j)}_{\text{new offset}}.\end{aligned}$$

The composite is again affine, so identifying each map with its parameter pair $(a, b)$ induces the binary operator

$$(a_i, b_i) \oplus (a_j, b_j) := (a_j a_i,\ a_j b_i + b_j), \qquad i < j,$$

where the left operand is the earlier segment of the sequence. Intuitively the two components accumulate different things: the multiplier is the running product of decay factors, recording how much of the initial state survives, while the offset is the running total of inputs, each discounted by all the decay factors applied after it entered.

*Associativity.* The operator inherits associativity from function composition, but it is worth verifying directly on the parameters. Expanding the two groupings,

$$\begin{aligned}&\big[(a_i, b_i) \oplus (a_j, b_j)\big] \oplus (a_k, b_k) \\ &\quad = (a_j a_i,\ a_j b_i + b_j) \oplus (a_k, b_k) \\ &\quad = \big(a_k a_j a_i,\ a_k a_j b_i + a_k b_j + b_k\big),\end{aligned}$$

$$\begin{aligned}&(a_i, b_i) \oplus \big[(a_j, b_j) \oplus (a_k, b_k)\big] \\ &\quad = (a_i, b_i) \oplus (a_k a_j,\ a_k b_j + b_k) \\ &\quad = \big(a_k a_j a_i,\ a_k a_j b_i + a_k b_j + b_k\big),\end{aligned}$$

which agree componentwise. Together with the identity element $(1, 0)$ - the identity map $\xi \mapsto \xi$ - the parameter pairs form a monoid under $\oplus$, which is exactly the algebraic structure a scan requires. Note that $\oplus$ is *not* commutative: $(a_j a_i, a_j b_i + b_j) \neq (a_i a_j, a_i b_j + b_i)$ in general, reflecting the obvious fact that reordering the timesteps changes the trajectory. This costs us nothing, since a scan requires associativity but never commutativity.

Running the scan over $\big((a_1, b_1), \ldots, (a_{L'}, b_{L'})\big)$ yields at position $t$ the pair representing $f_t \circ \cdots \circ f_1$; because $\xi_0 = 0$ the multiplier component annihilates and the state is read off directly from the offset component, $\xi_t = a_t \cdots a_1 \cdot 0 + (\text{offset}) = (\text{offset})$.

*Implementation.* JAX exposes this primitive as `jax.lax.associative_scan(fn, elems, axis)`, where `fn` implements $\oplus$ on a pair of PyTrees and is required (not merely assumed) to be associative. We supply the tuple $(\bar{A},\ \bar{B}z)$, both of shape $(L', n_{\text{batch}}, C', N)$ after moving the sequence axis to the front, and scan along `axis=0`; the operator is applied elementwise, so the $n_{\text{batch}} \times C' \times N$ independent recurrences are resolved simultaneously in a single call. The same routine serves the inter-modal block unchanged, where the scanned axis is the modality sequence of length $M$ rather than time, with the $L'$ time steps folded into the batch axis.

Finally, the log-space parameterisation of $A$ interacts favourably with the scan. Since $\bar{A}_t = \exp(\Delta_t A) \in (0, 1)$, the cumulative multipliers $a_t \cdots a_1$ form a decreasing product and cannot overflow, no matter how long the sequence; the worst case is underflow to zero, which is the gentle behaviour of a state that has simply forgotten its distant past. An unconstrained $A$ permitting $|\bar{A}| > 1$ would instead make these partial products grow geometrically in the sequence length, and the tree-structured reduction would surface that divergence just as surely as a serial loop would.

# Appendix F Two Rejected Fusion Arrangements

How the exchange between the $M$ intra-modal representations is arranged - specifically, which axis the state-space model treats as its sequence - determines both what the fusion can express and whether the learned modality ordering of Section 2.4 has any effect at all.

**Arrangement (i): concatenate along channels, scan over time.** Form

$$U^{(t)} = u_1^{(t)} \circ u_2^{(t)} \circ \cdots \circ u_M^{(t)} \in \mathbb{R}^{MC'},$$

where $\circ$ denotes concatenation and $u_i^{(t)} \in \mathbb{R}^{C'}$ is the $i$-th modality's representation at time $t$, and apply the BiMamba block along the time axis with feature width $MC'$. Note that $\circ$ places the $M$ vectors end to end, producing one long vector of length $MC'$ in which entries $(i-1)C'+1, \ldots, iC'$ belong to modality $i$. This is different from stacking them as the rows of an $M \times C'$ matrix, which is what the arrangement of Section 2.3.2 does. Modalities then interact only through the block's dense projections $W \in \mathbb{R}^{MC' \times MC'}$, which mix all channels of all modalities at every time step. The fusion is expressive but structurally unconstrained, and it has two problems.

First, any custom reordering of the input modalities becomes useless. Because the reordering operation happens right before a dense layer (a linear weight matrix), the network simply absorbs the fixed rearrangement directly into its weight calculations without changing the model's capabilities. The only benefit comes from making the reordering dynamic (input-dependent), but even then, it creates a soft blend of modalities rather than a true sequential order. This defeats the original goal of learning an ordering, which relies on processing the modalities step-by-step.

Formally, let $P \in \mathbb{R}^{M \times M}$ be the reordering matrix of Section 2.4, and let $I_{C'}$ be the $C' \times C'$ identity matrix - the subscript only states its size. Their Kronecker product $P \otimes I_{C'} \in \mathbb{R}^{MC' \times MC'}$ is the block matrix made of $M \times M$ blocks of size $C' \times C'$, whose block $(i, j)$ is $P_{ij} I_{C'}$. For $M = 2$ and the permutation that swaps the two modalities,

$$P = \begin{pmatrix} 0 & 1 \\ 1 & 0 \end{pmatrix}, \qquad P \otimes I_{C'} = \begin{pmatrix} \mathbf{0} & I_{C'} \\ I_{C'} & \mathbf{0} \end{pmatrix},$$

so multiplying $U^{(t)}$ by it exchanges the two halves of length $C'$: it moves whole modalities while leaving the order of the channels inside each modality unchanged. Reordering before the dense projection then gives $W(P \otimes I_{C'})U^{(t)} = W'U^{(t)}$ with $W' := W(P \otimes I_{C'})$, so for any fixed $P$ the reordered model computes exactly what the unreordered model computes with weights $W'$: the two are the same model class, and the permutation is unlearnable because it is already absorbed.

Second, the parameter count grows quadratically with the number of modalities ($M$). Combining all modalities into a single wide feature dimension causes the fusion layer to require roughly $M^2$ times as many parameters. This makes the fusion stage take up most of the network's capacity, which easily leads to severe overfitting on smaller datasets containing only a few dozen sessions.

**Arrangement (ii): concatenate along channels, scan over the concatenated axis.** A second approach treats the combined index as the sequence, scanning over all $MC'$ positions so each modality forms a block of $C'$ steps. This fails due to an information bottleneck, which becomes clear when we unroll the recurrence over the scan index $k$:

$$\xi_k = \bar{A}_k\, \xi_{k-1} + b_k, \qquad b_k := \bar{B}_k s_k, \qquad \xi_0 = \mathbf{0},$$

where $k$ is the position, $s_k$ is the input, $\xi_k$ is the hidden state, $\bar{A}_k$ is the decay factor, and $\bar{B}_k$ is the input operator. Unrolling this step-by-step gives:

$$\begin{aligned}
\xi_1 &= \bar{A}_1 \cdot \mathbf{0} + b_1 = b_1, \\
\xi_2 &= \bar{A}_2 \xi_1 + b_2 = \bar{A}_2 b_1 + b_2, \\
\xi_3 &= \bar{A}_3 \xi_2 + b_3 = \bar{A}_3 \bar{A}_2 b_1 + \bar{A}_3 b_2 + b_3, \\
&\vdots \\
\xi_k &= \sum_{k'=1}^{k} \left( \prod_{l=k'+1}^{k} \bar{A}_l \right) b_{k'},
\end{aligned}$$

with an empty product equaling 1. The product $\prod_{l=k'+1}^{k} \bar{A}_l$ is the weight with which the input $b_{k'}$ still contributes to the state at position $k$. Each factor $\bar{A}_l = \exp(\Delta_l A) \in (0, 1)$ is a *retention factor*: the fraction of the state that survives one step, from position $l-1$ to position $l$ ($\bar{A}_l = 0.9$ keeps 90% of the state and forgets 10%). An input travelling from position $k'$ to position $k$ is multiplied by one such factor for every step in between, so the share of it that arrives is their product; with a constant $\bar{A} = 0.9$, only $0.9^{10} \approx 0.35$ of it is left after 10 steps. At the start of training, the model's ability to change this factor depending on the input is weak, so the retention factor stays close to a constant baseline, $\bar{A}$. Because it is roughly constant, multiplying it for every step in the gap simplifies to $\bar{A}$ raised to the power of the distance between positions:

$$\prod_{l=k'+1}^{k} \bar{A}_l \approx \bar{A}^{\,k-k'}$$

Under this arrangement, one modality is separated from the next by $C'$ steps, so the information passed between them shrinks by a factor of $\bar{A}^{\,C'}$. Since $\bar{A}$ is a fraction, raising it to a large power like $C'$ shrinks the surviving information to practically zero. To successfully pass information across this gap, the network would have to push $\bar{A}$ incredibly close to 1. However, doing so stops the memory from fading, causing the block to lose its ability to distinguish different positions along the sequence. Furthermore, the gradient signal needed to increase $\bar{A}$ is blocked by this exact same bottleneck.

Compared with arrangements (i) and (ii), the modality-axis scan of Section 2.3.2 has two advantages:

- **The sorting mechanism works:** Because the fusion process is now sensitive to order, the learned permutation actively decides which modalities give context to which. This effect can no longer be bypassed or absorbed by standard network weights.
- **Efficiency gains:** The feature width shrinks to $C'$, which drops the parameter cost from a heavy $\Theta(M^2C'^2)$ down to just $\Theta(C'^2)$. Additionally, the depth of the dependent math operations (the associative scan) drops from $\lceil \log_2 L' \rceil$ to just $\lceil \log_2 M \rceil$, running on a much smaller state.

In the corrected layer (Appendix O), every slot is returned before the heads to the stream it came from. Slot $i$ of the scan holds $\sum_j P_{ij} u_j$, so stream $j$ receives back $\hat{H}_j^{(t)} = \sum_{i=1}^{M} P_{ij} H_i^{(t)}$, i.e. the output is multiplied by $P^\top$, which for a permutation is its inverse. Without this step the layout of the heads' input would change from window to window: under an input-dependent $P$, the part of $H$ that the read-out weights associate with slot 3 would hold, say, the expert's face in one window and the novice's text in the next. With it, part $j$ of $H$ always belongs to stream $j$, and the order influences only the scan, where it is meant to. Finally, the output is stitched back together side-by-side to match the expected format for the final prediction heads:

$$H^{(t)} = \hat{H}_1^{(t)} \circ \cdots \circ \hat{H}_M^{(t)} \in \mathbb{R}^{MC'}$$

which returns the data to its original shape of $H \in \mathbb{R}^{L' \times MC'}$.

# Appendix G Details of the Learned Modality Ordering

## The Order-Sensitivity Problem

Recall from Section 2.3.2 that the inter-modal BiMamba module treats modality identity as its sequence axis, processing at each time step the length-$M$ sequence

$$\big(u_1^{(t)}, u_2^{(t)}, \ldots, u_M^{(t)}\big), \qquad u_i^{(t)} \in \mathbb{R}^{C'},$$

with each modality contributing exactly one position.

The ordering of these positions - audio before video, or video before pose - is chosen arbitrarily by the practitioner; no prior knowledge assigns a canonical rank to distinct measurement modalities. We show that this arbitrariness introduces a structural bias, because selective state-space models are inherently order-sensitive.

Fix a time step $t$, let $s_k \in \mathbb{R}^{C'}$ denote the input at sequence position $k$ - the representation of the modality placed $k$-th - and let $\xi_k$ be the SSM hidden state after position $k$. The Mamba selective SSM [2] defines the recurrence

$$\xi_k = \bar{A}_k(s_k)\, \xi_{k-1} + \bar{B}_k(s_k)\, s_k, \qquad y_k = C_k(s_k)\, \xi_k,$$

where $\xi_0 = \mathbf{0}$ and $\bar{A}_k, \bar{B}_k, C_k$ are input-dependent operators instantiated via the selection mechanism.

**Proposition.** For any SSM with non-trivial state transition (i.e. $\bar{A} \neq I$), the output sequence is not invariant under permutations of the input.

*Proof.* It suffices to consider $M = 2$ and a linear, non-selective SSM with constant operators $\bar{A}, \bar{B}, C$. Under the ordering $(u_1, u_2)$:

$$\xi_1 = \bar{B}\, u_1, \qquad y_2 = C\big(\bar{A}\bar{B}\, u_1 + \bar{B}\, u_2\big)\,.$$

Under the swapped ordering $(u_2, u_1)$:

$$\xi_1' = \bar{B}\, u_2, \qquad y_2' = C\big(\bar{A}\bar{B}\, u_2 + \bar{B}\, u_1\big)\,.$$

The difference is

$$y_2 - y_2' = C\bar{B}(\bar{A} - I)(u_1 - u_2).$$

This vanishes for all $u_1 \neq u_2$ only if $\bar{A} = I$, which degenerates the SSM to a memoryless map and eliminates all temporal memory - contradicting the purpose of state-space modelling. In the selective Mamba SSM, the input-dependent operators $\bar{A}_k(s_k)$ and $\bar{B}_k(s_k)$ introduce additional asymmetric cross-terms that further break permutation symmetry. □

Bidirectionality alone does not resolve the problem. In the inter-modal block the backward pass reverses the modality sequence, so the backward SSM processes the modalities in the order $M, M-1, \ldots, 1$; each modality's

backward hidden state therefore accumulates context from those that follow it in the reversed sequence. The averaged representation

$$H = \frac{h^{\rightarrow} + h^{\leftarrow}}{2}$$

remains order-dependent: both the forward and backward context seen by modality $i$ change qualitatively with its position in the arbitrary input order, so the same physical modality receives a structurally different representation depending solely on where it was placed in that order.

The key intuition behind a learned ordering is that the optimal ordering is itself a function of the data: for a sample in which audio is uninformative, placing it first in the forward SSM pass deposits unreliable context into the hidden states of all subsequent modalities, whereas placing it last confines the contamination to the final position.

## Uniform Channel Projection

Different InitEncoders naturally produce output representations of different widths: for instance, an audio encoder may output $C'_{\text{audio}} = 64$ channels while a video encoder outputs $C'_{\text{video}} = 256$ channels. These *heterogeneous dimensions* prevent treating the modality outputs as interchangeable objects of the same type, which is a prerequisite for learning a permutation over them. To resolve this, a modality-specific affine map $f_i : \mathbb{R}^{C'_i} \to \mathbb{R}^{C'}$, defined by $f_i(v) = W_i^{\text{proj}} v + b_i^{\text{proj}}$ with $W_i^{\text{proj}} \in \mathbb{R}^{C' \times C'_i}$ and $b_i^{\text{proj}} \in \mathbb{R}^{C'}$, is appended to each InitEncoder to linearly project its output into a shared embedding space of dimension $C'$. After this projection, and after the intra-modal module that follows it, $u_i \in \mathbb{R}^{L' \times C'}$ for all $i \in \{1, \ldots, M\}$: all $M$ representations have the same shape, which is what allows them to be treated as interchangeable positions of one sequence and reordered. As with the encoders themselves, the projection is shared between the expert and novice streams of a given feature type.

## Score Matrix

A *meta-network* $\phi$ is a small auxiliary network whose sole purpose is to predict how modalities should be ordered, operating on top of the main feature representations without participating in the primary task of engagement prediction. Concretely, $\phi$ maps the set $\{u_i\}_{i=1}^{M}$ to an $M \times M$ assignment *score* matrix $Z \in \mathbb{R}^{M \times M}$, where the entry $Z_{ij}$ quantifies the fitness of placing modality $j$ at sequence position $i$ in the inter-modal BiMamba: a large value of $Z_{ij}$ means the meta-network believes modality $j$ should be processed at step $i$. Row $i$ of $Z$ therefore asks how well each stream fits position $i$, and column $j$ how well stream $j$ fits each position: rows and columns index different kinds of objects. Our first formulation used a query computed from the data, $q_i = W_Q \, \bar{u}_i$, so that $Z_{ij} = q_i^{\top} k_j$ compared stream $i$ with stream $j$ and contained no notion of position at all; it also made the result depend on how the streams are numbered (see below). The division by $\sqrt{d_s}$ keeps the scores at a magnitude independent of $d_s$, as in scaled dot-product attention. It matters here because $Z$ is next divided by the annealing temperature $\tau$: an unscaled score of large magnitude has the same effect as a small $\tau$ and drives the Sinkhorn output towards a hard assignment before the annealing schedule intends it to. Both changes are evaluated in Appendix O.

## Gumbel Perturbation

The Gumbel distribution is classically used in extreme value theory [5] to model the asymptotic distribution of the maximum of a sequence of independent and identically distributed random variables. Its probability density function for location $\mu$ and scale $\beta$ is given by:

$$f(x) = \frac{1}{\beta} e^{-(x-\mu)/\beta} e^{-e^{-(x-\mu)/\beta}}$$

In deep learning, the Gumbel-Max trick [4] leverages this distribution to draw discrete samples from a categorical distribution in a fully differentiable manner. By adding independent Gumbel noise to unnormalized log-probabilities (scores), the deterministic argmax of these perturbed values becomes mathematically equivalent to drawing a sample from the true underlying multinomial distribution.

To generate standard Gumbel noise ($\mu = 0, \beta = 1$) programmatically, we apply inverse transform sampling. This technique maps a standard uniform random variable to a target distribution by passing it through the inverse of that target's cumulative distribution function (CDF). Given that the standard Gumbel CDF is $F(x) = e^{-e^{-x}}$, setting a uniform random variable $U \sim \text{Uniform}(0, 1)$ equal to $F(x)$ and solving explicitly for $x$ yields the inverse mapping $x = -\ln(-\ln U)$. In practice $U$ is drawn from the open interval $(\epsilon, 1 - \epsilon)$ with $\epsilon = 10^{-6}$, since the double logarithm diverges at both endpoints.

The temperature $\tau$ is annealed over the course of training to progressively concentrate probability mass towards a single hard permutation.

## Sinkhorn Normalisation

The **Birkhoff-von Neumann theorem** [6] establishes that the set of doubly-stochastic matrices (square matrices with non-negative real entries whose rows and columns each sum to exactly 1) constitutes a convex polytope whose extreme points are precisely the set of discrete permutation matrices. Geometrically, a convex polytope is a bounded, multi-dimensional solid defined by flat facets, and its extreme points represent its absolute vertices. Because any interior point of a convex polytope can be expressed uniquely as a convex combination (a weighted average) of its vertices, any doubly-stochastic matrix can be decomposed into a convex combination of hard permutation matrices. This structural property makes the Birkhoff polytope a mathematically principled continuous relaxation of discrete permutations.

A standard Softmax operator is insufficient in this context because it operates independently across a single dimension, ensuring only that the rows sum to 1 (yielding a row-stochastic matrix). In an inter-modal fusion framework where rows represent sequence positions and columns map to distinct modalities, a row-stochastic matrix introduces severe structural redundancies. It permits multiple sequence positions to concurrently assign high probability mass to the exact same dominant modality column (such as audio), which causes the network to attend to duplicate representations while completely suppressing and ignoring other available modalities.

Constraining both rows and columns to sum to 1 eliminates this issue by enforcing a strict continuous one-to-one assignment map. Following [3], the doubly-stochastic matrix $P$ is obtained by the iterative Sinkhorn-Knopp algorithm, which alternates row and column normalisation of $\exp(\tilde{Z})$ until convergence.

**Log-domain implementation.** We do *not* evaluate $\exp(\tilde{Z})$ explicitly. With real feature magnitudes the scores of our first, unscaled formulation reached $10^4$–$10^5$, and nothing bounds the scaled scores during training either, so $\exp(\tilde{Z})$ overflows to $+\infty$ in single precision; the subsequent row normalisation then computes $\infty/\infty$ and returns NaN, which propagates through the entire network and destroys training. We therefore carry out the alternating normalisation entirely in log-space.

The operation that replaces division is the *log-sum-exp*, defined for a finite set of reals $\{x_1, \ldots, x_n\}$ as

$$\operatorname*{logsumexp}_j x_j \;:=\; \log \sum_{j=1}^{n} \exp(x_j),$$

that is, the logarithm of the sum of the exponentials. Its role here follows from a single identity. If a set of quantities is held in logarithmic form, $x_j = \log p_j$, then normalising them to sum to one, $p_j \mapsto p_j / \sum_{j'} p_{j'}$, becomes in logarithms

$$\begin{aligned} \log\left(\frac{p_j}{\sum_{j'} p_{j'}}\right) &= \log p_j - \log \sum_{j'} p_{j'} \\ &= x_j - \operatorname*{logsumexp}_{j'} x_{j'}. \end{aligned}$$

A normalisation is therefore a *subtraction* in log-space, never a division, and the sums themselves are never formed. Crucially, log-sum-exp is evaluated by first factoring out the largest element, $m = \max_j x_j$,

$$\operatorname*{logsumexp}_j x_j = m + \log \sum_j \exp(x_j - m),$$

which is algebraically exact and guarantees every exponential argument is non-positive, so no term can exceed 1 and overflow cannot occur regardless of how large the $x_j$ become.

Writing $\log Q^{(k)}$ for the matrix obtained after the row pass of iteration $k$, and $\log P^{(k+1)}$ for the result after the subsequent column pass, the scheme is the one given in Section 2.4. The first update normalises each row (the inner index runs over columns $j'$), the second normalises each column (the inner index runs over rows $i'$); $Q^{(k)}$ is simply the intermediate that is row-stochastic but not yet column-stochastic, and it is discarded once the column pass consumes it. Alternating the two passes is what drives the matrix towards satisfying both constraints at once.

This is algebraically identical to Sinkhorn-Knopp on $\exp(\tilde{Z})$ - each step divides by a row or column sum, which by the identity above is a subtraction of its logarithm - but the largest intermediate quantity is $\max_j \tilde{Z}_{ij}$ rather than $\exp(\max_j \tilde{Z}_{ij})$. The exponential map is applied once, at the end, to values that are by construction non-positive log-probabilities, so the returned entries lie in $(0, 1]$ and the gradient operator $\partial P / \partial Z$ remains well-conditioned throughout optimisation.

The number of iterations matters. Sinkhorn-Knopp reaches a doubly-stochastic matrix only in the limit; after finitely many iterations the result satisfies exactly only the constraint of its last pass, here the columns. With $n_{\text{iter}} = 10$ and unscaled scores, the rows of the learned $P$ summed to between 0.6 and 2.0 (Appendix O), so some

positions received about two streams and others about half of one. The corrected layer therefore uses $n_{\text{iter}} = 50$ and check the row and column sums of the learned $P$ on the validation windows.

### Soft Reordering

With $P$ computed as above, the permuted representation for position $i$ is the $P$-weighted convex combination of all intra-modal outputs. Concretely, the $i$-th row of $P$, denoted $P_{i\cdot} = (P_{i1}, \ldots, P_{iM})$, defines a probability distribution over the $M$ modalities; since $P$ is doubly-stochastic, we have $P_{ij} \geq 0$ and $\sum_j P_{ij} = 1$ for every $i$. The entry $P_{ij} \in [0, 1]$ is the soft probability that modality $j$ is assigned to position $i$ in the inter-modal sequence; when $P$ is close to a hard permutation matrix (as happens after temperature annealing), exactly one $P_{ij}$ per row will be close to 1 and the rest close to 0, recovering a near-discrete assignment. At every time step $t$ the inter-modal BiMamba then processes the reordered sequence $\left(\tilde{u}_1^{(t)}, \ldots, \tilde{u}_M^{(t)}\right)$ instead of $\left(u_1^{(t)}, \ldots, u_M^{(t)}\right)$; all equations of Section 2.3.2 remain unchanged under this substitution. Note that $P$ is computed per sample: the ordering is input-dependent, so different sessions may resolve to different modality orderings.

### Inference

The model is run at the temperature of the epoch whose checkpoint is used, not at $\tau_\infty$: the checkpoint was trained and selected at that temperature, and a lower one would produce a sharper $P$ than the model has ever seen. In our first implementation inference always used $\tau_\infty$, although training stops early and the selected epoch $e$ has $\tau = 0.95^{\,e-1}$, for example 0.63 at epoch 10.

### Dependence on the Input Numbering

With one query per position, renumbering the streams by a permutation $\rho$ renumbers only the columns of $Z$: $Z' = ZR^\top$, where $R$ is the permutation matrix of $\rho$. Sinkhorn normalisation commutes with this, so $P' = PR^\top$, and the reordered sequence $\tilde{u}'_i = \sum_j P'_{ij} u'_j = \sum_j P_{ij} u_j = \tilde{u}_i$ is exactly the same, for the soft $P$ and at every temperature: the inter-modal BiMamba receives the same physical order of streams however they are numbered. Our first, stream-query formulation lacked this property. There the query of row $i$ was computed from stream $i$, so a renumbering renumbered the rows as well, $Z' = RZR^\top$, and the reordered sequence came out renumbered by $\rho$.

## Appendix H Why Predictive Variance is a Monotonic Proxy for Differential Entropy at a Fixed Mean

The choice of the predictive variance as $U(x)$ (Section 2.6) is justified because variance is a *strictly monotonic* function of the differential entropy $H(p)$ of the Beta distribution. To see this explicitly, re-parameterise the Beta distribution by its mean and concentration:

$$\mu = \frac{\hat{\alpha}}{\hat{\alpha} + \hat{\beta}}, \qquad \kappa = \hat{\alpha} + \hat{\beta}.$$

Substituting these parameters yields the simple expression

$$U(x) = \frac{\mu(1-\mu)}{\kappa + 1}.$$

For any fixed mean $\mu \in (0, 1)$, the partial derivative

$$\frac{\partial U}{\partial \kappa} = -\frac{\mu(1-\mu)}{(\kappa+1)^2} < 0$$

shows that variance is strictly decreasing in $\kappa$: larger concentration $\kappa$ produces a tighter distribution and therefore smaller variance.

The differential entropy of the Beta distribution has the closed-form expression

$$\begin{aligned} H(p) = \ln B(\hat{\alpha}, \hat{\beta}) - (\hat{\alpha} - 1)\psi(\hat{\alpha}) - (\hat{\beta} - 1)\psi(\hat{\beta}) \\ + (\hat{\alpha} + \hat{\beta} - 2)\psi(\hat{\alpha} + \hat{\beta}), \end{aligned}$$

where $B(\cdot, \cdot)$ is the Beta function and $\psi(\cdot)$ is the digamma function. Substituting the same re-parameterisation $\hat{\alpha} = \mu\kappa$, $\hat{\beta} = (1 - \mu)\kappa$ and taking the derivative with respect to $\kappa$ likewise yields

$$\frac{\partial H}{\partial \kappa} < 0$$

for any fixed $\mu \in (0,1)$. Thus both $U(x)$ and $H(p)$ are strictly decreasing functions of $\kappa$: larger concentration (tighter distribution) produces both smaller variance *and* smaller differential entropy. Consequently, for predictions with the same mean, ranking by variance and ranking by differential entropy give exactly the same order.

The argument holds only at a fixed mean. Across different means the two measures can disagree: Beta$(1.5, 7)$ (mean 0.18) has the larger variance, 0.0153 against 0.0122, but the smaller entropy, $-0.825$ against $-0.787$, compared with Beta$(9.5, 10)$ (mean 0.49). Among randomly drawn pairs of Beta distributions with $\alpha, \beta > 1$, about 5% are ordered differently by the two measures. Variance is therefore a cheap proxy that agrees with differential entropy on how concentrated a prediction is at a given engagement level, not an exact substitute for it.

Variance is numerically stable because its formula consists only of basic arithmetic operations (no logarithms, no digamma or Gamma functions, and no risk of underflow when $\hat{\alpha}$ or $\hat{\beta}$ become large). It is boundary-aware: $\lim_{\mu \to 0^+} U = 0$ and $\lim_{\mu \to 1^-} U = 0$, which matches the intuition that a prediction that is certain to be near the extremes of engagement (fully disengaged or fully engaged) should carry low uncertainty. Finally, variance is already required for the Beta negative log-likelihood (Beta NLL) loss used during training:

$$\begin{aligned}\mathcal{L}_{\mathrm{NLL}}(x, y) = -[&(\hat{\alpha} - 1) \ln y + (\hat{\beta} - 1) \ln(1 - y) \\ &- \ln B(\hat{\alpha}, \hat{\beta})].\end{aligned}$$

Because the variance appears directly in the predictive distribution (and therefore in every forward pass), it incurs no extra computation at inference time. All these properties make variance the natural, cheap uncertainty proxy for regression.

# Appendix I Architectural Justification for the Beta Regression Framework

**Why not a Gaussian.** While a Gaussian assumption $p(y|x) = \mathcal{N}(\mu, \sigma^2)$ simplifies the differential entropy to $H(y) = \frac{1}{2}\ln(2\pi e\sigma^2)$, it is fundamentally inappropriate for engagement modeling. Engagement scores are strictly bounded within the interval $[0, 1]$. A Gaussian distribution assigns non-zero probability mass to values in $(-\infty, 0)$ and $(1, \infty)$, leading to "probability leakage" and poor calibration near the boundaries.

**Shared hidden layer.** Both read-outs of the Beta head (Section 2.5) consume the *same* $v$: the hidden layer extracts one shared intermediate feature from which the two shape parameters are then predicted independently. This lets $\alpha$ and $\beta$ draw on common structure - both describe the same predictive distribution - while still being free to move in opposite directions, which is what allows the head to represent "high mean, low variance" and "high mean, high variance" as distinct outputs.

**Why the offset of 1.** The softplus, $\ln(1 + e^z)$, maps any real number to a positive one, which is all a Beta distribution formally requires ($\alpha, \beta > 0$). The added 1 goes further: since softplus is strictly positive, it guarantees $\alpha, \beta > 1$. The reason is the shape of the Beta density on either side of 1. With $\alpha, \beta > 1$ the density is zero at both ends of $[0, 1]$ and has a single peak inside, at $(\alpha - 1)/(\alpha + \beta - 2)$; it says "engagement is probably around here", which is the kind of answer we want, and its mean and variance describe a best guess and the spread around it. If $\alpha < 1$, the density instead grows without bound as $y \to 0$ (and likewise at 1 if $\beta < 1$); with both below 1 it is U-shaped, piling its probability onto the two extremes and making the middle of the scale the *least* likely region. Such a prediction is useless as a point estimate: its mean $\alpha/(\alpha + \beta)$ lies exactly where the distribution itself expects the target least, and its variance no longer measures the spread around a single best guess - yet that is how both $\hat{\mu}$ and $\mathrm{Var}[y]$ are used in Section 2.5 and in test-time adaptation. The unbounded densities would also be an easy way to gain likelihood: some annotations lie very close to 0 or 1 (see target clipping below), and on those frames a model could raise the likelihood without limit by pushing $\alpha$ or $\beta$ below 1. The offset rules all of this out by construction. As a side effect, $\alpha + \beta > 2$ caps the predictive variance at $\mu(1 - \mu)/3 \leq 1/12$, the variance of the uniform distribution on $[0, 1]$: the least certain prediction the model can make is "every engagement level is equally likely".

**Boundary-aware variance.** The Beta variance is naturally boundary-aware, satisfying:

$$\lim_{\hat{\mu}\to 0} \mathrm{Var}[y] = 0 \quad \text{and} \quad \lim_{\hat{\mu}\to 1} \mathrm{Var}[y] = 0$$

This provides a principled measure of confidence that scales with the proximity to the interval limits.

**Target clipping.** Taking the logarithm of the Beta density above gives

$$\ln p(y \mid \alpha, \beta) = (\alpha - 1)\ln y + (\beta - 1)\ln(1 - y) - \ln B(\alpha, \beta),$$

so the log-likelihood contains the terms $\ln y$ and $\ln(1-y)$ explicitly. Both diverge at the endpoints of the support: $\ln y \to -\infty$ as $y \to 0^+$, and $\ln(1-y) \to -\infty$ as $y \to 1^-$. The engagement annotations do attain exactly 0 and 1, at which points the expression is undefined and evaluates to `-inf` or `NaN` in floating-point arithmetic - a single such frame is enough to corrupt the gradient of the entire batch. Targets are therefore clipped to $[\varepsilon, 1 - \varepsilon]$ with $\varepsilon = 10^{-6}$ before the likelihood is evaluated. This is a numerical safeguard only: it moves an affected target by $10^{-6}$ on a scale of $[0, 1]$, which is four orders of magnitude below the resolution at which human annotators can meaningfully distinguish engagement levels.

To model bounded continuous engagement levels $y \in [0, 1]$ alongside reliable predictive uncertainty, several alternative statistical formulations could be considered: the Kumaraswamy distribution, logit-normal regression, and distribution-free conformalized regression. In this section, we mathematically demonstrate why the Beta distribution is uniquely suited to meet the real-time constraints, closed-form requirement, and test-time adaptation (TTA) mechanics of EngageNet.

## Comparison with the Kumaraswamy Distribution

The Kumaraswamy distribution [8] is often preferred over the Beta distribution in standard deep learning tasks [9] because its probability density function and cumulative distribution function rely strictly on elementary algebraic powers, avoiding transcendental functions. For shape parameters $a, b > 0$, its CDF is $F(x; a, b) = 1 - (1 - x^a)^b$. This formulation simplifies the calculation of the Negative Log-Likelihood (NLL) during training and avoids computing digamma and trigamma functions during backpropagation, circumventing the gradient instabilities that cause the Variance Starvation Problem (VSP).

However, EngageNet's TTA selection filter $S(x)$ evaluates the predictive variance $U(x)$ at *inference time* on every incoming frame of a non-stationary data stream. The $n$-th raw moment of a Kumaraswamy random variable $Y$

is given by:

$$\mathbb{E}[Y^n] = b \cdot B\left(1 + \frac{n}{a}, b\right) = \frac{b\,\Gamma(1 + n/a)\,\Gamma(b)}{\Gamma(1 + n/a + b)}$$

where $B(\cdot, \cdot)$ is the transcendental Beta function and $\Gamma(\cdot)$ is the Gamma function. Consequently, the predictive variance of the Kumaraswamy distribution is expressed as:

$$\mathrm{Var}[Y] = b \cdot B\left(1 + \frac{2}{a}, b\right) - \left[b \cdot B\left(1 + \frac{1}{a}, b\right)\right]^2$$

If EngageNet adopted the Kumaraswamy distribution, the model would be forced to compute multiple expensive Gamma and Beta functions during real-time streaming inference to evaluate the TTA filter. In contrast, the Beta distribution shifts this transcendental computational burden entirely to the offline training phase via the polygamma functions in the backward pass. Its inference-time predictive variance $U(x)$ is computed via lightweight, pure algebraic operations:

$$U(x) = \frac{\alpha\beta}{(\alpha + \beta)^2(\alpha + \beta + 1)}$$

Furthermore, proving a strictly monotonic relationship between the variance $\mathrm{Var}[Y]$ and the differential entropy $H(Y)$ under arbitrary parameter updates is mathematically intractable for the Kumaraswamy distribution, whereas the Beta distribution cleanly satisfies $\frac{\partial U}{\partial \kappa} < 0$ and $\frac{\partial H}{\partial \kappa} < 0$ under the precision mapping $\kappa = \alpha + \beta$.

## Comparison with Logit-Normal Regression

Logit-normal regression maps the bounded domain $y \in [0, 1]$ to an unbounded latent domain $z \in \mathbb{R}$ using the logit transformation, assuming the latent variable follows a Gaussian distribution:

$$z = \mathrm{logit}(y) = \ln\left(\frac{y}{1 - y}\right) \sim \mathcal{N}(\mu, \sigma^2)$$

While the latent Gaussian log-likelihood is highly stable to optimize during training, the moments of the resulting logit-normal variable do not exist in closed form. The true predictive mean and variance must be resolved via numerical integration:

$$\mathbb{E}[Y] = \int_0^1 \frac{1}{y(1 - y)\sigma\sqrt{2\pi}} \exp\left(-\frac{(\mathrm{logit}(y) - \mu)^2}{2\sigma^2}\right) \cdot y\, dy$$

Performing numerical integration over $N$ categories across multiple unimodal branches for every incoming frame introduces an insurmountable latency bottleneck during real-time test-time adaptation.

Crucially, EngageNet utilizes an inter-modal information sharing loss ($\mathcal{L}_{mis}$) that minimizes the Kullback-Leibler (KL) divergence between the unimodal predictions and the fused network prediction. While computing the KL divergence between two latent Gaussians in logit space is trivial, minimizing it optimizes a distorted geometry that stretches gradients to infinity near the boundaries (0 and 1). Computing the exact KL divergence between two true logit-normal densities within the probability domain $[0, 1]$ lacks an analytical closed-form expression [7]. Because the Beta distribution possesses a known analytical KL divergence 1, it provides a stable, exact, and geometry-preserving target for cross-modal alignment.

## Comparison with Conformalized Regression

Conformalized regression (or Conformal Prediction) [10] offers a distribution-free, non-parametric framework that provides a valid prediction interval $[\hat{y} - q, \hat{y} + q]$ satisfying a user-defined coverage guarantee $1 - \alpha$. While mathematically robust, conformal prediction fundamentally requires the data stream to satisfy the property of exchangeability.

In streaming test-time adaptation settings, the user exhibits non-stationary distribution shifts (e.g., sensor degradation, fluctuating lighting conditions, or progressive fatigue). This explicitly violates the exchangeability assumption, causing the empirical quantile threshold $q$ computed on a static source calibration set to lose its strict coverage guarantees. While online adaptive variants (such as Adaptive Conformal Inference) [11] can dynamically scale the interval width based on sequential coverage errors, they operate as reactive heuristic controllers rather than generative models of the target density.

Most importantly, conformal prediction produces a discrete boundary region rather than a smooth, parametric probability density function. Because it is non-differentiable, it cannot supply a gradient operator to back-propagate local self-supervised likelihood updates ($\mathcal{L}_{TTA}$) during a single-frame backward pass. It also cannot participate in information-theoretic objectives like the mutual information sharing loss ($\mathcal{L}_{mis}$). Thus, while conformal regression is excellent for post-hoc uncertainty visualization, it cannot serve as the active functional engine that drives online weight updates within an adaptive neural network architecture.

# Appendix J Details of Test-Time Adaptation

**What $U(x)$ is, intuitively.** In the original BiMamba-TTA formulation [1], $U(x)$ is the model's own admission of how unsure it is about the sample $x$. Test data carries no labels, so the model cannot know which of its predictions are correct; $U(x)$ is the next best thing, a self-assessment used to decide which unlabelled windows are trustworthy enough to learn from. Low $U(x)$ means the predictive distribution is sharply peaked - the model is committing to an answer - and such frames make safe pseudo-labels. High $U(x)$ means the distribution is spread out and the prediction is close to a guess; adapting on those would teach the model its own noise.

**Why variance.** For classification, $U(x)$ is the Shannon entropy of the softmax output, a direct measure of how spread the predicted distribution is. Regression has no softmax, so the natural generalisation is the differential entropy $H(p)$ of the predictive density - but for a Beta distribution $H(p)$ requires the log-Beta function and two digamma evaluations per frame, which is the transcendental cost we are trying to avoid in a real-time streaming filter.

The way out is to notice what the filter actually does with $U(x)$. It never uses the value of $U(x)$ on its own; it only asks whether a window's uncertainty is higher or lower than that of the other windows in the same batch (below). Any measure that puts the windows in the same order - from most to least uncertain - therefore selects exactly the same windows as $H(p)$, and we are free to choose the cheapest such measure. This reframes the problem from "compute the entropy" to "find the cheapest quantity that ranks windows the same way", and the predictive variance is the obvious first candidate: it is the standard measure of spread, it is already available in closed form from the shape parameters the network emits, and it costs four arithmetic operations. Appendix H examines how far it does rank them the same way.

**Adaptive thresholds.** To handle non-stationary streaming data (i.e., test-time engagement signals that arrive continuously and whose statistical distribution drifts over time due to fatigue, cultural differences, sensor drift, etc.), the thresholds are not fixed but recomputed for every inference batch $\mathcal{W}$ of $B_{\text{inf}}$ consecutive windows from one session:

$$\gamma_m = \text{Quantile}_{q_m}\Big(\{U_{\text{multi}}(x)\}_{x\in\mathcal{W}}\Big),$$
$$\gamma_u = \text{Quantile}_{q_u}\Big(\Big\{\tfrac{1}{M}\textstyle\sum_i U_i(x)\Big\}_{x\in\mathcal{W}}\Big),$$

with $q_m = 0.3$, $q_u = 0.7$ and $B_{\text{inf}} = 16$. $\text{Quantile}_q$ of a set of numbers is the value below which a fraction $q$ of them lies. With $q_m = 0.3$, $\gamma_m$ is the 30th percentile of the fused-head uncertainties in the batch, so the first condition, $U_{\text{multi}}(x) < \gamma_m$, keeps the 30% of windows on which the multimodal head is *most* confident (five of the 16). With $q_u = 0.7$, $\gamma_u$ is the 70th percentile of the averaged unimodal uncertainties, so the second condition keeps the 30% of windows on which the unimodal heads are *least* confident. A window is used for adaptation only if it belongs to both groups. If the two uncertainties were unrelated, about $0.3 \times 0.3 = 9\%$ of the windows would qualify; in practice it was 2 to 6% (Section 3). Presumably the fused and the unimodal uncertainties tend to rise and fall together, which makes the joint condition rare, although we have not measured this correlation.

The thresholds are computed afresh for every batch, from that batch's own $B_{\text{inf}}$ windows rather than from a running history. With 10 s windows and a 5 s window hop, one batch covers about 85 s of the interaction, so the thresholds follow drift within a session while selection and update run as one batched operation. Here "non-stationary streaming data" means the incoming test distribution is not fixed but changes gradually; recomputing the thresholds on every batch tracks this drift. The batch must contain several windows: batches with fewer than four windows (the last, partial batch of a session) are left unadapted.

The quantile levels make the thresholds *relative rather than absolute*. A fixed cutoff such as $U(x) \leq 0.02$ would be meaningless across domains: a model that is uniformly less certain on Japanese sessions than on English ones would have every frame rejected on one corpus and every frame accepted on the other, purely because its overall uncertainty level shifted. By setting the thresholds to quantiles of the uncertainties in the current batch, "confident" is redefined at each moment to mean *confident by the standards of what this model is currently producing on this stream*, and the filter keeps selecting a stable fraction of windows regardless of the absolute uncertainty level. Percentiles are used rather than the mean and standard deviation because they are order

statistics and therefore insensitive to the occasional extreme value - a few corrupted frames shift a percentile barely at all, whereas they can move a mean arbitrarily far.

**Kinds of uncertainty.** Uncertainty is formally quantified as the variance of the predictive distribution. Two kinds are usually distinguished. *Aleatoric* uncertainty is noise in the data itself: annotators disagree, behaviour is ambiguous, a face is partly out of frame. More training data would not remove it. *Epistemic* uncertainty is the model's own lack of knowledge: it is large on inputs unlike those seen in training - for example, recordings from a different corpus or culture - and shrinks as the model sees more data. Section 2.6 uses two measures, the parametric Beta variance and the total uncertainty of MC dropout; a third, MC dropout alone, is described below. They do *not* each capture both kinds: the parametric Beta variance measures only aleatoric uncertainty, MC dropout alone only epistemic uncertainty, and the total uncertainty is their sum. All three are expressed in terms of the Beta predictive distribution $p(y \mid x) = \mathrm{Beta}(\hat{\alpha}(x), \hat{\beta}(x))$. MC dropout alone is not used on its own.

**Parametric Beta.** The parametric Beta variance measures only aleatoric uncertainty: a single network with fixed weights can express how noisy it expects the target to be for a given input, but it has no means of expressing doubt about its own weights, and on an input unlike anything seen in training it can be confidently wrong.

**MC dropout alone (epistemic uncertainty).** With the $T$ passes of Section 2.6, the epistemic uncertainty is the variance of the means:

$$U_{\mathrm{epi}}(x) = \frac{1}{T} \sum_{t=1}^{T} \big(\hat{\mu}^{(t)}(x) - \bar{\mu}(x)\big)^2,$$

where $\bar{\mu}(x) = \frac{1}{T} \sum_{t=1}^{T} \hat{\mu}^{(t)}(x)$. This term quantifies the model's "lack of knowledge" (how sensitive the prediction is to random weight masks) and is especially useful under distribution shift (NoXi → NoXi+J). It measures only epistemic uncertainty: it looks at how much the means of the $T$ passes disagree with each other and ignores how wide each pass's own distribution is.

**Total uncertainty.** It captures both kinds because the law of total variance splits the variance of the mixture of the $T$ predicted distributions exactly into these two parts. The decomposition is mainly used as a diagnostic to monitor whether the shift is mostly epistemic. The law of total variance guarantees that $U_{\mathrm{total}}$ is the correct variance of the mixture distribution induced by MC dropout.

**Implementation of MC dropout.** Dropout with rate $p$ sits before both dense layers of every Beta head, multimodal and unimodal; the rest of the network is unchanged, and without dropout the model is exactly the one described above. At inference, $T$ passes are run with dropout active and batch normalisation in evaluation mode; the prediction is then the mean $\bar{\mu}(x)$ of the $T$ means, and the filter uses $U_{\mathrm{total}}$. With a single deterministic pass the filter uses the parametric Beta variance, as in all earlier runs. Results are in Appendix Q: neither the averaging over passes nor the total-variance filter changes the scores.

**Beta KL divergence.** The closed-form KL divergence between two Beta distributions used in $\mathcal{L}_{\mathrm{mis}}$ (Section 2.9), with $B_i := B(\alpha_i, \beta_i)$, is:

$$\begin{aligned} D_{\mathrm{KL}}(B_1 \parallel B_2) = \ln \frac{B(\alpha_2, \beta_2)}{B(\alpha_1, \beta_1)} &+ (\alpha_1 - \alpha_2)\psi(\alpha_1) \\ &+ (\beta_1 - \beta_2)\psi(\beta_1) \\ &+ (\alpha_2 - \alpha_1 + \beta_2 - \beta_1)\psi(\alpha_1 + \beta_1) \end{aligned} \tag{1}$$

**Adaptation step.** A larger $\lambda$ emphasises direct supervision from the multimodal teacher, while smaller $\lambda$ puts more weight on cross-modal consistency. Each role's multimodal head teaches only the unimodal heads that read that role's streams, and both loss terms of Section 2.9 are averaged over the frames of the *selected* windows only,

$$\mathcal{L}_{TTA}(\mathcal{W}) = \frac{\sum_{x \in \mathcal{W}} S(x)\, \ell_{TTA}(x)}{\sum_{x \in \mathcal{W}} S(x)},$$

where $\ell_{TTA}(x)$ is the loss above evaluated on window $x$; windows with $S(x) = 0$ contribute nothing. The pseudo-label $\hat{\mu}_{\mathrm{multi}}$ is treated as a constant (no gradient flows into the teacher through it), whereas the MIS term acts on both heads. Gumbel noise is switched off during adaptation, and batch normalisation uses the statistics of the current batch for the update step. After the update, the predictions for the batch are recomputed in evaluation mode with the adapted weights, so every output reflects the adaptation it triggered. Adaptation is episodic: parameters and optimiser state are reset to the trained model at the start of every session. The update is a single Adam step with learning rate $\eta_{\mathrm{TTA}}$ per batch.

**Surgical layers.** BatchNorm layers encode per-channel activation statistics, allowing for immediate adaptation to domain shifts. The first convolution in the InitEncoder re-calibrates low-level feature extraction (e.g., sensor noise) before temporal/modal mixing. The first FC layer in the inter-modal BiMamba recalibrates cross-modal

fusion (e.g., adjusting the weight of audio vs. visual cues for different cultures). The adaptation uses its own optimiser for this purpose - Adam on the surgical layers and an identically zero update elsewhere - because masking only the gradients under the training optimiser would still let its weight decay move the frozen weights.

The word *surgical* refers to the choice of layers, not to their size. In the core configuration (Section 3.1) the listed layers hold 1.20M of the model's 2.06M parameters, almost all of them in the first convolutions of the widest streams, so by parameter count the adaptation touches the majority of the network.

This surgical approach mitigates the **Variance Starvation Problem (VSP)**. In VSP, a model minimises the Beta NLL by artificially inflating $\mathrm{Var}[y]$ (i.e., reducing the concentration $\kappa = \hat{\alpha} + \hat{\beta}$) on hard samples; the gradient to the mean head then vanishes because the loss term becomes insensitive to prediction error. By freezing the majority of the backbone and updating only the listed surgical layers, we force the model to improve genuine feature alignment rather than using uncertainty as a "slack variable" to bypass difficult data.

# Appendix K Details of the Evaluation Metrics

## Combined Score

Following the challenge protocol [13], the headline score is the **unweighted mean CCC across the four held-out test sets** - NoXi, NoXi+J, NoXi (Additional Languages), and MPIIGroupInteraction:

$$\mathrm{CCC}_{\mathrm{combined}} = \frac{1}{4} \sum_{d \in \mathcal{D}} \mathrm{CCC}_d,$$

$$\mathcal{D} = \{\mathrm{NoXi},\ \mathrm{NoXi{+}J},\ \mathrm{NoXi\text{-}Add},\ \mathrm{MPIIGI}\}.$$

Because every test set enters with the same weight $\frac{1}{4}$, each counts equally, however many sessions or frames it contains - unlike a score pooled over all frames, in which the largest test set would dominate and a poor result on a small one would barely register. Within the mean, the scores of different test sets do offset each other one-to-one: 0.8 on NoXi and 0.2 on NoXi+J (with the other two scores fixed) give the same combined score as 0.5 on both. MultiMediate'26 additionally reports a global score that adds PInSoRo, a classification task with categorical ground truth, with weight $\frac{1}{3}$ and gives each of the four sets above $\frac{1}{6}$.

## Interpreting the Correlation Ceiling

The first factor of the decomposition in Section 2.7 measures whether the prediction moves together with the target: whether frames that are more engaged than others also receive higher predictions than those others, so that the predicted curve rises and falls where the true one does. When this holds we say that the prediction *orders* the target well. (Strictly, the Pearson correlation measures linear agreement rather than rank order; we use "ordering" loosely for it.) The second factor measures whether the prediction's level and spread *match* those of the target.

The names come from measurement. An instrument is precise when its readings are consistent with each other; correspondingly, $\rho$ is high when the predictions follow the ups and downs of the target closely, even if all of them are shifted or stretched by the same amount. An instrument is accurate when its readings are centred on the true value; correspondingly, $C_b$ equals 1 when the predictions have the target's mean and spread, however well or badly they follow its ups and downs.

**Implication.** No shifting or stretching of the predictions after training can push the CCC above $\rho$. Matching the predictions' mean and standard deviation to those of the target brings $C_b$ to 1, but it leaves $\rho$ unchanged, because $\rho$ only depends on whether the predictions go up and down together with the target. Once a model's predictions have roughly the right level and spread, the only way to improve further is therefore to raise $\rho$: to get better at telling more engaged moments from less engaged ones. This is why the architecture gives the model a longer memory (Section 2.3.1) and lets the modalities actually exchange information (Section 2.3.2), and why the training objective adds a CCC term to the frame-by-frame likelihood (Section 2.8).

## Conditional Demographic Disparity (CDD)

To quantify fairness across demographic groups we adopt the Conditional Demographic Disparity [14, 13], which asks whether, *at the same ground-truth engagement level*, the model systematically over- or under-predicts for one group relative to another. Conditioning on $y$ is what distinguishes CDD from a raw demographic-parity gap: it separates genuine model bias from legitimate differences in the underlying engagement distributions of the groups.

For gender,

$$\mathrm{CDD}_G = \mathbb{E}\big[\hat{y} \,\big|\, \text{male},\, y\big] - \mathbb{E}\big[\hat{y} \,\big|\, \text{female},\, y\big],$$

where positive values indicate higher predictions for males than for females at the same $y$, and negative values the reverse. For language, each language $L$ is compared against the pooled expectation across all languages at the same $y$:

$$\mathrm{CDD}_L = \mathbb{E}\big[\hat{y} \,\big|\, L,\, y\big] - \mathbb{E}\big[\hat{y} \,\big|\, y\big].$$

Both quantities are **signed** and centred at 0; values closer to zero indicate smaller disparity, and the sign indicates the direction of the bias. This is a substantive difference from an absolute-value formulation: the sign carries the information about *which* group is favoured, and averaging absolute values across groups would discard it.

**Estimation.** Since $y$ is continuous, the conditional expectations are approximated by binning the ground truth into $n_b$ equal-frequency (quantile) bins and averaging the within-bin group differences, weighted by bin prevalence:

$$\widehat{\mathrm{CDD}} = \frac{\sum_{b=1}^{n_b} |\mathcal{B}_b| \cdot \big(\bar{\hat{y}}_b^{\,A} - \bar{\hat{y}}_b^{\,B}\big)}{\sum_{b=1}^{n_b} |\mathcal{B}_b|},$$

where $\mathcal{B}_b$ is the set of frames whose target falls in bin $b$, and $\bar{\hat{y}}_b^{\,A}, \bar{\hat{y}}_b^{\,B}$ are the mean predictions of the two groups within that bin. Bins in which either group is unrepresented are skipped, since no comparison is defined there. We use $n_b = 10$.

**Applicability.** $\mathrm{CDD}_G$ requires exactly two gender codes to be present in the evaluated split, and $\mathrm{CDD}_L$ requires at least two languages; where a split does not satisfy these conditions the corresponding metric is undefined and is reported as such rather than as zero. Note also that the sign of $\mathrm{CDD}_G$ depends on which annotation code denotes male, which must be resolved against the corpus metadata; the magnitude is invariant to this choice. We acknowledge, following [13], that gender is not binary; the corpora provide only male/female self-identifications.

Because every step in the estimator is differentiable, CDD is not only measured but trained against: a squared form of it appears as the fairness term of Section 2.8. At its current weight that term has no measurable effect on $\mathrm{CDD}_G$ (Section 3).

# Appendix L Details of the Training Objective

**Likelihood and CCC.** Take two frames whose true engagement is 0.55 and 0.60, and a model that predicts them the wrong way round, 0.60 and 0.55, each with a moderately wide distribution (concentration $\kappa = 10$, a standard deviation of about 0.15). Each prediction is only 0.05 away from its target, well inside its own spread, so the likelihood barely notices: the summed negative log-likelihood of the two frames rises by only about 0.1 nats compared with the correct predictions. Yet the model now claims that the second frame is *less* engaged than the first, which is precisely the kind of error CCC penalises. Over a whole session, a model whose predictions stay close to the true level but wobble in directions unrelated to the true ups and downs can achieve a good likelihood and a poor correlation at the same time.

**Reweighting the likelihood.** Describe a Beta density by its mean $\mu = \alpha/(\alpha+\beta)$ and its precision $\kappa = \alpha + \beta$, so $\alpha = \mu\kappa$ and $\beta = (1-\mu)\kappa$; large $\kappa$ means a narrow, confident distribution. Differentiating $\ln p(y) = (\alpha-1)\ln y + (\beta-1)\ln(1-y) - \ln B(\alpha,\beta)$ with respect to $\mu$, with $\partial\alpha/\partial\mu = \kappa$ and $\partial\beta/\partial\mu = -\kappa$, and using $\ln B(\alpha,\beta) = \ln\Gamma(\alpha) + \ln\Gamma(\beta) - \ln\Gamma(\alpha+\beta)$ so that $\partial \ln B/\partial\alpha = \psi(\alpha) - \psi(\alpha+\beta)$ and $\partial \ln B/\partial\beta = \psi(\beta) - \psi(\alpha+\beta)$, the $\psi(\alpha+\beta)$ terms cancel and leave

$$\begin{aligned}\frac{\partial(-\ln p)}{\partial\mu} &= \kappa\left[\ln\frac{1-y}{y} + \psi(\mu\kappa) - \psi\big((1-\mu)\kappa\big)\right] \\ &\propto\ \kappa.\end{aligned}$$

The correction the mean receives is thus multiplied by the model's own confidence, so frames it is already sure about push hardest and frames it is unsure about barely move it - the opposite of what we want, since the uncertain frames are the ones with something left to learn. This is a known failure of likelihood training with predicted uncertainty [21]. We fix it by scaling each frame's loss by $w_t = \kappa_t^{-\beta_w}$, giving $\mathcal{L}^w_{\mathrm{NLL}} = \sum_t w_t \mathcal{L}_{\mathrm{NLL},t} / \sum_t w_t$ and a correction proportional to $\kappa^{1-\beta_w}$; $\beta_w = 0$ leaves the likelihood untouched and $\beta_w = 1$ removes the confidence factor completely, and we use $\beta_w = 0.5$. Crucially $w_t$ is computed from the current $\alpha_t, \beta_t$ but treated as a fixed number when derivatives are taken, so no gradient flows back through it. Were it differentiable, $w_t$ would become part of the objective: the model could then lower the loss by shifting its confidence so as to shrink the weight, rather than by predicting better, and the best $\kappa$ would no longer be the one the likelihood asks for. Treated as a constant, $w_t$ changes only how strongly each frame pulls, not where the pull ends - any point at

which every frame's likelihood gradient vanishes is still a stationary point of the weighted loss. In practice $w_t$ is recomputed from the current prediction at every training step and discarded after the update; it is never learned. The ablation of Section 3 measures what the reweighting contributes.

**Ordering term.** Every ingredient - the two means, the two variances, the covariance - is a smooth function of the predictions, so the term can be differentiated, and since $\mathrm{CCC} = \rho\, C_b$, minimising $1 - \widehat{\mathrm{CCC}}$ pushes on exactly the factor the likelihood leaves loose. Two limitations follow from estimating it on a batch. It is biased when the batch is small, because the same frames supply both the moments and the ratio built from them; and it reflects the pooled quantity we are scored on only if the batch spans several sessions, since a batch from one session measures ordering within that session alone.

**Per-modality supervision.** This keeps every modality branch predictive in its own right instead of drifting into whatever representation happens to suit the fusion stage, and it supplies the calibrated per-modality distributions that test-time adaptation (Section 2.6) compares against each other. Without the division, at $\lambda_u = 0.5$ and $M$ streams the undivided sum would outweigh the multimodal term by $\lambda_u M$, which for the final configuration is a factor of five - so most of the gradient would come from heads that are thrown away at evaluation time.

**Fairness term.** Squaring removes the sign, so the term is smallest exactly when the two groups get the same prediction at the same true engagement, and weighting by bin size matches how the metric is estimated at evaluation. Note that the penalty is identically zero on a batch containing only one group, so batches must mix groups for it to do anything. With 8 windows per batch this is frequently violated at the level of individual bins, and in the ablations of Section 3 the term has no measurable effect on $\mathrm{CDD}_G$ at $\lambda_f = 0.05$.

# Appendix M Hyperparameters

| Symbol | Description | Value |
|---|---|---|
| *Data* | | |
| $L$ | Window length (frames; 10 s at 25 Hz) | 250 |
| – | Window hop (frames; 50% overlap) | 125 |
| – | Feature types $\lvert\mathcal{F}\rvert$ (core 4 + text) | 5 |
| $M$ | Role-feature pairs $= 2\lvert\mathcal{F}\rvert$ | 10 |
| – | Training batches | mixed sessions |
| $\varepsilon$ | Target clipping bound | $10^{-6}$ |
| *Architecture* | | |
| $C'$ | Shared channel width after projection | 128 |
| $N$ | SSM state dimension | 16 |
| $D_C$ | Depthwise convolution kernel size (intra-modal) | 4 |
| – | Depthwise convolution kernel size (inter-modal, scan over $M$) | 2 |
| $d_h$ | Beta head hidden width | 128 |
| – | Total parameters (final configuration) | $\approx 2.75$M |
| $\Delta_{\min}$ | Minimum timestep at initialisation | $10^{-3}$ |
| $\Delta_{\max}$ | Maximum timestep at initialisation | $10^{-1}$ |
| – | $A$ initialisation scheme | S4D-Real |
| *Gumbel-Sinkhorn* | | |
| $d_s$ | Query/key projection dimension | 64 |
| $n_{\text{iter}}$ | Sinkhorn normalisation iterations (50 in the corrected layer, Appendix O) | 10 |
| $\tau_0$ | Initial temperature | 1.0 |
| $\tau_\infty$ | Minimum temperature | 0.1 |
| $\gamma$ | Temperature decay rate per epoch | 0.95 |
| *Optimisation* | | |
| $\eta$ | Learning rate (AdamW) | $2 \times 10^{-4}$ |
| – | Weight decay (AdamW) | $10^{-4}$ |
| – | Batch size | 8 |
| – | Maximum epochs | 50 |
| – | Early-stopping patience (epochs, on val CCC) | 15 |
| – | Seeds (final configuration: 6) | $95, 1, 2\,(3, 4, 5)$ |
| $\lambda_c$ | Weight of the ranking (CCC) term | 1.0 |
| $\lambda_u$ | Unimodal deep-supervision weight (before $1/M$) | 0.5 |
| $\lambda_f$ | Fairness penalty weight | 0.05 |
| $\beta_w$ | Likelihood reweighting exponent | 0.5 |
| *Test-time adaptation* | | |
| $\lambda$ | Pseudo-label supervision weight in $\mathcal{L}_{TTA}$ | 1.0 |
| $q_m$ | Quantile of the multimodal-uncertainty threshold | 0.3 |
| $q_u$ | Quantile of the unimodal-uncertainty threshold | 0.7 |
| $B_{\text{inf}}$ | Windows per inference batch | 16 |
| $\eta_{\text{TTA}}$ | Adaptation learning rate (Adam) | $10^{-4}$ |
| *Evaluation* | | |
| $n_b$ | Ground-truth bins for CDD estimation | 10 |

**Table 5:** Hyperparameters of the final configuration (core features plus text, mixed batches, 10 s windows). The current system adds the temporal block after fusion (Section 3.5) and uses batches of 4 on NoXi, and on NoXi+J 60 s windows (1500 frames, hop 750), batches of 4 and at most 100 epochs (Section 3.6). The learning rate was lowered from the initial $10^{-3}$: at that rate a full run reached its best validation CCC at epoch 2 and then stalled while the training loss kept falling, the signature of steps that are too large once input standardisation lets gradients propagate properly. All results in Section 3 use $\eta = 2 \times 10^{-4}$ and patience 15.

# Appendix N Additional Experimental Results

## Seed Variability and Window Length

The experiment of this part was made with the original single-session batches of Section 3.2.

| Corpus | Window | Seed 95 | Seed 1 | Seed 2 | Mean ± sd |
|---|---|---|---|---|---|
| NoXi | 10 s | 0.6987 | **0.7111** | 0.7170 | $0.709 \pm 0.009$ |
| NoXi | 20 s | **0.7252** | 0.6947 | **0.7228** | $\mathbf{0.714 \pm 0.017}$ |
| NoXi+J | 10 s | **0.5298** | 0.5481 | 0.5082 | $0.529 \pm 0.020$ |
| NoXi+J | 20 s | 0.5005 | **0.6044** | **0.5759** | $\mathbf{0.560 \pm 0.054}$ |

**Table 6:** Seed variability and window length. Validation CCC (session level, as in the official scoring; higher is better) of three training seeds and their mean ± sample standard deviation, for 10 s and 20 s windows. Single-session batches, core features.

Bold marks the better window length within each corpus and column. The seed-to-seed standard deviation lies between 0.01 and 0.05, so single-run differences of that size carry no information. The 20 s windows ($L = 500$, window hop 250) were tested because after the S4D-Real initialisation the SSM can retain information for up to $\sim 10^3$ steps, while a 10 s window resets the state every 250 steps. On NoXi the longer window changes nothing; on NoXi+J it raises the mean by 0.03, but with a standard deviation of 0.054 the difference is not established. The window-length comparison of the seed-variability experiment was made with single-session batches and core features and has not been repeated in the final setting; the final configuration keeps 10 s windows.

## Batch Composition

The windows of a training batch were originally taken in order from the data stream, which walks through one session before starting the next. With a few hundred windows per session, practically every batch of 8 windows therefore came from a single session, and a single session contains exactly two people. This matters for three parts of the objective. The ordering term can then only learn the order of frames *within* one conversation, whereas the evaluation pools all sessions and also rewards placing whole sessions correctly relative to one another (Section 2.8). The fairness term is active only when that one pair happens to be of mixed gender. And consecutive batches are strongly correlated, which makes the gradient noisy.

We therefore load the active streams of all training sessions into memory once and draw every batch from a random permutation of all windows of all sessions, re-shuffled each epoch; a batch now almost always mixes several sessions. The full objective was retrained under both schemes, three seeds each. In the table, $\Delta$ is the mixed-session mean minus the single-session mean, and the number in parentheses is the $p$-value of a two-sided Welch $t$-test [22] comparing the two groups of three seed scores. Welch's test asks whether two means differ by more than the spread within each group would explain, without assuming that both groups vary equally; $p$ is the probability of seeing a difference at least this large if the batch scheme in fact made no difference, and we call a difference significant when $p < 0.05$. For $|\mathrm{CDD}_G|$ lower is better; bold marks the better scheme in each column.

| | NoXi | | NoXi+J | |
|---|---|---|---|---|
| **Training batches** | **CCC** | **mean** $\lvert\mathrm{CDD}_G\rvert$ | **CCC** | **mean** $\lvert\mathrm{CDD}_G\rvert$ |
| One session per batch | $0.709 \pm 0.009$ | 0.0069 | $0.529 \pm 0.020$ | 0.0249 |
| Mixed sessions | $\mathbf{0.724 \pm 0.008}$ | **0.0064** | $\mathbf{0.599 \pm 0.029}$ | **0.0121** |
| $\Delta$ ($p$, Welch) | +0.015 (0.10) | | +0.070 (0.03) | |

**Table 7:** Batch composition. Validation CCC (mean ± sd over three seeds; higher is better) and mean absolute gender disparity $|\mathrm{CDD}_G|$ (lower is better) for batches drawn from one session and batches mixed across sessions. $\Delta$: mixed minus single-session mean, Welch $p$-value in parentheses.

Mixing sessions improves NoXi+J significantly and NoXi in the same direction. The gender disparity on NoXi+J halves (per seed 0.009, 0.016, 0.012, against 0.000, 0.039, 0.036 before), but with three seeds the difference is not significant ($p = 0.41$). One NoXi+J seed was by mistake trained twice concurrently into the same directory; the two copies scored 0.585 and 0.624, of which the table uses the later one, and the improvement remains significant with either. All results from here on use mixed batches unless stated otherwise.

## Ablation of the Training Objective

An *ablation* removes one component of a system at a time and measures how much the result changes; a component whose removal lowers the score was contributing to it. Here the components are those of the training objective of Section 2.8, which has four terms: the per-frame Beta likelihood, the ordering (CCC) term, per-modality supervision and the fairness penalty. We trained one *variant* per component, identical to the full model except that this component is switched off by setting its weight to zero (10 s windows, core features, three seeds per variant). Besides the three auxiliary terms, we also switched off the reweighting of the likelihood ($\beta_w = 0$). The reweighting is not a separate term but the per-frame weight $w_t = \kappa_t^{-\beta_w}$ inside both likelihood terms; with $\beta_w = 0$ every frame gets weight 1 and the plain likelihood remains. The per-frame likelihood itself is the one term we never remove, because it is the only term that fits the whole predicted distribution of the multimodal heads - its width as well as its mean. The ordering and fairness terms look only at the predicted means, so without the likelihood nothing would determine the concentration $\kappa = \alpha + \beta$, i.e. how wide the predicted distribution is, and the uncertainty used by test-time adaptation would be meaningless.

We ran the whole ablation twice, once under each batch scheme of Section 3.2, since the scheme turned out to matter. Each entry is the difference between the variant's three-seed mean and that of the full objective under the same scheme, with the Welch $p$-value of Section 3.2 in parentheses. A negative difference means that the score dropped when the component was removed, i.e. that the component was helping. Bold marks the largest drop in each column, and * marks $p < 0.05$.

| | One session per batch | | Mixed sessions | |
|---|---|---|---|---|
| **Variant** | **NoXi** | **NoXi+J** | **NoXi** | **NoXi+J** |
| Full objective (mean ± sd) | $0.709 \pm 0.009$ | $0.529 \pm 0.020$ | $0.724 \pm 0.008$ | $0.599 \pm 0.029$ |
| No ordering ($\lambda_c = 0$) | $-0.020$ (0.20) | $\mathbf{-0.132}$ (0.048)* | $+0.008$ (0.41) | $-0.011$ (0.69) |
| No per-modality ($\lambda_u = 0$) | $-0.035$ (0.26) | $-0.031$ (0.44) | $-0.008$ (0.39) | $-0.009$ (0.75) |
| No reweighting ($\beta_w = 0$) | $\mathbf{-0.037}$ (0.22) | $-0.034$ (0.13) | $+0.002$ (0.87) | $+0.004$ (0.85) |
| No fairness ($\lambda_f = 0$) | $+0.001$ (0.91) | $-0.019$ (0.69) | $\mathbf{-0.028}$ (0.06) | $\mathbf{-0.026}$ (0.26) |

**Table 8:** Ablation of the training objective. First row: validation CCC of the full objective (mean ± sd over three seeds; higher is better). Other rows: change of the mean CCC when one component is switched off (negative means the component helped), Welch $p$-value in parentheses, under both batch schemes. 10 s windows, core features.

**Ordering term.** With single-session batches, removing $\lambda_c(1 - \widehat{\mathrm{CCC}})$ causes the largest loss and the only individually significant one: on NoXi+J the mean falls from 0.529 to 0.396. With mixed batches its removal has no measurable effect. A plausible explanation, which we have not tested directly, is that a single-session batch shows the likelihood only one conversation at a time, so it cannot learn that one session is on the whole more engaged than another, and the ordering term compensates for this; once a batch mixes sessions, the likelihood sees those differences itself. Whatever the mechanism, the result shows that the value of a loss term cannot be judged independently of how the batches it is computed on are composed.

**Per-modality supervision and likelihood reweighting.** With single-session batches, removing the per-modality term or switching off the reweighting lowers the mean by 0.03 to 0.04 on both corpora - not significant individually, but consistent in all four cases. With mixed batches both effects shrink below 0.01. Neither term is shown to help in the final setting; neither is shown to hurt.

**Fairness term.** With single-session batches, removing it changes nothing measurable. With mixed batches, removing it lowers the mean by about 0.027 on both corpora ($p = 0.06$ and 0.26); in other words, keeping the term slightly *raised* accuracy, although it was added for fairness and not for accuracy. A possible explanation is that it acts as a regulariser - an extra constraint that keeps the model from fitting peculiarities of the training data too closely and so helps it generalise - but we have not tested this, and the effect is not significant. Its effect on the quantity it was designed for is not measurable in either scheme (lower is better; bold marks the lowest value in each column):

| **Batches** | **Variant** | **NoXi** mean $\lvert\mathrm{CDD}_G\rvert$ | **NoXi+J** mean $\lvert\mathrm{CDD}_G\rvert$ |
|---|---|---|---|
| One session | $\lambda_f = 0.05$ | 0.0069 | 0.0249 |
| One session | $\lambda_f = 0$ | 0.0118 | 0.0258 |
| Mixed | $\lambda_f = 0.05$ | **0.0064** | **0.0121** |
| Mixed | $\lambda_f = 0$ | 0.0074 ($p = 0.89$) | 0.0163 ($p = 0.53$) |

**Table 9:** Effect of the fairness term on fairness. Mean absolute gender disparity $\lvert\mathrm{CDD}_G\rvert$ over three seeds (lower is better) with and without the fairness penalty, under both batch schemes; $p$ from Welch's test against $\lambda_f = 0.05$.

**What the ablation can and cannot show.** With three seeds per group and a seed standard deviation of 0.01 to 0.03, only differences of roughly 0.04 or more are detectable. Moreover, when eight comparisons are made at once, the chance that at least one of them reaches $p < 0.05$ by luck alone is far larger than 5%. The Holm correction [23] compensates for this: the $p$-values are sorted, the smallest is multiplied by the number of comparisons (8), the next by 7, and so on, and a result counts as significant only if its corrected value stays below 0.05. In the mixed-batch ablation the smallest $p$-value, 0.055 (shown as 0.06 in the table), becomes 0.44, so none of the eight differences is significant. We therefore keep the full objective: no term is shown to hurt, and dropping one on the basis of these differences would itself be a decision made on noise.

## Input Features

The core set and core plus text were trained with six seeds, the others with three; $\Delta$ and $p$ (Welch) are relative to the core set. Bold marks the best value in each column.

| | NoXi | | | NoXi+J | | |
|---|---|---|---|---|---|---|
| **Inputs** | **Mean ± sd** | $\Delta$ | $p$ | **Mean ± sd** | $\Delta$ | $p$ |
| Core 4 | $0.726 \pm 0.010$ | – | – | $0.593 \pm 0.023$ | – | – |
| + text | $\mathbf{0.731 \pm 0.020}$ | **+0.005** | 0.58 | $\mathbf{0.641 \pm 0.018}^{*}$ | **+0.047**$^{*}$ | **0.003** |
| + image | $0.701 \pm 0.017$ | −0.025 | 0.11 | $0.593 \pm 0.020$ | −0.001 | 0.97 |
| + video | $0.712 \pm 0.027$ | −0.014 | 0.47 | $0.509 \pm 0.033$ | −0.084 | 0.03 |
| All ten | $0.714 \pm 0.017$ | −0.012 | 0.34 | $0.641 \pm 0.038$ | +0.048 | 0.15 |

**Table 10:** Input feature sets. Validation CCC (mean ± sd over seeds; higher is better) when feature groups are added to the four core streams; $\Delta$ and Welch $p$ relative to the core set. Six seeds for the core set and core plus text, three for the others. $^{*}$ All ten streams score marginally higher on NoXi+J (0.6412 against 0.6406), far below the seed-to-seed spread, while taking about 2.5 times longer to train, varying twice as much across seeds and scoring lower on NoXi; we therefore count core plus text as the best input set.

## Level versus Within-Person Dynamics

The full numbers behind Section 3.4:

| **Final models (mean over six seeds)** | **NoXi** | **NoXi+J** |
|---|---|---|
| Share of the label variance between people | 51% | 26% |
| CCC | 0.731 | 0.641 |
| CCC with the true level | 0.774 | 0.692 |
| CCC of the true level alone | 0.673 | 0.414 |
| CCC with the true dynamics | **0.955** | **0.945** |
| Pearson $r$ of the person means | 0.90 | 0.89 |
| Mean within-person Pearson $r$ | 0.47 | 0.60 |

**Table 11:** Level versus within-person dynamics, final models (mean over six seeds). Validation CCC (higher is better) of the prediction as it is and with one part replaced by the truth: each person's mean (true level), the deviations from it (true dynamics), or the true mean alone. Also the share of the label variance between people, and the Pearson correlation of the person means and within persons.

Two simple explanations can be excluded. If the annotators reacted with a delay, a shifted prediction would score higher; shifting the predictions by −4 to +6 s changes nothing on NoXi (the best shift is 0) and gains at most 0.013 on NoXi+J (a delay of 1.5 s). If the predictions were merely noisy, smoothing would help; a centred moving average of 0.5 to 8 s gains at most 0.003 on NoXi and 0.018 on NoXi+J. The gap is a matter of modelling.

## Temporal Block after Fusion

Both runs use the first implementation of the ordering layer (Appendix O).

| | NoXi | NoXi+J |
|---|---|---|
| Final model | $\mathbf{0.731 \pm 0.020}$ | $0.641 \pm 0.018$ |
| + temporal block after fusion | $0.724 \pm 0.014$ | $\mathbf{0.684 \pm 0.024}$ |
| $\Delta$ ($p$, Welch) | $-0.007$ (0.53) | $+\mathbf{0.043}$ ($\mathbf{0.006}$) |
| Mean of the six models (not rescaled): final | 0.756 | 0.696 |
| Mean of the six models (not rescaled): + temporal block | 0.755 | **0.729** |
| Within-person $r$ of the mean: final | 0.512 | 0.687 |
| Within-person $r$ of the mean: + temporal block | 0.529 | **0.746** |

**Table 12:** Temporal block after fusion. Validation CCC (mean ± sd over six seeds; higher is better) without and with the temporal BiMamba after fusion, their difference with the Welch $p$-value, and for the frame-wise mean of the six models (not rescaled) the CCC and the within-person Pearson $r$.

## The Label-Scale Offset across Corpora

Take the NoXi model on NoXi+J: its predictions rise and fall roughly where the annotations do, but the whole predicted curve sits about 0.26 below the annotated one (mean 0.577 against 0.834). Measured against the spread of the two curves (standard deviations 0.090 and 0.102), this offset is large, $\omega \approx -2.7$, and since $C_b = \dfrac{2}{\varphi + \varphi^{-1} + \omega^2}$ with $\varphi + \varphi^{-1} \approx 2.02$, it alone pulls $C_b$ down to about $2/9.2 \approx 0.22$; the difference in spread would by itself only cost about 1%. The NoXi+J model on NoXi shows the mirror image, predicting 0.245 too high.

## Label-Free Rescaling

The rescaled ensemble prediction is

$$\hat{y}'_t = \mu_{\text{ens}} + \left(\hat{y}_t - \mu_{\text{ens}}\right) \frac{\bar{\sigma}_{\text{mem}}}{\sigma_{\text{ens}}}.$$

Here $\hat{y}_t$ is the ensemble prediction (the frame-wise average of the members), $\mu_{\text{ens}}$ and $\sigma_{\text{ens}}$ are the mean and standard deviation of this averaged curve over all frames of the split, and $\bar{\sigma}_{\text{mem}}$ is the average of the members' own standard deviations (below). The result is clipped to $[0, 1]$.

Where the members disagree about how high or low a frame should be, their average lands in between, so the averaged curve rises and falls at the same places as the members' curves, but not as far. The stretch does not change which frames are predicted higher than which, only how far apart they are. $\bar{\sigma}_{\text{mem}}$ is computed the other way round: first the standard deviation of each member's own curve, then the average of these six numbers. The two orders of operation give different results for the spread - the spread of an average is smaller than the average spread, unless all members agree perfectly - and that difference is exactly what the stretch undoes; on NoXi+J the factor is $0.086/0.078 \approx 1.10$. For the level, both orders give the same number, since the mean of the averaged curve equals the average of the members' means, so the mean is left where it is.

| | NoXi | | | NoXi+J | | |
|---|---|---|---|---|---|---|
| **Predictor** | **CCC** | $\rho$ | $C_b$ | **CCC** | $\rho$ | $C_b$ |
| Single model (mean of 6 seeds) | 0.731 | – | – | 0.641 | – | – |
| Ensemble of 6 seeds | 0.756 | **0.761** | 0.993 | 0.696 | **0.744** | 0.936 |
| Ensemble of 6 seeds, rescaled | **0.758** | **0.761** | **0.996** | **0.714** | **0.744** | **0.959** |

**Table 13:** Ensembling, final configuration. Validation CCC (higher is better) of single models and of the frame-wise mean of six seeds, before and after label-free rescaling, with the correlation $\rho$ and the bias correction $C_b$ (CCC $= \rho\, C_b$).

## Scoring

The network predicts overlapping windows ($L = 250$ frames, window hop 125). For evaluation, the window predictions of a session are reassembled into one sequence per role by averaging every frame over the windows that cover it (overlap-add). CCC is then computed exactly as in the official MultiMediate'26 scoring script: for each dataset, all sessions and both roles are concatenated into a single sequence, each prediction is truncated to the length of its annotation, non-finite frames are dropped, and one CCC is taken over the result. Applied to the same prediction files, our evaluation code and the official script agree to four decimals.

The validation score logged during training pools the raw overlapping windows instead of reassembled sessions, so interior frames enter twice. The two quantities differ, and not in a fixed direction: for the same checkpoints we measured 0.7942 (window-level) against 0.6987 (session-level) on NoXi, and 0.4887 against 0.5298 on NoXi+J.

Checkpoints are still selected on the window-level score; re-scoring every saved checkpoint of the NoXi run at session level (epochs 10, 16, 20, 30: 0.6732, 0.6987, 0.6267, 0.6472) confirmed that the selected epoch 16 was also the best of those available.

# Appendix O Learned versus Fixed Modality Ordering

The ordering layer of Section 2.4 is a contribution only if it does better than a fixed order. We trained the final configuration (core features plus text, mixed batches, full objective) with the meta-network removed and $P$ replaced by a constant permutation matrix, for four fixed orders of the $M = 10$ streams, with three seeds each (95, 1, 2), and compared each with the six seeds of the learned ordering by Welch's $t$-test, as in Section 3.3. The four orders are: (i) role-blocked, the five streams of the expert followed by the five of the novice, feature types in alphabetical order (the order in which the code stacks the streams before $P$ is applied); (ii) role-interleaved, the expert and novice streams of each feature type next to each other; (iii) and (iv) two random orders, drawn once and kept fixed for all seeds. An order and its reverse are not both included: the forward and backward scans of the bidirectional block have the same structure and separately initialised parameters, so reversing the sequence only exchanges their roles.

| | **NoXi** | | | **NoXi+J** | | |
|---|---|---|---|---|---|---|
| **Ordering** | **Mean ± sd** | $\Delta$ | $p$ | **Mean ± sd** | $\Delta$ | $p$ |
| Learned (6 seeds) | $\mathbf{0.731 \pm 0.020}$ | – | – | $0.641 \pm 0.018$ | – | – |
| Role-blocked | $0.702 \pm 0.023$ | $-0.028$ | 0.15 | $0.672 \pm 0.006$ | $+0.031$ | $0.007^*$ |
| Role-interleaved | $0.717 \pm 0.006$ | $-0.014$ | 0.17 | $\mathbf{0.676 \pm 0.027}$ | $+0.036$ | 0.13 |
| Random 1 | $0.710 \pm 0.008$ | $-0.021$ | 0.06 | $0.647 \pm 0.014$ | $+0.006$ | 0.59 |
| Random 2 | $0.718 \pm 0.016$ | $-0.013$ | 0.34 | $0.667 \pm 0.007$ | $+0.027$ | $0.016^*$ |
| All fixed (12 runs) | $0.712 \pm 0.014$ | $-0.019$ | 0.07 | $0.666 \pm 0.018$ | $+0.025$ | $0.02^*$ |

**Table 14:** Learned versus fixed ordering. Validation CCC (mean ± sd; higher is better) of the learned ordering (six seeds) and of four fixed orders (three seeds each). $\Delta$: fixed minus learned; $p$ from Welch's test. $\Delta$ and $p$ (Welch) are relative to the learned ordering. Bold marks the best mean in each column; $^*$ marks $p < 0.05$ before correction.

The learned ordering does not do better than a fixed order. On NoXi every fixed order scores somewhat lower ($-0.013$ to $-0.028$), but none of the differences is significant, and pooled over the four orders the gap is $-0.019$ ($p = 0.07$). On NoXi+J the picture is reversed: every fixed order scores *higher*, by up to 0.036, and pooled over the four orders by 0.025 ($p = 0.02$). Two single comparisons reach $p < 0.05$, but after the Holm correction over the eight comparisons the smallest corrected value is 0.057, so no single fixed order is shown to differ from the learned one. The four fixed orders differ from each other by about as much as seeds do, so on these data the choice of order matters little, and learning it brings no measurable gain; on NoXi+J it costs accuracy. The fixed models also lack the meta-network and the Gumbel noise, so we cannot separate the effect of the ordering from that of removing the noise.

**What the learned $P$ looks like.** We read out $P$ on the validation windows for one learned model per corpus (seed 95). It is far from a permutation: the largest entry of a row averages 0.73 on both corpora, only 55% (NoXi) and 49% (NoXi+J) of rows have an entry above 0.9, and rounding each row to its largest entry gives a valid permutation for only 0.4% and 2.1% of the windows (1,006 and 1,431 distinct rounded orders). Moreover, the rows of the averaged $P$ do not sum to one but to between 0.6 and 2.0 on NoXi and between 0.86 and 1.37 on NoXi+J. With $n_{\text{iter}} = 10$, the final Sinkhorn pass normalises the columns, but the iteration has not converged, so the matrix is column-stochastic without being doubly stochastic: some positions receive the weight of about two streams, others of about half a stream. In practice the layer therefore acts as a learned, input-dependent soft mixing of streams into positions rather than as an ordering. Whether the unscaled scores of Section 2.4 are the reason for the slow convergence we have not tested.

**Four problems in the first implementation.** Inspecting the layer against its intended mathematics revealed four faults, two of which penalise only the learned ordering and therefore bias the comparison above against it.

1. **The heads saw a changing layout.** The fused slots were concatenated in scan order and read by one dense layer per role. Under an input-dependent $P$, which stream occupied which part of the heads' input changed from window to window, so the read-out weights could not specialise; with a fixed order the layout never changes. Corrected by mapping the slots back to stream order with $P^\top$ before the heads (Section 2.3.2).

2. **Inference ran at a different temperature.** The best checkpoint was selected at the temperature of its epoch, but inference always used $\tau_\infty = 0.1$, giving a sharper $P$ than the model was trained or selected with. Fixed orders do not depend on $\tau$. Corrected by storing the temperature of the selected epoch with the checkpoint and using it at inference (Appendix G).

3. **Sinkhorn had not converged.** With 10 iterations and unscaled scores, $P$ was column-stochastic but not doubly stochastic. Corrected by the $1/\sqrt{d_s}$ scaling and 50 iterations.

4. **The score matrix had no notion of position.** With data-dependent queries, $Z_{ij}$ compared stream $i$ with stream $j$ rather than scoring stream $j$ for position $i$, and the result depended on how the streams were numbered. Corrected by one learned query per position.

All other results in this document were obtained with the first implementation, except that the models trained after this correction (Sections 3.5, 3.6 and 3.9) are run at the temperature of their selected epoch.

**Effect of the inference temperature alone.** Re-scoring the six existing learned models per corpus at the temperature of their selected epoch (0.29 to 0.49 on NoXi, 0.36 to 0.95 on NoXi+J) instead of $\tau_\infty = 0.1$, without retraining, changes the validation CCC by $-0.001$ on NoXi ($0.729 \pm 0.022$; paired $t$-test over the same models, $p = 0.15$) and by $+0.005$ on NoXi+J ($0.645 \pm 0.017$; $p = 0.03$, all six seeds improve). The effect is real on NoXi+J but an order of magnitude smaller than the gap to the fixed orders.

**Corrected layer.** With all four corrections (position queries, scaled scores, $n_{\text{iter}} = 50$, unsorting before the heads, inference at the selected temperature), trained with the same configuration and seeds (95, 1, 2):

| | NoXi | | | NoXi+J | | |
|---|---|---|---|---|---|---|
| **Compared with** | **Other** | $\Delta$ | $p$ | **Other** | $\Delta$ | $p$ |
| Role-blocked | 0.702 | +0.014 | 0.44 | 0.672 | −0.030 | 0.21 |
| Role-interleaved | 0.717 | −0.000 | 0.98 | 0.676 | −0.034 | 0.21 |
| Random 1 | 0.710 | +0.007 | 0.57 | 0.647 | −0.004 | 0.83 |
| Random 2 | 0.718 | −0.001 | 0.94 | 0.667 | −0.025 | 0.27 |
| All fixed (12 runs) | 0.712 | +0.005 | 0.68 | 0.666 | −0.023 | 0.29 |
| First learned layer (6 seeds) | 0.729 | −0.013 | 0.39 | 0.645 | −0.003 | 0.88 |

**Table 15:** Corrected ordering layer. Validation CCC (mean over seeds; higher is better) of each configuration the corrected layer is compared with (*Other*), the difference corrected minus other, and the Welch $p$-value. Three seeds for the corrected layer. The corrected layer scores $0.717 \pm 0.017$ on NoXi and $0.642 \pm 0.029$ on NoXi+J. $\Delta$ is the corrected layer minus the other configuration; $p$ from Welch's test. The first learned layer is scored at the selected temperature.

The corrections do not change the conclusion. The corrected layer is level with the fixed orders on NoXi and below them on NoXi+J, and it does not differ from the first learned layer on either corpus; no comparison approaches significance (smallest Holm-corrected $p = 1.0$ over the eight comparisons with fixed orders).

The read-out of $P$ (seed 95) shows that the corrections changed the layer itself. On NoXi, $P$ is now close to a permutation: the mean largest row entry is 0.89, 69% of rows have an entry above 0.9, and rounding gives a valid permutation for 85% of the windows (previously 0.4%), with 754 distinct orders. The ordering is still strongly input-dependent; the most frequent order covers only 2% of the windows. Sinkhorn has still not fully converged on NoXi (row sums 0.50 to 1.33): the learned position queries grew during training until the per-row spread of $Z/\tau$ reached a median of 76, at which point 50 iterations are not enough. On NoXi+J the layer stayed soft (mean largest row entry 0.53, 10% valid rounded permutations, 1,172 distinct orders), with a median spread of $Z/\tau$ of 8.3 and row sums between 0.92 and 1.05.

**Why ordering cannot show a gain here.** The four fixed orders, which include very different arrangements of roles and feature types, differ from each other by at most 0.016 on NoXi and 0.030 on NoXi+J, which is about the seed standard deviation. A layer that always picked the best of them could therefore gain at most this much over a fixed order, below the difference of about 0.04 that three seeds can detect (Section 3.1). On these data the order in which the inter-modal block scans the streams matters little, and a learned ordering has little to improve.

**When the scan cannot depend on the order.** Consider a simplified bidirectional scan with no state decay ($\bar{A} = 1$), no convolution, and the same $\bar{B}_j$, $C_j$ for the forward and the backward direction, each computed from stream $j$ alone. The forward state at position $i$ is $h_i^{\rightarrow} = \sum_{j \le i} \bar{B}_j x_j$, the backward state $h_i^{\leftarrow} = \sum_{j \ge i} \bar{B}_j x_j$, so

$$y_i = C_i^\top \left(h_i^{\rightarrow} + h_i^{\leftarrow}\right) = C_i^\top \Big(\sum_{j=1}^{M} \bar{B}_j x_j + \bar{B}_i x_i\Big),$$

which depends only on stream $i$ itself and on the sum over all streams. Renumbering the positions renumbers the outputs in the same way and changes nothing else: the scan is permutation-equivariant, and after unsorting, its output does not depend on the order at all. Our block departs from this case in three places: $\bar{A} = \exp(\Delta A) < 1$, a depthwise convolution of width 4 over neighbouring positions, and separate forward and backward parameters. Order can only matter through these, and how much it does is an empirical question, which the following tests answer.

**Testing that the order does not matter.** A non-significant difference is not evidence that there is none, so the claim is tested as an equivalence, with the margin fixed in advance at $\delta = 0.02$ CCC (about one seed standard deviation; smaller differences are of no practical consequence). Equivalence within $\pm\delta$ is shown by two one-sided tests (TOST) at $\alpha = 0.05$, i.e. when the 90% confidence interval of the difference lies inside $(-\delta, \delta)$; for every comparison we also report the smallest margin the data establish, the largest absolute end of that interval.

*Training-time order.* We trained three more seeds (3, 4, 5) for each fixed order on both corpora, six per order in all. Each order is compared by Welch's TOST with the runs of the other three orders:

| | NoXi | | | NoXi+J | | |
|---|---|---|---|---|---|---|
| **Order** | **Mean ± sd** | 90% **CI of Δ** | $p_{\mathrm{TOST}}$ | **Mean ± sd** | 90% **CI of Δ** | $p_{\mathrm{TOST}}$ |
| Role-blocked | $0.713 \pm 0.019$ | $[-0.018, +0.013]$ | **0.035** | $0.670 \pm 0.019$ | $[-0.008, +0.025]$ | 0.11 |
| Role-interleaved | $0.719 \pm 0.008$ | $[-0.002, +0.014]$ | **0.005** | $0.663 \pm 0.028$ | $[-0.024, +0.022]$ | 0.08 |
| Random 1 | $0.711 \pm 0.008$ | $[-0.013, +0.003]$ | **0.002** | $0.657 \pm 0.017$ | $[-0.023, +0.007]$ | 0.09 |
| Random 2 | $0.716 \pm 0.012$ | $[-0.009, +0.012]$ | **0.005** | $0.664 \pm 0.007$ | $[-0.009, +0.010]$ | **0.001** |
| ANOVA | $F = 0.47$, $p = 0.71$ | | | $F = 0.43$, $p = 0.74$ | | |

**Table 16:** Equivalence of training-time orders, six seeds per order. Validation CCC (mean ± sd), 90% confidence interval of the difference to the other three orders, and TOST $p$-value for equivalence within $\pm 0.02$ ($p < 0.05$: equivalent). Last row: one-way ANOVA over the four orders. Δ is the order minus the pooled runs of the other three orders. Bold marks equivalence within $\pm 0.02$ ($p_{\mathrm{TOST}} < 0.05$).

A one-way ANOVA finds no effect of the order on either corpus. Splitting the variance into a seed and an order component, the seed standard deviation is 0.013 (NoXi) and 0.019 (NoXi+J), the estimated order standard deviation is 0 on both, and its approximate 95% upper bound is 0.009 and 0.013: the order contributes less spread than the seed does. With six seeds the order means span only 0.008 and 0.012, against 0.016 and 0.030 with three, so most of the earlier spread was seed noise. On NoXi all four orders are equivalent to the rest within $\pm 0.02$; since the joint claim requires every one of the four tests to pass, no multiplicity correction is needed (intersection-union principle). On NoXi+J only random order 2 passes: the other intervals reach 0.022 to 0.025, so with a seed standard deviation of 0.019 six seeds exclude only differences above about 0.025.

*Inference-time order.* Each of the 12 fixed-order models per corpus (four orders, seeds 95, 1, 2) was run, without retraining, with the scan in six other orders (the three other fixed orders and three further random orders). The outputs are mapped back to the layout the heads were trained on, so only the scan order changes. The difference $\Delta = \mathrm{CCC}(\text{other order}) - \mathrm{CCC}(\text{own order})$ is paired, so seed variance drops out. The unit of analysis is the trained model, with Δ averaged over its six probes:

| | **NoXi** | **NoXi+J** |
|---|---|---|
| Mean Δ per model (12 models) | $+0.0004$ | $-0.0074$ |
| 90% CI | $[-0.0033, +0.0042]$ | $[-0.0125, -0.0022]$ |
| $p_{\mathrm{TOST}}$ ($\pm 0.02$) | $< 0.0001$ | 0.0005 |
| Excluded beyond | 0.004 | 0.013 |
| Mean $\lvert\Delta\rvert$ over the 72 probes | 0.006 | 0.009 |
| Worst single probe | $-0.022$ | $-0.044$ |

**Table 17:** Equivalence of inference-time orders. Each of the 12 fixed-order models is run, without retraining, with the scan in six other orders (72 probes). Δ: validation CCC in the other order minus that in the trained order (0: the order does not matter); TOST margin $\pm 0.02$. *Excluded beyond*: the largest absolute bound of the 90% CI.

Equivalence within $\pm 0.02$ holds clearly on both corpora; on NoXi the data exclude any effect larger than 0.004. On NoXi+J the models score slightly lower in an order they were not trained with ($-0.007$; $t$-test against zero $p = 0.03$, 10 of 12 models lower): the block has adapted a little to its training order, but a foreign order costs less than 0.013 on average and at most 0.044 for a single probe.

*Mechanism.* We read out $\bar{A}$ in the inter-modal block on the validation windows for the eight seed-95 models (four orders, two corpora). In both directions, 43% to 56% of the entries exceed 0.9, the median is 0.90 to 0.95, and only 1% to 6% are below 0.1. The mean share of the state that survives the whole sequence of streams, $\bar{A}^{M-1}$, is 0.36 to 0.48. The trained block therefore operates close to the no-decay case of the proposition above: most state channels carry each stream across the whole sequence with little loss, so every position sees nearly the same summary of all streams whatever their order. Order can enter only through the minority of fast-decaying channels and the width-4 convolution, which matches the small effects measured above.

# Appendix P Further Results on Long Context

**Setup.** A 60 s window has 1500 frames and the stride is 750; one extra window ending at the last frame covers the end of the session, which the regular stride would leave to the last predicted value. Since an epoch with smaller batches has fewer updates, training runs for up to 100 epochs.

**Where the 60 s windows gain.** We repeat the analysis of Section 3.4 for the six single models with 10 and with 60 s windows on NoXi+J:

| **NoXi+J, mean over six single models** | 10 s | 60 s |
|---|---|---|
| CCC with the true level | 0.747 | 0.774 |
| Pearson $r$ of the person means | 0.86 | 0.89 |
| Mean within-person Pearson $r$ | 0.68 | 0.72 |
| Band $r$: fast, $< 2$ s | 0.01 | 0.02 |
| Band $r$: mid, 2 to 10 s | 0.28 | 0.32 |
| Band $r$: slow, 10 to 60 s | 0.64 | 0.66 |
| Band $r$: very slow, $> 60$ s | 0.80 | **0.84** |

**Table 18:** Where the 60 s windows gain on NoXi+J (mean over six single models). CCC with each person's true level, Pearson $r$ of the predicted and true person means, mean within-person $r$, and $r$ in each band of Section 3.4; higher is better throughout.

Both parts improve: each person's level is placed better, and within a person the prediction follows the label more closely. Within a person the gain lies mainly in the very slow band, while the slow band from 10 to 60 s, which Section 3.4 singled out, barely changes. A 60 s window cannot resolve changes slower than itself either. Presumably it gives each window more evidence for the person's current level, and the overlapping windows, half a minute apart, then follow that level as it drifts over the session.

**Context at inference only.** The BiMamba blocks run on sequences of any length, so a model can be given more context at inference than it had in training. A model trained on 60 s windows loses slightly on 120 s windows ($-0.004$, six seeds, paired $p = 0.08$) and more on 300 s windows ($-0.015$, five seeds, $p = 0.03$). A NoXi model trained on 10 s windows (batches of 4, three seeds) scores the same on 60 and 120 s windows (0.747 and 0.745, against 0.744). The models stay stable on longer sequences but do not use context they were not trained on.

**Instability on NoXi.** With 60 s windows the validation score of some NoXi seeds swings from epoch to epoch; clipping the global gradient norm does not remove this (one seed oscillates between 0 and 0.7 for the whole run).

**A two-rate model.** Since the models use only context they were trained on, we also gave them the whole session during training, at a low rate: a second path averages each stream over bins of 2 s for the whole session (about 300 to 600 bins), passes it through its own projection, intra-modal BiMamba, inter-modal BiMamba (fixed order) and a BiMamba over time, and the heads read its output, interpolated at the frames of the window, next to $[H, z]$ (+0.34M parameters). With 10 s windows it is neutral on NoXi+J ($0.693 \pm 0.028$, $+0.001$ against the same three seeds without it) and harmful on NoXi ($0.692 \pm 0.008$, $-0.040$, $p = 0.008$), where the validation score peaks after 2 to 6 epochs and then declines. A likely cause is a shortcut: the whole-session input identifies each training participant and lets the model memorise their level, which does not transfer to new participants. Removing the session mean from the inputs and the output of the slow path, so that it can only move the prediction within a session, does not help: it makes the model worse on both corpora ($0.662 \pm 0.028$ on NoXi and $0.671 \pm 0.021$ on NoXi+J, $-0.070$ and $-0.022$ against the same three seeds without the slow path). Either the shortcut does not run through the session mean alone, or the slow path hurts for another reason; we have not separated the two. The whole-session path is a negative result.

**A within-person loss term.** The CCC term of the objective is computed over a batch of windows from different people, so it rewards placing each person's level as much as following their changes. We added $\lambda_w(1-\bar{r})$ with $\lambda_w = 0.5$, where $\bar{r}$ is the Pearson correlation between prediction and label within each window and role, averaged with weights proportional to the label's standard deviation in the window, so that windows in which the label barely moves count little. On the two best configurations it changes nothing: $0.744 \pm 0.011$ against 0.744 on NoXi (10 s windows, batches of 4) and $0.732 \pm 0.037$ against 0.736 on NoXi+J (60 s windows), on the same three seeds each, with a larger spread between seeds on NoXi+J.

# Appendix Q Further Results on Test-Time Adaptation

**Whole sessions.** The settings of Section 3.9 in full:

| Setting $(q_m, q_u, \eta_{\mathrm{TTA}})$ | NoXi → NoXi+J selected | NoXi → NoXi+J CCC | NoXi+J → NoXi+J selected | NoXi+J → NoXi+J CCC |
|---|---|---|---|---|
| No adaptation | – | 0.0922 | – | 0.5298 |
| $(0.3,\ 0.7,\ 10^{-4})$ | $\approx 2\%^{\ddagger}$ | 0.0921 | – | **0.5339** |
| $(0.5,\ 0.5,\ 10^{-4})$ | 16.7% | 0.0927 | 17.2% | 0.5332 |
| $(0.5,\ 0.5,\ 10^{-3})$ | 14.7% | **0.0953** | 18.4% | 0.4178 |
| $(0.3,\ 0.7,\ 10^{-3})$ | 4.5% | 0.0897 | 5.5% | 0.4796 |

**Table 19:** Test-time adaptation on whole sessions, across corpora (trained on NoXi, evaluated on NoXi+J) and within NoXi+J. Fraction of windows selected by the filter and validation CCC (higher is better) for each setting of the quantiles $(q_m, q_u)$ and the learning rate $\eta_{\mathrm{TTA}}$. $^{\ddagger}$ Estimated from the first three sessions; the fraction was not logged for the full run. Bold marks the best CCC in each column.

**Adaptation on a single person.** In the runs above, the stream being adapted to is a whole session, and the sessions of a split come from many participants, so the shift the adaptation meets mixes differences between persons with the label scale of the corpus, which an adaptation without labels cannot observe. We therefore also ran it on one participant at a time: for each session and each role, the adaptation starts again from the trained model, only that person's multimodal and unimodal uncertainties enter the filter, only that person's heads provide the loss, and only that person's predictions are kept. Both variants were run in-corpus on the best models of Section 3.6 (10 s windows with batches of 4 on NoXi, 60 s windows on NoXi+J), three seeds each, and compared with the same seeds without adaptation; "improved" counts the 20 people of each validation split whose own CCC, averaged over the seeds, rises.

| Adapted to, setting $(q_m, q_u, \eta_{\mathrm{TTA}})$ | NoXi Δ CCC | NoXi improved | NoXi+J Δ CCC | NoXi+J improved |
|---|---|---|---|---|
| Session, $(0.3,\ 0.7,\ 10^{-4})$ | −0.001 | 9/20 | −0.000 | 3/20 |
| Person, $(0.3,\ 0.7,\ 10^{-4})$ | −0.002 | 11/20 | −0.001 | 6/20 |
| Person, $(0.5,\ 0.5,\ 10^{-3})$ | −0.022 | 8/20 | −0.208 | 3/20 |

**Table 20:** Test-time adaptation on a single person and on a whole session. Change of the validation CCC caused by the adaptation (positive is better), mean over three seeds, and the number of the 20 validation people whose own CCC rises. Best configurations of Section 3.6. Δ CCC: change of the pooled CCC, mean over the three seeds (unadapted: 0.744 on NoXi, 0.736 on NoXi+J).

Adapting to one person behaves like adapting to a session. With the design setting the filter selects 4 to 8% of the windows, and the predictions barely move: no person's CCC changes by more than 0.015, and the changes over people are not different from zero (Wilcoxon signed-rank, $p = 0.62$ on NoXi and 0.10 on NoXi+J). With the larger learning rate and quantiles of 0.5, which select about 16% of the windows, the adaptation is harmful, mildly on NoXi and strongly on NoXi+J ($p < 0.001$), where single people lose up to 0.54. Restricting the adaptation to one person therefore does not change the earlier result. A likely reason lies in the loss: its target is the model's own fused prediction, so an update can only pull the unimodal heads and the adapted layers towards what the model already predicts, and it carries no information about the person that the model does not have.

**Total uncertainty from MC dropout.** We then trained the same two configurations with dropout $p = 0.2$ in the Beta heads (Appendix J), three seeds each, and made three comparisons on the same seeds: the dropout model with a single deterministic pass against the model without dropout; the mean of $T = 10$ passes against that single pass; and adaptation on a single person with the total-variance filter $U_{\mathrm{total}}$ (design setting $(0.3, 0.7, 10^{-4})$) against the mean of $T = 10$ passes without adaptation.

| Comparison | NoXi Δ CCC | NoXi improved | NoXi+J Δ CCC | NoXi+J improved |
|---|---|---|---|---|
| Dropout, single pass vs. no dropout | +0.008 | 3/3 seeds | −0.039 | 0/3 seeds |
| Mean of 10 passes vs. single pass | −0.000 | 6/20 | −0.001 | 9/20 |
| Person, $U_{\mathrm{total}}$ filter vs. mean of 10 passes | −0.002 | 14/20 | −0.000 | 7/20 |

**Table 21:** MC dropout. Change of the validation CCC (positive is better) in three comparisons on the same three seeds, and how many seeds (first row) or how many of the 20 validation people (other rows) improve. Δ CCC: change of the pooled CCC, mean over the three seeds. With dropout: $0.751 \pm 0.004$ on NoXi and $0.698 \pm 0.026$ on NoXi+J; without: $0.744 \pm 0.008$ and $0.736 \pm 0.013$.

Dropout itself brings no detectable gain: on NoXi all three seeds are slightly higher (Welch $p = 0.23$), on NoXi+J

all three are lower ($p = 0.11$; paired over seeds $p = 0.04$). Averaging the passes leaves the prediction practically unchanged: the pooled CCC moves by less than 0.001, and the changes over people are not different from zero (Wilcoxon $p = 0.14$ on NoXi and 0.43 on NoXi+J). As dropout acts only in the heads, all passes share the same representation up to the heads, which likely keeps them close together. With $U_{\text{total}}$, the filter selects 4.7% of the windows on NoXi and 2.4% on NoXi+J, no more than with the parametric variance, and the adaptation again stays within noise (Wilcoxon $p = 0.26$ and 0.59; no person changes by more than 0.021). The total uncertainty therefore does not change the result: the filter now sees the full predictive variance, but the target of the loss is still the model's own prediction, the limitation named above. Test-time adaptation remains a negative result, and dropout is not used in the final systems.