



StockMount API Services  
Application Guide  
Version 1.1

12.10.2015

## Content

1	Updates .....	2
2	Introduction.....	3
3	Writing Markings .....	3
4	Service Address and Requirements.....	3
5	Authentication and Security.....	3
6	Services.....	4
6.1	Authentication Service .....	4
6.1.1	DoLogin.....	4
6.2	Integration Service .....	5
6.2.1	GetStores Service .....	5
6.2.2	GetSales.....	6
6.2.3	GetMessages .....	7
6.2.4	GetAllUserMessage .....	8
6.2.5	SendUserMessage .....	9
6.2.6	SetMessageRead .....	10
6.2.7	ConfirmOrRejectOrderItem.....	11
6.2.8	GetIntegrationShipmentCompanies.....	12
6.2.9	SetOrderShipmentInformation .....	13
7	Appendix.....	14
7.1	Classes .....	14
7.1.1	Common Classes.....	14
7.1.2	Criteria Classes .....	14
7.1.3	Integration Classes .....	16
7.2	Constants.....	18
7.2.1	Integration .....	18
7.2.2	Message Type .....	18
7.2.3	Order Listing Status .....	18
7.2.4	OrderItemStatus.....	19
7.3	Error List .....	20
7.3.1	General .....	20



## 1 Updates

Version	Date	Description
1.0	11.07.2015	Login service added.
		GetStores service added.
		GetSales service added.
		GetMessages service added.
		SendUserMessage service added.
1.1	12.10.2015	GetAllUserMessage service added.
		ConfirmOrRejectOrderItem service added.
		GetIntegrationShipmentCompanies service added.
		SetOrderShipmentInformation service added.

2



+90 850 840 77 77



[www.stockmount.com](http://www.stockmount.com)

## 2 Introduction

StockMount API services can be used to get sales, messages, shipment etc. information from StockMount. You can integrate some information to your ERP system using by these services. Being a StockMount member is enough to use these services.

## 3 Writing Markings

\* required fields

\*\* Only one of the fields is necessary

## 4 Service Address and Requirements

You can use below link to reach StockMount API services

<https://out.stockmount.com/>

## 5 Authentication and Security

To use services you need to take a “token” using by username and password. You can use this token to use all API services methods.



+90 850 840 77 77



www.stockmount.com

## 6 Services

### 6.1 Authentication Service

#### 6.1.1 DoLogin

You can use this method to login API service. You can use received ApiCode value to call other methods. You can recall this methot to get new ApiCode value when the session timed out

You get (00006) error code when the session timed out.

#### Request (POST)

<https://out.stockmount.com/api/user/dologin>

Parameter Name	Type	Description
Login	Login Object	User credentials. <a href="#">See Login</a>

#### Response [See ResultInfo](#)

```
{
  Result: true,
  Message: "",
  ErrorCode: null,
  ErrorMessage: null,
  Response: {
    UserId : 5688,
    Username : "Someuser",
    Email : "mail@example.com",
    Name : "name",
    Surname : "surname",
    Avatar : "avatar link",
    ApiCode : "XXXXXXXX"
  }
}
```



## 6.2 Integration Service

### 6.2.1 GetStores Service

This method gets current user store(s) information.

#### Request (POST)

<https://out.stockmount.com/api/Integration/GetStore>

Parameter Name	Type	Description
getStoreCriteria	GetStoreCriteria	Get stores criteria. <a href="#">See GetStoreCriteria</a>

#### Response [See ResultInfo](#)

```
{
  Result: true,
  Message: "",
  ErrorCode: null,
  ErrorMessage: null,
  Response: [{
    StoreId : 1,
    StoreName : "Store 1",
    IntegrationId : 1,
    IntegrationName : "Integration 1"
  },
  {
    StoreId : 2,
    StoreName : "Store 2",
    IntegrationId : 2,
    IntegrationName : "Integration 2"
  }
  ]
}
```



### 6.2.2 GetSales

This method gets sales based on store and order status.

#### Request (POST)

<https://out.stockmount.com/api/Integration/GetSales>

Parameter Name	Type	Description
getSaleCriteria	GetSaleCriteria	Get sales criteria. <a href="#">See GetSaleCriteria</a>

Response [See ResultInfo](#){

```
Result: true,
Message: "",
ErrorCode: null,
ErrorMessage: null,
Response: {
  TotalOrderCount : 10,
  TotalNotInvoicedCount : 2,
  TotalUnreadCount : 1,
  Orders : [{
    OrderId : 1111,
    Name : "name1",
    Surname : "surname1",
    Nickname : "nickname1",
    IntegrationOrderCode : "123456788",
    OrderDate : "08.05.2015",
    Fullname : "fullname1",
    OrderStatus : "new",
    Telephone : "+908508407777",
    TaxAuthority : "taxauthority1",
    TaxNumber : "taxnumber1",
    City : "city1",
    Address : "address1",
    OrderDetails : [{
      OrderDetailId : 555,
      ProductId : 5688,
      IntegrationProductCode : "code",
      ProductName : "name",
      ProductImage : "imagelink",
      TaxRate : 18,
      Price : 8.90,
      Quantity : 1,
      Invoiced : false,
      Unread : false,
      DeliveryTitle : "DeliveryTitle",
      ProductSourceName : "ProductSourceName",
      Telephone : "+908508407777",
      Address : "address",
      ShipmentPayment : "CargoPayment",
      ShipmentCompany : "CargoCompany",
      ShipmentLabelCode : "ShippmentLabelCode",
      ShipmentDate : 08.07.2015
    }]
  }]
}
```



### 6.2.3 GetMessages

This method gives messages based on store and type.

#### Request (POST)

<https://out.stockmount.com/api/Integration/GetMessages>

Parameter Name	Type	Description
getMessageCriteria	GetMessageCriteria	Get messages criteria. <a href="#">See GetMessageCriteria</a>

#### Response [See ResultInfo](#)

```
{
  Result: true,
  Message: "",
  ErrorCode: null,
  ErrorMessage: null,
  Response: {
    MessageCount : 10,
    Messages : [{
      UserMessageId : 1,
      Code : "Code",
      Subject : "Code",
      From : "From",
      To : "To",
      MessageTypeId : 1,
      Avatar : "Avatar",
      Body : "Body",
      Time : "",
      Unread : true,
      Surname : "Surname",
      Name : "Name"
    },
    {
      UserMessageId : 2,
      Code : "Code",
      Subject : "Code",
      From : "From",
      To : "To",
      MessageTypeId : 1,
      Avatar : "Avatar",
      Body : "Body",
      Time : "",
      Unread : false,
      Surname : "Surname",
      Name : "Name"
    }
  ]
}
```





#### 6.2.4 GetAllUserMessage

This method gets all messages history of specific user.

##### Request (POST)

<https://out.stockmount.com/api/Integration/GetAllUserMessage>

Parameter Name	Type	Description
getMessageCriteria	GetMessageCriteria	Get messages criteria. <a href="#">See GetAllUserMessageCriteria</a>

##### Response [See ResultInfo](#)

```
{
  Result: true,
  Message: "",
  ErrorCode: null,
  ErrorMessage: null,
  Response: {
    MessageCount : 10,
    Messages : [{
      UserMessageId : 1,
      Code : "Code",
      Subject : "Code",
      From : "From",
      To : "To",
      MessageTypeId : 1,
      Avatar : "Avatar",
      Body : "Body",
      Time : "",
      Unread : true,
      Surname : "Surname",
      Name : "Name"
    },
    {
      UserMessageId : 2,
      Code : "Code",
      Subject : "Code",
      From : "From",
      To : "To",
      MessageTypeId : 1,
      Avatar : "Avatar",
      Body : "Body",
      Time : "",
      Unread : false,
      Surname : "Surname",
      Name : "Name"
    }
  ]
}
```



### 6.2.5 SendUserMessage

This method allows you to send message to specific user.

#### Request (POST)

<https://out.stockmount.com/api/Integration/SendUserMessage>

Parameter Name	Type	Description
setMessageCriteria	SetMessageCriteria	Sent message criteria. <a href="#">See SetMessageCriteria</a>

#### Response [See ResultInfo](#)

```
{  
  Result: true,  
  Message: "",  
  ErrorCode: null,  
  ErrorMessage: null,  
  Response: null  
}
```



### 6.2.6 SetMessageRead

This method sets specific message read.

#### Request (POST)

<https://out.stockmount.com/api/Integration/SetMessageRead>

Parameter Name	Type	Description
setMessageCriteria	SetMessageCriteria	Set message read criteria. <a href="#">See SetMessageReadCriteria</a>

#### Response [See ResultInfo](#)

```
{
  Result: true,
  Message: "",
  ErrorCode: null,
  ErrorMessage: null,
  Response: null
}
```



### 6.2.7 ConfirmOrRejectOrderItem

This method confirms or rejects specific order item.

11

#### Request (POST)

<https://out.stockmount.com/api/Integration/ConfirmOrRejectOrderItem>

Parameter Name	Type	Description
setMessageCriteria	SetMessageCriteria	Confirm or reject orderItem criteria. <a href="#">See ConfirmOrRejectOrderItemCriteria</a>

#### Response [See ResultInfo](#)

```
{
  Result: true,
  Message: "",
  ErrorCode: null,
  ErrorMessage: null,
  Response: null
}
```



+90 850 840 77 77



[www.stockmount.com](http://www.stockmount.com)

### 6.2.8 GetIntegrationShipmentCompanies

This method gets shipment companies for specific e-commerce place.

#### Request (POST)

<https://out.stockmount.com/api/Integration/GetIntegrationShipmentCompanies>

Parameter Name	Type	Description
setMessageCriteria	SetMessageCriteria	Get integration shipment company criteria. <a href="#">See GetIntegrationShipmentCompanyCriteria</a>

#### Response [See ResultInfo](#)

```
{
  Result: true,
  Message: "",
  ErrorCode: null,
  ErrorMessage: null,
  Response: [{
    IntegrationShipmentId: 6
    IntegrationId: 2
    Code: "25050"
    Name: "Aramex"
    ShortName: "ARX"
  },
  {
    IntegrationShipmentId: 7
    IntegrationId: 2
    Code: "345"
    Name: "Aras"
    ShortName: "AR"
  }
]
```



### 6.2.9 SetOrderShipmentInformation

This method sets shipment information of specific order item.

#### Request (POST)

<https://out.stockmount.com/api/Integration/SetOrderShipmentInformation>

Parameter Name	Type	Description
setMessageCriteria	SetMessageCriteria	Set shipment criteria. <a href="#">See SetShipmentCriteria</a>

#### Response [See ResultInfo](#)

```
{
  Result: true,
  Message: "",
  ErrorCode: null,
  ErrorMessage: null,
  Response: null
}
```



## 7 Appendix

### 7.1 Classes

#### 7.1.1 Common Classes

##### 7.1.1.1 Login

Property	Type	Description
<b>Username*</b>	String	StockMount username
<b>Password*</b>	String	StockMount password

##### 7.1.1.2 ResultInfo

Property	Type	Description
Result	Boolean	Transaction result (Success: true, Error: false)
Message	String	Result message
ErrorCode	String	Error code
ErrorMessage	String	Error message
Response	Object	Response object for successful transaction

#### 7.1.2 Criteria Classes

##### 7.1.2.1 GetStoreCriteria

Property	Type	Description
<b>ApiCode*</b>	String	StockMount token
StoreId	int	Store id
IntegrationId	int	Integration id. <a href="#">See Integration</a>

##### 7.1.2.2 GetSaleCriteria

Property	Type	Description
<b>ApiCode*</b>	String	StockMount token
<b>StoreId*</b>	Int	Store id
<b>OrderStatus*</b>	String	Order status <a href="#">See OrderListingStatus</a>
SmallestOrderDetailId	Int	Smallest Order Detail Id (Get orders have id's bigger than this order id.)
BiggestOrderDetailId	Int	Biggest Order Detail Id (Get orders have id's bigger than this order id.)

##### 7.1.2.3 GetMessageCriteria

Property	Type	Description
<b>ApiCode*</b>	String	StockMount token
<b>StoreId*</b>	Int	Store Id
<b>MessageType*</b>	Int	Message type <a href="#">See MessageType</a>
User	String	User
Smallest Message Id	Int	Smallest Message Id (Get messages have id's bigger than this message id)
Biggest Message Id	Int	Biggest Message Id (Get messages have id's less than this message id)

##### 7.1.2.4 SetMessageReadCriteria

Property	Type	Description
<b>ApiCode*</b>	String	StockMount token
<b>StoreId*</b>	Int	Store Id
<b>IntegrationId*</b>	Int	Integration id. <a href="#">See Integration</a>



<b>UserMessageId*</b>	String	User message id
<b>UserMessageCode*</b>	String	Integration user message code

#### 7.1.2.5 GetAllUserMessageCriteria

Property	Type	Description
<b>ApiCode*</b>	String	StockMount token
<b>StoreId*</b>	Int	Store Id
<b>MessageTypeId*</b>	Int	Message type <a href="#">See MessageType</a>
<b>User*</b>	String	User
Smallest Message Id	Int	Smallest Message Id (Get messages have id's bigger than this message id)
Biggest Message Id	Int	Biggest Message Id (Get messages have id's less than this message id)

#### 7.1.2.6 SetMessageCriteria

Property	Type	Description
<b>ApiCode*</b>	String	StockMount token
<b>StoreId*</b>	Int	Store Id
<b>IntegrationId*</b>	Int	Integration id. <a href="#">See Integration</a>
<b>UserMessageId*</b>	String	User message id
<b>UserMessageCode*</b>	String	Integration user message code
<b>From*</b>	String	From
<b>To*</b>	String	To
<b>Subject*</b>	String	Subject
<b>Message*</b>	String	Message body
SetMessageRead	Boolean	Set message read

#### 7.1.2.7 ConfirmOrRejectOrderItemCriteria

Property	Type	Description
<b>ApiCode*</b>	String	StockMount token
<b>StoreId*</b>	Int	Store Id
<b>IntegrationId*</b>	Int	Integration id. <a href="#">See Integration</a>
<b>IntegrationOrderDetailId*</b>	Int	Integration Order Detail Id
<b>Status*</b>	Int	Status <a href="#">See OrderItemStatus</a>

#### 7.1.2.8 GetIntegrationShipmentCompanyCriteria

Property	Type	Description
<b>ApiCode*</b>	String	StockMount token
IntegrationId	Int	Integration id. <a href="#">See Integration</a>

#### 7.1.2.9 SetShipmentCriteria

Property	Type	Description
<b>ApiCode*</b>	String	StockMount token
<b>StoreId*</b>	Int	Store Id
<b>IntegrationId*</b>	Int	Integration id. <a href="#">See Integration</a>
IntegrationOrderCode	Int	Integration Order Code
<b>ShipmentCompany*</b>	String	Shipment Company
<b>ShipmentTrackingCode*</b>	String	Shipment Tracking Code
<b>ShipmentBranch*</b>	String	Shipment Branch
CampaignNumber	String	Campaign Number





ShipmentCompanyId	Long	Shipment Company Id
<b>OrderDetailId*</b>	Int	Order Detail Id
SendShipmentInformation	Boolean	Send shipment information

### 7.1.3 Integration Classes

#### 7.1.3.1 Store

Property	Type	Description
StoreId	Int	Store id
StoreName	String	Store name
IntegrationId	Int	Integration id. <a href="#">See Integration</a>
IntegrationName	String	Integration name

#### 7.1.3.2 Order

Property	Type	Description
OrderId	Int	StockMount order id
Nickname	String	Nickname
Name	String	Customer first name
Surname	String	Customer surname
OrderDate	DateTime	Order date and time
IntegrationOrderCode	String	Integration order code
OrderStatus	String	Order listing status. <a href="#">See Order Listing Status</a>
Fullname	String	Full name
PersonalIdentification	String	Personal identification
TaxNumber	String	Tax number
TaxAuthority	String	Tax authority
Telephone	String	Telephone
Address	String	Invoice address
District	String	Invoice district
City	String	Invoice city
Notes	String	Order notes
OrderDetails	Array of OrderDetail	Order items. <a href="#">See OrderDetail</a>



7.1.3.3 OrderDetail

Property	Type	Description
OrderDetailId	Int	Order item id
ProductId	Int	Product id
IntegrationProductCode	String	Integration product code
ProductName	String	Product name
Quantity	Int	Quantity
Price	Decimal	Price
Telephone	String	Delivery phone
Address	String	Delivery address
City	String	Delivery city
ShipmentDate	DateTime	Shipment date and time
ShipmentCompany	String	Shipment company
ShipmentLabelCode	String	Shipment reference code
ShipmentPayment	String	Shipment payment.
DeliveryTitle	String	Delivery title
TaxRate	Decimal	Tax rate
Invoiced	Boolean	Invoiced
ProductSourceName	String	Product source name
ProductImage	String	Product image link

7.1.3.4 UserMessage

Property	Type	Description
UserMessageId	String	User message id
Code	String	Code
From	String	From
To	String	To
Subject	String	Subject
Body	String	Body
Unread	Boolean	Unread
Name	String	Name
Surname	String	Surname
Avatar	String	Avatar
Time	DateTime	Time



## 7.2 Constants

### 7.2.1 Integration

Code	Description
1	GiittiGidiyor
2	N11
3	NeTicaret
4	ePTTAvm
5	OpenCart
6	SanalPazar
9999	StockMount

### 7.2.2 Message Type

Code	Description
1	Inbox
2	Sent

### 7.2.3 Order Listing Status

#### 7.2.3.1 GittiGidiyor

Code	Description
P	Waiting Payment
S	Waiting Cargo
C	Waiting Confirmation
T	Money Transfer
R	Returned Order
O	Completed

#### 7.2.3.2 N11

Code	Description
New	New order
Approved	Approved order
Shipped	Shipped
Rejected	Rejected
Delivered	Delivered
Completed	Completed



#### 7.2.3.3 SanalPazar

Code	Description
ODEME_ONAYI_BEKLENIYOR	Payment Confirmation
KARGO_GONDERIMI_BEKLENIYOR	Waiting Shipment
KARGO_ALICIYA_ULASMADI	Shipment Not Received
KARGO_TESLIMATI_BEKLENIYOR	Shipment On Way
ALICI_URUNU_ONAYLADI	Customer Confirmed
ALICI_URUNU_IADE_ETTI	Customer Returned
PARA_TRANSFERI_YAPILDI	Money Transfer
ALICIYA_PARA_IADESI_YAPILDI	Money Refund
SIPARIS_ASKIYA_ALINDI	Order Suspended
SATICI_IPTAL_ETTI	Seller Cancelled
ALICI_IPTAL_ETTI	Customer Cancelled
SANALPAZAR_IPTAL_ETTI	SanalPazar Cancelled

#### 7.2.3.4 StockMount

Code	Description
New	New order
Approved	Approved order
Shipped	Shipped
Rejected	Rejected
Delivered	Delivered
Completed	Completed

#### 7.2.4 OrderItemStatus

Code	Description
1	Confirm
2	Reject



## 7.3 Error List

### 7.3.1 General

Code	Description
00001	Not authenticated!
00002	Account is passive!
00003	Missing parameter!
00004	Required field!
00005	Bad request!
00006	Session timed out!
10001	Invalid Store!
60001	Integration error !
60002	Sale item was shipped before!
99999	Unexpected error!

