



StockMount API Services
Application Guide
Version 1.1

12.10.2015

Content

| | | |
|-------|---------------------------------------|----|
| 1 | Updates | 3 |
| 2 | Introduction..... | 4 |
| 3 | Writing Markings | 4 |
| 4 | Service Address and Requirements..... | 4 |
| 5 | Authentication and Security..... | 4 |
| 6 | Services..... | 5 |
| 6.1 | Authentication Service | 5 |
| 6.1.1 | DoLogin..... | 5 |
| 6.2 | General Service..... | 6 |
| 6.2.1 | GetCurrencies Service | 6 |
| 6.3 | Integration Service | 7 |
| 6.3.1 | GetStores Service | 7 |
| 6.3.2 | GetSales..... | 8 |
| 6.3.3 | GetMessages | 10 |
| 6.3.4 | GetAllUserMessage | 11 |
| 6.3.5 | SendUserMessage | 12 |
| 6.3.6 | SetMessageRead | 13 |
| 6.3.7 | ConfirmOrRejectOrderItem..... | 14 |
| 6.3.8 | GetIntegrationShipmentCompanies..... | 15 |
| 6.3.9 | SetOrderShipmentInformation | 16 |
| 6.4 | Product Service..... | 17 |
| 6.4.1 | GetProductSources Service | 17 |
| 6.4.2 | GetProductCategories Service..... | 18 |
| 6.4.3 | GetProduct Service..... | 19 |
| 6.4.4 | AddProduct Service | 20 |
| 6.4.5 | UpdateProduct Service..... | 21 |
| 6.4.6 | StopProduct Service | 22 |
| 6.4.7 | DeleteProduct Service | 23 |
| 6.4.8 | GetProducts Service | 24 |
| 7 | Appendix..... | 25 |
| 7.1 | Classes | 25 |
| 7.1.1 | Common Classes..... | 25 |



| | | |
|-------|----------------------------|----|
| 7.1.2 | Criteria Classes | 25 |
| 7.1.3 | Integration Classes | 29 |
| 7.2 | Constants | 33 |
| 7.2.1 | Integration | 33 |
| 7.2.2 | Message Type | 33 |
| 7.2.3 | Order Listing Status | 33 |
| 7.2.4 | OrderItemStatus | 34 |
| 7.2.5 | Status (product) | 34 |
| 7.2.6 | Product List Order | 35 |
| 7.2.7 | Order Direction | 35 |
| 7.3 | Error List | 36 |
| 7.3.1 | General | 36 |



1 Updates

| Version | Date | Description |
|---------|------------|---|
| 1.0 | 11.07.2015 | Login service added. |
| | | GetStores service added. |
| | | GetSales service added. |
| | | GetMessages service added. |
| | | SendUserMessage service added. |
| 1.1 | 12.10.2015 | GetAllUserMessage service added. |
| | | ConfirmOrRejectOrderItem service added. |
| | | GetIntegrationShipmentCompanies service added. |
| | | SetOrderShipmentInformation service added. |
| 1.2 | 09.05.2016 | GetCurrencies service added. |
| | | GetProductSources service added. |
| | | GetProductCategories service added. |
| | | GetProduct service added. |
| | | AddProduct service added. |
| | | UpdateProduct service added. |
| | | StopProduct service added. |
| | | DeleteProduct service added. |
| 1.3 | 12.04.2017 | GetProducts service added. |
| 1.3 | 11.05.2017 | GetSales invoice, waybill, package numbers added. |



2 Introduction

StockMount API services can be used to get sales, messages, shipment etc. information from StockMount. You can integrate some information to your ERP system using by these services. Being a StockMount member is enough to use these services.

3 Writing Markings

* required fields

** Only one of the fields is necessary

4 Service Address and Requirements

You can use below link to reach StockMount API services

<https://out.stockmount.com/>

5 Authentication and Security

To use services you need to take a “token” using by username and password. You can use this token to use all API services methods.



+90 850 840 77 77



www.stockmount.com

6 Services

6.1 Authentication Service

6.1.1 DoLogin

You can use this method to login API service. You can use received ApiCode value to call other methods. You can recall this methot to get new ApiCode value when the session timed out

You get (00006) error code when the session timed out.

Request (POST)

<https://out.stockmount.com/api/user/dologin>

| Parameter Name | Type | Description |
|----------------|--------------|---|
| Login | Login Object | User credentials. See Login |

Response [See ResultInfo](#)

```
{
  Result: true,
  Message: "",
  ErrorCode: null,
  ErrorMessage: null,
  Response: {
    UserId : 5688,
    Username : "Someuser",
    Email : "mail@example.com",
    Name : "name",
    Surname : "surname",
    Avatar : "avatar link",
    ApiCode : "XXXXXXXX"
  }
}
```



6.2 General Service

6.2.1 GetCurrencies Service

This service gets the available currencies in the system

Request (POST)

<https://out.stockmount.com/api/General/GetCurrencies>

| Parameter Name | Type | Description |
|---------------------|---------------------|--|
| getCurrencyCriteria | getCurrencyCriteria | Get currency criteria. See GetCurrencyCriteria |

Response [See ResultInfo](#)

```
{
  Result: true,
  Message: "",
  ErrorCode: null,
  ErrorMessage: null,
  Response: JSON of List<Currency>. See Currency
}
```



6.3 Integration Service

6.3.1 GetStores Service

This method gets current user store(s) information.

Request (POST)

<https://out.stockmount.com/api/Integration/GetStore>

| Parameter Name | Type | Description |
|------------------|------------------|---|
| getStoreCriteria | GetStoreCriteria | Get stores criteria. See GetStoreCriteria |

Response [See ResultInfo](#)

```
{
  Result: true,
  Message: "",
  ErrorCode: null,
  ErrorMessage: null,
  Response: [{
    StoreId : 1,
    StoreName : "Store 1",
    IntegrationId : 1,
    IntegrationName : "Integration 1"
  },
  {
    StoreId : 2,
    StoreName : "Store 2",
    IntegrationId : 2,
    IntegrationName : "Integration 2"
  }]
}
```



6.3.2 GetSales

This method gets sales based on store and order status.

Request (POST)

<https://out.stockmount.com/api/Integration/GetSales>

| Parameter Name | Type | Description |
|-----------------|-----------------|---|
| getSaleCriteria | GetSaleCriteria | Get sales criteria. See GetSaleCriteria |

Response [See ResultInfo](#){

```
Result: true,
Message: "",
ErrorCode: null,
ErrorMessage: null,
Response: {
  TotalOrderCount : 10,
  TotalNotInvoicedCount : 2,
  TotalUnreadCount : 1,
  Orders : [{
    OrderId : 1111,
    Name : "name1",
    Surname : "surname1",
    Nickname : "nickname1",
    IntegrationOrderCode : "123456788",
    OrderDate : "08.05.2015",
    Fullname : "fullname1",
    OrderStatus : "new",
    Telephone : "+908508407777",
    TaxAuthority : "taxauthority1",
    TaxNumber : "taxnumber1",
    City : "city1",
    Address : "address1",
    OrderDetails : [{
      OrderDetailId : 555,
      ProductId : 5688,
      IntegrationProductCode : "code",
      ProductName : "name",
      ProductImage : "imagelink",
      TaxRate : 18,
      Price : 8.90,
      Quantity : 1,
      Invoiced : false,
      Unread : false,
      DeliveryTitle : "DeliveryTitle",
      ProductSourceName : "ProductSourceName",
      Telephone : "+908508407777",
      Address : "address",
      ShipmentPayment : "CargoPayment",
      ShipmentCompany : "CargoCompany",
      ShipmentLabelCode : "ShippmentLabelCode",
      ShipmentDate : 08.07.2015,
      InvoiceNumber : "InvoiceNumber",
      WayBillNumber : "WayBillNumber",
      PackageNumber : "PackageNumber"
    ]
  ]
}
```



} } }

9



+90 850 840 77 77



www.stockmount.com

6.3.3 GetMessages

This method gives messages based on store and type.

Request (POST)

<https://out.stockmount.com/api/Integration/GetMessages>

| Parameter Name | Type | Description |
|--------------------|--------------------|---|
| getMessageCriteria | GetMessageCriteria | Get messages criteria. See GetMessageCriteria |

Response [See ResultInfo](#)

```
{
  Result: true,
  Message: "",
  ErrorCode: null,
  ErrorMessage: null,
  Response: {
    MessageCount : 10,
    Messages : [{
      UserMessageId : 1,
      Code : "Code",
      Subject : "Code",
      From : "From",
      To : "To",
      MessageTypeId : 1,
      Avatar : "Avatar",
      Body : "Body",
      Time : "",
      Unread : true,
      Surname : "Surname",
      Name : "Name"
    },
    {
      UserMessageId : 2,
      Code : "Code",
      Subject : "Code",
      From : "From",
      To : "To",
      MessageTypeId : 1,
      Avatar : "Avatar",
      Body : "Body",
      Time : "",
      Unread : false,
      Surname : "Surname",
      Name : "Name"
    }
  ]
}
```



6.3.4 GetAllUserMessage

This method gets all messages history of specific user.

11

Request (POST)

<https://out.stockmount.com/api/Integration/GetAllUserMessage>

| Parameter Name | Type | Description |
|--------------------|--------------------|--|
| getMessageCriteria | GetMessageCriteria | Get messages criteria. See GetAllUserMessageCriteria |

Response [See ResultInfo](#)

```
{
  Result: true,
  Message: "",
  ErrorCode: null,
  ErrorMessage: null,
  Response: {
    MessageCount : 10,
    Messages : [{
      UserMessageId : 1,
      Code : "Code",
      Subject : "Code",
      From : "From",
      To : "To",
      MessageTypeId : 1,
      Avatar : "Avatar",
      Body : "Body",
      Time : "",
      Unread : true,
      Surname : "Surname",
      Name : "Name"
    },
    {
      UserMessageId : 2,
      Code : "Code",
      Subject : "Code",
      From : "From",
      To : "To",
      MessageTypeId : 1,
      Avatar : "Avatar",
      Body : "Body",
      Time : "",
      Unread : false,
      Surname : "Surname",
      Name : "Name"
    }
  ]
}
```



6.3.5 SendUserMessage

This method allows you to send message to specific user.

Request (POST)

<https://out.stockmount.com/api/Integration/SendUserMessage>

| Parameter Name | Type | Description |
|--------------------|--------------------|---|
| setMessageCriteria | SetMessageCriteria | Sent message criteria. See SetMessageCriteria |

Response [See ResultInfo](#)

```
{  
  Result: true,  
  Message: "",  
  ErrorCode: null,  
  ErrorMessage: null,  
  Response: null  
}
```



6.3.6 SetMessageRead

This method sets specific message read.

Request (POST)

<https://out.stockmount.com/api/Integration/SetMessageRead>

| Parameter Name | Type | Description |
|--------------------|--------------------|---|
| setMessageCriteria | SetMessageCriteria | Set message read criteria. See SetMessageReadCriteria |

Response [See ResultInfo](#)

```
{  
  Result: true,  
  Message: "",  
  ErrorCode: null,  
  ErrorMessage: null,  
  Response: null  
}
```



6.3.7 ConfirmOrRejectOrderItem

This method confirms or rejects specific order item.

14

Request (POST)

<https://out.stockmount.com/api/Integration/ConfirmOrRejectOrderItem>

| Parameter Name | Type | Description |
|--------------------|--------------------|--|
| setMessageCriteria | SetMessageCriteria | Confirm or reject orderItem criteria. See ConfirmOrRejectOrderItemCriteria |

Response [See ResultInfo](#)

```
{
  Result: true,
  Message: "",
  ErrorCode: null,
  ErrorMessage: null,
  Response: null
}
```



+90 850 840 77 77



www.stockmount.com

6.3.8 GetIntegrationShipmentCompanies

This method gets shipment companies for specific e-commerce place.

Request (POST)

<https://out.stockmount.com/api/Integration/GetIntegrationShipmentCompanies>

| Parameter Name | Type | Description |
|--------------------|--------------------|--|
| setMessageCriteria | SetMessageCriteria | Get integration shipment company criteria. See GetIntegrationShipmentCompanyCriteria |

Response [See ResultInfo](#)

```
{
  Result: true,
  Message: "",
  ErrorCode: null,
  ErrorMessage: null,
  Response: [{
    IntegrationShipmentId: 6
    IntegrationId: 2
    Code: "25050"
    Name: "Aramex"
    ShortName: "ARX"
  },
  {
    IntegrationShipmentId: 7
    IntegrationId: 2
    Code: "345"
    Name: "Aras"
    ShortName: "AR"
  }
]
```



6.3.9 SetOrderShipmentInformation

This method sets shipment information of specific order item.

Request (POST)

<https://out.stockmount.com/api/Integration/SetOrderShipmentInformation>

| Parameter Name | Type | Description |
|--------------------|--------------------|--|
| setMessageCriteria | SetMessageCriteria | Set shipment criteria. See SetShipmentCriteria |

Response [See ResultInfo](#)

```
{
  Result: true,
  Message: "",
  ErrorCode: null,
  ErrorMessage: null,
  Response: null
}
```



6.4 Product Service

6.4.1 GetProductSources Service

This function gets the product sources

Request (POST)

<https://out.stockmount.com/api/Product/GetProductSources>

| Parameter Name | Type | Description |
|---------------------------|---------------------------|---|
| getProductSourcesCriteria | GetProductSourcesCriteria | See GetProductSourcesCriteria |

Response [See ResultInfo](#)

```
{
  Result: true,
  Message: "",
  ErrorCode: null,
  ErrorMessage: null,
  Response: [{
    ProductSourceId: 1
    Name: "Product Source 1"
  },
  {
    ProductSourceId: 2
    Name: "Product Source 2"
  }]
}
```



6.4.2 GetProductCategories Service

This function gets the categories of a product source with a given id

Request (POST)

<https://out.stockmount.com/api/Product/GetProductCategories>

| Parameter Name | Type | Description |
|----------------|------------------------------|--|
| criteria | GetProductCategoriesCriteria | See GetProductCategoriesCriteria |

Response [See ResultInfo](#)

```
{
  Result: true,
  Message: "",
  ErrorCode: null,
  ErrorMessage: null,
  Response: [{
    ProductCategoryId: 1
    Name: "Electronics"
  },
  {
    ProductCategoryId: 2
    Name: "Clothes"
  }]
}
```



6.4.3 GetProduct Service

This function returns a product given its Id

19

Request (POST)

<https://out.stockmount.com/api/Product/GetProduct>

| Parameter Name | Type | Description |
|--------------------|--------------------|--|
| getProductCriteria | GetProductCriteria | See GetProductCriteria |

Response [See ResultInfo](#)

```
{  
  Result: true,  
  Message: "",  
  ErrorCode: null,  
  ErrorMessage: null,  
  Response: JSON of Product. See Product  
}
```



+90 850 840 77 77



www.stockmount.com

6.4.4 AddProduct Service

This function adds a product and returns the id of the added product

20

Request (POST)

<https://out.stockmount.com/api/Product/AddProduct>

| Parameter Name | Type | Description |
|----------------|---------|-----------------------------|
| product | Product | See Product |

Response [See ResultInfo](#)

```
{  
  Result: true,  
  Message: "",  
  ErrorCode: null,  
  ErrorMessage: null,  
  Response: 7690660  
}
```



+90 850 840 77 77



www.stockmount.com

6.4.5 UpdateProduct Service

This function updates a product with the given id and returns the id of the updated product

21

Request (POST)

<https://out.stockmount.com/api/Product/UpdateProduct>

| Parameter Name | Type | Description |
|----------------|---------|-----------------------------|
| product | Product | See Product |

Response [See ResultInfo](#)

```
{  
  Result: true,  
  Message: "",  
  ErrorCode: null,  
  ErrorMessage: null,  
  Response: 7690663  
}
```



+90 850 840 77 77



www.stockmount.com

6.4.6 StopProduct Service

This function stops selling for a product with a given id

22

Request (POST)

<https://out.stockmount.com/api/Product/StopProduct>

| Parameter Name | Type | Description |
|--------------------|--------------------|--|
| getProductCriteria | GetProductCriteria | See GetProductCriteria |

Response [See ResultInfo](#)

```
{  
  Result: true,  
  Message: "",  
  ErrorCode: null,  
  ErrorMessage: null,  
  Response: 7694323  
}
```



+90 850 840 77 77



www.stockmount.com

6.4.7 DeleteProduct Service

This function deletes selling for a product with a given id

23

Request (POST)

<https://out.stockmount.com/api/Product/DeleteProduct>

| Parameter Name | Type | Description |
|--------------------|--------------------|--|
| getProductCriteria | GetProductCriteria | See GetProductCriteria |

Response [See ResultInfo](#)

```
{  
  Result: true,  
  Message: "",  
  ErrorCode: null,  
  ErrorMessage: null,  
  Response: 7694323  
}
```



+90 850 840 77 77



www.stockmount.com

6.4.8 GetProducts Service

This function searched products of a product source upon a criteria

Request (POST)

<https://out.stockmount.com/api/Product/GetProducts>

| Parameter Name | Type | Description |
|---------------------|---------------------|---|
| getProductsCriteria | GetProductsCriteria | See GetProductsCriteria |

Response [See ResultInfo](#)

```
{  
  Result: true,  
  Message: "",  
  ErrorCode: null,  
  ErrorMessage: null,  
  Response: JSON of Product List. See Product  
}
```



7 Appendix

7.1 Classes

7.1.1 Common Classes

7.1.1.1 Login

| Property | Type | Description |
|------------------|--------|---------------------|
| Username* | String | StockMount username |
| Password* | String | StockMount password |

7.1.1.2 ResultInfo

| Property | Type | Description |
|--------------|---------|--|
| Result | Boolean | Transaction result (Success: true, Error: false) |
| Message | String | Result message |
| ErrorCode | String | Error code |
| ErrorMessage | String | Error message |
| Response | Object | Response object for successful transaction |

7.1.2 Criteria Classes

7.1.2.1 GetStoreCriteria

| Property | Type | Description |
|-----------------|--------|---|
| ApiCode* | String | StockMount token |
| StoreId | int | Store id |
| IntegrationId | int | Integration id. See Integration |

7.1.2.2 GetSaleCriteria

| Property | Type | Description |
|-----------------------|--------|--|
| ApiCode* | String | StockMount token |
| StoreId* | Int | Store id |
| OrderStatus* | String | Order status See OrderListingStatus |
| SmallestOrderDetailId | Int | Smallest Order Detail Id (Get orders have id's bigger than this order id.) |
| BiggestOrderDetailId | Int | Biggest Order Detail Id (Get orders have id's bigger than this order id.) |

7.1.2.3 GetMessageCriteria

| Property | Type | Description |
|---------------------|--------|--|
| ApiCode* | String | StockMount token |
| StoreId* | Int | Store Id |
| MessageType* | Int | Message type See MessageType |
| User | String | User |
| Smallest Message Id | Int | Smallest Message Id (Get messages have id's bigger than this message id) |
| Biggest Message Id | Int | Biggest Message Id (Get messages have id's less than this message id) |



7.1.2.4 SetMessageReadCriteria

| Property | Type | Description |
|-------------------------|--------|---|
| ApiCode* | String | StockMount token |
| StoreId* | Int | Store Id |
| IntegrationId* | Int | Integration id. See Integration |
| UserMessageId* | String | User message id |
| UserMessageCode* | String | Integration user message code |

7.1.2.5 GetAllUserMessageCriteria

| Property | Type | Description |
|---------------------|--------|--|
| ApiCode* | String | StockMount token |
| StoreId* | Int | Store Id |
| MessageType* | Int | Message type See MessageType |
| User* | String | User |
| Smallest Message Id | Int | Smallest Message Id (Get messages have id's bigger than this message id) |
| Biggest Message Id | Int | Biggest Message Id (Get messages have id's less than this message id) |

7.1.2.6 SetMessageCriteria

| Property | Type | Description |
|-------------------------|---------|---|
| ApiCode* | String | StockMount token |
| StoreId* | Int | Store Id |
| IntegrationId* | Int | Integration id. See Integration |
| UserMessageId* | String | User message id |
| UserMessageCode* | String | Integration user message code |
| From* | String | From |
| To* | String | To |
| Subject* | String | Subject |
| Message* | String | Message body |
| SetMessageRead | Boolean | Set message read |

7.1.2.7 ConfirmOrRejectOrderItemCriteria

| Property | Type | Description |
|----------------------------------|--------|---|
| ApiCode* | String | StockMount token |
| StoreId* | Int | Store Id |
| IntegrationId* | Int | Integration id. See Integration |
| IntegrationOrderDetailId* | Int | Integration Order Detail Id |
| Status* | Int | Status See OrderItemStatus |

7.1.2.8 GetIntegrationShipmentCompanyCriteria

| Property | Type | Description |
|-----------------|--------|---|
| ApiCode* | String | StockMount token |
| IntegrationId | Int | Integration id. See Integration |



7.1.2.9 SetShipmentCriteria

| Property | Type | Description |
|------------------------------|---------|---|
| ApiCode* | String | StockMount token |
| StoreId* | Int | Store Id |
| IntegrationId* | Int | Integration id. See Integration |
| IntegrationOrderCode | Int | Integration Order Code |
| ShipmentCompany* | String | Shipment Company |
| ShipmentTrackingCode* | String | Shipment Tracking Code |
| ShipmentBranch* | String | Shipment Branch |
| CampaignNumber | String | Campaign Number |
| ShipmentCompanyId | Long | Shipment Company Id |
| OrderDetailId* | Int | Order Detail Id |
| SendShipmentInformation | Boolean | Send shipment information |

7.1.2.10 GetProductSourcesCriteria

| Property | Type | Description |
|-----------------|--------|------------------|
| ApiCode* | String | StockMount token |

7.1.2.11 GetProductCategoriesCriteria

| Property | Type | Description |
|-------------------------|--------|-------------------|
| ApiCode* | String | StockMount token |
| ProductSourceId* | Int | Product source id |

7.1.2.12 GetProductCriteria

| Property | Type | Description |
|-------------------|--------|----------------------|
| ApiCode* | String | StockMount token |
| ProductId* | Int | Requested Product id |

7.1.2.13 GetCurrencyCriteria

| Property | Type | Description |
|-----------------|--------|------------------|
| ApiCode* | String | StockMount token |



7.1.2.14 *GetProductsCriteria*

| Property | Type | Description |
|-------------------------|----------|---|
| ApiCode* | String | StockMount token |
| ProductSourceId* | Int | Product Source Id |
| ProductId | Int | Product Id |
| ProductCode | String | Product Code |
| Keywords | String | Product Name |
| ProductCategory | String | Product Category |
| PriceFrom | Decimal | Product Price From |
| PriceTo | Decimal | Product Price To |
| QuantityFrom | Int | Product Quantity From |
| QuantityTo | Int | Product Quantity To |
| CurrencyId | Int | Product Currency. See GetCurrenciesService and Currency |
| ProductStatus | Int | Product Status (Default: -1) . See Status |
| CreationTimeFrom | DateTime | Product Creation Time From |
| CreationTimeTo | DateTime | Product Creation Time To |
| RowsByPage | Int | Rows By Page (Max: 100) |
| PageIndex | Int | Page Index |
| OrderBy | String | Products List Order. See Product List Order |
| OrderDirection | String | Products List Order Direction. See Order Direction |



7.1.3 Integration Classes

7.1.3.1 Store

| Property | Type | Description |
|-----------------|--------|---|
| StoreId | Int | Store id |
| StoreName | String | Store name |
| IntegrationId | Int | Integration id. See Integration |
| IntegrationName | String | Integration name |

7.1.3.2 Order

| Property | Type | Description |
|------------------------|----------------------|--|
| OrderId | Int | StockMount order id |
| Nickname | String | Nickname |
| Name | String | Customer first name |
| Surname | String | Customer surname |
| OrderDate | DateTime | Order date and time |
| IntegrationOrderCode | String | Integration order code |
| OrderStatus | String | Order listing status. See Order Listing Status |
| FullName | String | Full name |
| PersonalIdentification | String | Personal identification |
| TaxNumber | String | Tax number |
| TaxAuthority | String | Tax authority |
| Telephone | String | Telephone |
| Address | String | Invoice address |
| District | String | Invoice district |
| City | String | Invoice city |
| Notes | String | Order notes |
| OrderDetails | Array of OrderDetail | Order items. See OrderDetail |



7.1.3.3 OrderDetail

| Property | Type | Description |
|------------------------|----------|--------------------------|
| OrderDetailId | Int | Order item id |
| ProductId | Int | Product id |
| IntegrationProductCode | String | Integration product code |
| ProductName | String | Product name |
| Quantity | Int | Quantity |
| Price | Decimal | Price |
| Telephone | String | Delivery phone |
| Address | String | Delivery address |
| City | String | Delivery city |
| ShipmentDate | DateTime | Shipment date and time |
| ShipmentCompany | String | Shipment company |
| ShipmentLabelCode | String | Shipment reference code |
| ShipmentPayment | String | Shipment payment. |
| DeliveryTitle | String | Delivery title |
| TaxRate | Decimal | Tax rate |
| Invoiced | Boolean | Invoiced |
| ProductSourceName | String | Product source name |
| ProductImage | String | Product image link |
| InvoiceNumber | String | Invoice number |
| WayBillNumber | String | Waybill number |
| PackageNumber | String | Package number |

7.1.3.4 UserMessage

| Property | Type | Description |
|---------------|----------|-----------------|
| UserMessageId | String | User message id |
| Code | String | Code |
| From | String | From |
| To | String | To |
| Subject | String | Subject |
| Body | String | Body |
| Unread | Boolean | Unread |
| Name | String | Name |
| Surname | String | Surname |
| Avatar | String | Avatar |
| Time | DateTime | Time |



7.1.3.5 Product

| Property | Type | Description |
|--|----------------------|---|
| ApiCode* | String | StockMount token |
| ProductId* <small>(not required in AddProduct)</small> | Int | Product id |
| ProductSourceId* | Int | Product source id |
| Description | String | Description of product |
| Code* | String | Product code |
| Code2 | String | Product code 2 |
| Barcode | String | Product barcode |
| Name* | String | Product name |
| Subtitle | String | Product secondary title |
| Price* | Decimal | Product price |
| Quantity | Int | Product available quantity |
| Brand | String | Product brand |
| TaxRate | Decimal | Tax rate of the product |
| Model | String | Product model |
| Category* | String | Product category name |
| CurrencyId* | Int | See GetCurrenciesService and Currency |
| Images* | List<ProductImage> | Product images. See ProductImage |
| MarketPrice | Decimal | Product market price |
| Status | Int | Product status. See Status |
| Volume | Decimal | Product volume |
| Height | Decimal | Product Height |
| Length | Decimal | Product length |
| Width | Decimal | Product Width |
| VariantName1 | String | Product Variant 1 name |
| VariantName2 | String | Product Variant 2 name |
| VariantName3 | String | Product Variant 3 name |
| VariantName4 | String | Product Variant 4 name |
| Variants | List<ProductVariant> | Product variants. See ProductVariant |
| Specs | List<ProductSpec> | Product specifications. See ProductSpec |

7.1.3.6 ProductImage

| Property | Type | Description |
|----------|--------|-------------|
| Order | Int | Image order |
| Url | String | Image URL |



7.1.3.7 *ProductVariant*

| Property | Type | Description |
|---------------|---------|--|
| Code | String | Variant code |
| Price | Decimal | Variant price |
| Quantity | Int | Variant available quantity |
| Barcode | String | Variant barcode |
| CurrencyId | Int | Currency id. See GetCurrenciesService and Currency |
| ImageUrl | String | Variant image URL |
| VariantValue1 | String | Value of variant 1 |
| VariantValue2 | String | Value of variant 2 |
| VariantValue3 | String | Value of variant 3 |
| VariantValue4 | String | Value of variant 4 |

7.1.3.8 *ProductSpec*

| Property | Type | Description |
|----------|--------|---------------------|
| Name* | String | Specification name |
| Value* | String | Specification value |

7.1.3.9 *Currency*

| Property | Type | Description |
|------------|--------|---------------|
| CurrencyId | Int | Currency id |
| Code | String | Currency code |
| Name | String | Currency name |



7.2 Constants

7.2.1 Integration

| Code | Description |
|------|---------------|
| 1 | GiittiGidiyor |
| 2 | N11 |
| 3 | NeTicaret |
| 4 | ePTTAvm |
| 5 | OpenCart |
| 6 | SanalPazar |
| 8 | HepsiBurada |
| 9999 | StockMount |

7.2.2 Message Type

| Code | Description |
|------|-------------|
| 1 | Inbox |
| 2 | Sent |

7.2.3 Order Listing Status

7.2.3.1 GittiGidiyor

| Code | Description |
|------|----------------------|
| P | Waiting Payment |
| S | Waiting Cargo |
| C | Waiting Confirmation |
| T | Money Transfer |
| R | Returned Order |
| O | Completed |

7.2.3.2 N11

| Code | Description |
|-----------|----------------|
| New | New order |
| Approved | Approved order |
| Shipped | Shipped |
| Rejected | Rejected |
| Delivered | Delivered |
| Completed | Completed |



7.2.3.3 SanalPazar

| Code | Description |
|-----------------------------|-----------------------|
| ODEME_ONAYI_BEKLENIYOR | Payment Confirmation |
| KARGO_GONDERIMI_BEKLENIYOR | Waiting Shipment |
| KARGO_ALICIYA_ULASMADI | Shipment Not Received |
| KARGO_TESLIMATI_BEKLENIYOR | Shipment On Way |
| ALICI_URUNU_ONAYLADI | Customer Confirmed |
| ALICI_URUNU_IADE_ETTI | Customer Returned |
| PARA_TRANSFERI_YAPILDI | Money Transfer |
| ALICIYA_PARA_IADESI_YAPILDI | Money Refund |
| SIPARIS_ASKIYA_ALINDI | Order Suspended |
| SATICI_IPTAL_ETTI | Seller Cancelled |
| ALICI_IPTAL_ETTI | Customer Cancelled |
| SANALPAZAR_IPTAL_ETTI | SanalPazar Cancelled |

7.2.3.4 Hepsiburada

| Code | Description |
|----------|-------------|
| Open | Open |
| Unpacked | Unpacked |

7.2.3.5 StockMount

| Code | Description |
|-----------|----------------|
| New | New order |
| Approved | Approved order |
| Shipped | Shipped |
| Rejected | Rejected |
| Delivered | Delivered |
| Completed | Completed |

7.2.4 OrderItemStatus

| Code | Description |
|------|-------------|
| 1 | Confirm |
| 2 | Reject |

7.2.5 Status (product)

| Code | Description |
|------|-------------|
| 0 | Not Changed |
| 1 | New |
| 2 | Changed |
| 3 | Deleted |
| 4 | Re-listed |



7.2.6 Product List Order

| Code | Description |
|-----------|---------------------------|
| ProductId | Order by ProductId |
| Code | Order by product code |
| Name | Order by product name |
| Price | Order by product price |
| Quantity | Order by product quantity |
| Category | Order by product Category |

7.2.7 Order Direction

| Code | Description |
|------|-------------|
| ASC | Ascending |
| DESC | Descending |



7.3 Error List

7.3.1 General

36

| Code | Description |
|-------|-------------------------------|
| 00001 | Not authenticated! |
| 00002 | Account is passive! |
| 00003 | Missing parameter! |
| 00004 | Required field! |
| 00005 | Bad request! |
| 00006 | Session timed out! |
| 10001 | Invalid Store! |
| 60001 | Integration error ! |
| 60002 | Sale item was shipped before! |
| 99999 | Unexpected error! |



+90 850 840 77 77



www.stockmount.com