

6/10 meeting

應名宥

training result

model size = 4/5

training images = 80000

batch size = 8

training step = 0.5%

result



A living area with a television and a table.



A group of skiers are preparing to ski down a mountain.

random captions result



fake



real


new stuff

loss function


XMC-GAN

We thoroughly evaluate the different components of XMC-GAN and analyze their impact. Table 4 summarizes our ablations³ on the COCO-14 validation set. To study the effects of each contrastive loss component used in XMC-GAN, we experiment with four losses: (1) image-sentence, (2) region-word, (3) image-image using discriminator features, and (4) image-image using VGG features. For (3), we use the discriminator encoder projection (indicated by D in Table 4) to extract image features. For (4), we extract image features from a VGG-19 network [49] pretrained on ImageNet.

contrastive structure



(a) Original architecture for text to image synthesis



testing

- add text features mapping network
- add img-img discriminator contrastive loss
- disable img-txt discriminator contrastive loss

compare : img-txt loss



A living area with a television and a **table**.



A **green** train is coming down the tracks.

compare : img-img loss



A living area with a television and a **table**.



A **green** train is coming down the tracks.

same caption



img-txt loss



img-img loss

MOO

problem

problem

- high dimension problem
- stuck in the early part
- termination criterion
- adaptive inference
- parameter setting


termination criterion

- Number of Evaluations
- Number of Generations
- Based on Time
- Design Space Tolerance (?)


adaptive inference

- have label
 - calculate image-text score
 - calculate image-real score
 - calculate word-label score
- otherwise
 - calculate image-text score

crossover parameter




low




high

mutation parameter



low



high