

Event handling in Android

DT228/3

Dr. Susan McKeever



ANDROID

Event-driven programming

- Developing a GUI uses event driven programming..
 - Flow of program is driven by events
 - In this case, user actions
- Typically :
 - an “event” triggers .. E.g. button click
 - a “callback” method/ event handler
e.g. onClick()

Event-driven programming

Android (and Java Swing) – 3 ways

1. Declare/implement “**listeners**” in the activity, with event handler methods – “LONG”!

OR

2. Use anonymous classes for each widget “MED”!

OR

3. Embed event handler method name in the XML (ANDROID only) - “EASY!”

Be aware of tradeoffs

First way... Listeners implemented in the class

```
public class MyPass extends Activity  
    implements View.OnClickListener {
```

```
    @Override  
    public void onCreate(Bundle savedInstanceState) {
```

```
        // other onCreate code  
        use Button class "setOnClickListener"  
        to assign the button listener;
```

```
    }
```

```
    public void onClick(View view) {  
        // do whatever you want as a result of the  
        // the button click;  
    }
```

```
}
```

1. Implement the
"listener" needed

2. Assigning that
listener to the
widget that takes
the user action (e.g.
button)

3. Implementing the
"behaviour" we
wanted when the
user action was
taken e.g. button
clicked

First way... Listeners implemented in the class – more than one button?

```
public class MainActivity extends Activity  
    implements View.OnClickListener {
```

```
    Button btn;  
    @Override  
    public void onCreate(Bundle savedInstanceState) {
```

```
        // other onCreate code
```

```
        btn = (Button)findViewById(R.id.whateverbuttoniscalled)  
        btn.setOnClickListener(this);
```

```
    }
```


```
    public void onClick(View view) {  
        // do whatever you want as a result of the  
        // the button click;
```

```
    }
```

```
}
```

What code needs to change?

The **onClick** Method Will be Shared Across more Than one Button.. Need to use The View object **getId** method to check which button was clicked..



Second way ... Use anonymous listener classes for each widget

```
public class MainActivity extends Activity {  
    private Button button;  
    public void onCreate(Bundle savedInstanceState) {  
        super.onCreate(savedInstanceState);  
        setContentView(R.layout.main);  
        button = (Button) findViewById(R.id.buttonToast);  
  
        button.setOnClickListener(// anonymous listener  
class goes here)  
    }  
}
```

Third way... Embed event handler method into XML

```
<?xml version="1.0" encoding="utf-8"?>
<LinearLayout
  xmlns:android="http://schemas.android.com/apk/res/android"
  android:layout_width="fill_parent"
  android:layout_height="fill_parent"
  android:orientation="vertical" >

  <Button
    android:id="@+id/buttonToast"
    android:layout_width="wrap_content"
    android:layout_height="wrap_content"
    android:onClick="showToast"
    android:text="Show Toast" />

</LinearLayout>
```

Third way... Embed callback method into XML

```
public class MainActivity extends Activity {  
    private Button button;  
    public void onCreate(Bundle savedInstanceState) {  
        super.onCreate(savedInstanceState);  
        setContentView(R.layout.main);  
        button = (Button) findViewById(R.id.buttonToast);  
  
        public void showToast(View v)  
        {  
            Toast.makeText(getApplicationContext(),  
                           "Button is clicked",  
                           Toast.LENGTH_LONG).show();  
        }  
    }  
}
```


Implementing event Programming –best way?

- Implement listeners as interfaces in the activity, with Shared event handlers
 - Shared listener across widgets .. shared callback + -
 - Longer to code - OR
- Anonymous class for each widget
 - **Can't reuse – separate class per widget -**
 - potential performance hit -
 - Easier to follow code? +

Implementing listeners

+s/ -s

- Put callback into the XML

Simplest to implement +

But

1. Presentation coupled with logic- bad -
2. Changes to method name - > need to remember to refactor the xml -
3. Multiple XML files using a single method can lead to maintenance problems if functionality diverges -

Examples of other widgets..using <EditText> in an activity

- Implement ?
- Respond to text changes?

How do we know which listener to implement?

e.g.

Could have a **checkbox** OR

A **button** OR

An **input field**.. etc

Is it the same listener for all widgets?

Unfortunately.. NO.. Need to use the right one, for the right Widget, and the right user action (clicking, hovering with the mouse etc)