FLAT PATTERN - viewed from bend-note face (UP = toward viewer) scale 1:1

red dash-dot = BEND UP blue dash-dot = BEND DOWN green = ETCH/mark datum A = bottom-left corner of flat



BEND TABLE

No	Dir	Angle	R in	From A	BA	BD	V-die
No bends - flat laser-cut part.							

BA = bend allowance, BD = bend deduction (mm), K = 0.44, inside radius as listed.
V-die = recommended opening (mm). "From A" = bend-line centre from datum edge.

FORMED SECTION (neutral axis, to scale)

Flat part - no section.

FORMED VIEW (reference, not to scale)



NOTES: (1) Redrawn from assembly drawing sheet 8 (no flat supplied in source). Dia 30 hole, R30 boss. (2) Laser or plasma cut 8 mm; dress the hole for a 30 mm pin / shackle bow.

VELD ARMOUR

BUILT FOR THE VELD

CNC / PRESS-BRAKE DATA PACK

PART NO.
VA-BB-07

TITLE
Recovery lug - FLAT PATTERN

MATERIAL	THICKNESS	QTY / ASSY
S355JR	**8 mm**	**4**
FLAT SIZE	NET MASS	K-FACTOR
90.6 × 91.7	0.29 kg	0.44 (air bend)
BENDS	SOURCE ITEM	DXF
0	#7	VA-BB-07_Recovery_lug_8mm.dxf
TOL. LINEAR	TOL. ANGULAR	FINISH
+/- 0.5 mm	+/- 1 deg	Deburr; powder coat

Veld Armour (Pty) Ltd - proprietary; not for distribution without written consent