FLAT PATTERN - viewed from bend-note face (UP = toward viewer) scale 1:5

red dash-dot = BEND UP blue dash-dot = BEND DOWN green = ETCH/mark datum A = bottom-left corner of flat



BEND TABLE

No	Dir	Angle	R in	From A	BA	BD	V-die
B1	DOWN	90°	1.25	613.41 (X)	3.35	3.15	12
B2	DOWN	17°	1.25	137.90 (X)	0.63	0.34	12
B3	DOWN	162°	42	53.54 (X)	121.24	434.37	roll

BA = bend allowance, BD = bend deduction (mm), K = 0.44, inside radius as listed.
V-die = recommended opening (mm). "From A" = bend-line centre from datum edge.

FORMED SECTION (neutral axis, to scale)

Flats from A: 53.5 / 84.4 / 475.5 / 247.0 mm

FORMED VIEW (reference, not to scale)

NOTES: (1) SOURCE DRAWING CARRIES THE NOTE "NO BENDING" ON THIS PART while also showing three bend callouts. (2) Bend lines are supplied as drawn. CONFIRM WITH DESIGN before forming. R42 bend = roll/bump form.

VELD ARMOUR

BUILT FOR THE VELD

CNC / PRESS-BRAKE DATA PACK

PART NO.
VA-BB-17

TITLE
Face 1 (RH trim strip) - FLAT PATTERN

MATERIAL	THICKNESS	QTY / ASSY
S355JR	**2 mm**	**1**
FLAT SIZE	NET MASS	K-FACTOR
860.4 × 87.2	0.48 kg	0.44 (air bend)
BENDS	SOURCE ITEM	DXF
3	#17	VA-BB-17_Face_1_2mm.dxf
TOL. LINEAR	TOL. ANGULAR	FINISH
+/- 0.5 mm	+/- 1 deg	Deburr; powder coat

Veld Armour (Pty) Ltd - proprietary; not for distribution without written consent