FLAT PATTERN - viewed from bend-note face (UP = toward viewer) scale 1:2

red dash-dot = BEND UP blue dash-dot = BEND DOWN green = ETCH/mark datum A = bottom-left corner of flat

BEND TABLE

No	Dir	Angle	R in	From A	BA	BD	V-die
B1	UP	40.84°	1.5	243.32 (X)	2.05	1.30	24

BA = bend allowance, BD = bend deduction (mm), K = 0.46, inside radius as listed. V-die = 8T opening (mm).
"From A" = bend-line centre from datum edge. 304: ~1.5x mild-steel tonnage, 2-3 deg extra springback.
WARNING: B1 inside R < 1T - cracking risk in 304; use R >= 3 tooling or prove on first-off.

FORMED SECTION (neutral axis, to scale)

Flats from A: 243.3 / 25.5 mm

FORMED VIEW (reference, not to scale)

NOTES: (1) Single shallow bend; use a sharp-radius V-die (V = 6T = 18 mm).

VELD ARMOUR

BUILT FOR THE VELD

CNC / PRESS-BRAKE DATA PACK

PART NO.
VA-BB-05

TITLE
End plate - FLAT PATTERN

MATERIAL	THICKNESS	QTY / ASSY
304 SS 2B	**3 mm**	**2**
FLAT SIZE	NET MASS	K-FACTOR
268.8 × 78.0	0.50 kg	0.46 (air bend, 304)
BENDS	SOURCE ITEM	DXF
1	#5	VA-BB-05_End_plate_3mm.dxf
TOL. LINEAR	TOL. ANGULAR	FINISH
+/- 0.5 mm	+/- 1 deg	Deburr; brush; passivate

Veld Armour (Pty) Ltd - proprietary; not for distribution without written consent