FLAT PATTERN - viewed from bend-note face (UP = toward viewer) scale 1:5

red dash-dot = BEND UP blue dash-dot = BEND DOWN green = ETCH/mark datum A = bottom-left corner of flat



BEND TABLE

No	Dir	Angle	R in	From A	BA	BD	V-die
B1	DOWN	90°	1.25	613.41 (X)	3.41	3.09	16
B2	DOWN	17°	1.25	137.90 (X)	0.64	0.33	16
B3	DOWN	162°	42	53.54 (X)	121.35	434.26	roll

BA = bend allowance, BD = bend deduction (mm), K = 0.46, inside radius as listed. V-die = 8T opening (mm).
"From A" = bend-line centre from datum edge. 304: ~1.5x mild-steel tonnage, 2-3 deg extra springback.
WARNING: B1, B2 inside R < 1T - cracking risk in 304; use R >= 2 tooling or prove on first-off.

FORMED SECTION (neutral axis, to scale)

Flats from A: 53.5 / 84.4 / 475.5 / 247.0 mm

FORMED VIEW (reference, not to scale)

opposite hand shown

NOTES: (1) Mirror of VA-BB-17 (generated). Same "NO BENDING" caveat applies - confirm before forming.

VELD ARMOUR

BUILT FOR THE VELD

CNC / PRESS-BRAKE DATA PACK

PART NO.
VA-BB-18

TITLE
Face 1 LH (trim strip) - FLAT PATTERN

MATERIAL **304 SS 2B**	THICKNESS **2 mm**	QTY / ASSY **1**
FLAT SIZE 860.4 × 87.2	NET MASS 0.48 kg	K-FACTOR 0.46 (air bend, 304)
BENDS 3	SOURCE ITEM #18	DXF VA-BB-18_Face_1_LH_2mm.dxf
TOL. LINEAR +/- 0.5 mm	TOL. ANGULAR +/- 1 deg	FINISH Deburr; brush; passivate

Veld Armour (Pty) Ltd - proprietary; not for distribution without written consent