

OpenText™ Identity Manager

Release notes 25.4 (v4.10.2)

Version : 25.4

PDF Generated on : April 21, 2026

Table of Contents

1. Release notes 25.4 (v4.10.2)	1
1.1. What's new?	2
1.2. Supported component versions	3
1.3. System requirements	5
1.4. Resolved issues	6
1.5. Product installation	14
1.6. Upgrade to the latest version	22
1.7. Known issues	29

1. Release notes 25.4 (v4.10.2)

November 2025

OpenText Identity Manager 25.4 (v4.10.2) includes new features and enhancements, improves usability, and resolves several previous issues.

The updates in this release are cumulative. They include software fixes and enhancements in the current version, as well as all previously released fixes from the service packs, patches, and hotfixes. Many of these improvements were made in direct response to suggestions from our customers. We thank you for your time and valuable input. We hope you continue to help us ensure that our products meet all your needs. You can post feedback in the [OpenText Identity Manager Community Forum](#), our online community that also includes product information, blogs, and links to helpful resources. You can also share your ideas for improving the product on the forum.

To download this product, see the [Software License and Download](#) portal.

For information about the product support life cycle, see the [Product Support Life Cycle](#) page.

1.1. What's new?

This release includes the following enhancements:

Operating system support

This release adds support for the following platforms:

- Red Hat Enterprise Linux (RHEL) 10
- SUSE Linux Enterprise Server (SLES) 15 SP7

For a complete list of supported operating systems, see the [System requirements](#) page.

For information about the components packaged, databases, and browsers supported with this release, see [Supported component versions](#).

Documentation updates



Important

Help file: The context-sensitive help files are not updated for version 25.4 (v4.10.2). For the latest content, see [Help for the Identity Applications Dashboard](#).

Identity Applications enhancement: custom entity search limit configuration

Identity Applications now support a configurable search limit for custom entities. You can modify the default limit of 500 results by setting the `com.microfocus.idm.max.users.count.limit` property in the `ism-configuration.properties` file. A Tomcat restart is required for the change to take effect. This enhancement allows you to define the maximum number of records returned in search results as needed.

1.2. Supported component versions

This section provides information about the supported versions of the components.

OpenText Identity Manager component versions

This release bundles the following components:

- OpenText eDirectory 25.4 (v9.3.2)
- OpenText Identity Console 25.4
- Identity Manager engine 4.10.2
- Identity Manager Remote Loader 4.10.2
- Identity Manager Fan Out Agent 4.10.2
- Designer for OpenText Identity Manager 25.2 (v4.10.1)
- Identity Applications 25.4 (v4.10.2)
- One SSO Provider (OSP) 7.1.0
- Self Service Password Reset (SSPR) 4.8.1.0
- Identity Reporting 25.3
- Sentinel Log Management for IGA 8.7.0.0 (for event auditing)
- OpenText Identity Manager drivers



Note

- OpenText Identity Manager 25.4 (v4.10.2) is also compatible with OpenText eDirectory 26.1 (v9.3.3) and 25.2 (v9.3.1) versions.
- OpenText Identity Manager 25.4 (v4.10.2) contains the latest versions of supported drivers. For more information, see **Version Shipped with 25.4 (v4.10.2)** on the [OpenText Identity Manager drivers](#) page.

Third-party component versions

This release adds support for the following third-party components:

- Zulu 21.0.9+10-LTS

- Apache Tomcat 10.1.48
- PostgreSQL 14.18 (standalone and containers)
- OpenSSL 3.0.15
- Nginx 1.28
- ActiveMQ 6.1.6

Web browsers

You must use any of the following browsers, at a minimum.

- Google Chrome 142
- Mozilla Firefox 144.0.2
- Apple Safari 26.0
- Microsoft Edge 142.0.3595.53

1.3. System requirements

For information about hardware requirements and supported operating systems, see the [System requirements](#) page.

1.4. Resolved issues

This release includes the following software fixes:

Component	Global ID	Description
Identity Applications	OCTCR56A580939	A team requester is unable to view recipients under Access > Permissions > Others in the OpenText Identity Manager Dashboard.
	OCTCR56A583531	Selecting and clearing role check boxes to revoke access for a user results in duplicate roles appearing on the Permissions and Permissions of Other's pages.
	OCTCR56A583654	Unable to increase the search limit for a custom-defined entity beyond 500 even after updating the <code>com.microfocus.idm.max.users.count.limit</code> property in the <code>ism-configuration.properties</code> file.
	OCTCR56A584216	After changing the username format from <code>Given Name + Last Name</code> to <code>Full Name</code> , usernames no longer appear under People > Users .

Component	Global ID	Description
	OCTCR56A584368	In Workflow Monitoring, the Reassign option is available even after a workflow is completed or terminated.
	OCTCR56A584490	When selecting roles for revocation on the Access > Permissions > Others page, previously selected roles are incorrectly retained, leading to unintended role revocations.
	OCTCR56A585312	The search functionality for roles and entitlements fails in some languages when the search term includes an ampersand (&).
	OCTCR56A585345	On the New Request page, the arrow symbol is not rendered in the selected permission field when the permission is a PRD or resource and supports bulk approval.
	OCTCR56A627213	The <code>RoleVault.findRoles()</code> method throws a <code>NullPointerException</code> when invoked within a request workflow.

Component	Global ID	Description
	OCTCR56A629207	The organization chart option appears on the People > Users page even for users who do not have access to the organization chart feature.
	OCTCR56A639043	When a user requests permission from an OpenText Identity Governance application, Identity Applications displays permissions for the first application in the list, regardless of the selected application.
	OCTCR56A673072	The Task of Others page for a team manager displays a <i>Failed to fetch teams list</i> message when searching for teams that do not have any PRD permissions configured.
	OCTCR56A685073	On the Permissions of Other's page, a team manager can view only ten users, with no indication of additional users or pagination options.

Component	Global ID	Description
	OCTCR56A690096	Escalation of approval workflows fails when the Approver Type is set to Normal.
	OCTCR56A696278	The JSON forms are not loading properly in browsers without internet connection.
	OCTCR56A705063	OpenText Identity Manager does not display user attribute values derived from a Global List under People > Users or custom DAL entities list view, although they appear correctly in edit mode.
	OCTCR56A708024	After upgrading to version 24.4 (v4.10), custom workflow log events are not displaying correctly in the <code>catalina.out</code> log file.
	OCTCR56A713293	Unable to download the CSV file from the Entities page when results include boolean attributes or attributes with UI Control set to Boolean in the DAL.

Component	Global ID	Description
	OCTCR56A713294	The Entities page fails to display the value of boolean attributes.
	OCTCR56A716104	The Access > Request History displays an HTTP failure with a 489 OK message when the first item displayed in the request history is a resource.
	OCTCR56A736461	A session data corruption in 25.2 (v4.10.1) causes logged-in users to intermittently see another user's details.
Installation and Upgrade	OCTCR56A725057	The <code>configupdate.sh</code> script in the Identity Reporting container prompts for unnecessary settings and fails to save configuration changes.
	OCTCR56A730203	The PostgreSQL upgrade using the <code>pg-upgrade.sh</code> script fails with a <i>Permission denied</i> message when a custom data directory is used for PostgreSQL.

Component	Global ID	Description
	OCTCR56A730324	In the Identity Manager Engine container deployed on Microsoft Azure Kubernetes Service (AKS), the ingress certificate is imported with the alias <code>rootcertfromtlscrtfile</code> instead of the expected root CA certificate.
Identity Reporting	OCTCR56A696227	Inconsistencies in <code>valid_from</code> and <code>valid_to</code> values data within Identity Manager reporting views.
Identity Manager Engine	OCTCR56A584645	The DCS driver's policy <code>NOVLIDMDCSB-otp-ReformatMemberQuery</code> fails with LDAPS connection.
	OCTCR56A629139	The <code>cn=monitor</code> option fails to display cache statistics for running drivers.
	OCTCR56A721394	The <code>notifSMTPMailProtocol</code> option works with the <code>do-send-email</code> action but fails with <code>do-send-email-from-template</code> .

Component	Global ID	Description
	OCTCR56A725017	The <code>do-invoke-rest-endpoint</code> action incorrectly treats a HTTP 204 No Content successful response as an error, preventing proper success determination.

1.5. Product installation

This release includes the Advanced Edition and Standard Edition in a single ISO file. Before downloading the installation files, you should understand the features available in each edition and the options for downloading the product components. For information about the features supported by each edition, see the [Overview and planning guide](#).

Downloading OpenText Identity Manager

After purchasing the product, sign in to the [Software License and Download portal](#) and follow the link that allows you to download the software. The following files contain the OpenText Identity Manager components:

File name	Description
Identity_Manager_4.10.2_Linux.iso	Contains Identity Manager Server (Identity Manager Engine, Remote Loader, and Fan-Out Agent), Identity Applications, Identity Reporting, and OpenText Identity Console.
Identity_Manager_4.10.2_RL_Linux.iso	Contains the Identity Manager Remote Loader for Linux.
Identity_Manager_4.10.2_Containers.tar.gz	Contains individual container images for Identity Manager Engine, Remote Loader, Fanout Agent, ActiveMQ, PostgreSQL, Form Renderer, OSP, Identity Applications, Identity Reporting, SSPR, and OpenText Identity Console.
Identity_Manager_4.10.2_Windows.iso	Contains Identity Manager Server (Identity Manager Engine, Remote Loader, and Fan-Out Agent), Identity Applications, and Identity Reporting.
Identity_Manager_4.10.2_RL_Windows.iso	Contains the 64-bit and .NET Remote Loader for Windows.
Identity_Manager_4.10.1_Designer.zip	Contains Designer for Linux, Windows, and macOS platforms.

File name	Description
SentinelLogManagementForIGA8.7.0.0.tar.gz	Contains Sentinel Log Management for Identity Governance and Administration (IGA). This installation is supported only on Linux.
acdi_v25.2.zip	Contains Audit, Compliance & Data Intelligence (includes ACDI driver, ACDI Monitor packages, and ACDI Workflow Monitor package).



Important

- The product no longer compiles the 32-bit version of the Remote Loader and is available with .NET and 64-bit versions.
- The Analyzer tool is not included in the installer. If Analyzer is already installed, ensure that you update it to version 4.8.5 and use it with OpenText Identity Manager 25.4 (v4.10.2). For installing and upgrading Analyzer, see [Install and upgrade guide for Linux](#) or [Install and upgrade guide for Windows](#).

Product executable and default installation path

- [Executables and default installation paths on Linux](#)
- [Executables and default installation paths on Windows](#)

Executables and default installation paths on Linux

Component	Location of the Executable within ISO	Default Installation Path
Identity Manager Server (contains Identity Manager Engine, Remote Loader, and Fanout Agent)	<code>install.sh</code> in the mounted location	• Engine: <code>/opt/novell/eDirectory/lib/dirxml</code> • Remote Loader: <code>/opt/novell/dirxml/bin/x86_64</code> • Fanout Agent: <code>/opt/novell/dirxml/fanoutagent</code> • OpenText Identity Console: <code>/opt/novell/eDirAPI/sbin/</code>

Component	Location of the Executable within ISO	Default Installation Path
Identity Applications (Identity Manager Dashboard and Administration Interface, User Application, Role and Resource Service driver, User Application driver, Configuration Update Utility, One SSO Provider, Self Service Password Reset)	<code>install.sh</code> in the mounted location	• Identity Applications: <code>/opt/netiq/idm/apps</code> • User Application: <code>/opt/netiq/idm/apps/UserApplication</code> • Configuration Update Utility: <code>/opt/netiq/idm/apps/configupdate</code> • Form Renderer: <code>/opt/netiq/idm/apps/sites</code> • NGINX: <code>/opt/netiq/common/nginx</code> • OSP: <code>/opt/netiq/idm/apps/osp</code>
Identity Reporting	<code>install.sh</code> in the mounted location	<code>/opt/netiq/idm/apps/IDMReporting</code>
Password Management Component	<code>./install.sh</code> in the <code>/sspr</code> directory from the mounted location	<code>/opt/netiq/idm/apps/sspr</code>

Component	Location of the Executable within ISO	Default Installation Path
Sentinel Log Management for IGA	<code>./install.sh</code> in the <code>/SentinelLogManagementforIGA</code> directory of the <code>SentinelLogManagementForIGA8.7.0.0.tar.gz</code> file	<code>/opt/novell/sentinel</code>

Executables and default installation paths on Windows

Component	Location of the Executable within ISO	Default Installation Path
Identity Manager Server (contains Identity Manager Engine, Remote Loader, Fan-Out Agent)	install.exe located in \<iso mounted location>\IdentityManagerServer\	• Engine: C:\netiq\idm • Remote Loader: C:\netiq\idm\Remote Loader • Fanout Agent: C:\netiq\idm\Fanout Agent
Identity Applications (Identity Manager Dashboard and Administration Interface, User Application, Role and Resource Service driver, User Application driver, Configuration Update Utility, One SSO Provider, Self Service Password Reset)	install.exe located in \<iso mounted location>\IdentityApplications\	• Identity Applications: C:\netiq\idm\apps\ • User Application: C:\netiq\idm\apps\UserApplication • Configuration Update Utility: C:\netiq\idm\apps\configupdate • Form Renderer: C:\netiq\idm\apps/sites • NGINX: C:\netiq\common\nginx • OSP: C:\netiq\idm\apps\osp

Component	Location of the Executable within ISO	Default Installation Path
Identity Reporting	install.exe located in \<iso mounted location>\IdentityReporting\	C:\netiq\idm\apps\IdentityReporting
Password Management Component	install.exe located in the <iso mounted location>\common\sspr	C:\netiq\idm\apps\common\sspr

Installing the product

Depending on the edition you are installing, review the information from one of the following resources:

- Advanced Edition: [Install and upgrade guide for Linux](#) or [Install and upgrade guide for Windows](#)
- Standard Edition: [Quick start guide for installing and upgrading OpenText Identity Manager standard edition](#)

1.6. Upgrade to the latest version

You can directly upgrade to OpenText Identity Manager 25.4 (v4.10.2) from 4.9.x, 24.4 (v4.10), and 25.2 (v4.10.1) versions.



Note

Before starting the upgrade, review the information from the release notes for your current version.

Upgrade from 25.2 (v4.10.1), 24.4 (v4.10), and 4.9.x versions

The following table lists the component-wise upgrade paths for OpenText Identity Manager 25.2 (v4.10.1), 24.4 (v4.10), and 4.9.x versions:

Component	Base Version	Upgraded Version
Identity Manager Engine	4.10.1, 4.10, or 4.9.x	1. Upgrade the operating system to a supported version. 2. Upgrade Identity Vault to 25.4 (v9.3.2) or later. 3. Upgrade Identity Manager Engine to 4.10.2.
Remote Loader	4.10.1, 4.10, or 4.9.x	Upgrade to 4.10.2 Remote Loader.
Fanout Agent	4.10.1, 4.10, or 1.3	Upgrade to 4.10.2 Fanout Agent.
Designer	24.4 (v4.10)	If you are on version Designer 24.4 (v4.10), directly upgrade to 25.2 (v4.10.1).

Component	Base Version	Upgraded Version
Identity Applications	25.2 (v4.10.1), 24.4 (v4.10), or 4.9.x	Before you upgrade Identity Applications, ensure that the Identity Vault and Identity Manager engine are upgraded to 25.4 (v9.3.2) and 4.10.2, respectively. 1. Upgrade the operating system to a supported version. 2. Stop Tomcat. 3. Upgrade the database to a supported version. For the supported database versions, see System requirements. 4. (Conditional) If SSPR is installed on a separate server, upgrade the component to version 4.8.1.0. 5. Update the User Application driver package using Designer. 6. Upgrade Identity Applications to 25.4 (v4.10.2).

Component	Base Version	Upgraded Version
		7. Start Tomcat.

Component	Base Version	Upgraded Version
Identity Reporting	24.4 (v7.4.0)	Before you upgrade Identity Reporting, ensure that the Identity Vault, Identity Manager engine, and Identity Applications are upgraded to 25.4 (v9.3.2), 4.10.2, and 25.4 (v4.10.2), respectively. 1. Upgrade the operating system to a supported version. 2. Upgrade the database to a supported version. For more information about the supported database versions, see System requirements. 3. Upgrade SLM for IGA to a supported version. 4. Update the Data Collection Services driver package using Designer. 5. Upgrade Identity Reporting to 25.3 (v7.6.0). 6. Start Tomcat.

Component	Base Version	Upgraded Version
		7. (Conditional) Create a data synchronization policy from the Identity Manager Data Collection Services page.

For more information about upgrading OpenText Identity Manager, see [Upgrading OpenText Identity Manager](#) in the **Install and upgrade guide for Linux** or [Upgrading OpenText Identity Manager](#) in the **Install and upgrade guide for Windows**.

Upgrade to Advanced Edition

The following upgrade paths are available for upgrading to version 25.4 (v4.10.2) Advanced Edition from a previous Advanced Edition or Standard Edition:

- Identity Manager 4.9.x Advanced Edition to 25.4 (v4.10.2) Advanced Edition
- OpenText Identity Manager 24.4 (v4.10) Advanced Edition to 25.4 (v4.10.2) Advanced Edition
- OpenText Identity Manager 25.2 (v4.10.1) Advanced Edition to 25.4 (v4.10.2) Advanced Edition
- Identity Manager 4.9.x, 24.4 (v4.10), and 25.2 (v4.10.1) Standard Edition to 25.4 (v4.10.2) Advanced Edition, in one of the following ways:
 - From Identity Manager 4.9.x Standard Edition to 25.4 (v4.10.2) Standard Edition and then to 25.4 (v4.10.2) Advanced Edition
 - From Identity Manager 4.9.x Standard Edition to 4.9.x Advanced Edition and then to 25.4 (v4.10.2) Advanced Edition
 - From OpenText Identity Manager 24.4 (v4.10) Standard Edition to 25.4 (v4.10.2) Standard Edition and then to 25.4 (v4.10.2) Advanced Edition
 - From OpenText Identity Manager 24.4 (v4.10) Standard Edition to 24.4 (v4.10) Advanced Edition and then to 25.4 (v4.10.2) Advanced Edition

- From OpenText Identity Manager 25.2 (v4.10.1) Standard Edition to 25.4 (v4.10.2) Standard Edition and then to 25.4 (v4.10.2) Advanced Edition
- From OpenText Identity Manager 25.2 (v4.10.1) Standard Edition to 25.2 (v4.10.1) Advanced Edition and then to 25.4 (v4.10.2) Advanced Edition

Upgrade Standard Edition

You can upgrade to OpenText Identity Manager 25.4 (v4.10.2) Standard Edition from Identity Manager 4.9.x, 24.4 (v4.10), and 25.4 (v4.10.1) Standard Edition. For upgrade instructions, see the [Quick start guide for Standard Edition](#).

1.7. Known issues

OpenText strives to ensure our products provide quality solutions for your enterprise software needs. The following issues are currently being researched. If you need further assistance with any issue, please contact [Technical support](#).

For the list of known issues in Designer, see the [Designer 25.2 \(v4.10.1\) release notes](#).

Custom configuration settings lost after upgrade

Issue: When upgrading from version 25.2 (v4.10.1) to 25.4 (v4.10.2) on distributed Linux setup, custom modifications in the `configupdate.sh.properties` file may get removed or overwritten. Specifically, parameters such as `app_versions` and `sso_apps` revert to their default values causing any previously configured settings (for example, for Identity Reporting) to be lost.

For example:

- Before upgrade (v4.10.1):

```
app_versions="ua#4.10.1,rpt#7.6.0"
sso_apps=ua,rpt
```

- After upgrade (v4.10.2):

```
app_versions="ua#4.10.2"
sso_apps=ua
```

This may result in issues, such as failure to launch Identity Reporting.
[OCTCR56A733667]

Workaround: Back up your custom settings before upgrading, or manually reapply them after the upgrade.

Designer does not display Identity Manager Version 4.10.2

Issue: When using Designer 4.10.1 with OpenText Identity Manager 25.4 (v4.10.2), the **Identity Manager Version** list in the **Add Server Association** window does not display version **4.10.2**. This issue occurs when adding the Identity Vault to a project. Designer 4.10.1 is unable to retrieve the Identity Manager engine version 4.10.2.

[OCTCR56A740200]

Workaround: There is no workaround at this time. To proceed, retain the default selection in the **Identity Manager Version** list and continue with the next step.

The eDirectory driver fails to connect after upgrade

Issue: After upgrading to version 25.4 (v4.10.2), the eDirectory-to-eDirectory (eDir2eDir) driver might fail to establish a connection between two eDirectory trees. The driver trace log display the following error message: `<status level="error" type="driver-general">java.net.MalformedURLException: Illegal character found in host: ' '</status>`. The error occurs because Java 21 enforces stricter URL parsing rules, and any invalid characters (such as spaces) in the host URL result in a `MalformedURLException`. [OCTCR56A731322]

Workaround:

1. In OpenText Identity Console, navigate to **IDM Administration**.
2. Select the **Driver Set**, then open **Driver Set Properties**.
3. Under **Driver Set Configuration**, go to **Java Environment Parameters**.
4. In **JVM Options**, add the following parameter:

```
-Djdk.net.url.delayParsing=true
```

5. Click **Save**.

The configuration update utility hangs during launch

Issue: The Identity Applications configuration utility (`configupdate.sh` for Linux and `configupdate.bat` for Windows) might fail to start if it cannot access the hibernate.org website while trying to download content from <http://hibernate.org/dtd/hibernate-configuration-3.0.dtd>. [OCTCR56A731026]

Workaround: To resolve this issue, add the following entry to your hosts file: `127.0.0.1 www.hibernate.org`. It will direct your system to resolve hibernate.org to your localhost (your own machine).

Self Service Password Reset 5071 error after upgrade

Issue: After upgrading to version 25.4 (v4.10.2) on Windows, you might encounter the following error when signing into the User Application:

Error SSPR 5071: An error using the OAuth authentication protocol has occurred. Please try again later.

Additionally, the following error messages might be logged in the `catalina.out` file:

WARN, provider.FailOverRotationMachine, unable to reach ldap server ldaps://<engine server>:636, last error: unable to bind to ldaps://<engine server>:636

FATAL, ldap.LdapOperationsHelper, check ldap proxy settings: 5017
 ERROR_DIRECTORY_UNAVAILABLE (error connecting as proxy user: unable to create
 connection: unable to connect to ldap url, error: unable to bind to
 ldaps://<server>:636]

[OCTCR56A726205]

Workaround: Perform the following steps:

1. To open Self Service Password Reset in the config mode.
 1. Open the `SSPRConfiguration.xml` file in a text editor.
 2. Locate the `configsEditable` property.
 3. Change the value associated with the `configsEditable` property from `false` to `true`.
 4. Save the file.
2. To import the server certificate:
 1. Open SSPR Configuration Editor using the following URL:
<https:///sspr/private/config/editor>
 2. In Config Editor, navigate to **LDAP > LDAP Directories > default > Connection > LDAP Certificates** and click **Import From Server**.
 3. Save the changes.
3. Open the `SSPRConfiguration.xml` file in a text editor.
 1. Change the value associated with the `configsEditable` property from `true` to `false`.
 2. Save the file.
4. Sign in to the User Application.

A Sentinel driver issue after the upgrade

Issue: When starting the Sentinel driver, the following error is encountered:

`IllegalAccessError: class security.base.security.SecurityHandler`

This occurs because the Sentinel packages are not compatible with Java 21.

Workaround: To resolve this issue, choose one of the following options:

- Install the Sentinel driver on Java Remote Loader (dirxml_jremote) version 4.10.1 or 4.10.2
- Install the Sentinel driver on the native (rdxml) or Java Remote Loader version 4.10

The exception executing batch error seen in the catalina.out file

Issue: On requesting a Provisioning Request Definition (PRD) containing branch data, the following error is consistently seen in the `catalina.out` log file:

```
ERROR org.hibernate.engine.jdbc.batch.internal.BatchingBatch - HHH000315:
Exception executing batch [org.hibernate.StaleStateException: Batch update returned
unexpected row count from update
```

```
[OCTCR56A724034]
```

Workaround: There is no workaround at this time. However, this error does not impact functionality, so you can ignore it.

Excessive warnings logged in the catalina.out file

Issue: In version 25.4 (v4.10.2), the following warning repeatedly appears in the `catalina.out` log file:

```
[https-jsse-nio-8543-exec-141] WARN org.hibernate.orm.deprecation -
HHH90000022: Hibernate's legacy org.hibernate.Criteria API is deprecated; use the
JPA jakarta.persistence.criteria.CriteriaQuery instead
```

Although these warnings are not critical, they can clutter the logging file, making it difficult to identify genuine issues. `[OCTCR56A717164]`

Workaround: To reduce the noise level of these warnings:

1. Depending on your operating system, navigate to the following directory:

- **Linux:** `/opt/netiq/idm/apps/tomcat/lib`
- **Windows:** `C:\NetIQ\IDM\apps\tomcat\lib`

2. Add the following property to the `logging.properties` file:

```
log4j.logger.org.hibernate.orm.deprecation=OFF
```

3. Navigate to the following directory:

- **Linux:** `/opt/netiq/idm/apps/tomcat/conf`
- **Windows:** `C:\NetIQ\IDM\apps\tomcat\conf`

4. Open the `userapp-log4j.xml` file in a text editor and set the logger as follows:

```
<Logger name="org.hibernate.orm.deprecation" level="off"
additivity="false">
```

```
<AppenderRef ref="CONSOLE"/>
```

```
</Logger>
```

5. Save the file.
6. Repeat steps 4 and 5 for the `userapp-log4j2.xml`, `idmuserapp_logging.xml`, and `workflow_logging.xml` logging files.
7. Restart Tomcat.

Linux and Windows installer displays a Liquibase service license warning

Issue: During the upgrade of Identity Applications and Identity Reporting components to version 25.4 (v4.10.2), you might encounter the following warning:

WARNING: License service not loaded, cannot determine Liquibase Pro license status. Please consider re-installing Liquibase to include all dependencies. Continuing operation without Pro license.

This warning is specific to Liquibase version 4.31.0, which is supported by OpenText Identity Manager 25.4 (v4.10.2).

[OCTCR56A717032]

Workaround: This warning does not impact functionality, so you can ignore it.

Warning displayed when starting Java Remote Loader

When you start or stop a driver instance in Remote Loader using the `rdxml` command line utility, you may encounter the following warning:

OpenJDK 64-Bit Server VM warning: Options `-Xverify:none` and `-noverify` were deprecated in JDK 13 and will likely be removed in a future release.

[OCTCR56A701134]

Workaround: It does not affect any functionality. You can ignore it.

Failed to load class "org.slf4j.impl.StaticLoggerBinder" error

Issue: During the configuration of Identity Applications, the Linux installation program generates a new master key. However, you may encounter the error "SLF4J: Failed to load class 'org.slf4j.impl.StaticLoggerBinder'" during this process or while updating the master key. [OCTCR56A701128]

Workaround: The error does not affect any functionality. You can ignore it.

An Ellucian Banner driver issue after the upgrade

Issue: The Integration Module for Banner by Ellucian fails due to incompatibility with Jetty libraries shipped with OpenText Identity Manager 25.4 (v4.10.2).

Workaround: If you have installed the driver, it is recommended to use with Remote Loader 4.9.

An Appender error is seen in Catalina logs for WFCEF

Issue: While upgrading Identity Application to 25.4 (v4.10.2), you might see an appender error similar to the following in the catalina logs:

```
com.netiq.logging.log4j2.Log4jLogger.addAppender Error adding Appender WFCEF
to Logger com.microfocus
```

```
com.netiq.logging.log4j2.Log4jLogger.addAppender Error adding Appender WFCEF
to Logger com.sssw
```

```
com.netiq.logging.log4j2.Log4jLogger.addAppender Error adding Appender WFCEF
to Logger com.novell
```

```
com.netiq.logging.log4j2.Log4jLogger.addAppender Error adding Appender WFCEF
to Logger workflow.log
```

```
com.netiq.logging.log4j2.Log4jLogger.addAppender Error adding Appender WFCEF
to Logger com.netiq
```

This happens when you configure auditing prior to upgrading the Identity Applications.

```
[OCTCR56A679501]
```

Workaround:

1. Navigate to the following `conf` directory.

- **Linux:** `/opt/netiq/idm/apps/tomcat/conf`
- **Windows:** `C:\NetIQ\IDM\apps\tomcat\conf`

2. Edit the `ism-configuration.properties` as follows:

- Comment out the following entries (prefix each line with `#`):

```
workflow.logging.wfs.definition.workflow.log =
{"name":"workflow.log","level":"INFO","additivity":true,"appenderRef
s":["WFCEF"]}
```

```
workflow.logging.wfs.definition.com.novell =
{"name":"com.novell","level":"INFO","additivity":true,"appenderRefs\"
```

```
:["WFCEF"]}
```

```
workflow.logging.wfs.definition.com.netiq =
{"name":"com.netiq","level":"INFO","additivity":true,"appenderRefs":
["WFCEF"]}
```

```
workflow.logging.wfs.definition.com.sssw =
{"name":"com.sssw","level":"INFO","additivity":true,"appenderRefs":
["WFCEF"]}
```

```
workflow.logging.wfs.definition.com.microfocus =
{"name":"com.microfocus","level":"INFO","additivity":true,"appender
Refs":["WFCEF"]}
```

- Ensure the following entries are uncommented (remove # if present):

```
workflow.logging.wfs.definition.workflow.log =
{"name":"workflow.log","level":"INFO","additivity":true}
```

```
workflow.logging.wfs.definition.com.novell =
{"name":"com.novell","level":"INFO","additivity":true}
```

```
workflow.logging.wfs.definition.com.netiq =
{"name":"com.netiq","level":"INFO","additivity":true}
```

```
workflow.logging.wfs.definition.com.sssw =
{"name":"com.sssw","level":"INFO","additivity":true}
```

```
workflow.logging.wfs.definition.com.microfocus =
{"name":"com.microfocus","level":"INFO","additivity":true}
```

3. Save the file.
4. (Optional) If your `workflow_logging.xml` or `idmuserapp_logging.xml` contain `<appenders>` or `appenderRefs` entries, you can comment them out. For more information, see the latest [workflow_logging.xml](#) and [idmuserapp_logging.xml](#).
5. Restart Tomcat services.

Authentication reports are not generated on Sentinel after the upgrade

Issue: After upgrading OpenText Identity Manager from version 4.9.x, the reports for *Authentication by User* and *Authentication by server* are not generated on Sentinel.

[OCTCR56A655281]

Workaround: Delete the existing data synchronization policy in Identity Manager Data Collection Service (idmdcs) and Sentinel Log Management for IGA, then create a new one. For more information about how to create a data synchronization policy, see [Administrator Guide to Identity Reporting](#).

An error occurred in the OpenText eDirectory log file after the upgrade

Issue: After upgrading OpenText Identity Manager from version 4.9 to 25.4 (v4.10.2), users may encounter the following error in the `ndsd.log` file:

```
Loader Failed:for lib/opt/novell/eDirectory/lib64/nds-
modules/libdxevent.so.3.so,error lib/opt/novell/eDirectory/lib64/nds-
modules/libdxevent.so.3.so: cannot open shared object file: No such file or
directory,errno 2
```

This issue is observed in the *All-in-One* server setup for OpenText Identity Manager on Linux. [OCTCR56A639009]

Workaround: The error does not affect any functionality. You can ignore it.

An error during non-root installation of engine

Issue: When installing the Identity Manager engine, non-root users may encounter the following error in the `idminstall.log` file:

```
novell-edirectory-xdaslog-9.3.0.0000-1error: lsetfilecon: (/opt/novell,
system_u:object_r:usr_t:s0) Operation not permittederror: Plugin selinux: hook
fsm_file_prepare failed#####error:
unpacking of archive failed on file /opt/novell: cpio: (error 0x2)error: novell-
edirectory-xdaslog-9.3.0.0000-169.x86_64: install failed
```

This occurs when unpacking the `novell-edirectory-xdaslog-<version>` RPM at `/opt/novell` location fails because a non-root user does not have the required access to this directory. [OCTCR56A647216]

Workaround: The error does not affect any functionality. You can ignore it.

An error reported in the PostgreSQL startup log

Issue: When configuring Identity Applications and Identity Reporting components on PostgreSQL database, users may encounter the following errors in the startup logs:


```
[16154] ERROR: relation "databasechangelog" does not exist at character 13
[16154] STATEMENT: insert into databasechangelog(id, author, filename, dateexecuted, orderexecuted, exectype,
description, comments, liquibase) values('410', 'IDMRBPM', 'ProvisioningViewValueConstraint45.xml', now(),
796, 'EXECUTED', 'sql', 'Dummy RECORD - TEMP SOLUTION', '3.2.2')
[16220] ERROR: relation "public.databasechangeloglock" does not exist at character 22
[16220] STATEMENT: SELECT COUNT(*) FROM public.databasechangeloglock
[16249] ERROR: relation "public.databasechangeloglock" does not exist at character 22
[16249] STATEMENT: SELECT COUNT(*) FROM public.databasechangeloglock
[15803] LOG: received fast shutdown request
[15803] LOG: aborting any active transactions
[15803] LOG: background worker "logical replication launcher" (PID 15810) exited with exit code 1
[15805] LOG: shutting down
[15803] LOG: database system is shut down
[1389] LOG: starting PostgreSQL 14.13 on x86_64-pc-linux-gnu, compiled by gcc (SUSE Linux) 7.4.1 20190424
[gcc-7-branch revision 270538], 64-bit
[1389] LOG: listening on IPv4 address "0.0.0.0", port 5432
[1389] LOG: listening on IPv6 address ":::", port 5432
[1389] LOG: listening on Unix socket "/tmp/.s.PGSQL.5432"
[1389] LOG: could not open configuration file "/opt/netiq/idm/postgres/data/pg_hba.conf": Permission denied
[1389] FATAL: could not load pg_hba.conf
[1389] LOG: database system is shut down
[1473] LOG: starting PostgreSQL 14.13 on x86_64-pc-linux-gnu, compiled by gcc (SUSE Linux) 7.4.1 20190424
[gcc-7-branch revision 270538], 64-bit
[1473] LOG: listening on IPv4 address "0.0.0.0", port 5432
[1473] LOG: listening on IPv6 address ":::", port 5432
[1473] LOG: listening on Unix socket "/tmp/.s.PGSQL.5432"
[1474] LOG: database system was shut down at 2024-10-05 07:39:04 IST
[1473] LOG: database system is ready to accept connections
[1679] ERROR: relation "idm_rpt_data.databasechangeloglock" does not exist at character 22
[1679] STATEMENT: select count(*) from idm_rpt_data.databasechangeloglock
[1733] ERROR: relation "idm_rpt_cfg.databasechangeloglock" does not exist at character 22
[1733] STATEMENT: select count(*) from idm_rpt_cfg.databasechangeloglock
```

[OCTCR56A662182]

Workaround: The error does not affect any functionality. You can ignore it.

An error reported in the upgrade log file

Issue: After upgrading OpenText Identity Manager to 25.4 (v4.10.2), users may encounter the following SSPR-related errors in the `idmupgrade.log` file:

```
ERROR password.pwm.util.cli.MainClass - 5083 ERROR_ENVIRONMENT_ERROR
(unable to establish operating environment: file for option 'outputFile' at
'/opt/netiq/idm/apps/sspr/sspr_data/SSPRConfiguration.xml' already exists)
```

[OCTCR56A662286]

Workaround: These errors does not affect any SSPR functionality. You can ignore it.

An error reported in the Catalina log file

Issue: After installing or upgrading to OpenText Identity Manager 25.4 (v4.10.2), users may encounter an error when starting Tomcat. The error is reported in the `catalina.out` log file.

```
[RPT-CORE] Error validating report configuration
schema.com.netiq.persist.PersistenceException: java.lang.RuntimeException: Cannot
use default schema name idm_rpt_cfg on Microsoft SQL Server because the login
```

schema of the current user (dbo) is different and MSSQL does not support setting the default schema per session.

This issue occurs when the Identity Manager engine and Identity Reporting are configured in a distributed server setup on the MS SQL 2019 database.

[OCTCR56A667011]

Workaround: The error does not affect any functionality. You can ignore it.

The DirXML command-line utility displays an error after upgrade

Issue: After upgrading OpenText Identity Manager to version 25.4 (v4.10.2), users may encounter the following LDAP error when launching the DirXML command-line utility:

```
Connection lost waiting for results from 10.71.142.57:636 (91) Connect Error
javax.net.ssl.SSLException: Unexpected error:
java.security.InvalidAlgorithmParameterException: the trustAnchors parameter must
be non-emp
```

This issue occurs when OpenText Identity Manager is configured to operate in the FIPS-enabled mode. [Issue: OCTCR56A669101]

Workaround: The error does not affect any functionality. You can ignore it.

Invalid keystore format error during upgrade

Issue: While upgrading OpenText Identity Manager in the FIPS-enabled mode, users may encounter the following error while importing the reCAPTCHA public key certificate into the keystore:

```
keytool error: java.io.IOException: Invalid keystore format
```

[Issue: OCTCR56A671139]

Workaround: Import the public key certificate from the cacerts file into the idm.bcfks keystore by using the following command:


```
keytool -importkeystore -srckeystore
/opt/netiq/common/jre/lib/security/cacerts -srcstorepass
changeit -srcstoretype BCFKS -destkeystore
/opt/netiq/idm/apps/tomcat/conf/idm.bcfks -deststorepass novell
-deststoretype BCFKS -providerclass
org.bouncycastle.jcajce.provider.BouncyCastleFipsProvider -
providerpath $CLASSPATH --noprompt
```

An error is displaying during engine upgrade

Issue: While upgrading Identity Manager engine in FIPS-enabled mode, users might encounter the following exception on Linux and Windows:

LDAPException: Error configuring LDAP SSL/TLS. (82) Local
Errorjava.security.KeyStoreException: BCFKS not found

[Issue: OCTCR56A670109]

Workaround: The error does not affect any functionality. You can ignore it.

The Windows installer displays an error

Issue: After installing OpenText Identity Manager 25.4 (v4.10.2) components, the following error is displayed on starting Tomcat: SEVERE [main]
org.apache.catalina.util.LifecycleBase.handleSubClassException Failed to start
component [Connector["ajp-nio-<IP_address>-8010"]]

This issue occurs during a fresh installation and after upgrading to OpenText Identity Manager 25.4 (v4.10). [Issue: OCTCR56A607041]

Workaround: It does not cause any functionality loss. However, if you want to resolve the issue, delete the following line in the `server.xml` file:

```
<Connector port="8010" protocol="AJP/1.3" redirectPort="8543"/>
```

The `server.xml` file is available in `C:\NetIQ\idm\apps\tomcat\conf`

Some reports do not fetch any data while using MS SQL database

Issue: If you are using MS SQL 2022 as the Identity Reporting database, the **Access Requests by Recipient**, **Access Requests by Requester**, and **Access Requests by Resource** reports do not return any data.

Workaround: To fetch the data for the above reports, perform the following steps:

1. Sign in to the server where Identity Reporting is installed.
2. Open a database administrator tool such as SQL Server Management Studio.
3. Run the following query:



Note

Specify the appropriate Identity Reporting database name in the `<identity reporting database name>` field.

```

USE
USE [<identity reporting database name>];
GO
-- Drop old function safely

IF OBJECT_ID('[IDM_RPT_DATA].[get_formatted_user_dn]', 'FN')
IS NOT NULL

    DROP FUNCTION [IDM_RPT_DATA].[get_formatted_user_dn];
GO
SET ANSI_NULLS ON;
GO
SET QUOTED_IDENTIFIER ON;
GO

-- □ get_formatted_user_dn: Cursor-based logic
preserved

CREATE FUNCTION [IDM_RPT_DATA].[get_formatted_user_dn]
(
    @user_path NVARCHAR(MAX),
    @user_name NVARCHAR(200)
)
RETURNS NVARCHAR(MAX)
AS
BEGIN
    DECLARE
        @new_path          NVARCHAR(200),
        @new_path_2        NVARCHAR(MAX),
        @l_user_path       NVARCHAR(MAX),
        @l_old_delimiter   NVARCHAR(1) = '\\',
        @l_new_delimiter   NVARCHAR(1) = '.',
        @MyCursor CURSOR,
        @MyField NVARCHAR(MAX);
    IF @user_path IS NOT NULL

    BEGIN
        SET @l_user_path = SUBSTRING(@user_path, 2,
LEN(@user_path) - 1);
        SET @MyCursor = CURSOR FOR

```

```

        SELECT value FROM STRING_SPLIT(@l_user_path,
@l_old_delimiter)
    OPEN @MyCursor;
    FETCH NEXT FROM @MyCursor INTO @MyField;
    WHILE @@FETCH_STATUS = 0
    BEGIN
        IF @MyField IS NOT NULL
        BEGIN
            SET @new_path = @l_new_delimiter + @MyField;
        END
        IF @new_path_2 IS NOT NULL
        BEGIN
            SET @new_path = @new_path + @new_path_2;
        END
        SET @new_path_2 = @new_path;
        FETCH NEXT FROM @MyCursor INTO @MyField;
    END
    CLOSE @MyCursor;
    DEALLOCATE @MyCursor;
    IF @new_path IS NOT NULL
    BEGIN
        SET @new_path = @user_name + @new_path;
    END
    ELSE
    BEGIN
        SET @new_path = @user_name;
    END
    END
    RETURN LTRIM(RTRIM(@new_path));
END;
GO
-- Drop patternReplace if exists
IF OBJECT_ID('[IDM_RPT_DATA].[patternReplace]', 'FN') IS NOT
NULL
    DROP FUNCTION [IDM_RPT_DATA].[patternReplace];
GO

-- □ patternReplace: Logic and flow preserved
CREATE FUNCTION [IDM_RPT_DATA].[patternReplace]
(

```

```

    @InputString VARCHAR(4000),
    @Pattern VARCHAR(100),
    @ReplaceText VARCHAR(4000)
)
RETURNS VARCHAR(4000)
AS
BEGIN
    DECLARE @Result VARCHAR(4000) = '';
    DECLARE @First INT;
    DECLARE @Next INT = 1;
    DECLARE @Len INT = COALESCE(LEN(@InputString), 8001);
    DECLARE @EndPattern INT;

    WHILE (@Next <= @Len)
    BEGIN
        SET @First = PATINDEX('%' + @Pattern + '%',
SUBSTRING(@InputString, @Next, @Len));
        IF COALESCE(@First, 0) = 0
        BEGIN
            SET @Result = @Result +
                CASE
                    WHEN @InputString IS NULL OR @Pattern IS
NULL OR @ReplaceText IS NULL THEN NULL
                    ELSE SUBSTRING(@InputString, @Next, @Len)
                END;
            BREAK;
        END
        ELSE
        BEGIN
            SET @Result = @Result + SUBSTRING(@InputString,
@Next, @First - 1);
            SET @Next = @Next + @First - 1;
            SET @EndPattern = 1;
            WHILE PATINDEX(@Pattern, SUBSTRING(@InputString,
@Next, @EndPattern)) = 0
                SET @EndPattern = @EndPattern + 1;
            WHILE PATINDEX(@Pattern, SUBSTRING(@InputString,
@Next, @EndPattern)) > 0
                AND @Len >= (@Next + @EndPattern - 1)
                SET @EndPattern = @EndPattern + 1;
        END
    END

```

```

        SET @Result = @Result + @ReplaceText;
        SET @Next = @Next + @EndPattern - 1;
    END
END
RETURN @Result;
END;
GO

```

4. Navigate to the [CDN](#) website.
5. Click the **Access Requests by Recipient** report.
6. Download the .rpz and .zip files for the **Access-Requests-by-Recipient** report.
7. Perform steps 5 and 6 for the **Access Requests by Requester** and **Access Requests by Resource** reports.

OpenText Identity Manager does not reflect changes made to the Use SMTP TLS option in OpenText Identity Console

Issue: While setting up an email server in OpenText Identity Console, if you enable or disable the `notSMTPUseTLS` attribute for the default notification template in the Tree View, the same value might not be available on the Email Based Approval page in OpenText Identity Manager. However, the selection is saved, and the email server is updated based on your preference.

This discrepancy happens because the `notfSMTPUseTLS` LDAP attribute is updated differently in Identity Applications and OpenText Identity Console. When you make the change in OpenText Identity Console, the attribute is updated directly. However, changing the **Use SMTP TLS** value in **Outgoing Email Settings** of OpenText Identity Manager's Email Based Approval page, it updates the `com.netiq.rbpm.smtp.tls` property in the `ism-configuration.properties` file. But, the value you select in OpenText Identity Console is still applied, even if it does not appear on the Email Based Approval page in OpenText Identity Manager. [Issue: OCTCR56A585739]

Workaround: To ensure consistent behavior, you can modify the **Use SMTP TLS** value in the **Outgoing Email Settings** option on Identity Manager's Email Based Approval page based on the value you select in Identity Console.

Organization chart buttons for a level 2 or higher relationship hierarchy is missing

Issue: For a level 2 or higher relationship, the organization chart does not show the options to choose a relationship for viewing, navigate to the next level in the

relationship hierarchy, send emails, and view more information about that entity. This issue is seen when the hierarchical depth in the **General Settings** is set to a level 2 (or higher). [Issue: OCTCR56A585426]

Workaround: To view the organization chart buttons for the level 2 (or higher) relationship, search for the level 2 user/entity in the organization chart.

Remote Loader reports invalid driver object password after upgrade

Issue: After upgrading the Remote Loader version to 25.4 (v4.10.2) on Windows, it is unable to connect to the Active Directory driver using the basic authentication password. [Issue: OCTCR56A584022]

Workaround: After upgrading Identity Manager to 25.4 (v4.10.2), perform the following steps:

1. Stop the Remote Loader instance on the Remote Loader server.
2. Reset the driver object password and the Remote Loader password.
3. Start the Remote Loader instance for the Active Directory driver.

Observing Error: StatusLogger Reconfiguration failed in catalina log file

Issue: After you install OpenText Identity Manager 25.4 (v4.10.2) on Windows, you might encounter the following error in catalina.out logs:

```
ERROR StatusLogger Reconfiguration failed: No configuration found for '<xxxxxxx>'
at 'null' in 'null'
```

[Issue: OCTCR56A584800]

Workaround: The error does not affect any functionality. You can ignore it.

Form Builder issues

You might encounter the following issues while working with JSON forms in Form Builder:

- [Field validation messages lack clarity](#)
- [Form builder hangs while scrolling](#)
- [The Button component does not work](#)
- [Tree component issues](#)

Field validation messages lack clarity

Issue: Form field validation messages notify users when they enter an invalid or unacceptable value into a field. These messages typically consist of a key-value pair, with the value intended for user display. However, in this release, the form fields display keys rather than the corresponding values. For example, entering an invalid email address presents `invalid_email` instead of `Email must be a valid email`.

[Issue: OCTCR56A598009]

Workaround: To add the messages in English:

1. Launch Form Builder.
2. Click  **Localization**.
3. Click **English** to expand.
4. Add a trailing comma and the key-value pairs for the messages to the last line.

For example,

```
{
  "Submit": "",
  "error": "Please fix the following errors before
submitting.",
  "invalid_date": "{{field}} is not a valid date.",
  "invalid_email": "{{field}} must be a valid email.",
  "invalid_regex": "{{field}} does not match the pattern
{{regex}}.",
  "mask": "{{field}} does not match the mask.",
  "max": "{{field}} cannot be greater than {{max}}.",
  "maxLength": "{{field}} must be shorter than {{length}}
characters.",
  "min": "{{field}} cannot be less than {{min}}.",
  "minLength": "{{field}} must be longer than {{length}}
characters.",
  "next": "Next",
  "pattern": "{{field}} does not match the pattern
{{pattern}}",
  "previous": "Previous",
  "required": "{{field}} is required"
}
```

5. Click **Save**.

Form Builder hangs while scrolling

Issue: The Form Builder occasionally freezes while scrolling through the JSON forms in **Form JSON** and **JS Editor** views. This issue is observed in two scenarios:

- While working with a JSON form that contains many functions and methods.
- When your screen resolution differs from the system-recommended value.

[Issue: OCTCR56A602415]

Workaround: There is no workaround available. You can relaunch Form Builder.

The Button component does not work

Issue: After upgrading Designer, the Button component in JSON forms does not work for approve and request actions. [Issue: OCTCR56A604329]

Workaround: Perform the following steps:

1. Navigate to the Button component's **Display** tab.
2. Copy the logic specified in the **Button Request Logic** or **Button Approve Logic** fields.
3. Change the **Action** to **custom**.
4. Specify the logic copied from step 2.
5. Click **Save**.

Tree component issues

You might encounter the following issues with the Tree component in Form Builder:

- The fields display a non-array validation error in the form **Preview**. This error occurs when the Tree component is set to display a default value. You cannot submit the form until you resolve the validation error. [Issue: OCTCR56A585664]

To resolve the error, change the default value with ID of that field in the **Form JSON** view.

- The expand functionality of a Tree component does not work as expected. The **Preview** form does not allow you to expand or select a sub-container.
- When you select a container or sub-container, the field displays the **dn** value instead of **name**.

The following **Data Source Raw JSON** is a sample data from the Tree component:

```
{
  "dn": "unique id",
  "name": "container data",
  "data": "any meta-data attached with the container",
  "subContainers": [
    {
      "dn": "id1",
      "name": "container data1",
      "icon": "glyphicon glyphicon-cloud"
    },
    {
      "dn": "id2",
      "name": "container data2",
      "data": "any meta-data attached with the container",
      "subContainers": [
        {
          "dn": "id3",
          "name": "container data3",
          "icon": "glyphicon glyphicon-cloud"
        }
      ]
    }
  ]
}
```

When you select the **container data** option in **Preview**, the field displays the `unique id` instead of the `container data` . [Issue: OCTCR56A603396].



© Copyright 2026 Open Text

For more info, visit <https://docs.microfocus.com>
