

OpenText™ Identity Manager

Understanding Designer concepts

Version : 25.4

PDF Generated on : April 21, 2026

Table of Contents

1. Understanding Designer concepts	1
1.1. Designer concepts	2
1.1.1. How Opentext Identity Manager works	3
1.1.2. How Designer works with OpenText Identity Manager	6
1.1.3. Designer features	9
1.1.4. Administration tools	11
1.2. Getting help	12
1.2.1. Help from the welcome page	13
1.2.2. Browsing for information	14
1.2.3. Getting context-sensitive help	16
1.2.4. Getting help from the web	17
1.2.5. Viewing demos	18
1.2.6. Searching for information	19
1.2.7. Customizing the browser and help server	20
1.4. Workspaces, perspectives, and views	23
1.4.1. Specifying the workspace	24
1.4.2. Project file format	25
1.4.3. Managing perspectives	26
1.4.4. Managing views	29
1.4.5. The Project view	39
1.4.6. The Outline view	47
1.4.7. The Navigator view	75
1.4.8. Policy Set view	82
1.4.9. The Properties view	89
1.4.10. The Search Results view	92
1.4.11. The Tasks view	93
1.4.12. The Trace and Error Log views	101

1.4.13. The Dataflow view	103
1.4.14. The Project Checker	105
1.5. Editors, builders, and wizards	106
1.5.1. Editors	107
1.5.2. Builders	112
1.5.3. Wizards	114
1.6. Planning identity solutions	115
1.6.1. Planning an identity project	116
1.6.2. Using Designer in your planning process	122
1.6.3. Security best practices	125
1.8. Terminology	129
1.9. Menu options	135
1.9.1. File menu	136
1.9.2. Edit menu	143
1.9.3. View menu	146
1.9.4. Project menu	147
1.9.5. Live menu	150
1.9.6. Tools menu	154
1.9.7. Model menu	156
1.9.8. Window menu	170
1.9.9. Help menu	187

1. Understanding Designer concepts

This guide is for anyone who wants to better understand how the Designer tool fits into the OpenText Identity Manager framework. The guide also covers basic Designer concepts and features that are available. This guide is intended for OpenText Identity Manager administrators and consultants.

1.1. Designer concepts

Designer for OpenText Identity Manager helps you design, test, document, and deploy the solution in a network or test environment. From a design perspective, Designer helps you graphically see all of the components that make up your solution and how they interact. From a test perspective, Designer enables you to modify your OpenText Identity Manager implementations to ensure they perform as expected.

From a document perspective, Designer keeps track of your design and layout information and presents that information in a format of your choosing with the simple click of a button. From a deployment perspective, Designer allows you to deploy and enable part or all of your solution into your actual networking environment. In addition, Designer enables teams to share work on enterprise-level projects.


- [How OpenText Identity Manager works](#)
- [How Designer works with OpenText Identity Manager](#)
- [Designer features](#)
- [Administration tools](#)

1.1.1. How Opentext Identity Manager works

OpenText Identity Manager is a collection of products that provide the following capabilities:

- Data Synchronization
- Workflow
- Role Assignments
- Self-Service
- Auditing and Reporting

It provides these capabilities through a number of components, as shown in the following figure:



Data synchronization

Simply put, data synchronization is the ability to move data that has been changed in one location to a different location. Data synchronization can include password

synchronization, but it is not limited to that because OpenText Identity Manager can synchronize any data that is stored in a connected system that has access to the Identity Vault.

Data synchronization, including password synchronization, is provided by the five base components of the OpenText Identity Manager solution: the Identity Vault, Identity Manager engine, drivers, Remote Loader, and connected applications.

Workflow

Through the User Application, OpenText Identity Manager provides the means to perform such functions as workflow approval, role assignments, attestation, and identity self-service. The User Application is a browser-based Web application that allows you to initiate provisioning and role assignment requests, as well as manage the approval process for these requests.

Workflow approval allows users to request access to networking resources, which can include an approval process involving one or more managers.

Role assignments

Role assignments allow users to receive access to network resources that have been assigned to them. You can receive access to role assignments either at an individual level or at a group membership level.

The Identity Applications Administration interface allows business and security analysts manage roles and resources in OpenText Identity Manager. The role and resource management features allows you to view and manage permission assignments across various connected systems in organizations managed by OpenText Identity Manager. You can also design roles and map them with resources across connected systems. For more information about roles-based provisioning, see [User Application Parameters](#) in the [Install and Upgrade Guide for Linux](#).

Self-service

The self-service capabilities of OpenText Identity Manager allow users to edit their own profiles, search a directory, change their passwords (including password hints and challenge responses), review password status, and, if authorized, create accounts for new users or groups. If you are an administrator, you can also view reports on the applications that are associated with a user.

For more information about self-service capabilities, see [“Managing Your Profile”](#) in the [User’s Guide to the Identity Applications](#).

Auditing and reporting


OpenText Identity Manager uses a Platform Agent to capture events from the Identity Vault and tracks those events through Sentinel Log Management for IGA (Sentinel). It collects identity information and events from the Identity Vault, administration tools, and OpenText Identity Manager.

For more information about Sentinel Log Management for IGA, see [Installing Sentinel Log Management for Identity Governance and Administration](#) in the [Install and Upgrade Guide for Linux](#).

1.1.2. How Designer works with OpenText Identity Manager

Designer is a powerful, graphical toolset that works on Windows, Linux, or MAC workstations or laptops. Designer is self-contained, with a complete help system as part of the software. This allows you to take a laptop anywhere to work on your OpenText Identity Manager solution.

Designer helps you plan, design, test, document, and deploy OpenText Identity Manager solutions in a network or test environment. Designer does this through a series of windows called "views," as well as a number of builders, wizards, and editors.



The Outline View, Modeler, and Palette in Designer

Planning

- Designer allows you to set up complete OpenText Identity Manager solutions in a test environment so you can work through any problems before deploying the solution into an actual work environment.
- The Project view has directories that allow you to use drag and drop to store plans, documents, and figures pertaining to your solution.

- For more information about planning your OpenText Identity Manager solution, see [Planning Identity Solutions](#).

Designing

- Designer can help you graphically see all of the components that make up your solution and how they interact with each other.
- The Architect view in the Modeler gives you icons and a graphics area to help you organize and visualize your environment. For more information about the Architect view, see "[Architect Mode](#)" in the [Designer Administration Guide](#).
- The Developer view in the Modeler allows you to design and configure the components that make up your Identity solution. For more information about the Modeler view, see "[Creating a Model](#)" in the [Designer Administration Guide](#).

Testing

- Designer allows you to modify your OpenText Identity Manager implementations in a test environment to ensure that they perform as expected.
- Designer is team-enabled, allowing teams to share work on enterprise-level projects. Through the Version Control view, teams can work on the same solutions, share policy procedures, and keep track of who make changes to objects. For more information about the Version Control view, see "[Version Control](#)" in the [Designer Administration Guide](#).

Project documentation

- Designer keeps track of your design and layout information in a project and can present that information in a format of your choosing with the simple click of a button.
- Using Designer to document your OpenText Identity Manager solution can save you weeks or months of gathering and writing driver specifications and their implementations. For more information about documenting your projects, see "[Documenting Projects](#)" in the [Designer Administration Guide](#).

Deployment

- Designer allows you to deploy and enable part or all of your solution into your actual networking environment.

- Through the Import feature, you can import tested solutions or parts of a project from a test or working environment. For more information about importing, see ["Importing into Designer"](#) in the [Designer Administration Guide](#).
- After you have a tested solution that is ready for deployment, you can use Designer's Deploy feature to place that project into production. For more information about deploying a project, see ["Deploying and Exporting"](#) in the [Designer Administration Guide](#).

1.1.3. Designer features

Highly productive environment

The following Designer features help you be more productive:

- A disconnected mode that enables you to work from your laptop when you're on the go
- Strong visual editors, minimal pop-ups, and well-synchronized views maximize productivity
- Powerful window, view, perspective, and tool management
- Designer is team-enabled, allowing teams to share work on enterprise-level projects through the Version Control view
- Dozens of wizards and builders help you configure projects and policies
- Auto-creation of objects, auto-value, auto-connection, auto-layouts
- Strong copy/paste functionality within and across editors
- Full keyboard support in all editors
- Full undo/redo functionality in most editors and views
- Ability to scale the UI from basic to more advanced views
- Ability to filter key views to see as much or as little as you need to see
- Integrated XML editor with syntax highlighting, auto-suggest, and search and replace capabilities
- Very efficient, compact, powerful, and productive off-line schema management tools
- Value history on many fields to reduce typing
- Many preferences and settings that can help you customize the UI to fit how you want to use Designer
- Logs and traces that are easy to access and view
- Thorough contextual help and a powerful searchable help system
- Quick and easy installation

- Auto-update notifies you of any updates and easily pulls them in

Tools for developers

- Easily add and model something that is not in the shipping version of Designer.

For example, you can add your own applications, drivers, resources, and icons.

- Configure Designer to use a different editor.

You can configure all file types (for example, `.xml` and `.txt`) to use your text editor of choice. Eclipse-based text editors work best, but you can also include various artifacts (for example, word processing documents and spreadsheets). Your system's native text editor is automatically integrated into Designer if the platform supports it.

- Develop and debug in Java.

If you install Designer plug-ins into a full Eclipse install, you can perform Java development and debugging, ANT, C#, and UML modeling, all in the same tool alongside Designer. This has particular value to OpenText Identity Manager driver writers (Java or C) who want the tools all together.

- Use public APIs.

OpenText Identity Manager uses fully published public Eclipse APIs as an underlying project data model that is consistent with open industry standards in its format, along with published Eclipse extension points.

With an off-the-shelf Eclipse book and knowledge of our extension points, you should be able to contribute very rich content to Designer. There are books, resources, and forums in the Eclipse community to address most of your needs. For further information, see [Eclipse Resources](#).

1.1.4. Administration tools

OpenText Identity Manager contains multiple tools to assist you in setting up and configuring a working solution. These are Analyzer, Designer, iManager, Catalog Administrator, and the User Application administration console.

Analyzer is an Eclipse-based identity management toolset that helps you ensure that internal data quality policies are adhered to by providing data analysis, data cleansing, data reconciliation, and data monitoring and reporting. Analyzer lets you analyze, enhance, and control all data stores throughout the enterprise.

iManager and Designer have similarities, but their features and user experience are optimized for their respective target users and environments. Designer is a planning and design tool, and iManager is a real-time administrator tool. They are compatible. However, package management is only done through Designer. iManager is package-aware, but it can't support package management.

iManager is a browser-based tool that provides a single point of administration for many products, including Identity Manager. By using the Identity Manager plug-ins for iManager, you can manage Identity Manager and receive real-time health and status information about your OpenText Identity Manager system.

The User Application provides a Web-based administration console that allows you to configure, manage, and customize password self-service, roles, and provisioning. The administration console is added as an **Administration** tab in the User Application for anyone who has been assigned administrative rights.

These tools can help you to implement a viable OpenText Identity Manager solution into your organization.

1.2. Getting help

You can find information about Designer in its local help system, in the `readme.txt` file, and in the online documentation. Information in the help system is not localized. If you need localized information, refer to the [Designer Administration Guide](#).

- [Help from the welcome page](#)
- [Browsing for information](#)
- [Getting context-sensitive help](#)
- [Getting help from the web](#)
- [Viewing demos](#)
- [Searching for information](#)
- [Customizing the browser and help server](#)

1.2.1. Help from the welcome page

When Designer starts, a welcome page appears and makes it easy for you to get started.

Options on the Welcome Page

Option	Description
Overview	Provides an overview of Designer and OpenText Identity Manager.
What's New	• Describes what's new in this release. • Enables you to update Designer. • Links to the Readme file.
Tutorials	Launches Flash demos of some Designer tasks.
Web Resources	Provides links to online information and downloads.
Run Designer	Takes you to the Designer program.

The icons on the toolbar take you to the Welcome page, toggle between previous and next pages, and enable you to customize the Welcome page.


You can close the Welcome page at any time by clicking the **X** next to **Welcome**.

To return to the Welcome page, click **Help > Welcome**.

1.2.2. Browsing for information


To navigate all of the help topics, you can use a built-in Web browser:

1. From Designer's main menu, select **Help > Help Contents**.



The text under **Using the Eclipse help system** describes the icons that help you navigate and use the Help system.

2. In the Contents pane, select **Designer for Identity Manager**.



3. Navigate to the topic that you're interested in.

or


Select the **Index** icon in the Contents pane to see an index of the topics.

1.2.3. Getting context-sensitive help

1. Press F1 or click the Help icon  .

If you maximize an editor (for example, the Modeler), help topics do not display when you press F1. To view the help, minimize the editor.


2. Click links under **About** and **Dynamic Help**.



1.2.4. Getting help from the web

To view results found through Google or in the Eclipse help system:

1. Select **Help > Search**.
2. Type text in the **Search expression** field, then click **Go** or press Enter.
3. Click **Web Search**.



Related Topics in Google and Eclipse

1.2.5. Viewing demos

To see how Designer works, view the Flash demos that are available on the Welcome page:

1. Select **Help > Welcome**.
2. Select the **Tutorials** icon.
3. Select a demo:
 - Model Projects
 - Import
 - Create a Workflow
 - Manage and Simulate Policies
 - Documentation Generation Overview


1.2.6. Searching for information

1. Select **Help > Search**.
2. Type a topic in the **Search** field, then click **Go**.

You can also select **Help > Help Contents**, then use the Search option above the Contents pane, or click **Search** at the bottom of the context-sensitive Help view.

1.2.7. Customizing the browser and help server

1. From the main menu, click **Window > Preferences**.
2. Select **Help**, make changes, then click **OK**.



Because Designer is built on Eclipse, you are able to use Help server functionality, as a development tool for building your own tools. If you have a team environment where the entire team is using Eclipse, you might want to set up a common Help server, and then use that server for help files and content.

For more information about Help and the Help server:

- See ["Help"](#) in the [Designer Administration Guide](#).
- Go to the Eclipse Website.

3. (Optional) Expand **Help**, then click **Content**.
4. (Optional) Click **Include help content from a remote infocenter**.
5. Click **Add**, then fill in the following fields for the remote help server:

Name: Specify a name for the remote help server.

Host: Specify the IP address or DNS name of the remote help server.

Path: Specify the path to the help files on the remote help server.

Use default port: Click this option if you want to use the default port.

Use port: Click this option, then specify the custom port.

6. (Optional) Click **OK**. to add the help server information.
7. Click **OK** to close the Help Content page.

1.3. What's new in Designer

Designer is constantly being updated with new features and enhancements. To find out what's new in Designer:

1. Run Designer for OpenText Identity Manager.
2. Click **Help > What's New**.

You can also click **Help > Help Contents > Designer for Identity Manager > What's New in Designer**.

In addition, Designer's auto-update feature notifies you of new features so you can download them to have the most current version of Designer.

1.4. Workspaces, perspectives, and views

Designer has many views to help you manage your projects. Many of these views help you manage the different elements that appear in the Modeler view and give you a different perspective on the projects you are creating.

For instance, the Project view shows all of the projects you have created, and the Outline view shows all of the objects that have been created and added to the project. The Navigator view shows all of the files that have been created for the project and their respective file types and locations.

For information about the Modeler view and its functions, see [Creating a Model](#) in the [Designer Administration Guide](#). For information about policies, see [Understanding Policies Guide](#) and [Using Designer to Create Policies](#).

- [Specifying the workspace](#)
- [Project file format](#)
- [Managing perspectives](#)
- [Managing views](#)
- [The Project view](#)
- [The Outline view](#)
- [The Navigator view](#)
- [Policy Set view](#)
- [The Properties view](#)
- [The Search Results view](#)
- [The Tasks view](#)
- [The Trace and Error Log views](#)
- [The Dataflow view](#)
- [The Project Checker](#)

1.4.1. Specifying the workspace

A workspace is a directory on your local hard drive where your projects and settings are stored. You specify your workspace directory each time you launch Designer, unless you select the **Use this as the default and do not ask again** option to skip the Workspace Launcher window.

The default workspace directory for a Designer 3.0 and above on a Windows workstation is `Documents and Settings\username\designer_workspace`.



Important

Earlier Designer workspaces are not compatible with Designer 3.0 and above. Designer stores projects and configuration information in a workspace. These workspaces are not compatible from one version of Designer to another. You need to point Designer 4.0.2 to a new workspace, and not to a workspace used by a previous version of Designer.

If you have Designer 2.x or 3.0 Milestone projects, you can import the projects into Designer 4.5 (**File > Import > Project from File System**). Be sure the **Copy project into the workspace** option is selected. Importing the project runs the Converter Wizard, making the project compatible with Designer 4.5 architecture and placing it under your designated Designer 4.5 workspace directory (`designer_workspace` by default).


You can switch to another workspace by selecting **File > Switch Workspace > Other**. Select or type the name of the different workspace. Designer quickly restarts, loads the new workspace, and loads any projects and settings you have in that workspace. If the workspace doesn't exist, Designer creates it. Do not use previous Designer workspaces with Designer 3 and above.

For quick access, the most recently used workspaces appear when you select **File > Switch Workspace**.

You can have multiple workspaces.

1.4.2. Project file format

All projects are stored on the file system in a directory. By default, this is in the `C:\Documents and Settings\Username\designer_workspace` directory on a Windows workstation. However, you can specify a different directory when you create the project. (See “[Creating a Project](#)” in the [Designer Administration Guide](#) All of your data and graphical layout information is saved in a directory corresponding to the project name. For example, the following files and directories are stored under the `\designer_workspace3\Blanston01` directory:



Name	Size	Type
Designer		File Folder
Model		File Folder
.project	1 KB	PROJECT File
Blanston01.cproj	1 KB	CPROJ File
Blanston01.proj	1 KB	PROJ File

Local Directory Structure

The main file in the project’s directory is the `.proj` file. This file uses an industry-standard XML format called XMI (XML Metadata Interchange Format). You never need to directly edit this file.

What is XMI?

XMI enables easy interchange of metadata between modeling tools and between tools and metadata repositories in distributed heterogeneous environments. XMI integrates three key industry standards:

- XML (Extensible Markup Language, a W3C standard)
- UML (Unified Modeling Language, an Object Management Group (OMG) modeling standard)
- MOF (Meta Object Facility, an OMG modeling and metadata repository standard)

The integration of these three standards into XMI combines the best of OMG and W3C metadata and modeling technologies. The integration enables developers of distributed systems to share object models and other metadata. XMI, together with MOF and UML, forms the core of the OMG repository architecture that integrates object-oriented modeling and design tools with each other and with a MOF-based extensible repository framework.

For more information about XMI, go to [XML Metadata Interchange \(XMI\)](#).

1.4.3. Managing perspectives

A perspective is a collection of related views and editors. To get to the perspective choices, select **Window > Open Perspective**. The following perspectives are available:

- **Debug:** Used for XML development.
- **Designer (default):** Provides views (for example, Project, Outline, Property, and Tasks) and editors (for example, the Modeler or the Policy Editor) to help you design and deploy Identity Management solutions.
- **Java/Java Browsing:** Used for Java development.
- **Java Type Hierarchy:** Optimized for use with the Hierarchy view for Java projects.
- **Plug-in Development:** Used for developing the Eclipse plug-in applications.
- **Resource:** A generic perspective. You can use this perspective for projects other than Designer.
- **Team Synchronizing:** Used for comparing the local project with the version controlled project.

Use the following information to manage each perspective:

- [Opening a perspective](#)
- [Resetting a perspective](#)
- [Closing a perspective](#)

Opening a perspective


The Designer perspective should be open and active the first time you run the application. If you close the perspective and want to reopen it, use menus or the Perspective Bar.

Using menus to open a perspective

1. On the main menu, click **Window > Open Perspective**.
2. Select **Designer**, then click **OK**.

Using the perspective bar to open a perspective

1. On the main Perspective Bar (found on the right side, on the same level as the toolbar), click the **Perspective Switcher** icon.



2. From the list, select **Designer**, then click **OK**.

Resetting a perspective


After moving or resizing items in the Modeler workspace, you might want to return your perspective to its original layout. To quickly reset items in the workspace:

1. From the main menu, click **Window**.
2. Click **Reset Perspective**.

Closing a perspective

Do one of the following:

- On the main menu, select **Window > Close Perspective** (or **Close All Perspectives**).



Options to Close a Perspective


- On the Perspective Bar, right-click the perspective, then click **Close**.

1.4.4. Managing views

Views enable you to view or edit projects.

Available views in Designer

Below is a list of all of the views that are available to you in Designer. The view names are followed by a brief description and a cross reference to more information. The views are broken into two groups: the views that appear in the **Window > Show View** option and the views that appear in the **Window > Show View > Other** option. Some views are listed in both locations.



Selecting a View

- [Views in the Window > Show View Option](#)
- [Views in the Window > Show View> Other Option](#)

Views in the Window > Show View option

The views that appear in the **Window > Show View** option include:

- **Dataflow:** Designer allows you to manage how the data flows between the Identity Vault and the connected systems. You can see how the data flows between all of the connected systems, make changes as needed, create reports about the data, and view the flow of passwords between the systems. For more information, see [Managing the Flow of Data](#).
- **Outline:** The Outline view provides an outline of all of the objects you have open in an active editor. The Outline view's contents vary, depending on the editor you have open at the time. For example, if you have a project open in the Modeler

view, you see an outline of all of the objects that have been created for that project. See [The Outline View](#).

- **Policy Set:** The Policy Set view lists policies and displays a toolbar. The list displays all policies contained in the selected policy set. During a transformation, the policies within the list are executed from top to bottom. For a description of the icons located on the Policy Set view toolbar, see [Policy Set View](#).
- **Project:** The Project view lists all existing Designer projects. From the Project view, you can quickly find, open, view, navigate, manage, close, and delete any Designer project. See [The Project View](#).
- **Project Checker:** Designer provides a Project Checker tool to check your project. The Project Checker checks for proper design, contexts, server associations, policies, missing user data, and dependency problems that would cause the project deployment into the Identity Vault to fail. The project can be checked at any time, but you should always run the Project Checker before deploying your project. See [Checking Your Projects](#).
- **Provisioning View:** The Provisioning view provides persistent access to Designer's provisioning features. Use the Provisioning view to access the editors that allow you to create and manipulate User Application components, manipulate object definitions, such as import or export object definitions, and define the User Application driver's supported and default locales.
- **Search/Replace Results:** You can use the Search/Replace Results view to search across an entire project. It allows you to search for a string and replace the string with a different one. With the Modeler view active, press Ctrl+F, then select the object types for which you want to search. The results appear in the Search Results view, sorted by name, class, type, and notes. See [The Search Results View](#).
- **Tasks:** The Tasks view enables you to make and prioritize notes while you manage identities. This view is for your convenience; it can contain whatever you want and won't affect the functionality of your solution. See [The Tasks View](#).
- **Trace:** The Error Log view can help you troubleshoot. If something isn't working, messages written to the error log might help you. The log is named `.log`. It is a hidden file. To view the error log, you can use menus or browse the file system. See [Viewing the Error Log](#).
- **Version Control:** Version control enables you to track revisions of your project, along with all the objects and files in that project, share those revisions with other members of your team, manage the history of your objects, and make sure

that every member of your team is using the same version of your project. See [Version Control](#).

Views in the Window > Show View> Other option

The **Window > Show View > Other** option contains views under the following headings:

- [General](#)
- [Designer for OpenText Identity Manager](#)
- [Help](#)
- [PDE Runtime](#)
- [Provisioning](#)
- [XML](#)

General

- **Bookmarks:** The Bookmarks view enables you to see bookmarks that you have set in your text editors. To access the Bookmarks view, select **Window > Show View > Other** and select the **Bookmarks** option under the **General** heading.
- **Classic Search:** The Classic Search view enables you to search files, Java, or plug-ins. This is a default Eclipse function.
- **Console:** The Console view allows you to view any consoles you have open. To access the Console view, select **Window > Show View > Other** and select the **Console** option under the **General** heading.
- **Error Log:** The Error Log view can help you troubleshoot. If something isn't working, messages written to the error log might help you. The log is named `.log`. It is a hidden file. See [Viewing the Error Log](#)
- **Internal Web Browser:** You can open the Internal Web Browser view by selecting **Window > Show View > Other** and then selecting the **Internal Web Browser** option under the **General** heading. You can also open a Web browser within the Designer utility. The Web browser button is available from the main toolbar. See [Opening a Web Browser](#)
- **Markers:** A marker is associated with the Workbench, where it is used for tasks, problems, and bookmarks. The Markers view displays all markers in your project.

- **Navigator:** The Navigator view enables you to manage and view the file resources that are in your workspace. You can see your projects and files as they actually exist in the file system. You can add files and folders, and append them to your projects or workspace. See [The Navigator View](#).
- **Outline:** The Outline view provides an outline of all of the objects you have open in an active editor. The Outline view's contents vary, depending on the editor you have open at the time. For example, if you have a project open in the Modeler view, you see an outline of all of the objects that have been created for that project. See [The Outline View](#).
- **Problems:** You can validate your XML files by using the right-mouse menu in the Source editor. If any validation errors or warnings occur, they are displayed in the Problems view.

The Problems view shows you errors, warnings, and information about any problems relating to data source explorer failures, EMF problems, moduleCore validation markers, problems, or validation messages.

- **Progress:** The Progress view displays the progress of an operation.
- **Project Explorer:** The Project Explorer view allows you to view information about all of the objects found in a project. Pertinent information about a selected object is displayed in the Properties view.
- **Properties:** The Properties view displays information about key-value pairs (for example, Max Log Entries 2). The information displayed depends on what is selected in the active view (for example, the Modeler or Outline view). Often, the Properties view lets you edit the information. You can also view and edit the Administrator settings in an Identity Vault. See [The Properties View](#).
- **Tasks:** The Tasks view enables you to make and prioritize notes while you manage identities. This view is for your convenience; it can contain whatever you want and won't affect the functionality of your solution. See [The Tasks View](#).
- **Templates:** The Templates view allows you to work within the templates of the active editor. The content of this view is editor specific, and not all editors provide templates.

Designer for OpenText Identity Manager

- **Dataflow:** Designer allows you to manage how the data flows between the Identity Vault and the connected systems. You can see how the data flows between all of the connected systems, make changes as needed, create reports

about the data, and view the flow of passwords between the systems. For more information, see [Managing the Flow of Data](#).

- **Policy Set:** The Policy Set view lists policies and displays a toolbar. The list displays all policies contained in the selected policy set. During a transformation, the policies within the list are executed from top to bottom. For a description of the icons located on the Policy Set view toolbar, see [Policy Set View](#).
- **Project:** The Project view lists all existing Designer projects. From the Project view, you can quickly find, open, view, navigate, manage, close, and delete any Designer project. See [The Project View](#).
- **Project Checker:** Designer provides a Project Checker tool to check your project. The Project Checker checks for proper design, contexts, server associations, policies, missing user data, and dependency problems that would cause the deployment of project into the Identity Vault to fail. The project can be checked at any time, but you should always run the Project Checker before deploying your project. See [Checking Your Projects](#)
- **Search/Replace Results:** You can use the Search/Replace Results view to search across an entire project. It allows you to search for a string and replace the string with a different one. With the Modeler view active, press Ctrl+F, then select the object types you want to search on. The results appear in the Search Results view, sorted by name, class, type, and notes. See [The Search Results View](#).
- **Trace:** The Error Log view can help you troubleshoot. If something is not working, messages written to the error log might help you. The log is named `.log`. It is a hidden file. To view the error log, you can use menus or browse the file system. See [Viewing the Error Log](#)
- **Version Control:** Designer contains a new feature called version control. Version control enables you to track revisions of your project, along with all the objects and files in that project, share those revisions with other members of your team, manage the history of your objects, and make sure that every member of your team is using the same version of your project. See [Version Control](#).

Help

- **Help:** You can bring up the Help view by pressing F1 or by clicking a help button. You can also access help by clicking the Help menu at the top of Designer. See [Getting Help](#).

PDE runtime

- **Plug-in Registry:** A problem can occur if a plug-in fails to load. Use the Plug-in Registry view to see which plug-ins are loaded. See [Checking Loaded Plug-Ins](#)


Provisioning

- **Data Item Mapping:** Specifies how object attributes are mapped. See [Mapping Identity Vault to an LDAP Schema](#)
- **E-Mail Notification:** Notification templates enable you to customize and send e-mail messages that users receive when triggers occur. The E-Mail Notification view allows you to view how notification templates are mapped to an e-mail server. See [Setting Up E-Mail Notification Templates](#)
- **Provisioning View:** The Provisioning view provides persistent access to Designer's provisioning features. Use the Provisioning view to access the editors that allow you to create and manipulate User Application components, manipulate object definitions such as import or export object definitions, and define the User Application driver's supported and default locales.

XML

- **XPath Navigator:** The XPath Navigator view supports context-sensitive editing of XPath expressions and syntax highlighting. It automatically attaches to the currently selected XML editor and uses its Document node as the evaluation context. The namespace context shows all namespaces in scope on its document element. See [XPath Navigator](#)

Opening a view



Selecting a View to Open

To open a view, select **Windows > Show View**, then select an option. There are a number of available views that you can see when you select the **Window > Show View > Other** option.


To narrow the list of views from the **Other** option, use the view filter:

1. Select **Window > Show View > Other**.
2. In the edit box, type the name of the view that you want (for example, Trace).

You can open, maximize, and close these views. You can also arrange them however you want, or make Fast Views from them. See [Using Fast Views](#).

To quickly expand or contract a view, double-click the view's tab.

When you minimize a view or an editor stack, a placeholder tray appears in the closest location along the left, bottom, or right edge of the workbench. Each view from the view stack acts as a fast view while it is in this location. You can restore the stack by clicking the tray's Restore icon. You can drag and drop minimized trays to new locations along the workbench edge. Maximizing any stack triggers minimization of all others.



A Placeholder Tray for the Project View

Moving a view

To move a view, drag the view's tab to one of the following locations:

- The left, bottom, top, or right of Designer
- Stacked with other views
- Outside of Designer, where it floats on your desktop

If two or more views are open, you can switch their order.

Minimizing and maximizing views

To minimize a view, do one of the following:

- Click the **Minimize** button in the view's title bar .
- Press Ctrl+M.

To restore the view to its original size, click the **Restore** button in the view's title bar.

To maximize a view or editor, do one of the following

- Double-click the view's tab.
- Click the **Maximize** button .
- Press Ctrl+M.


When it is expanded, the view or editor fills the entire application space. This feature provides maximum working space.

To restore the editor or view to its original dimensions, double-click the view's tab.

Closing a view

To close a view or editor, do one of the following:


- Click the **X** on the view's tab.
- Right-click the view's tab, then select **Close**.



Options to Close a View

Reopening a view window

1. From the main menu, select **Window > Show View**.




2. Select one of the views (for example, Outline).

You can also select **Window > Show View > Other**, then select one of the views under **Designer for Identity Manager** (for example, Projects).

Using fast views

The Fast View toolbar provides an efficient way to manage certain types of views that you don't want to clutter the desktop, but still want to have readily accessible. To add a view to the Fast View toolbar:

1. Click the **Show View as a Fast View Perspective** icon  in the bottom left corner of the Designer window (under the Properties view).
2. Select a view.
3. The view appears to the left of the Modeler view. Right-click the view's tab and deselect **Fast View** to see the view's default placement in Designer.
4. Reselect **Fast View** to have the view with its icon appear next to the **Show View as a Fast View Perspective** icon.




After the icon appears next to the **Show View as a Fast View Perspective** icon, do the following to restore a Fast View to a normal view:

1. Right-click the view icon in the Fast View toolbar.
2. Deselect **Fast View**.

You can also set the following:

- Whether you want the Fast View to appear horizontally or vertically (the **Orientation** option)



Options for Fast Views

- Where you want to dock the Fast View

Views and selected items that appear by default in the Modeler view do not have the Fast View option.


1.4.5. The Project view

The Designer Project view lists all existing Designer projects. From the Project view, you can quickly find, open, view, navigate, manage, close, and delete any Designer project.

To open the Project view, select the **Project** tab in the upper left view of Designer, or if the view is not open, click **Window > Show View > Project** from the main menu.

The Project view provides a standard menu of functions, which are available by right-clicking the **Project** tab. Similarly, the Project view provides an icon bar with additional functions.

[The Project View](#) shows a typical Project view displaying the icons available in a Designer project.



The Project View


[Project Icons Displayed in the Project View](#) describes the project icons displayed in the Project view.


Project Icons Displayed in the Project View

Icon Name	Description
-----------	-------------

Icon Name	Description
Project Name  Blanston1 or  Blanston1	The name of the created project. It is the name of the project stored in the selected workspace directory. Double-clicking the Project name expands and collapses the entries under the project. Right-clicking a project name allows you to do the following: • Create a new Identity Manager Project. • Open the project with the System Model (Modeler view). • Import an Identity Manager Project from: ◦ An Identity Vault ◦ An iManager Export file ◦ A file system ◦ A version control server • Export the project. • Refresh the project. • Make a copy of the project. • Move the project to another workspace. • Disable/enable the project. Disabled projects are taken out of the Version Control view. • Rename the project. • Delete the project.

Icon Name	Description
	• View the project's properties page. Projects under a version control server have a different icon  and have two additional choices: • Check the project into the version control server. • Update the project from the version control server.
System Model  System Model or  System Model	Double-clicking the System Model entry puts the project into the Modeler view. You can create or import driver sets, drivers, channels, or policies into the Modeler to modify the project as needed. Then you can deploy the driver set, drivers, channels, or policies into an Identity Manager system. System Models under a version control server have a different icon  . Right-clicking the System Model allows you to: • Open the project in the Modeler view

Icon Name	Description
Documents  <pre> graph TD Designer[Designer] --> Documents[Documents] Documents --> Generated[Generated] Generated --> images[images] </pre>	Use the Designer > Documents folder for documents that are related to the project. You can also create new folders to organize your projects as needed. The Generated folder under Documents holds your generated documentation files, and the images folder under the Generated folder holds any graphic files that are created when you generate documents. Right-clicking the Documents folder or the Generated folder allows you to: • Create a new file. • Create a new folder. • Import a file or a folder. • Export the project. • Copy the folder. • Paste items into the folder. • Refresh the folder's view.

Icon Name	Description
Toolbox 	The Toolbox folder is for special files that ship with Designer. You cannot create new files or folders under this folder. The Styles folder under the Toolbox > DocumentGenerator folder contains the document generation styles. Right-click this folder to create a new style from the context menu that comes up. Right-clicking the Toolbox folder or its subfolders allows you to: • Copy the folder. • Right-click the Styles folder and select New > Document Generation Style (.docgen) to create a new style. The wizard generates a style (template with a .docgen extension) that displays under the Styles folder. (See Documenting Projects for more information.)

Icon Name	Description
.docgen File  Blanston001.docgen	Right-clicking the .docgen file entry allows you to: • Open the .docgen file with a Style editor. • Copy and delete the .docgen file. Use Copy and Paste to copy documentation files to different projects or folders. • Refresh and rename the file. • Generate documentation using this style.
Additional File Types 	Because the Generated and Images folders can contain many different files, you can see different icons displayed, depending on the file extension. Right-clicking these any of these files allows you to: • Copy and delete the file. Use Copy and Paste to copy documentation files to different projects or folders. • Refresh and rename the file. • Open the file or open the file with a text or system Editor. You can also double-click the file and have Designer choose an editor for the file. • Delete the file.

1.4.6. The Outline view

The Outline view provides an outline of the active editor. To open the Outline view, select the **Outline** tab in the upper left view of Designer, or if the view is not open, click **Window > Show View > Outline**.


The Outline view's contents vary, depending on the editor you have open at the time.

- For the standard Designer editors, you see a tree view of the information, a thumbnail graphical view, or a Policy Flow view, depending on which mode you are in.
- If you open an XML editor for an XML file in the Navigator view (not the embedded XML editor that is part of the Designer editors), you see a tree view of the XML document.

Selecting items in the Outline view also selects them in the Modeler. If the selected item isn't visible in the Modeler, it automatically scrolls into view. Similarly, as you add or remove items the Modeler, they are automatically added or removed in the Outline view.

The Outline view provides a standard menu of functions, which are available by right-clicking the **Outline** tab. The Outline view also provides an icon bar of additional functions specific to the Outline view.

[The Outline View](#) shows a typical Outline view along with its icon bar.



The Outline View

The following sections describe the project icons displayed in the Outline view.

Project name

The Project Name displays the name of the project when you create it. This is the name of the project stored in the `\workspace\project name` directory.

Right-click the project name  to do the following:

New: Under **New**, you can add an application, a Domain Group, or an Identity Vault to the Modeler.

Document Selection: Generates the documentation for the project.

Live: Allows you to import a driver set from the Identity Vault.

Check in: Not available if version control is not enabled for the project.

Update: Not available if version control is not enabled for the project.

Delete: Deletes the project.

Properties: Launches the Properties page associated with this object.

Version control project name

The Project Name icon changes when you commit the project to a version control server.

Right-click the project name  to do the following:

New: Under **New**, you can add an application, a Domain Group, or an Identity Vault.

Document Selection: Generates the documentation for the project.

Live: Allows you to import a driver set from the Identity Vault.

Check in: Checks in the project into a version control server.

Update: Updates the project from a version control server.

Delete: Deletes the project.

Properties: Launches the Properties page associated with this object.

Package catalog

A Package Catalog stores packages that are used in your OpenText Identity Manager solution. The Package Catalog is only displayed in the Outline view.

Right-click the Package Catalog  to perform the following:

Import Package: Allows you to download any available packages to use in your OpenText Identity Manager solution. For more information, see [Importing Packages into the Package Catalog](#)

New Category: Creates a new category to store your packages in.

Category

A category helps organize packages into common categories.

Right-click the category  to perform the following:

New Group: Creates a new group to store your packages in.

Delete: You can delete the category as long as none of the packages in the category are currently installed.

Properties: Allows you to rename the category and add a description for the category.

Group

A group helps organize packages with common functionality together.

Right-click the group  to perform the following:

New Package: Creates a new package. For more information, see [Creating Feature Packages](#)

Delete: You can delete the group as long as none of the packages in the group are currently installed.

Properties: Allows you to rename the group and add a description for the group.

Package

A package contains the components of a driver organized according to what functionality you want to provide to a driver.

The first time you right-click the package  icon, the following options are available:

Request Ownership: Allows you to move a development package from one Designer project to another. It unlocks a package that is not released, only if the package is found in at least one project in the workspace.

Copy Package: Creates a copy of the package.

Delete: Deletes the package.

Properties: Displays the properties of the package.

After you request the ownership of the package, the following options are available:

Generate Prompt Resource: Generates Global Configuration objects that create prompts in the Driver Configuration Wizard. You can create the following prompt types:

- Driver Name
- Initial Settings
- Upgrade Settings
- Remote Loader

For more information, see [Editing Package Prompts](#)

Localization Allows you to generate properties files for localization or imports the properties files for localization.

New Package Version: Changes the package version.

Copy Package: Copies the package.

Build: Builds the package for release.

Delete: Deletes the package.

Properties: Displays the properties of the package.

Identity vault

An Identity Vault represents the OpenText eDirectory tree that has OpenText Identity Manager installed on it.

Right-click the Identity Vault  to perform the following:

New: Under **New**, you can add a driver set, a library, or a server object to the project.

Manage Vault Schema: Allows you to manage the Identity Vault schema.

DirXML Script Tracing: Allows you to turn on or turn off actions, conditions, and tokens on every policy at the Identity Vault level. This allows you to control how rules, conditions, and tokens flow through policies.

Document Selection: Generates the documentation for the Identity Vault.

Import from Configuration File: Imports a driver configuration file.

Import Schema from File: Imports schemas from a file.

Export to File: Exports the Identity Vault configuration and schema to a file.

Live: Allows you to perform the following actions to the Identity Vault:

- **Import:** Imports a driver set from the Identity Vault.
- **Deploy:** Deploys the Identity Vault in Designer to the live system.
- **Compare:** Compares the contents of the Identity Vault in Designer to the live system.
- **Schema:** Allows you to import, deploy, or compare the schema in Designer to the schema in the live system.
- **Manage Directory:** Allows you to manage the objects in the Identity Vault.
- **DS Trace:** Runs a DS Trace from the live system.
- **iManager:** Launches iManager.

- **Driver Status:** Displays the status of the drivers in the selected Identity Vault.
- **Start All Drivers:** Starts all of the drivers in the selected Identity Vault.
- **Stop All Drivers:** Stops all of the drivers in the selected Identity Vault.
- **Restart All Drivers:** Restarts all of the drivers in the selected Identity Vault.

Delete: Deletes the Identity Vault.

Properties: Launches the Properties page associated with this object.

Domain group

Domain groups allow you to group projects into granular portions.

Right-click the Domain  object to perform the following:

New: Under **New**, you can add an application, a Domain Group, or an Identity Vault.

Document Selection: Generates the documentation for the Domain.

Live: Allows you to import objects from the Identity Vault.

Delete: Deletes the Domain Group.

Properties: Launchers the Properties page associated with this object.

If you select to document this group, the generated document filters items that are outside the Domain Group. Drivers bordering the domain are included in the document.

Library

The Library object is a repository of commonly used policies, scripts, and resources that can be referenced from multiple locations. You can place a policy in the library that every driver in the driver set can reference.

Right-click the Library  object to perform the following:

New: Under **New**, you can add the following types of objects:

- Credential application
- Credential repository
- DirXML Script
- ECMAScript

- Mapping Table
- Global Configuration
- DS Object
- Resource
- Schema Map
- XSLT
- From a copy

DriXML Script Tracing: Allows you to turn on or turn off actions, conditions, and tokens on every policy at the Library level. This allows you to control how rules, conditions and tokens flow through policies.

Export to Configuration File: Exports the library to a configuration file.

Import from Configuration File: Imports a configuration file.

Live: Under **Live**, you can:

- **Import:** Imports content into the library. For example you can import a policy.
- **Deploy:** Deploys the library to the Identity Vault.
- **Compare:** Compares the library to the library in the live system.

Delete: Deletes the Library object.

Properties: Launches the Properties page associated with this object.

Server

The Server object is the server in the tree where you have OpenText Identity Manager installed.

Right-click the Server  object to perform the following:

Migrate: Migrates the information from this Server object to another Server object.

Delete: Deletes the Server object.

Properties: Launchers the Properties page associated with this object.

Driver set

The driver set is a collection of OpenText Identity Manager drivers that are stored in a single location.

Right-click the driver set  to perform the following:

New: Under **New**, you can create the following objects:

- Driver
- Job
- Library
- Role-Based Entitlement Policies
- DS Object
- Global Configuration

Copy: Allows you to copy the driver set settings and global configuration values to another driver set.

DirXML Script Tracing: Allows you to turn on or turn off actions, conditions, and tokens on every policy at the driver set level. This allows you to control how rules, conditions, and tokens flow through policies.

Document Selection: Generates the documentation for the driver set.

Import from Configuration File: Imports a configuration file.

Export to Configuration File: Exports the driver set to a configuration file.

Live: Under **Live**, you can:

- **Import:** Import a driver into the driver set.
- **Deploy:** Deploys the selected driver set into the live system.
- **Compare:** Compares the driver set in Designer to a deployed driver set in the Identity Vault
- **Driver Set Configuration:** Allows you to import, deploy, and compare driver set configuration attributes.
- **Driver Status:** Displays the status of all of the drivers in the driver set.
- **Start All Drivers:** Starts all drivers in the driver set.
- **Stop All Drivers:** Stops all drivers in the driver set.

- **Restart All Drivers:** Restarts all drivers in the driver set.

Delete: Deletes the driver set.

Properties: Launches the Properties page associated with the driver set.

If you select **Document Selection**, the generated document filters most items that are outside the driver set. Child objects are also included and parent objects are included in the document for perspective purposes.

ID policy container and ID policy



An ID Policy container is created under an ID Provider driver and is a repository for ID policies. An ID policy allows the ID Provider driver to assign unique IDs to objects. When the ID Provider driver receives an ID request from a client, it generates an identification that is based on the ID policy specified in the request and passes it to the client.

Right-click the ID Policy container to perform the following:

New: Creates a new policy.

Export to Configuration File: Exports the policy container object to a configuration file.

Live: Under **Live**, you can:

- **Import:** Imports a policy in to the policy container.
- **Deploy:** Deploys the ID Policy container into the Identity Vault.
- **Compare:** Compares the ID Policy container in Designer to a deployed ID Policy container in the Identity Vault

Delete: Deletes the ID Policy container.

Properties: Launches the Properties page associated with this object.

Right-click the ID Policy to perform the following:

Add to Package: Allows you to include the policy in a package if it was not installed with a package.

Package Properties: Displays the properties of the package that installed the selected policy.

Revert Customization: Revert Customization is available if the policy is part of a package, and if the policy is customized. Revert Customization is like an undo, and it removes any customizations you made.

Live: Under **Live**, you can:

- **Deploy:** Deploys the ID Policy into the Identity Vault.
- **Compare:** Compares the ID Policy in Designer to a deployed ID Policy container in the Identity Vault.

Delete: Deletes the ID Policy.

Properties: Launches the Properties page associated with this object. To configure ID policies, see [Configuring ID Policies](#)

Driver

A Driver object is a collection of channels, policies, rules, resources, and filters that connect an application to OpenText Identity Manager. Each driver performs different tasks. Policies, rules, resources, and filters tell the driver how to manipulate the data to perform those tasks.

Right-click the Driver object  to do the following:

New: Under **New**, you can add the following policy types:

- Credential application
- Credential repository
- DirXML Script
- ECMAScript
- Entitlement
- Job
- Mapping Table
- Global Configuration
- DS Object
- Resource
- Schema Map

- XSLT
- From a copy

Copy: Copies the driver settings or server-specific driver settings.

Show Dataflow View Launches the Dataflow view for the driver. For more information, see [The Dataflow View](#).

Show Policy Sets: Display the policy sets in this driver.

DirXML Script Tracing: Allows you to turn on or turn off actions, conditions, and tokens on every policy at the driver level. This allows you to control how rules, conditions, and tokens flow through policies.

Simulate: Launches the Policy Simulator, which allows you to test the policies in the driver. For more information, see [Testing Policies with the Policy Simulator](#).

Run Configuration Wizard: Launches the Driver Configuration Wizard, which allows you to install more packages or import a driver configuration file.

Password Synchronization: Allows you to configure the driver to synchronize password between the application and the Identity Vault. For more information, see the [Password Management Guide](#).

Manage Application Schema: Allows you to manage the application's schema from Designer.

Document Selection: Generates the documentation for this driver.

Import from Configuration File: Imports a driver configuration file. This overwrites you current policies with the content in the driver configuration file.

Export to Configuration File: Exports the driver to a configuration file.

Copy Server-Specific Data: Copies server-specific data between servers. To do this, you must have more than one server associated with the driver set. You can add a server to a driver set by going into the Driver Set Properties page. The replica data that you can copy includes:

- Global configuration values
- Named passwords
- Driver authentication information
- Driver startup option

- Driver parameters

Live: Under **Live**, you can:

- **Import:** Imports a driver.
- **Deploy:** Deploys a driver.
- **Compare:** Compares the driver in Designer to a deployed driver in the Identity Vault
- **Driver Configuration:** Imports, deploys, and compares driver configuration attributes.
- **Refresh Application Schema:** Refreshes the application schema in Designer.
- **Driver Status:** Displays the selected driver's status.
- **Start Driver:** Starts the selected driver.
- **Stop Driver:** Stops the selected driver.
- **Restart Driver:** Restarts the selected driver.
- **Set Up Driver Security:** Allows you to configure the driver security that is deployed to the Identity Vault.
- **Set Driver Trace Level:** Allows you to set the driver trace level. The driver trace level is what determines the information displayed in the driver trace.

Delete: Deletes the Driver object.

Properties: Launches the Properties page associated with this object.

If you select **Document Selection**, the generated document filters most items that are outside the driver. Child objects are also included and parent objects are included in the document for perspective purposes.

Publisher and subscriber channels

A channel is a combination of rules, policies, and resources. Designer allows you to import a channel instead of the entire driver. The Subscriber and Publisher channels describe the direction in which the information flows.

The Publisher channel takes the event from the application, database, CSV file, etc., and sends that event to the Identity Vault. Channel events do not need to be the same on each channel.

The Subscriber channel takes the event from the Identity Vault and sends that event to whatever the receiving system is (application, database, CSV file, etc.).

Right-click the Publisher  or Subscriber  channel to perform the following:

New: Under **New**, you can add the following policy types:

- Credential application
- Credential repository
- DirXML Script
- ECMAScript
- Mapping Table
- DS Object
- Resource
- Schema Map
- XSLT
- From a copy

DirXML Script Tracing: Allows you to turn on or turn off actions, conditions, and tokens on every policy at the channel level. This allows you to control how rules, conditions, and tokens flow through policies.

Simulate: Launches the Policy Simulator on the channel to ensure that the policies are working correctly.

Import from Configuration File: Imports information from configuration file.

Export to Configuration File: Exports the channel configuration to a file.

Live: Under **Live**, you can:

- **Import:** Imports items into the channel. For example, you can import a policy.
- **Deploy:** Deploys a channel into the Identity Vault.
- **Compare:** Compares the channel in Designer to a deployed driver channel in an Identity Vault

Properties: Launches the Properties page associated with this object.

Policy

A policy is a collection of rules and arguments that allow you to configure an application to send or receive events to or from the Identity Vault. You use policies to manipulate the data you receive from the Identity Vault or from the application. Each driver performs different tasks, and policies tell the driver how to manipulate the data to perform those tasks.

Right-click the Policy object  to perform the following:

Edit: Launches the Policy Builder so you can edit the policy.

Copy: Creates a copy of the selected policy.

Save As: Allows you to save the policy as an XML file.

DirXML Script Tracing: Allows you to turn on or turn off actions, conditions, and tokens on every policy at the policy level. This allows you to control how rules, conditions, and tokens flow through policies.

Add to Package: Allows you to include the policy in a package if it was not installed with a package.

Package Properties: Displays the properties of the package that installed the selected policy.

Revert Customization: Revert Customization is available if the policy is part of a package, and if the policy is customized. Revert Customization is like an undo, and it removes any customizations you made.

Simulate: Launches the Policy Simulator to test that the policy is working correctly.

Export to Configuration File: Exports the policy to a configuration file.

Live: Under **Live**, you can:

- **Deploy:** Deploys the policy to the Identity Vault.
- **Compare:** Compares the policy in Designer to a deployed policy in the Identity Vault.

Open With: Allows you to open the policy with one of the following editors:

- Designer Built-in Editor
- OpenText XML Editor
- XML Editor
- Text Editor

Delete: Deletes the selected policy.

Properties: Launches the Properties page associated with this object.

Overlay icons

Overlay icons  have an overlay symbol in one of the corners to signify that the object is in a certain state. For example, the policy icon to the left signifies that the policy does not belong to a policy set. An application icon with an overlay signifies that there is more than one driver connected to the application. A driver set icon with a server overlay signifies that the driver set is connected to an OpenText Identity Manager server.

Overlay icons can be informational, warnings, or they can signify errors. In the Compare window, overlay icons tell you whether the object is on the server or in Designer.

They also tell you if you have customized the policies that come in packages. You can either keep your customizations or revert back to the original state of the policy as it is in the package.

Schema mapping

Schema Mapping allows OpenText Identity Manager to synchronize information to the connected system without changing the connected system. A schema translates all classes and attributes for the connected system.

Right-click the Schema Mapping object  to perform the following:

Edit: Launches the Schema Mapping editor so you can edit the Schema Mapping.

Copy: Creates a copy of the Schema Mapping.

Save As: Allows you to save the Schema Mapping as an XML file.

Add to Package: Allows you to include the Schema Mapping in a package, if it is not installed with a package.

Package Properties: Displays the properties of the package that installed the Schema Mapping.

Revert Customization: Revert Customization is available if the Schema Mapping is part of a package, and if the Schema Mapping is customized. Revert Customization is like an undo, and it removes any customizations you made.

Simulate: Launches the Policy Simulator to ensure that the Schema Mapping is working correctly.

Export to Configuration File: Exports a Schema Mapping policy configuration to an XML file.

Live: Under **Live**, you can:

- **Deploy:** Deploys a Schema Mapping policy to the Identity Vault.
- **Compare:** Compares the Schema Mapping policy in Designer to a deployed Schema Mapping policy in an Identity Vault.

Open With: Allows you to open the Schema Mapping policy with one of the following editors:

- Designer Built-in Editor
- OpenText XML Editor
- XML Editor
- Text Editor

Delete: Deletes the selected Schema Mapping policy.

Properties: Launches the Properties page associated with this object.

Resource

Resource objects store information that drivers use. Double-clicking a resource object brings up the object in an editor.

Right-click the Resource object  to perform the following:

Edit: Launches an editor so you can edit the Resource object.

Copy: Creates a copy of the selected Resource object.

Add to Package: Allows you to include the Resource object in a package, if it is not installed with a package.

Package Properties: Displays the properties of the package that installed the resource object.

Revert Customization: Revert Customization is available if the resource object is part of a package, and if the resource object is customized. Revert Customization is like an undo, and it removes any customizations you made.

Export to Configuration File: Exports the Resource policy to a configuration file.

Live: Under **Live**, you can:

- **Deploy:** Deploys the Resource object to the Identity Vault.
- **Compare:** Compares the Resource object in Designer to a deployed Resource object in the Identity Vault.

Open With: Allows you to open the Resource object with one of the following editors:

- Designer Built-in Editor
- OpenText XML Editor
- XML Editor
- Text Editor

Delete: Deletes the selected Resource object.

Properties: Launches the Properties page associated with this object.

Global configuration

Global Configuration objects contain GCV definitions that can be added to a package. The GCV definitions are identical to the GCVs that are contained on a driver or driver set.

Right-click the Global Configuration object  to perform the following:

Copy: Creates a copy of the Global Configuration object.

Add to Package: Allows you to add the Global Configuration object to a package, if it was not installed with a package.

Generate Prompt Resource: Allows you to generate a Prompt Resource object to add to a package. This allows for questions to be presented during the import of the packages.

Package Properties: Displays the properties of the package that installed the Global Configuration object.

Revert Customization: Revert Customization is available if the Global Configuration object is part of a package, and if the global configuration object is customized. Revert Customization is like an undo, and it removes any customizations you made.

Live: Under **Live**, you can:

- **Deploy:** Deploys the Global Configuration object to the Identity Vault.

- **Compare:** Compares the Global Configuration object in Designer to the deployed Global Configuration object in the Identity Vault.

Delete: Deletes the Global Configuration object.

Properties: Launches the Properties page of the Global Configuration object.

XSLT

XSLT represents XSLT style sheets, which are used instead of the DirXML Script.

Right-click the XSLT style sheet object  to perform the following:

Edit: Launches the XLM Editor so you can edit the XSLT style sheet.

Copy: Creates a copy of the XSLT style sheet.

Save As: Allows you to save the XSLT style sheet as an XML file.

Add to Package: Allows you to add the XSLT style sheet to a package, if it was not installed with a package.

Package Properties: Displays the properties of the package that installed the XSLT style sheet.

Revert Customization: Revert Customization is available if the XSLT style sheet is part of a package, and if the XSLT style sheet is customized. The Revert Customization is like an undo, and it removes any customizations you made.

Simulate: Launches the Policy Simulator to ensure that the XSLT style sheet is working correctly.

Export to Configuration File: Exports the XSLT style sheet to an XML file.

Live: Under **Live**, you can:

- **Deploy:** Deploys the XSLT style sheet to the Identity Vault.
- **Compare:** Compares the XSLT style sheet in Designer to an XSLT style sheet in the Identity Vault

Open With: Allows you to open the XSLT style sheet with one of the following editors:

- Designer Built-in Editor
- Novel XML Editor
- XML Editor

- Text Editor

Delete: Deletes the XSLT style sheet.

Properties: Launches the Properties page associated with this object.

Filter

Filter allows the objects to be sent. It's the gatekeeper that restricts the objects (groups, users, and the attributes associated with them) that can be sent to and from an Identity Vault.

Right-click the Filter object  to perform the following:

Edit: Launches the Filter Editor so you can edit the filter.

Save As: Allows you to save the filter as an XML file.

Simulate: Launches the Policy Simulator to ensure that the filter is working correctly.

Export to a Configuration File: Exports the filter to an XML file.

Live: Under **Live**, you can:

- **Deploy:** Deploys the filter into the Identity Vault.
- **Compare:** Compares the filter in Designer to a deployed filter in the Identity Vault.

Open With: Allows you to open the filter in one of the following objects:

- Designer Built-in Editor
- OpenText XML Editor
- XML Editor
- Text Editor

Application

The Application object represents a connected system, whether that system is a database, an application, or CSV files.

Right-click the Application object  to do the following:

New: Allows you to create a new Application object.

Show Dataflow View: Launches the Dataflow view. For more information, see [The Dataflow View](#)

Discover Domain Controller: Allows you to discover the domain controllers in your Active Directory environment. This option is displayed only for the Active Directory application.

Remote Control Desktop: Launches a remote control session for the selected application. The host server must have an existing VNC server running.

Document Selection: Generates the documentation for the application object.

Driver: Under **Driver**, you can:

- **DirXML Script Tracing:** Allows you to turn on or turn off actions, conditions, and tokens on every policy at the policy level. This allows you to control how rules, conditions, and tokens flow through policies.
- **Run Configuration Wizard:** Launches the Driver Configuration Wizard, which allows you to install more packages or import a driver configuration file.
- **Export to Configuration File:** Exports the driver configuration information to an XML file.
- **Import from Configuration File:** Imports a driver configuration file. This overwrites your existing driver with the contents in the configuration file.
- **Import:** Imports items into the driver. For example, you can import policies from configuration files.
- **Deploy:** Deploys the driver into the Identity Vault.
- **Compare:** Compares the driver in Designer to a deployed driver in the Identity Vault
- **Start Driver:** Starts the selected driver.
- **Stop Driver:** Stops the selected driver.
- **Restart Driver:** Restarts the selected driver.
- **Set Up Driver Security:** Allows you to configure the driver's security in the Identity Vault.
- **Set Driver Trace Level:** Allows you to set the driver trace level. The driver trace level is what determines the information displayed in the driver trace.
- **Properties:** Launches the Properties page of the driver.

Delete: Deletes the selected Application object.

Properties: See the Properties page associated with this object.

If you select **Document Selection**, the generated document filters most items that are outside the driver. The driver object is also included, and parent objects above the driver object are included in the document for perspective purposes.

Entitlement

The Entitlement object represents an entitlement assigned to the Subscriber channel.

Right-click the Entitlement object  to perform the following:

Edit: Launches the Entitlement editor so you can edit the Entitlement.

Copy: Creates a copy of the Entitlement.

Save As: Allows you to save the Entitlement as an XML file.

Add to Package: Allows you to include the Entitlement in a package, if it is not installed with a package.

Package Properties: Displays the properties of the package that installed the Entitlement.

Revert Customization: Revert Customization is available if the Entitlement is part of a package, and if the Entitlement is customized. Revert Customization is like an undo, and it removes any customizations you made.

Export to Configuration File: Exports the Entitlement configuration to an XML file.

Live: Under **Live**, you can:

- **Deploy:** Deploys the Entitlement to the Identity Vault.
- **Compare:** Compares the Entitlement in Designer to a deployed Entitlement in an Identity Vault.

Open With: Allows you to open the Entitlement with one of the following editors:

- Designer Built-in Editor
- OpenText XML Editor
- XML Editor
- Text Editor

Delete: Deletes the selected Entitlement.

Properties: Launches the Properties page associated with this object.

Job

The Job object represents a job that you can schedule to run either immediately or at a later date. Designer presently ships with three job types: Random Password Generator, Schedule Driver, and Subscriber Channel Trigger. You can also have custom jobs.

Right-click the Job object  to perform the following:

Copy: Creates a copy of the job.

Edit: Launches the Job Editor so you can edit the job.

Add to Package: Allows you to include the job in a package, if it is not installed with a package.

Package Properties: Launches the Properties page for the package that installed the job.

Revert Customization: Revert Customization is available if the job is part of a package, and if the job is customized. Revert Customization is like an undo, and it removes any customizations you made.

Export to Configuration File: Exports the job configuration to an XML file.

Live: Under **Live**, you can:

- **Deploy:** Deploys the job to the Identity Vault.
- **Compare:** Compare the job in Designer to a deployed job in the Identity Vault.

Open With: Allows you to open the job in one of the following editors:

- Designer Built-in Editor
- OpenText XML Editor
- XML Editor
- Text Editor

Delete: Deletes the job.

Properties: Launches the Properties page associated with this object.

ECMAScript

The ECMAScript object represents an ECMAScript assigned to the Subscriber Channel.

Right-click the ECMAScript object  to perform the following:

Edit: Launches the ECMAScript Editor so you can edit the ECMAScript.

Copy: Creates a copy of the ECMAScript.

Add to Package: Allows you to include the ECMAScript in a package, if it is not installed with a package.

Package Properties: Launches the Properties page for the package that installed the ECMAScript.

Revert Customization: Revert Customization is available if the ECMAScript is part of a package, and if the ECMAScript is customized. Revert Customization is like an undo, and it removes any customizations you made.

Export to Configuration File: Exports the ECMAScript configuration to an XML file.

Live: Under **Live**, you can:

- **Deploy:** Deploys the ECMAScript into the Identity Vault.
- **Compare:** Compares the ECMAScript in Designer to a deployed ECMAScript in an Identity Vault.

Open With: Allows you to open the ECMAScript with one of the following editors:

- Designer Built-in Editor
- OpenText XML Editor
- XML Editor
- Text Editor

Delete: Deletes the ECMAScript.

Properties: Launches the Properties page associated with this object.

Mapping table

The Mapping Table object represents a Mapping Table assigned to the driver.

Right-click the Mapping Table object  to perform the following:

Edit: Launches the Mapping Table Editor so you can edit the mapping table.

Copy: Creates a copy of the mapping table.

Add to Package: Allows you to include the mapping table in a package, if it is not installed with a package.

Package Properties: Launches the Properties page for the package that installed the mapping table.

Revert Customization: Revert Customization is available if the mapping table is part of a package, and if the mapping table is customized. Revert Customization is like an undo, and it removes any customizations you made.

Export to Configuration File: Export the mapping table configuration to an XML file.

Live: Under **Live**, you can:

- **Deploy:** Deploys the mapping table into the Identity Vault.
- **Compare:** Compares the mapping table in Designer to a deployed mapping table in the Identity Vault

Open With: Allows you to open the mapping table in one of the following editors:

- Designer Built-in Editor
- OpenText XML Editor
- XML Editor
- Text Editor

Delete: Deletes the mapping table.

Properties: Launches the Properties page associated with this object.

User Application

The User Application object allows you to manage workflow provisioning.

Right-click the User Application object  to perform the following:

Show Dataflow View: Launches the Dataflow view. For more information, see [The Dataflow View](#)

Remote Control Desktop: Launches a remote control session for the User Application. The host server must have an existing VNC server running.

Document Selection: Generates the documentation for the User Application.

Driver: Under **Driver**, you can:

- **DirXML Script Tracing:** Allows you to turn on or turn off actions, conditions, and tokens on every policy at the policy level. This allows you to control how rules, conditions, and tokens flow through policies.
- **Run Configuration Wizard:** Launches the Driver Configuration Wizard, which allows you to install more packages or import a driver configuration file.
- **Export to Configuration File:** Exports the driver configuration information to an XML file.
- **Import from Configuration File:** Imports a driver configuration file. This overwrites your existing driver with the contents in the configuration file.
- **Import:** Imports items into the driver. For example, you can import policies from configuration files.
- **Deploy:** Deploys the driver into the Identity Vault.
- **Compare:** Compares the driver in Designer to a deployed driver in the Identity Vault
- **Start Driver:** Starts the selected driver.
- **Stop Driver:** Stops the selected driver.
- **Restart Driver:** Restarts the selected driver.
- **Set Up Driver Security:** Allows you to configure the driver's security in the Identity Vault.
- **Set Driver Trace Level:** Allows you to set the driver trace level. The driver trace level is what determines the information displayed in the driver trace.
- **Properties:** Launches the Properties page of the driver.

Delete: Deletes the User Application.

Localize: Under **Localize**, you can:

- **Export Localization to File:** Creates properties files that can be sent to be localized.
- **Import Localization from File:** Imports the properties files that have been localized.

Configure: Under **Configure**, you can:

- **Locale:** Configures the supported localization data.
- **Default Locale:** Configures the default localization data.

Live: Under **Live**, you can:

- **Deploy:** Deploys the User Application object to the Identity Vault.
- **Compare:** Compares the User Application object in Designer to a deployed User Application object in the Identity Vault.
- **Import:** Imports the User Application object from the Identity Vault.

Migrate: (Conditional) Migrates the User Application object if it needs to be migrated.

Export to File: Exports the User Application object to a file.

Import from File: Imports the User Application object from a file.

Validate: Validates the User Application object.

Show Provisioning View: Launches the Provisioning view.

Properties: Launches the Properties page associated with this object.

Default notification collection

The default Notification Collection object is a placeholder for all notification templates.

Right-click the Notification Collection object  to perform the following:

New Template: Create a new notification template.

Edit Filer: If you want to see e-mail templates in other languages, click this option and select the languages.

Import Templates from File: Imports a notification template from a file.

Export Templates to File: Exports the notification templates to a file.

Add Default Templates: Adds only the default notification e-mail templates in English to the Identity Vault. You can also select to overwrite existing templates.

Add All Templates: Updates all of the notification e-mail templates in all of the languages that are installed with Designer to the Identity Vault. You can also select to overwrite existing templates.

Live: Under **Live**, you can:

- **Import:** Imports an e-mail template from an Identity Vault.
- **Deploy:** Deploys e-mail templates to the Identity Vault.
- **Compare:** Compares the Notification Collection in Designer to a deployed Notification Collection in the Identity Vault.

Localization: Under **Live**, you can:

- **Import Localization Data:** Imports the localization data from a folder that stores localization data.
- **Export Localization Data:** Exports the localization data to a folder.

Properties: Launches the Properties page associated with this object.

Notification template

The Notification template is an e-mail template you can use in policies to notify people of events.

Right-click the Notification object  to perform the following:

Live: Under **Live**, you can:

- **Deploy:** Deploys e-mail templates to the Identity Vault.
- **Compare:** Compares the Notification object in Designer to a deployed Notification object in the Identity Vault.

Add Localized Templates: Updates all of the localized versions for the selected notification template that are installed with Designer.

Edit: Launches an editor to allow you to edit the notification template.

Create: Creates a copy of the selected notification template.

Save As: Saves the notification template as an XML file.

Add to Package: Allows you to include the notification template in a package, if it is not installed with a package.

Package Properties: Launches the Properties page for the package that installed the notification template.

Revert Customization: Revert Customization is available if the notification template is part of a package, and if the notification template is customized. Revert

Customization is like an undo, and it removes any customizations you made.

Open With: Opens the notification template with one of the following editors:

- Designer Built-in Editor
- OpenText XML Editor
- XML Editor
- Text Editor

Delete: Deletes the select notification template.

Localization: Under **Localization**, you can:

- **Import Localization Data:** Imports the localization data from a folder that stores the localization data.
- **Export Localization Data:** Exports the localization data from a folder.

Properties: Launches the Properties page associated with this object.


1.4.7. The Navigator view

The Navigator view enables you to manage and view the file resources that are in your workspace. You can see your projects and files as they actually exist in the file system. You can add files and folders, and append them to your projects or workspace. These extra items won't change or affect the behavior of your OpenText Identity Manager solution. However, they enable you to conveniently append other pieces of information that you want to associate with your projects and workspace.



Important

Do not use the Navigator View to copy, rename, move, or delete files for a project that is under version control. Performing these operations from the Navigator view does not reflect properly in the Version Control view.




The Navigator View

The Navigator view enables you to do the following:

Navigator View Icons

Icon Name	Description
Project Name  Blanston1	The name of the created project. This is the name of the project stored in the selected workspace directory. Double-clicking the Project name expands or collapses the entries under the project. Right-clicking a project name allows you to do the following: • Under New: ◦ Create a new project ◦ Create a new Identity Manager Project ◦ Create a new provisioning artifact ◦ Create other projects • See just this project's workspace (the Go Into option). • Open in a new window. • Copy, paste, delete, move, and rename the project. • Import and export the project. • Refresh the project. • Close the project or close unrelated projects. • Use the Source option to format the document. • View the project's Properties window.

Icon Name	Description
Project's Documents Folder and Subfolders  The diagram shows a folder icon labeled 'Documents'. Below it, there are two subfolders: 'Generated' (indicated by a dashed line) and 'images' (indicated by a plus sign icon).	The Designer > Documents folder contains the files of the created project. Beneath the Designer > Documents directory are the documentation and resources folders and any other folders you have created in this project. Right-clicking any of the project folder names allows you to do the following: • Under New: ◦ Create a new project ◦ Create a new Identity Manager Project ◦ Create a new provisioning artifact ◦ Create other projects • See only this project's workspace (the Go Into option). • Open the directories in a new window. • Copy, paste, delete, move, and rename the folder. • Import and export the project. • Refresh the directory. • Use the Source option to format the document. • View the project's Properties window.

Icon Name	Description
All File Types  002CB0B867.notftemplate 002CB0B867.xml 007DA3A8BA.mappingpolicy	Because the project folders can contain many different files, you can see different icons displayed, depending on the file extension. Right-clicking any of these files allows you to: • Under New: ◦ Create a new project ◦ Create a new Identity Manager Project ◦ Create a new provisioning artifact ◦ Create other projects • Open the file in a Designer-chosen editor. • Open the file with the following choices: ◦ Text editor ◦ System editor ◦ In-place editor ◦ Default editor ◦ XML files can choose an XML editor ◦ Project files can choose the Modeler ◦ Filter files can choose the Filter editor ◦ Policy files can choose the Policy Builder editor

Icon Name	Description
	• Copy, paste, delete, move, and rename the files. • Import and export the files. • Refresh the file or directory. • Use the Source option to format the document. • View the file's Properties window.



Important


Copy and paste operations, and drag and drop operations in the Navigator View are not handling files properly if they are under version control. Perform these operations from the Project view if the project is under version control.

In the Navigator view, you can move any document into your project and edit it with a selected editor. For example, you can add a Word or PowerPoint document, then double-click the document. The native application loads inside Designer, as any other editor would, where you can view and edit the document. (This feature only works on Windows.)

You can create linked resources at any depth within projects. This allows you to put resources from different places in the file system anywhere you like in the project structure, including below other linked resources. The same resource can be linked to the same project.

To create a linked resource:

1. Select **Window > Show View > Navigator**.
2. In the Navigator view, right-click a project, then select **New > Other**.
3. Expand the **General** folder.




4. Select **Folder**, then click **Next**.
5. Click **Advanced**, then select **Link a folder in the filesystem**.
6. Browse to and select a folder, click **OK**, then click **Finish**.

Designer creates a link to that folder directly under the project. You can then easily access the folder.

You can use the same procedure to link to a file.

1.4.8. Policy Set view

The Policy Set view lists policies and displays a toolbar.



The Policy Set View

The list displays all policies contained in the selected policy set. During a transformation, the policies within the list are executed from top to bottom.

The Policy Set view includes the following icons in the icon bar at the top of the view:

Policy Set View Icons

Name	Description
Edit 	When you select a policy, this icon brings up the Policy Builder.
Create 	Creates, copies, or links a policy.
Delete 	Deletes a selected policy. You can also delete all policies in a policy set by selecting the policy set and clicking Delete .
Remove 	When you select a policy, this icon enables you to remove the selected policy from the policy set without deleting it. When you select a policy set, the icon enables you to remove all policies from the selected policy set.
Move Policy 	Moves the policy up and down in the policy chain.
Minimize/Maximize 	Minimizes and maximizes the Policy Set view.

The following options are available when you right-click a policy set:

Policy Set Right-Click Options

Operation	Description
New > DirXML Script	Enables you to create a new DirXML Script policy.
New > SchemaMap	Enables you to create a new Schema Mapping policy.
New > XSLT	Enables you to create a new XSLT policy.
New > From Copy	Launches the Model Browser window, which enables you to browse to and copy an already-existing policy.
Link Existing Policy in Set	Enables you to browse to an existing policy and link that policy to your selected policy set.
Remove All Set Policies	Enables you to remove all the policies from the selected policy set without deleting them.
Delete All Set Policies	Enables you to delete all the policies from the selected policy set.

Operation	Description
DirXML Script Tracing	Enables you to turn DirXML Script Tracing on or off for the policy set. You can also choose to apply your settings to all DirXML Scripts or to only the DirXML Script rules for the policy set.

The following options are available when you right-click a policy:

Policy Right-Click Options

Operation	Description
Edit	Launches the Policy Builder.
Copy	Enables you to copy a policy.
Save As	Enables you to name and save a policy in the file directory.
Simulate	Enables you to test and debug the selected policy
Remove	Enables you to remove the policy from the policy set without deleting the policy.
Link to Existing Policy	Enables you to link this policy to an existing policy.
Move Up	Enables you to move the policy up the policy chain.
Move Down	Enables you to move the policy down the policy chain.
Export to Configuration File	Enables you to export the selected policy to the driver configuration file.

Operation	Description
Live > Deploy	Enables you to deploy the selected policy to the Identity Vault.
Live > Compare	Compares selected policies. Enables you to reconcile or update policies.
Delete	Enables you to delete a selected policy.
Properties	Enables you to view the selected policy's properties.
Add to Package	Allows you to include the policy in a package if it was not installed with a package.
Package Properties	Displays the properties of the package that installed the selected policy
Revert Customization	This option is available if the policy is part of a package, and if the policy is customized. Revert Customization is like an undo, and it removes any customizations you made.

Operation	Description
DirXML Script Tracing	Enables you to turn DirXML Script Tracing on or off for the selected policy. You can also choose to apply your settings to all DirXML Script policies or to only DirXML Script rules for the policy.


The Policy Set view displays differently, depending on what mode the Outline view is in. If you are in Tree mode, the Policy Set view shows policies in a hierarchical containment. However, if you are in Policy Flow mode, the view shows a flat list of policies in the selected policy set.

To bring up a policy in the Policy Builder view, double-click the policy. For more on policies, see [Understanding Policies Guide](#) and [Using Designer to Create Policies](#).

1.4.9. The Properties view


The Properties view displays information about key-value pairs (for example, Max Log Entries 2). The information displayed depends on what is selected in the active view (for example, the Modeler or Outline view).

Often, the Properties view lets you edit the information. For example, you can select a driver in the Modeler and then edit the trace level associated with that driver. You can also view and edit the Administrator settings in an Identity Vault.



The Properties View of an Active Directory Driver

The spinner control



The Spinner Control

When you edit numeric values in the Properties view, Designer displays a spinner control so that you can increase or decrease the number.

The maximum value on the spinner is set appropriately, based on the attribute type. For example, the maximum for log entries is 500.

The DN cell editor

Deploy Context

O=novell

DN Cell Editor

To edit attributes that are of type DN syntax (for example, Driver Set Deploy Context):

1. Click **Deploy Context**.
2. Type the distinguished name of the context.

You can also click the **Browse** button, then browse to and select an object with the OpenText eDirectory browser. In this case, you are selecting the Distinguished Name of the container to deploy the driver set.

Editing boolean values

Trace Size Limit (10	
Use DS Log Settin true	▼
	false
	true

Drop-Down List for Boolean Values

To edit Boolean values, select **true** or **false** from the drop-down list.

Keyboard tips

Keyboard Tips

Task	Description
Save the value of the current cell editor and set the focus on the next editor.	Press Tab, Enter, the Up-arrow, or the Down-arrow.
Navigate backwards.	Press Shift+Tab. Navigation loops when you reach the top or bottom of a value.
Exit the Properties view.	Press Ctrl+Tab for forward navigation. Press Ctrl+Shift+Tab for backward navigation.

Resizing column widths

If you resize the columns in the Properties view, those column widths persist in user preferences. When you open the Properties view again or restart Designer, the resized widths are displayed.

Summary table

Properties View Tasks

Task	Description
Opening	If the view doesn't already display, select Window > Show View > Properties .
Edit	Edit the settings of any item selected in the Modeler or Outline View.
Multi-edit	If you have selected more than one item, you can edit any settings that both items have in common. For example, if both items have a Name setting, you can select both and edit once. The change is made to both items. This function can boost productivity on certain edit operations.
Saving	When you click Save , all changes are saved to the project file. When you reopen the project, all settings are restored.
Boolean Editor	You can edit Boolean settings (true/false) by clicking the value, which toggles to the other value.

1.4.10. The Search Results view

To search across an entire project:

1. With the Modeler view active, press Ctrl+F.
2. To make the search case-sensitive, select the **Case Sensitive** check box.
3. If you want to replace the string with a different one, select the **Enable Replace** check box and then specify a string in the **Replace** field.
4. Filter object types you want to search on. You can select or deselect all items through the **Select All** or **Deselect All** buttons.
5. Click **OK**.

The results appear in the Search Results view. You can sort the search results on any column by clicking that column header.


When you subsequently invoke the Search dialog box, Designer remembers your latest search settings.

Best practices for search/replace operation

This section includes some tips and best practices for using the search and replace operation in Designer:

- The Search operation can be performed on drivers, filters, policies, and so on. The Replace operation does not work with Provisioning.
- You can apply filters during your searches. The filter ensures that the replace operation works only for the selected area.
- Save the project after the replace operation is performed.
- When you perform a **Replace** operation on policies or other XML files, then the files will not be validated. We recommend that the text you use in the **Replace** field is supported by XML.

1.4.11. The Tasks view



The screenshot shows a window titled 'Tasks' with a close button. Below the title bar, there are icons for adding, deleting, and moving tasks. The main area displays a table with 2 items. The table has columns for Description, Resource, Path, and Location. The first row is selected and has a checkmark in the first column. The second row has an unchecked checkbox in the first column.

	Description	Resource	Path	Location
☒	Add eDirtoeDir			Unknown
☐	Trace errors			Unknown

The Tasks View

The Tasks view enables you to make and prioritize notes while you manage identities. This view is for your convenience. It can contain whatever you want. It won't affect the functionality of your solution.

This view enables you to do the following:

- Add tasks
- Delete tasks
- Set task properties
- Set filter properties
- Mark if completed
- Provide a description
- Set a priority
- Sort on all fields

To add a task:

1. Open the Tasks view by selecting **Window > Show View > Tasks**.
2. Right-click in the Tasks view, then click **Add Task**.
3. Type a name in the **Description** field, select a priority, then click **OK**.

Or:

1. Click the **Add Task** icon  located in the upper right corner of the tasks view.

To delete a task:

1. Right-click the task.
2. Click **Delete**.

Or:

1. Select the task so that the entire task is highlighted.
2. Click the **Delete** icon , located in the upper right corner of the tasks view.



Note

If you right-click the task description so only the task description is highlighted, then click **Delete**, only the task description is deleted. This is helpful if you want to redefine your task description.

- [Task Properties](#)
- [Filtering Tasks](#)
- [Marking Tasks Completed](#)
- [Right-Click Options](#)
- [Setting Task Priorities](#)
- [Sorting Tasks](#)

Task properties

To open the Task Properties page, right-click a task, then select **Properties**.

Task Properties Functionality

Operation	Description
Description	Enables you to describe or name your task.
Creation Time	Indicates when the task was created.
Priority	Enables you to set the priority of the task to High, Normal or Low.
Completed	Enables you to indicate whether the task is completed.
On Element	Enables you to specify what element the task will be on.
In Folder	Enables you to specify the folder the task will be in.
Location	Enables you to specify the location of the task.

Filtering tasks

1. Click the filter icon .
2. Select filters, then click **OK**.

[Filters Window Functionality](#) describes the functionality of Filter Window.

Filters Window Functionality

Operation	Description
User Filters	Enables you to select specific filters to filter your tasks.
New	Enables you to add a new filter to your user filters.
Remove	Enables you to remove an existing filter from your user filters.
Select All	Enables you to simultaneously select all your filters.
Deselect All	Enables you to simultaneously deselect all your filters.
On Any Element	Filters on any element.
On Any Element in the Same Project	Filters only on elements that are in the same project.
On Selected Element Only	Filters only on the elements you have selected.
On Selected Element and its Children	Filters only on the elements you have selected and the children of those elements.


Operation	Description
On Working Set	Filters only on the working set you have selected.
Select	Enables you to add, edit, remove and select working sets.
Description	Enables you to filter by description.
Where Priority is:	Enables you to filter by priority.
Where Status is:	Enables you to filter by status.
Show Items of Type	Enable you to filter by type.
Select All	Enables you to simultaneously select all types.
Deselect All	Enables you to simultaneously deselect all types.
Restore Default	Enables you to restore set defaults.

Marking tasks completed


1. Right-click the task you want to mark completed.
2. Click **Mark Completed**.

Or:

1. Click the check box in the left column of the Tasks view.



✓	!	Description	Resource	Path	Location
☐		Trace errors			Unknown
☒		Add eDirtoeDir			Unknown



Note

When you mark a task as completed, the task automatically moves to the bottom of your list of tasks.

You can set a priority for your task when you add a new task to your list. However, this is not the only location where you can set a priority.

Right-click options

Task Options


Operation	Description
Add Task	Enables you to add a task to the Tasks view.
Go To	Enables you to go to a designated place.
Show In	Enables you to show the task in another view.
Copy	Enables you to copy tasks.
Paste	Enables you to paste what has been cut or copied.
Delete	Enables you to delete all selected tasks.
Select All	Enables you to simultaneously select all tasks in the Tasks view.
Mark Completed	Marks the selected task as Completed.
Delete Completed Tasks	Deletes all tasks that are marked as Completed.
Properties	Opens the Properties window.

Setting task priorities

1. Right-click a task.
2. Select **Properties**.
3. Select the new priority.

Or:

1. In the Tasks view, locate the column with the exclamation mark (!).
2. Go to the task on which you want to change the priority.
3. Click in the column with the exclamation mark.
4. The task's current priority is displayed.
5. Click the drop-down arrow to the right of the current priority.
6. Select the desired priority.



Sorting tasks

1. Click the **Menu** icon located in the right corner of the Tasks view.
2. In the drop-down menu, click **Sorting**.

The Sorting window enables you to sort your tasks in different ways, in ascending or descending order. You can sort by completion, priority, description, resource, path, location, and creation time.

Click **Restore Defaults** to restore the sorting defaults.

1.4.12. The Trace and Error Log views

The Trace and Error Log views help you troubleshoot Designer.

Trace view

The Trace view includes the following icons in the icon bar at the top of the view:

Icons in the Trace View Toolbar

Icon Name	Description
 Clear Trace	Clears the Trace view.
 Save	Saves Trace view contents to a <code>.txt</code> file
 Preferences	Opens the Preferences window.
 Minimize/Maximize	Minimizes and maximizes the Trace view.

Error Log view

The Error Log view includes the following icons in the icon bar at the top of the view:

Icons on the Error Log View Toolbar

Icon Name	Description
 Export Log	Enables you to export the error log to a location on the file system.
 Import Log	Enables you to import a file from the file system to the error log.
 Clear Log Viewer	Clears all the entries in the Error Log viewer.
 Delete Log	Deletes all items in the error log.
 Open Log	Opens an error log entry.
 Restore Log	Restores log entries that have been previously cleared.
 Menu	Reveals a menu drop-down list.
Menu > Filters	Opens the Log Filters window.
Menu > Activate on New Events	Activates a log entry on a new event.
 Minimize/Maximize	Minimizes and maximizes the Error Log view.

For more information, see [Troubleshooting Designer](#).

1.4.13. The Dataflow view

Designer allows you to manage how the data flows between the Identity Vault and the connected systems. You can see how the data flows between all of the connected systems, make changes as needed, create reports about the data, and view the flow of passwords between the systems.

The Dataflow view enables you to perform the following functions:

- View the filters that allow the data to flow between all of the systems and the Identity Vaults
- View how the passwords flow through the different systems
- Add, delete, and edit driver sets, drivers, filters and Identity Vaults from one location
- Generate HTML reports of the data flow and password flow

The Dataflow view includes the following icons in the icon bar at the top of the view:

Dataflow View Icons

Icon	Description
 Add Filter Class	Adds a new filter class to the dataflow list.
 Add Filter Attribute	Adds a new filter attribute to a selected filter class.
 Expand All Classes	Simultaneously expands all filter classes to reveal all existing filter attributes.
 Collapse All Classes	Simultaneously collapses all filter classes to hide all existing filter attributes.
 Clear Arrows	Clears all dataflow arrows from the drivers in the Modeler.

The Dataflow view and the Dataflow editor manage the data. The Dataflow view displays the flow of data in the Modeler per driver. The Dataflow editor displays a more granular view. For more information, see [Managing the Flow of Data](#) in the [Designer Administration Guide](#).

1.4.14. The Project Checker

Designer provides a Project Checker tool to check your project. The project can be checked at any time, but you should run the Project Checker before deploying your project. The Project Checker checks for proper design, contexts, server associations, policies, missing user data, and dependency problems that would cause the deployment of project into the Identity Vault to fail. It only checks the objects in Designer; it does not check the current objects in the Identity Vault. For more information about the Project Checker, see [Checking Your Projects](#) in the [Designer Administration Guide](#).

1.5. Editors, builders, and wizards

Designer contains multiple builders to help you build working policies, packages, and drivers. It also contains editors to assist in you in editing projects, and wizards to help you build drivers and packages. Below is a brief explanation of what builders, editors and wizards do, along with some examples of their functionality.

Designer also contains many views to help you design and implement OpenText Identity Manager solutions. For more information about views, see [Managing Views](#).

- [Editors](#)
- [Builders](#)
- [Wizards](#)


1.5.1. Editors

Using an editor

Editors enable you to modify projects or other items that are listed in the Navigator or the Project view. Designer comes with a number of editors, and a default editor is designated for most file types.


To select an editor other than the default:

1. Expand a project in the Project or Navigator view (there are more editors in the Navigator view).
2. Select the `Documents\Generated` folder.
3. Right-click any of the files, such as `.xml`, `.pdf`, or `.txt`, and select **Open With** > **Editor Name**. The example below shows the process of opening a file with the Text Editor from the Navigator view.



The editor you choose depends on the type of file you select. Designer lists what it considers to be the best editor for the selected file type.

The following figure illustrates a text editor. When you right-click the editor, a menu is available:



The Text Editor's Menu

The Preferences window lets you set a text editor's preferences. You get to this window by selecting **Window > Preferences > General > Editors > Text Editors**.

For information about settings, see [Text Editors](#) in the [Designer Administration Guide](#).

Each file type you right-click brings up a list of editors.

- **.xml** extension:
 - OpenText XML Editor (default)
 - Text Editor
 - System Editor
 - In-Place Editor
 - Default Editor
- **.txt** extension:
 - Text Editor (default)
 - System Editor

- In-Place Editor
- Default Editor
- **.pdf** extension:
 - Text Editor
 - System Editor (default)
 - In-Place Editor
 - Default Editor
- **.project** extension:
 - Text Editor (default)
 - System Editor
 - In-Place Editor
 - Default Editor
- **.proj** extension:
 - Modeler (default)
 - Text Editor
 - System Editor
 - In-Place Editor
 - Default Editor
- **.log** extension:
 - DS Trace Editor
 - Text Editor
 - System Editor
 - In-Place Editor
 - Default Editor

You can also select **Open With > Other** to open the Editor Selection page.

Select an appropriate editor and click **OK**. If you have a particular editor in mind, select **External Programs**, then click **Browse** to select that program.

Below are some examples of editors and their functionality.

XML editor

You can use the XML editor in policy management and configuration editing. The XML editor can do the following:

- Outline view support
- Find and replace
- Highlight syntax
- Auto suggest
- Auto-insert end tags

Filter editor

- Add classes and attributes
- Copy the filter
- Delete
- Multiselect support
- Keyboard support
- Refresh the schema
- Expand/collapse all
- Configure default values
- Create a home directory
- Track member templates
- Merge authority
- Optimize modifications
- Undo/redo
- XML editor integration

Schema map editor

- Add classes and attributes

- Delete
- Multiselect support
- Keyboard support
- Refresh the schema
- Expand/collapse all
- Non-class-specific handling
- XML editor

1.5.2. Builders

A Builder is a complete graphical interface for creating and managing the policies that define the exchange of data between connected systems. Builders help you to build portions of a policy. For example, you define most arguments in the Argument Builder, and the Policy Builder enables you to add, view, and delete the rules that make up a policy. You can also use the Policy Builder to import and save policies and rules, and manage XML namespaces.

There are several more builders and editors that are used by the Condition editor and Action editor in the Policy Builder. Each builder can recursively call anyone of the builders. For more information about builders, see [Managing Policies with the Policy Builder](#) and [Using Additional Builders and Editors](#).

Builders give you powerful flexibility in designing data exchange. For example, the Policy Builder has the following capabilities:

- Creating and editing policy scripts
- Defining rules: conditions, actions, groups
- Support for predefined rules
- Emphasis on productivity
- Nested inline editors
- Keyboard support
- Copy/paste within an editor and across editors
- Drag and drop
- Integrated Help
- Policy creation wizards
- Import/export
- Namespace editing
- Expand/collapse all
- Reordering
- Integrated e-mail templates
- Integrated Global Configuration Values

- Integrated schema
- Various display preferences
- Argument builder and token editor
- Undo/redo
- Validation
- XML editor

1.5.3. Wizards

A wizard is a graphical interface that helps you build something in Designer. For example, the Add Policy Wizard enables you to create, copy, and link a policy. As another example, Designer allows you to create entitlements through the Entitlement Wizard, which steps you through the creation of entitlements by asking a series of questions about how the entitlement will be used in the enterprise. Because of this graphical interface, we recommend using Designer for creating and editing entitlements.

Below is a list of some of the Designer wizards and where to read more about them:

- Entitlement Wizard (see [Creating entitlements through the entitlement wizard](#))
- Project Converter Wizard (see [Converting earlier projects](#))
- Identity Manager Project Wizard (see [When no project exists](#))
- Driver Configuration Wizard (see [Creating a driver](#))
- Document Generation Wizard (see [Generating a document](#))

1.6. Planning identity solutions

- [Planning an identity project](#)
- [Using Designer in your planning process](#)
- [Security best practices](#)

1.6.1. Planning an identity project

Identity target goals

Make sure that you and others working on the project use the same terminology. For example, password synchronization and single sign-on are two different technologies.

Also, make sure that the meaning and usage of “Identity Vault” are clear as you communicate with others on the project.

Clearly write down the big picture of what you are trying to do.

Discover the business process

The process that you are trying to automate with OpenText Identity Manager is often already defined and written down.

Be careful. Even if a process exists, people commonly don’t fully understand how it works.

Clearly write down what the business process is, and clarify the process to others.

Identify all systems

Identify all systems and all connectivity interfaces between existing systems. Doing this can lead to an increase or decrease in the originally planned systems that you had in mind.

Keep in mind that telephony systems often don’t have an easy API interface.

SQL-based systems sometimes have a very complex database relationship model. It’s possible that nobody in your environment understands how the model actually works.

Identify how many Identity Vaults you will need, where they will be located, and what they will connect with.

What to Do In Designer: You can use the Designer Architect Modeler during this process. It’s very helpful to build a diagram of your enterprise, and capture key information about each of your systems and each of the users who administer those systems.

As you start a project, keep in mind that the “people management” aspect is vital to your ultimate success. As you identify systems, you need to start the process for getting access to those systems in the various departments of the organization.

Define high-level data sync flow

Define high-level data sync flow.

Define the different information types that you want to synchronize. It's common to have different employee types (for example, internal or external).

Be aware of the relationships and dependencies between information of different types (for example, employee, manager, organization, or location).

Doing this step well is critical in helping you to define your data and policy needs.

What to Do In Designer: You can design these data flows in the Dataflow view while you are in the Architect mode or Developer mode.

Define which objects and attributes to synchronize

After knowing the data and relationships, you can break the data into specific Identity Vault and Application object types and attributes.

Define merging behavior, pass through, notification, and reset of attributes.

Identify and derive additional operations based on an original event.

Identify attributes for match, creation, and placement behaviors.

What to Do In Designer: You can use the Task view to capture all of this information or add it to a section in a Document Generation form. One advantage for having it in the Task view is that you can then check off your tasks as you move into the implementation phase and write the policy to deliver your requirements.

You can also include other files (word processing document, spreadsheet, presentation) in your Designer project through the Navigator view. By default, the Navigator view launches the appropriate native application to edit and view that document in a way that integrates into Designer, as long as the platform supports it. If you prefer, you can also configure Designer to use a different editor. This view gives you many options for the types of documents you can include and edit in a Designer project.

Write a requirements assessment document

Document all of the above findings.

Write a high-level acceptance proposal.

Describe the infrastructure.

Create a project timeline.

What to Do In Designer: You can use Designer's Document Generator to capture your high-level design, systems, and basic data flows. You can also fill in sections in the document or create your own sections that describe the project.

Fill in technical details

Take the high-level diagram that you created in the Architect mode and transition it to a detailed diagram that you can use to configure your entire solution.

Configure server and authentication information about the Identity Vaults.

Create driver sets and drivers. Determine how many driver sets are on each vault. Define what drivers are associated with each driver set, and what servers the driver set is running on. Run the Driver Configuration Wizard on each driver.

Develop driver policies. Make sure that you define and use Global Configuration Values (GCVs) as much as possible. Doing this leads to easier maintenance.

What to Do In Designer: With the Modeler in Developer mode, use the Outline view, Policy Flow view, properties dialog boxes on all objects, Filter editor, Schema Map editor, E-mail Template editor, Policy Builder, and other functionality.



Note

The preceding six steps assume that you are building an identity solution from the beginning.

However, Designer is also intended for working on existing solutions. You can create a project and import existing driver sets, drivers, policies, and configurations. Designer lets you easily diagram and manage all components as one complete solution. You can edit existing policies or configurations, add new elements, and then redeploy.

Using Designer on existing solutions has several advantages. You can do the following:

- Work in a high-productivity development environment.
- Easily work off-line.
- Have everything on your local file system for versioning and backup.
- Simulate.
- Generate documentation for your projects.

Unit test

Use project-proposal documents and requirements as a basis.

Test all policies. In addition to the Designer tools, you can deploy the project (or parts of it) into a test environment to test more fully.

Generate a report on results.

What to Do In Designer: Use the Designer Policy Simulator to do much of your policy simulation and debugging. It is very easy to use, helps you identify many issues, and is ideal for offline development.

Build a production environment

As much as possible, mirror existing production environments.

Make sure of the following:

- All Identity Manager engines and drivers are installed.
- All servers have correct IP addresses.
- The applications your drivers will connect to are in place.

As an extra precaution, you might want to deploy to a full test environment or staging environment first. If you decide to do this, all of the above steps apply to configuring that environment.

What to Do In Designer: To make the next steps easier, you can click a button, get a full PDF document of all of the configuration details of your project, and use that document as you set up your machines and software.

Clean data before you deploy

- Each user has a unique and correctly formatted ID.
- All users and other objects are where you expect them to be.
- No duplicate objects exist.
- No extra or unnecessary objects exist.

Deploy to production

Make sure that the production systems are working well. For example, machines are up and running.

Before you deploy, make sure you have done adequate testing on your project.

If you have previously configured the project to deploy to a separate test or staging environment, you need to change the IP addresses on each Identity Vault (and maybe some GCVs) to successfully deploy to the production environment.

After you deploy, quickly test and redeploy all or any part of the project with any fixes you need.

What to Do In Designer: In the future, more will be done in Designer to help in this area. For now, the following tips can help in this process:

- Do a full copy of the project in the Project View.

This lets you fill in the new IP addresses for production and leave the old ones alone, so that you can have a project called Staging and another called Production. The disadvantage is that if you change something such as a policy in one project, you need to change it in the other to keep the policies in sync. Designer does let you copy/paste between projects to make synchronization easier.

- Always use GCVs to keep your policies easily portable.

If you have a value that is environment-dependent, you only need to edit a GCV when switching to a different environment.

- Use the Modeler's Table editor.

This editor is a quick and easy way to get to objects of a certain type (for example, all of your Identity Vaults or all of your servers), see their values, and edit them.

- Document your project.

Document Generation is always available to help you understand your configurations.

Document, back up, and maintain

What to Do In Designer: Run the Document Generator and save the document.

Make a copy of your project in the Project view. A copy is useful in case you ever need to return to that state or set up a production system again for any reason.

Over time, you will certainly add systems and policies, and make changes in your production environment. You can use iManager for the management of your system (especially if the change is more of an administrative task) and then reimport those changes into your local Designer project.

If the changes you need to make are more suited for a development environment, (for example, policy debugging, policy development, or adding new systems) then continuing to use Designer is the best practice. After each change, you can redeploy the project or just the elements that have changed.

As you version and extend your project over time, remember to always use Document Generation as your paper trail.

1.6.2. Using Designer in your planning process

Using the architect view to design your identity environment

1. Launch Designer.
2. Open or create a new project in the Modeler view.
3. Select the Architect view from the bottom of the Modeler view.
4. Drag and drop items from the Palette.

These items are representations of the drivers and applications that make up an OpenText Identity Manager solution. There are also a number of design elements to help you in designing your network layout.

5. Edit the item's names to match your OpenText Identity Manager environment.
6. Use the Architect view as a basis for your actual Designer project.
7. Use the Developer view to run the configuration wizards on any driver sets and drivers you have added through the Architect view.

Driver objects created through the Architect view are not configured to run in an OpenText Identity Manager system. Consequently, you need to import or create the drivers from the Developer view in the Modeler in order to run the Driver Wizard. The Driver Wizard configures the driver with policies, entitlements, and other configuration information that is necessary for the driver to run in an Identity network.

Designing new solutions

1. Launch Designer.
2. Using the New Project Wizard, open or create a project.
3. Drag and drop items from the Modeler Palette.
4. Edit the item settings and configurations (for example, names, IP addresses, and passwords).
5. Using the Policy Builder and other policy editors, write a policy for sharing data between systems.

6. Check your work.
7. Use the Document Generator to generate project documentation, and review the documentation with others.
8. Deploy the project to a test system for verification.
9. After the project is verified, deploy the project to a live system.

Redesigning existing solutions

1. Launch Designer.
2. Open or create a new project.
3. Import Identity Management elements (drivers, driver sets) from working directories.
4. Edit the element settings and configurations (for example, names, IP addresses, and passwords).
5. Using the Policy Builder and other policy editors, write a policy for sharing data between systems.
6. Check your work.
7. Use the Document Generator to generate project documentation, and review the documentation with others
8. Deploy the project to a test system for verification.
9. After the project is verified, deploy the project to a live system.

Working on live systems

The fundamental model/paradigm of Designer is to import solutions, configure them locally in the Designer environment, and then deploy when a solution is ready. This approach was taken to optimize the experience for the following:

- Offline work
- Highly productive development
- A safer model of configuring and testing before touching your live system

The best practice is to set up a test environment for configuration and testing before deploying the solution into a live system.

The Live Operations tool is aimed at developers and architects as the primary audience. For convenience, Designer enables you to perform key operations that a developer typically needs to do, so that the developer can effectively browse live trees, check driver status, start/stop drivers, and configure driver security.

The functionality of Live Operations options takes immediate effect on the end systems. These operations are clearly grouped in the Designer UI, so that you can tell if you are performing a live operation.

1.6.3. Security best practices

When using Designer for OpenText Identity Manager, observe best practices.

Limiting rights

Before giving a consultant an Identity Vault administrator password, limit the rights assigned to that administrator to areas of the tree that the consultant must access. Doing so protects sensitive data from being misused, damaged, or unintentionally compromised.

Changing passwords

After a consultant has completed work, change the password of the user (for example, admin) that the consultant used. If you created a special user (for example, consadmin) for that consultant to use, delete that user or change passwords. Doing so restricts access and brings closure to the consulting process.

Deleting or saving .proj files

Delete the project files (.proj) or save them to a company directory.

Designer . proj files are to remain at the company's project site. A consultant does not take the files after completing a project.

Deleting files that aren't needed

When project files, log files, and trace files are no longer needed, delete them. These files might contain sensitive information.

Verifying files

Before discarding or surplus a laptop, verify that project files have been deleted. Otherwise, someone might discover sensitive information.

Securing connections

Ensure that the connection from Designer to the Identity Vault server is physically secure. Otherwise, someone could monitor the wire and pull sensitive information.

Handling documents

When you create documents by using the Document Generator, take care with those documents. These documents can contain passwords and sensitive data in clear text.

Working with encrypted attributes

If Designer needs to read or write to an OpenText eDirectory attribute, you can mark the attribute to be encrypted, but you can also allow the attribute to be read over the wire in clear text. This means that you can have encrypted attributes, but they cannot be retrieved securely.

Handling sensitive passwords

Do not store passwords that are sensitive.

At this time, Designer projects are not encrypted. Passwords are only encoded. Therefore, do not share Designer projects that have saved passwords.

To save a password for a session, but not save it to the project:

1. In an expanded Outline view, right-click an Identity Vault.
2. Select **Properties**.
3. On the Configuration page, type a password, then click **OK**.

You can enter a password once per session. After you close Designer, the password is lost.

To save a password to the project, complete Step 1 through Step 3, select **Save**, then click **OK**.

Security for the user application

For information about security issues relating to the User Application, see the [Administrator's Guide to the Identity Applications](#).

1.7. Designer's architecture

Designer is built on Eclipse technology

Designer is based on Eclipse technology. This open source technology is actively supported by more than 60 leading companies (such as IBM, HP, Intel, SAP, Fujitsu, and Oracle) and by thousands of other developers throughout the commercial industry and the academic world.

With Designer based on Eclipse, you receive the following benefits:

- Published, well-documented, and supported APIs frequently used across the industry.
- An underlying model that integrates well with any plug-in.
- A rich, advanced UI.
- Capability to fully and easily extend our product in the future.
- Better integration and leveraging of other applications.
- Open source as the basic framework.

You can install OpenText tools into any Eclipse-based framework.

- Out-of-box tools (Java editor, debugger, JUnit, ANT, CVS integration) that are free if you want to access them (and other tools) within the Designer.
- Cross-platform benefits of Java, but the native performance and native look of the platform.
- Quick access to meaningful tools.
- A framework that quickly picks up entirely new capabilities contributed by a larger community.

Instead of focusing on tools, developers are able to concentrate on providing quality content so they don't need to spend as much time on creating, debugging, and fixing the framework.

The Designer core model uses the Eclipse modeling framework

At the heart of Designer is a strong object model that is based on the Eclipse Modeling Framework. This model uses the industry standard XMI format (XML

Metadata Interchange Format) for storing objects and their relationships.

The main purpose of XMI is to enable easy interchange of metadata between modeling tools, that are based on the Object Management Group Unified Modeling Language (OMG UML) and between tools and metadata repositories, that are based on the OMG MetaObject Facility (MOF) in distributed heterogeneous environments. XMI integrates three key industry standards:

- XML (Extensible Markup Language), a W3C standard
- UML (Unified Modeling Language), an OMG modeling standard
- MOF OMG modeling and metadata repository standard

The integration of these three standards into XMI integrates the best of OMG and W3C metadata and modeling technologies, allowing developers of distributed systems to share object models and other metadata. XMI, together with MOF and UML, forms the core of the OMG repository architecture that integrates object-oriented modeling and design tools with each other and with a MOF-based extensible repository framework.

Because Designer is based on this technology, you get the following benefits:

- Published industry-standard APIs so that you can programmatically interact with the model.
- A solid event-notification mechanism if the model ever changes.
- All views, editors, and plug-ins are notified and in sync.
- The ability to auto-generate Java code or UML from the model, or vice-versa.
- Undo/redo the stack across all views, editors, and plug-ins that are in sync with the model.

1.8. Terminology

The following terms are used in Designer:

Icon	Term	Description
	Application object	Represents a connected system, whether that system is a database or CSV files.
	Driver object	A collection of channels, policies, rules, and filters that connect an application to an OpenText eDirectory tree running OpenText Identity Manager. Each driver performs different tasks. Policies, rules, and filters tell the driver how to manipulate the data to perform those tasks.
	driver set	A collection of OpenText Identity Manager drivers that are stored in a single location.
	driver properties shortcut	Double-clicking the shortcut brings up the Properties window associated with the object's name.

Icon	Term	Description
	filter	A gatekeeper that determines which objects (groups, users, and the attributes associated with them) can be sent to and from OpenText eDirectory. Allows the objects to be sent.
	Identity Vault	Represents the OpenText eDirectory tree that has OpenText Identity Manager installed on it.
	Notification collection	A placeholder for all e-mail notification templates.
	Notification object	A notification template. Used to send an e-mail notification to a user concerning a password event (for example, a request for a password hint).
	package	A container for organizing the driver content. Replaces driver configuration files.

Icon	Term	Description
	policy	A collection of rules and arguments that enable you to configure an application to send or receive events to or from an Identity Vault. You use policies to manipulate the data that you receive from the Identity Vault or from the application. Each driver performs different tasks. Policies tell the driver how to manipulate the data to perform those tasks.
	project name	The name of the project when you create it. The name of the project is stored in the <code>\workspace\project_name</code> directory.

Icon	Term	Description
	Publisher channel	A combination of rules and policies. Designer enables you to import a channel instead of the entire driver. The Subscriber and Publisher channels describe the direction in which the information flows. The Publisher channel takes the event from the application, database, or CSV file and sends that event to OpenText eDirectory. The Subscriber and Publisher channels act independently; actions in one are not affected by what happens in the other.
	schema mapping	Enables OpenText Identity Manager to synchronize information to the connected system without changing the connected system. The schema translates all classes and attributes for the connected system.

Icon	Term	Description
	Server object	The server in the tree where you have OpenText Identity Manager installed.
	Subscriber channel	A combination of rules and policies. Designer enables you to import a channel instead of the entire driver. The Subscriber channel takes the event from OpenText eDirectory and sends that event to the receiving system (application, database, or CSV file). The Subscriber and Publisher channels act independently; actions in one are not affected by what happens in the other.
	XSLT	Represents XSLT style sheets. XSLT is used instead of DirXML Script.

1.9. Menu options

The following links provide information about options on the main menu and toolbar. If other items appear in the user interface, they are contributed by other plug-ins. Documentation for those items are in the plug-in's section of the help system.

- [File menu](#)
- [Edit menu](#)
- [View menu](#)
- [Project menu](#)
- [Live menu](#)
- [Tools menu](#)
- [Model menu](#)
- [Window menu](#)
- [Help menu](#)

1.9.1. File menu

Option	Description
File > New > New Project	Creates an OpenText Identity Manager project and location. The project then appears in the Project view. See Using Designer In Your Planning Process .
File > New > Project	Launches the New Projects Wizard. You can also select to create a new document generation style.
File > New > Provisioning	Helps you define directory abstraction layer objects and provisioning request definitions for the user application.
File > New > Other	Launches the OpenText Identity Manager Projects Wizard.
File > New > Other > General > File	Creates a new, empty file resource.
File > New > Other > General > Folder	Creates a new folder in the project resource folder.
File > New > Other > General > Untitled Text File	Creates an empty, untitled text file in the project folder.

Option	Description
File > New > Other > Designer Document Generation > Document Generation Style (.docgen)	Creates a Document Generation style (template).  Note At least one Designer project must exist before you can create a Document Generation style.
File > New > Other > Identity Manager > New Project	Creates an OpenText Identity Manager project name and location.
File > New > Other > Provisioning > Directory Abstraction Layer Entity	Specifies the project and application for the new entity, as well as the display name and key for the new entity. See the Administrator's Guide to the Identity Applications .
File > New > Other > Provisioning > Directory Abstraction Layer List	Specifies the project and application for the new list as well as the key for the new list. See the Administrator's Guide to the Identity Applications .
File > New > Other > Provisioning > Directory Abstraction Layer Query	Specifies the project and provisioning application for the new directory abstraction layer query object, as well as the display name and key. See the Administrator's Guide to the Identity Applications .

Option	Description
File > New > Other > Provisioning > Directory Abstraction Layer Relationship	Specifies the project and application for the new relationship as well as the display name and key for the new relationship.
File > New > Other > Provisioning > Provisioning Request Definition	Specifies the basic information from a workflow template of the provisioning request definition.
File > New > Other > Provisioning > Provisioning Team	Enables you to define a set of users who can act as a team for the Requests & Approvals tab of the User Application. The team definition determines who can manage provisioning requests and approval tasks associated with this team.
File > New > Other > Resource	Launches the Create a Resource Wizard for provisioning.
File > New > Other > Provisioning > Role	Launches the Create a Role Wizard for provisioning.
File > New > Other > Provisioning > Separation of Duties	Launches the Separation of Duties Constraint window, allowing you to set up and identifier and display name to act as a constraint.
File > Open File	Enables you to browse to and open a text or XML file.

Option	Description
File > Close	Closes the active editor.
File > Close All	Closes all open editors.
File > Save	Saves changes made in the active editor.
File > Save As	Saves changes made in the active editor to a different file.
File > Save All	Saves changes in all editors.
File > Move	Moves a file, folder, or project to a different location in the file system. Only available in the Navigator view.
File > Rename	Renames a file or project. Only available in the Navigator view.
File > Refresh	Loads the project or file from disk and makes sure it is in sync. (If you add new files outside of the tool directly in the file system, this option displays them in the Project view.)
File > Print	Prints from an editor.

Option	Description
File > Switch Workspace	Opens another workspace with its projects. This option automatically restarts Designer.
File > Restart	Restarts Designer.
File > Import	Imports resources, projects, or preferences. See Importing Projects in the Designer Administration Guide .
File > Import > Project (From File System)	Imports existing project files from selected directories or archive files.
File > Import > Project (From Identity Vault)	Imports existing projects from specified secure entities after entering the required authentication information.
File > Import > Project (From iManager Export File)	Imports an existing OpenText Identity Manager project from an iManager export file (driver set or driver).
File > Import > Project (From Version Control)	Imports a project from a version control server.
File > Export	Exports resources or preferences. See Exporting a Project in the Designer Administration Guide .

Option	Description
File > Export > General > Preferences	Exports preferences to the local file system.
File > Export > Designer for Identity Manager > Export Designer Project	Exports projects to the local file system or to an archive file on the local file system.
File > Export > Designer for Identity Manager > iManager Configuration File	Exports a driver set, driver, channel, or policy to an iManager-compatible configuration file.
File > Properties	Enables you to view the file's full name, date, size, type, and read-only status.
File > History	Lists the history of files and projects opened. By selecting items in this history list, you can reopen a file or project. To configure the length of this history list, use the Preferences dialog box.
File > Exit	Closes the application.

1.9.2. Edit menu

Option	Description
Edit > Undo	Undoes the last operation.
Edit > Redo	Redoes the last undone operation.
Edit > Cut	Copies the selected item to the Clipboard and removes it after it is pasted.
Edit > Copy	Copies the selected item to the Clipboard.
Edit > Paste	Pastes the current item in the Clipboard to the selected area.
Edit > Delete	Deletes the selected item.
Edit > Select All	Selects all items in a text or XML editor. To select all items in the Modeler, select it, then press Ctrl+A.
Edit > Find/Replace	Allows you to search for text strings in text or XML editors. You can also search for strings and then replace those strings based on your requirement.
Edit > Add Bookmark	Used in text editors.

Option	Description
Edit > Add Task	Adds a task and leaves a mark in the file. Used in text editors.

1.9.3. View menu

Option	Description
Zoom In	Increases an item's size. You can also slide the Zoom slider in the main toolbar. To reset Zoom to 100%, click the Zoom Restore icon. 
Zoom Out	Decreases an item's size. You can also slide the Zoom slider in the main toolbar. To reset Zoom to 100%, click the Zoom Restore icon. 
Grid	Provides a grid so that you can align items. See Using a Grid in the Designer Administration Guide.
Alignment Hints	Helps you see relationships in your model. You can align or attach items to the left, center, or right of alignment guides. See Aligning and Laying Out Components in the Designer Administration Guide.
Rulers	Turns rulers off and on, to help with alignment and layout. See Using Rulers in the Designer Administration Guide.

1.9.4. Project menu

Option	Description
Project > Document > New Style	Generates a new style document for a specified project.
Project > Document > Edit Style	Edits a style document for a project located in the Documentation folder under a project in the Project view.
Project > Document > Generate Documentation	Generates project PDF documentation after saving file changes. You can select the directory location where documentation is stored, specify to overwrite existing files, and create XML source files.
Project > New Project	Launches a new project.
Project > Import Project > File System	Imports an existing project from the file system into Designer from a selected root directory or archive file.
Project > Import Project > Identity Vault	Imports an existing project from an Identity Vault into Designer.
Project > Import Project > iManager Export File	Creates a Designer project by selecting an iManager .xml export file. The .xml file can be a driver set export, driver export, or OpenText preconfiguration file.

Option	Description
Project > Import Project > Version Control	Imports projects from the version control server.
Project > Export Project	Exports projects to the local file system or to an archive file on the local file system.
Project > Update	Allows you to update a project from a version control server.
Project > Check in	Allows you to check in a project to a version control server.
Project > Copy Project	Allows you to create a copy of a project.
Project > Move	Allows you to move a project from one location to another.
Project > Rename	Allows you to rename a project.

1.9.5. Live menu

Option	Description
Live > Manage Directory	Browses specified Identity Vault configurations. See Configuring Identity Vaults in the Designer Administration Guide .
Live > DS Trace	Launches DSTrace on the server where the Identity Vault resides.
Live > Import	Imports driver sets, drivers, or applications. Used in the Modeler and in the Outline view. See Importing a Library, a Driver Set, or a Driver from the Identity Vault in the Designer Administration Guide .
Live > Import Attributes	Imports a driver configuration from an already-saved XML file. See Importing a Driver Configuration File in the Designer Administration Guide .
Live > Import Schema	Imports a schema from an Identity Vault.
Live > Deploy	Deploys driver sets, drivers, or applications. Used in the Modeler and in the Outline view.
Live> Deploy Attributes	Deploys attributes to selected objects.

Option	Description
Live> Deploy Schema	Deploys a schema stored in Designer into an Identity Vault.
Live > Compare	Allows you to compare the information structure on an object in Designer to the object that is deployed or running on an OpenText eDirectory server.
Live > Compare Attributes	Allows you to compare the attributes of a policy to the attributes that are already deployed.
Live > Refresh Application Schema	Specifies the server on an OpenText eDirectory tree where the schema is refreshed after an application's schema changes. See Refreshing the Application Schema in the Designer Administration Guide .
Live > Start Driver	Starts an inactive driver. See Configuring Drivers in the Designer Administration Guide .
Live > Stop Driver	Stops an active driver.
Live > Restart Driver	Restarts an active driver.

Option	Description
Live > Driver Status	Displays each driver's status. Enables you to start, stop, or restart drivers. Enables you to browse, import, and deploy various functionality, depending on the item selected. See Configuring Drivers in the Designer Administration Guide .
Live > Create eDir-to-eDir Certificates	Configures two OpenText eDirectory drivers to communicate directly with each other. See Configuring TLS for eDir-to-eDir Drivers in the Designer Administration Guide .
Live > Set Driver Trace Level	Allows you to specify how much information you want to see in a trace level log from the driver. Settings go from 0-5.
Live > Setup Driver Security	Configures security parameters for drivers.

1.9.6. Tools menu

Option	Description
Tools > Manage Directory	Opens an OpenText eDirectory browser to view objects and their attributes in a tree. Use this tool only if you understand the intricacies of OpenText eDirectory.
Tools > DS Trace	Lets you view live DSTrace activity for a specific server, and save the trace to a log file. You can also open a previously saved DSTrace log file.
Tools > iManager	Specifies the iManager URL, which is stored in the application preferences folder.
Tools > Export Localization to File	Sends the User Application's display labels and e-mail notification templates to an XML or properties file so that the data can be localized.
Tools > Import Localization from File	Imports localization data from a project.
Tools > Access User Application	Automatically directs and opens a User Application session from within the embedded HTML browser, if a user application is configured in the Designer project.

1.9.7. Model menu

Option	Description
Model	Accesses the Modeler applications, tools, drivers, and other resources. See Creating a Model in the Designer Administration Guide .
Model > Application	Accesses tools to create Designer applications.  Note Functionality becomes active when objects in the Designer window are clicked.
Model > Application > New	Creates a new <code>.xml</code> application driver after a driver set is selected in the Modeler window. You can select from a preconfigured list of driver types and run the associated scripts to verify the driver requirements.
Model > Application > Connection Settings	Configures the VNC connectivity settings for objects created in the Modeler window.
Model > Application > Remote Control Desktop	Configures the remote control desktop of the resource if a VNC server is running on it.

Option	Description
Model > Application > Show Subsystems	Shows or hides an application's subsystems. See Show/Hide Subsystems in the Designer Administration Guide .
Model > Application > Notes	Opens the environment properties window in Modeler to document platform, hardware, and other environment notes about objects you create.
Model > Application > Administrator	Opens the administrator properties window in Modeler to document personal and contact information and other notes about objects you create.
Model > Application > Icon	Opens the general properties window in Modeler to create or edit icons you create for Designer objects. See Driver Icon in the Designer Administration Guide .
Model > Application > Properties	Opens the general properties window for objects selected in Modeler. See Configuring Application Properties in the Designer Administration Guide .
Model > Design Element > New	Instructs you to click the Architect tab, click the Design Element drawer in the palette, and drag and drop items into the Modeler.

Option	Description
Model > Design Element > Connection Settings	In Architect mode, launches the Connectivity page for design elements that have VNC connectivity. Enables you to connect to an element or object.
Model > Design Element > Remote Control Desktop	Connects to the application by using the VNC protocol. Displays an editor that you can use to control the application.
Model > Design Element > Administrator	Launches the Design Elements properties page. The Administrator option enables you to capture information about whom to contact concerning the application.
Model > Design Element < Properties	Specifies a design element's properties.
Model > Domain Group > New	Creates a new domain into which selected objects can be grouped in Modeler.
Model > Domain Group > Clear Domain Contents	Clears objects that are contained in a domain.
Model > Domain Group > Add to Group	Adds selected objects to a new group.

Option	Description
Model > Domain Group > Ungroup	Ungroups selected objects contained within a domain without deleting them.
Model > Domain Group > Properties	Specifies properties of domains contained within a group.
Model > Driver > New	Creates a new Driver object, specified from a list of templates.
Model > Driver > Copy > Server-Specific Settings	Copies replica data from one server to another server that is associated with the selected driver.
Model > Driver > Copy > Settings	Copies existing driver settings.
Model > Driver > Simulate	Opens the Simulate Policy Transformation - Entitlements Service Driver Wizard to test the driver's set-up parameters.
Model > Driver > Import from Configuration File	Allows you to browse to and import a driver.
Model > Driver > Log Level	Defines the level of errors to be tracked and reported in the error log. See Driver Log Level in the Designer Administration Guide .

Option	Description
Model > Driver > Global Configuration Values	Specifies settings for OpenText Identity Manager features in drivers and driver sets, including password synchronization values, driver heartbeat, and specific driver configuration. See Driver Global Configuration Values in the Designer Administration Guide .
Model > Driver > Trace Settings	Adds a trace level to your driver to display the Identity Manager (DirXML) events as the engine processes the events. For a description of each trace field and platform requirements, see Driver Set Trace in the Designer Administration Guide .
Model > Driver > Named Passwords	Stores multiple passwords securely for each driver, so they can be referenced in a driver policy. See Driver Set Named Passwords in the Designer Administration Guide .
Model > Driver > Driver Configuration	Launches the Driver Configuration Wizard, if a driver is selected.
Model > Driver > iManager Icon	Displays an application's icon as it is used in iManager, if a driver is selected.

Option	Description
Model > Driver > Engine Controls	Displays the Engine Control Values property page. Provides a list of associated servers and authentication credentials.
Model > Driver > Manifest	Specifies what the driver supports, including a few configuration settings. See Driver Manifest in the Designer Administration Guide .
Model > Driver > Add Entitlements	Launches the Entitlement Wizard, which allows you to set up criteria for a person or group that initiate an event to grant or revoke access to business resources within the connected system. See Using Entitlements in the Designer Administration Guide .
Model > Driver > Edit Entitlements	Enables you to change an entitlement's name, values, and role-based entitlements.
Model > Driver > Mark as Firewall	Indicates that the selected driver is communicating across a firewall.
Model > Driver > Password Synchronization	Synchronizes passwords between connected systems. See Integrating Passwords in the Designer Administration Guide .

Option	Description
Model > Driver > Credential Provisioning > Credential Repository	Creates a driver repository.
Model > Driver > Credential Provisioning > Credential Application	Creates a credential application.
Model > Driver > Icon	Displays driver icons, or turns icons on or off. See Driver Icon in the Designer Administration Guide .
Model > Driver > Properties	Launches the driver's Properties page.
Model > Driver Set > New	Launches a wizard to create a new driver set.
Model > Driver Set > Copy > Driver Set Settings	Copies existing driver set settings.
Model > Driver Set > Copy > Global Configuration Values	Copies settings for OpenText Identity Manager features such as password synchronization and driver heartbeat, as well as settings that are specific to the function of an individual driver configuration. See Driver Global Configuration Values in the Designer Administration Guide .

Option	Description
Model > Driver Set > Import from Configuration File	Imports an OpenText Identity Manager driver configuration file into the selected driver set for a project. See Importing a Driver Configuration File in the Designer Administration Guide .
Model > Driver Set > Log Level	Defines the level of errors that should be tracked. See Driver Set Log Levels in the Designer Administration Guide .
Model > Driver Set > Server List	Displays available servers and servers that the driver set is associated with.
Model > Driver Set > Global Configuration Values	Specifies settings for OpenText Identity Manager features such as password synchronization and driver heartbeat, as well as settings that are specific to the function of an individual driver configuration. See Driver Global Configuration Values in the Designer Administration Guide .
Model > Driver Set > Trace Settings	Sets the trace level for your driver set, which displays the OpenText Identity Manager (DirXML) events as the engine processes the events. See Driver Set Trace in the Designer Administration Guide .

Option	Description
Model > Driver Set > Properties	Launches the driver set Properties page. See Viewing Object Properties in the Designer Administration Guide .
Model > ECMAScript > New	Creates an ECMAScript object.
Model > ECMAScript > New from Copy	Creates an ECMAScript object by copying an existing ECMAScript object.
Model > eDir-to-eDir > New	Launches the eDirectory-to-eDirectory Wizard to create a new connection between two OpenText eDirectory objects.
Model > eDir-to-eDir > Secure Connection Settings	Opens the TLS Configuration window to enable SSL/TLS connection settings and encrypted key settings through advanced TLS configuration.
Model > eDir-to-eDir > Disconnect eDir-to-eDir	Disconnects the eDirectory-to-eDirectory connection.
Model > Identity Vault > New	Adds a new server to an Identity Vault.
Model > Identity Vault > Manage Schema	Opens a context-sensitive window to manage schema classes and attributes of the Identity Vault.

Option	Description
Model > Identity Vault > Import from Configuration File	Allows you to browse to and import an Identity Vault.
Model > Identity Vault > Duplicate Template	Opens an e-mail template list that you can duplicate.
Model > Identity Vault > Edit Template	Opens a template list to select and edit an e-mail template.
Model > Identity Vault > E-Mail Server Properties	Launches the e-mail notification server so you can enter notification settings and server authentication credentials.
Model > Identity Vault > Administrator	Opens the Administrator properties window of the Identity Vault to enter personal and contact information and other optional information.
Model > Identity Vault > Server List	Launches a wizard that displays the servers associated with a selected Identity Vault, which enables you to edit the properties and contact information. See Driver Set Server List in the Designer Administration Guide .

Option	Description
Model > Identity Vault > Properties	Opens the Properties window for the Identity Vault to access configuration, administrator, and server list properties. See Configuring Identity Vaults in the Designer Administration Guide .
Model > Job > New	Launches the Job Scheduler Wizard to create a job.
Model > Job > New from Copy	Creates a job by copying an existing job.
Model > Library > New	Launches the New Library Wizard to create a library after you have selected an Identity Vault or a driver set.
Model > Library > Import from Configuration File	Allows you to import a driver into a driver set.
Model > Policy > New DirXML Script	Opens a new Policy Name window to enable you to create XML policy scripts.
Model > Policy > New Schema Mapping	Opens a schema map editor to associate identity objects with associated service drivers. See Managing the Schema in the Designer Administration Guide .

Option	Description
Model > Policy > New XSLT	Opens a new Policy Name window to enable you to create Extensible Stylesheet Language Transformation (XSLT) policy scripts.
Model > Policy > New from Copy	Opens the Modeler browser to copy selected existing Driver Set objects.
Model > Policy > Manage Policy	Launches a policy manager GUI that exposes individual elements of a project design tree that can be edited in context by right-clicking each element.
Model > Resource > New	Prompts you to add new resource objects from the Modeler palette. After resource objects are added, you set up connection and control settings.
Model > Server > New	Associates a new OpenText eDirectory server or manual server to an Identity Vault.
Model > Select Connected Applications	Selects driver connections between application objects in modeler.
Model > Clear All Items	Enables you to clear all items in a project.

Option	Description
Model > Straighten Connections	Straightens line connections between selected objects in the Modeler.
Model > Distribute	Distributes selected objects in the Modeler either vertically or horizontally.
Model > Align	Aligns selected objects in the Modeler: top, bottom, left, right, center, or middle.
Model > Snapshot to Image File	In Developer or Architect mode, captures the model and stores it in a .bmp , .jpg , or . jpeg file, which is stored in the Designer driver_configs directory.

1.9.8. Window menu

Option	Description
Window > New Window	Opens a new instance of the application, making it easier to copy and paste between certain elements. You must synchronize changes between the instances.
Window > New Editor	Launches a new Designer editor.
Window > Open Perceptive	Toggles among perspectives: Debug, Designer (default), Java, Java Browsing, Java Type Hierarchy, Plug-in Development, Resource, and Team Synchronizing.
Window > Show View > Dataflow	Controls the flow of data between objects. See the Dataflow Mode .
Window > Show View > Navigator	Displays the Navigator view. See The Navigator View .
Window > Show View > Outline	Provides an outline view of the active editor (Modeler, XML Editor, or a text editor).
Window > Show View > Policy Set	Displays the Policy Set view. When you select a driver in the Modeler, this view displays the driver's policies. See Policy Set View .

Option	Description
Window > Show View > Project	Displays the main view for manipulating your project. See Creating a Project .
Window > Show View > Project Checker	Checks Designer objects for any problems that might cause the deployment of a project into the Identity Vault to fail. It does not check the current objects in the Identity Vault. See Checking Your Projects .
Window > Show View > Provisioning View	Displays entities, lists, and organizational charts; used in workflow-based provisioning.
Window > Show View > Search Results	Displays the Search Results view. See also The Search Results View .
Window > Show View > Tasks	Enables you to add your own tasks and notes as you do your work. You can assign them a priority; mark them as completed; or delete, sort, or filter them.
Window > Show View > Trace	Displays internal errors and messages, so that you can find out why something isn't working as expected. Use this feature to provide information for OpenText Support, engineers, or other consulting resources. See Trace .

Option	Description
Window > Show View > Version Control	Enables you to track revisions of your project and share them with team members. Also enables you to track objects and files inside of your project.
Window > Show View > Other > General > Bookmarks	Enables you to see bookmarks that you have set in your text editors.
Window > Show View > Other > General > Console	Displays the Console view.
Window > Show View > Other > General > Internal Web Browser	Enables you to immediately access the Eclipse Website, or otherwise access the Internet.
Window > Show View > Other > General > Navigator	Displays the Navigator view. See The Navigator View .
Window > Show View > Other > General > Outline	Displays the Outline view.
Window > Show View > Other > General > Progress	Displays the Progress view.
Window > Show View > Other > General > Problems	Displays the Problems view, with errors and warnings used for troubleshooting.

Option	Description
Window > Show View > Other > General > Project Explorer	Displays the project components.
Window > Show View > Other > General > Properties	Enables you to view and edit settings on the selected object.
Window > Show View > Other > General > Tasks	Enables you to list, prioritize, and track tasks
Window > Show View > Other > Designer for Identity Manager > Dataflow	Controls the flow of data between objects. See The Dataflow View and Dataflow Mode .
Window > Show View > Other > Designer for Identity Manager > Policy Set	Displays all policies contained in the selected policy set. See Policy Set View .
Window > Show View > Other > Designer for Identity Manager > Project	Displays the main view for manipulating your project. See Creating a Project .
Window > Show View > Other > Designer for Identity Manager > Project Checker	Checks Designer objects for any problems that might cause the deployment of a project into the Identity Vault to fail. It does not check the current objects in the Identity Vault. See Checking Your Projects .

Option	Description
Window > Show View > Other > Designer for Identity Manager > Search Results	Displays the Search Results view. For more information, see The Search Results View .
Window > Show View > Other > Designer for Identity Manager > Trace	Displays internal errors and messages, so that you can find out why something isn't working as expected. Use this feature to provide information for OpenText Support, engineers, or other consulting resources. For more information, see Trace .
Window > Show View > Other > Designer for Identity Manager > Version Control	Enables you to track revisions of your project and share them with team members. Also enables you to track objects and files inside of your project.
Window > Show View > Other > exteNd > Registry Manager	Launches the Registry Manager view.
Window > Show View > Other > Help > Help	Launches context-sensitive help in the Help view. Help topics depend on which part of the Modeler or Designer is active.
Window > Show View > Other > PDE Runtime > Error Log	Used for troubleshooting. For more information, see Viewing the Error Log .

Option	Description
Window > Show View > Other > PDE Runtime > Plug-in Registry	Displays the plug-in registry. Enables you to see which plug-ins are registered or running. For more information, see Checking Loaded Plug-Ins .
Window > Show View > Other > Provisioning	Enables you to view and configure entities, lists, and organizational charts. See the Administrator's Guide to the Identity Applications .
Window > Show View > Other > Provisioning > Data Item Mapping	Specifies how object attributes are mapped. See Mapping Identity Vault to an LDAP Schema in the Designer Administration Guide .
Window > Show View > Other > Provisioning > E-Mail Notification	Displays an e-mail notification map.
Window > Show View > Other > Provisioning > Provisioning	Displays entities, lists, and organizational charts used in workflow-based provisioning.
Window > Show View > Other > XML > XPath Navigator	Supports context-sensitive editing of XPath expressions. Automatically attaches to the currently selected XML editor.

Option	Description
Window > Customize Perspective	Configures the layout of a perspective. Controls the menus (New, Open Perspective, and Show View) and action sets that show up on the tool bar. See Managing Perspectives .
Window > Customize Perspective > Shortcuts	Lists the plug-in shortcuts that you can add as cascade submenus on the current perspective.
Window > Customize Perspective > Shortcuts > Designer Document Generation	Enables addition of a .docgen shortcut to create a new document generation style.
Window > Customize Perspective > Shortcuts > General	Enables selection of shortcuts to create a new file, folder, or empty untitled text file resources.
Window > Customize Perspective > Shortcuts > Identity Manager	Enables the addition of the OpenText Identity Manager Project shortcut to create a new project.
Window > Customize Perspective > Shortcuts > Provisioning	Enables selection of shortcuts to create new directory abstraction layer entities, lists, relationships, organizational charts provisioning request definitions.
Window > Customize Perspective > Shortcuts > XML	Enables addition of an XML shortcut.

Option	Description
Window > Customize Perspective > Commands	Alphabetically lists the command group plug-ins that you can add as cascade submenus on the current perspective. The Details field identifies which menu item organizational charts toolbar items are added to the perspective by the selected command group. See Using Menus to Open a Perspective .
Window > Customize Perspective > Commands > Breakpoints	Adds breakpoint functionality to the menu.
Window > Customize Perspective > Commands > com.novell.designer.idm.actionSet	Adds Help set functionality to the menu: Check for Designer Updates, What's New, Designer Readme, Report a Bug or Feedback, and OpenText Identity Manager Resources.
Window > Customize Perspective > Commands > Debug	Adds the Debug plug-in functionality to the menu.
Window > Customize Perspective > Commands > Deploy	Enables the Deploy plug-in command. See Deploying the Schema into the Identity Vault in the Designer Administration Guide .
Window > Customize Perspective > Commands > Designer	Adds standard Designer commands to the toolbar: Save All, Delete selected object(s), Undo, and Redo.

Option	Description
Window > Customize Perspective > Commands > Designer Projects ActionSet	Adds Designer project import control options to the menu.
Window > Customize Perspective > Commands > Document Generation	Adds the Generate Documentation icon to the toolbar.
Window > Customize Perspective > Commands > Editor	Adds cut, copy, and paste options to the menu and toolbar.
Window > Customize Perspective > Commands > Editor Navigation	Adds Last Edit Location navigation to the menu and toolbar.
Window > Customize Perspective > Commands > > Editor Presentation	Adds a toggle to Show Selected Element Only on the toolbar.
Window > Customize Perspective > Commands > Generate Documentation	Adds a Generate Documentation for This Project icon to the toolbar.
Window > Customize Perspective > Commands > Identity Vault	Adds Identity Vault resource information for a project to the menu.
Window > Customize Perspective > Commands > Insert	Enables the Insert plug-in command.
Window > Customize Perspective > Commands > Keyboard Shortcuts	Adds keyboard shortcuts to the menu.

Option	Description
Window > Customize Perspective > Commands > Launch	Adds Run program functionality to the menu and adds the Launch plug-in to the toolbar.
Window > Customize Perspective > Commands > Manage Objects in a eDirectory Tree	Adds the eDirectory Object Manager to the menu.
Window > Customize Perspective > Commands > Manage Objects in a eDirectory Tree	Adds the Live > Manage Directory functionality to the menu.
Window > Customize Perspective > Commands > Open Files	Adds the browse to and open a text or XML file plug-in to the menu.
Window > Customize Perspective > Commands > Profile	Adds the Run > Profile tools on the menu and toolbar.
Window > Customize Perspective > Commands > Project Actions	Launches the project snap-in.
Window > Customize Perspective > Commands > Project Checker	Places the Project Checker icon on Designer's toolbar.
Window > Customize Perspective > Commands > Resource Navigation	Adds Navigation tools as an option on the menu.

Option	Description
Window > Customize Perspective > Commands > Run the User Application	Adds Access User Application as an option on the Tools menu.
Window > Customize Perspective > Commands > Tools	Adds Tools as an option on the Project menu.
Window > Customize Perspective > Commands > Version Control Action Set	Adds Action Set as an option on the Web browser toolbar.
Window > Customize Perspective > Commands > View DS Trace Logs	Adds DS Trace as an option on the Tools menu.
Window > Customize Perspective > Commands > WebBrowser	Adds the Launch Web Browser Wizard to the Web browser toolbar.
Window > Customize Perspective > Commands > WebBrowser	Adds the Launch Web Browser Wizard to the Window menu.
Window > Customize Perspective > Commands > Window Working Set Menu	Adds Working Set to the Window drop-down menu.
Window > Customize Perspective > Commands > Window Working Set Toolbar	Adds Working Set to the Web browser toolbar.

Option	Description
Window > Save Perspective As	An easy, efficient way to lay out the current perspective in a certain way and then save it. You can freely switch between perspectives and still operate in the same editors and views.
Window > Reset Perspective	Returns the perspective to its original layout. If the perspective is a copied perspective, it returns to the original, preferred layout of the base perspective.
Window > Close Perspective	Closes the current perspective.
Window > Close All Perspectives	Closes all open perspectives.
Window > Navigation > Show System Menu	Displays the active system menu.
Window > Navigation > Show View Menu	When active, shows the View menu.
Window > Navigation > Quick Access	Enables you to search for a specific function by typing in the desired function into the
Window > Navigation > Maximize Active View or Editor	Maximizes the active view or editor. Ctrl+M toggles between views.

Option	Description
Window > Navigation > Minimize Active View or Editor	Minimizes the active view or editor. Ctrl+M toggles between views.
Window > Navigation > Activate Editor	Enables you to select which editor to activate. F12 is the keyboard shortcut.
Window > Navigation > Next Editor	Allows you to select and open an editor from a list. Ctrl+F6 navigates down this list.
Window > Navigation > Previous Editor	Allows you to select and open an editor from a list. Ctrl+Shift+F6 navigates up this list.
Window > Navigation > Switch to Editor	Allows you to select and manage editors.
Window > Navigation > Next View	Allows you to select and open a view from a list. Ctrl+F7 navigates down this list.
Window > Navigation > Previous View	Allows you to select and open a view from a list. Ctrl+Shift+F7 navigates up this list.
Window > Navigation > Next Perspective	Allows you to toggle perspectives within projects from a list. Ctrl+F8 is the keyboard shortcut.

Option	Description
Window > Navigation > Previous Perspective	Allows you to view previous perspectives from a list. Ctrl+Shift+F8 is the keyboard shortcut.
Window > Launch Web Browser	Specifies your Home Page URL, which is stored in Preferences.
Window > Working Sets > Edit	Allows you to create working sets in a project

Option	Description
Window > Preferences	Enables you to customize Designer's behavior in the following categories: • General ◦ Appearance ◦ Compare/Patch ◦ Content Types ◦ Editors ▪ File Associations ▪ Hex Editor ▪ Structured Text Editors ▪ Text Editors ◦ Keys ◦ Network Connections ◦ Perspectives ◦ Search ◦ Startup and Shutdown ◦ Web Browser ◦ Welcome ◦ Workspace ▪ Build Order ▪ Linked Resources ▪ Local History • Help • OpenText

Option	Description
	◦ Designer ◦ Identity Manager ◦ Package Manager ◦ Provisioning • Validation • Web • XML See Setting Preferences in the Designer Administration Guide.

1.9.9. Help menu

Option	Description
Help > Welcome	Displays the Welcome page. See Help from the Welcome Page .
Help > Help Contents	Enables you to navigate to and view information about all features and functions in Designer.
Help > Search	Locates instances in the help system and provides links.
Help > Dynamic Help	Provides context-sensitive information.
Help > Key Assist	Lists shortcuts.
Help > Check for Package Updates	Enables you to quickly download and install the latest package updates.
Help > Check for Designer Updates	Enables you to quickly download and install the latest Designer updates.
Help > What's New	Directs you to a OpenText Web page that describes new features in Designer.
Help > Designer Readme	Provides updated information about known issues.

Option	Description
Help > Report a Bug or Give Feedback	Allows you to enter a Designer bug or provide feedback into Bugzilla.  Note You must first establish a User Account to provide feedback.
Help > Identity Manager Forums	Provides a link to OpenText Identity Manager product support forums.
Help > Identity Manager Resources	Provides a link to the Designer Resource Page.
Help > About Designer	Provides information about Designer's version, configuration, product, license, and plug-in.



© Copyright 2026 Open Text

For more info, visit <https://docs.microfocus.com>
