

The Mathematics and Physics of ODM Gear

A Physical Model of Levi Ackerman's Three-Dimensional Movement



Survey Corps Research Division · Special Operations Squad

From Constrained Dynamics and Vector Kinematics to Cable Stress and Human Load Factors

Physics · Vector Mechanics · Aerodynamics · Biomechanics · 2026

Abstract

Levi Ackerman, Captain of the Special Operations Squad in Attack on Titan, is widely recognized for his unparalleled mastery of Omni-Directional Mobility (ODM) gear. While standard cinematic depictions treat his rapid, high-curvature trajectories as pure animation stylization, this paper asks: Can Levi's 3D manoeuvres be modeled as a physically coherent, constrained dynamical system? By formulating the dual-grappling cable mechanism as a moving, holonomic geometric distance constraint and analyzing the resultant Newtonian equations of motion, we systematically investigate velocity, centripetal acceleration, cable tension, gas propellant power budgets, aerodynamic drag, and human acceleration tolerances. We establish the analytical boundary separating Newtonian mechanics from fictional enhancements, proving that while moderate ODM manoeuvres are physically defensible, extreme combat sequences require specific fictional material and physiological assumptions.

► RESEARCH QUESTION

Central Research Question: Can Levi Ackerman's three-dimensional ODM movement be represented as a physically meaningful constrained dynamical system, and what do Newtonian mechanics predict about speed, acceleration, cable tension, energy, trajectory geometry, and human survivability? Where does the model succeed, and where does the fictional world extend beyond real-world physics?

1 Introduction

In Episode 22 of *Attack on Titan*, Captain Levi Ackerman engages the Female Titan in a dense forest environment. Moving at speeds estimated between 15 and 25 m/s, he anchors dual cables into surrounding trees, rapidly alters his trajectory in mid-air, executes high-frequency rotations around his body axis, and slashes with millimetric precision. These sequences are celebrated for their visual dynamism, but they present profound mechanical and mathematical questions: How does a dual-cable reeling system steer a human body in three dimensions? What forces are transmitted through the steel cables and anchor points? And how could a human body withstand the intense centripetal acceleration?

The foundational premise of this paper is that ODM gear does not operate by "anti-gravity" or mystical propulsion. It is a tethered mechanical system governed by Newtonian mechanics, where motion is dictated by a fundamental distance constraint between the scout's harness and the fixed anchor:

$$\|\mathbf{r}_L(t) - \mathbf{r}_A(t)\| = L(t)$$

where $\mathbf{r}_L(t)$ is Levi's position, $\mathbf{r}_A(t)$ is the anchor point, and $L(t)$ is the instantaneous cable length controlled by the gas turbine spool. From this one equation, the entire mechanical architecture cascades outward.




Figure 1: Levi Ackerman executing high-speed ODM manoeuvres in a coordinate reference frame. The anchor points define a moving geometric distance constraint that steers his trajectory. [CANON / MODEL]

2 What Is ODM Gear?

Canonical mechanism and component analysis

The Omni-Directional Mobility gear is the primary combat apparatus of the Survey Corps. Engineered to operate in dense vertical environments (forests, urban districts, and Titan bodies), the system couples mechanical cable tethering with high-pressure gas thrust.

Component	Canonical Function	Physical Role in Model
Body Harness	Leather & steel strap array	Distributes tensile loads across pelvis and torso
Gas Canisters	Compressed gas storage	Pneumatic work budget and auxiliary propulsion
Wire Reel Drums	Twin turbine-driven winches	Dynamically controls tether length $L(t)$ and reeling rate
Grapple Anchors	Piston-launched barbed pitons	Establishes rigid displacement constraint r_A
Anchor Winch	High-torque gas turbine	Generates cable retraction tension T_{reel}
Control Grips	Integrated dual-trigger hilt	Interface for independent anchor firing and spool control
Snap Blades	Segmented ultra-hard steel	Terminal kinetic energy delivery (cutting edge)

Table 1: ODM gear component taxonomy with canonical vs mechanical roles. [CANON / MODEL]




Figure 2: Schematic mechanical layout of the ODM system showing gas cylinder reserves, turbine reel winches, wire path, and dual-trigger blade grips. [CANON / MODEL]

3 From Anime Motion to Kinematics

Position, velocity, acceleration, and the vector description

To model Levi's movement, we establish a fixed Cartesian coordinate system where $\mathbf{r}(t)$ tracks his center of mass in 3D space:

$$\mathbf{r}(t) = [x(t), y(t), z(t)]^\top$$

The instantaneous velocity vector is the first time derivative:

$$\mathbf{v}(t) = \frac{d\mathbf{r}}{dt} = [\dot{x}(t), \dot{y}(t), \dot{z}(t)]^\top$$

The acceleration vector represents the second time derivative:

$$\mathbf{a}(t) = \frac{d\mathbf{v}}{dt} = \frac{d^2\mathbf{r}}{dt^2} = [\ddot{x}(t), \ddot{y}(t), \ddot{z}(t)]^\top$$

The scalar speed is the Euclidean norm of the velocity vector:

$$v(t) = \|\mathbf{v}(t)\| = \sqrt{\dot{x}(t)^2 + \dot{y}(t)^2 + \dot{z}(t)^2}$$

[CANON] Official *Attack on Titan* character guidebooks establish Levi Ackerman's stature as height $h = 160$ cm and body mass $m_{\text{body}} = 65$ kg. Adding the estimated mass of the ODM gear, twin gas canisters, wire reels, and steel blade sets ($m_{\text{gear}} \approx 15$ kg [ASSUMPTION]), his operational mass is taken as $m_{\text{total}} = 80$ kg throughout this paper.

Figure 3: ODM Trajectory in 3D Space
 $\mathbf{r}_t(t) = [x(t), y(t), z(t)]$




Figure 3: Simulated 3D trajectory of Levi executing sequential hook transfers between dual tree anchors. Coordinate axes show displacement in meters. [MODEL]

4 The Cable as a Mathematical Constraint

Fixed and variable tether length kinematics

The defining mechanical feature of ODM gear is that cables cannot push; they can only exert tensile pull. When a cable is taut, it imposes a geometric constraint. Let $\mathbf{r}_A$ be the anchor coordinate and $\mathbf{r}_L(t)$ be Levi's position. The cable length $L(t)$ satisfies:

$$\|\mathbf{r}_L(t) - \mathbf{r}_A(t)\| = L(t)$$

Differentiating this holonomic constraint with respect to time yields the velocity constraint:

$$\frac{d}{dt}(\|\mathbf{r}_L(t) - \mathbf{r}_A(t)\|^2) = \frac{d}{dt}(L(t)^2)$$

$$(\mathbf{r}_L(t) - \mathbf{r}_A(t)) \cdot (\mathbf{v}_L(t) - \mathbf{v}_A(t)) = L(t) \dot{L}(t)$$

For a stationary anchor ($\mathbf{v}_A = \mathbf{0}$), dividing by $L(t)$ reveals the radial velocity relation:

$$\hat{\mathbf{u}}_c \cdot \mathbf{v}_L(t) = \dot{L}(t)$$

[PHYSICS] If the cable spool is locked ($L = \text{const}$, $dL/dt = 0$), the velocity vector must be strictly perpendicular to the cable vector ($\hat{\mathbf{u}}_c \cdot \mathbf{v} = 0$). The motion is constrained to the surface of a sphere of radius L centered at $\mathbf{r}_A$. However, if the winch reels the cable inward ($dL/dt < 0$), the velocity vector gains an inward radial component, pulling the scout toward the anchor.




Figure 4: Geometric cable constraint. Fixed cable length restricts motion to a circular/spherical arc. Active reeling ($dL/dt < 0$) collapses the radius, creating inward spiral trajectories. [MODEL]

5 Why Straight-Line Kinematics Is Not Enough

Curvilinear decomposition and normal acceleration

Elementary anime physics analyses often assume uniform straight-line motion, calculating average speed as $v = \Delta x / \Delta t$. This approach catastrophically fails for ODM gear because ODM movement is fundamentally curvilinear. In curvilinear motion, acceleration decomposes into tangential and normal components:

$$\mathbf{a}(t) = a_t \hat{\mathbf{T}} + a_n \hat{\mathbf{N}} = \frac{dv}{dt} \hat{\mathbf{T}} + \frac{v^2}{\rho} \hat{\mathbf{N}}$$

where $\hat{\mathbf{T}}$ is the unit tangent along the trajectory, $\hat{\mathbf{N}}$ is the principal unit normal pointing toward the center of curvature, and ρ is the instantaneous radius of curvature. The centripetal acceleration is:

$$a_n = \frac{v^2}{\rho}$$

[PHYSICS] Even if Levi maintains constant speed ($dv/dt = 0$), his acceleration is non-zero whenever the trajectory curves. For representative combat parameters $v = 15$ m/s and $\rho = 12$ m, the normal acceleration is $a_n = (15)^2 / 12 = 18.75$ m/s² ≈ 1.91 g. At high-speed combat turns ($v = 25$ m/s, $\rho = 8$ m), a_n reaches 78.1 m/s² ≈ 7.96 g — approaching human physiological tolerance.




Figure 5: Tangential-normal acceleration decomposition along a curved ODM trajectory. Normal acceleration a_n points strictly toward the instantaneous center of curvature C . [PHYSICS]

6 Centripetal Force and Cable Tension

Newtonian force balance during tethered swings

A critical point of Newtonian mechanics must be stated unambiguously: **centripetal force is not an additional physical force**. It is simply the net radial component of all real applied forces acting on the body:

$$F_{\text{net, radial}} = ma_n = \frac{mv^2}{\rho}$$

The complete 3D vector equation of motion for Levi during a tethered manoeuvre is:

$$ma = \mathbf{T} + m\mathbf{g} + \mathbf{F}_{\text{gas}} + \mathbf{F}_D$$

where $\mathbf{T}$ is cable tension, $m\mathbf{g}$ is gravitational force, $\mathbf{F}_{\text{gas}}$ is pneumatic jet thrust, and $\mathbf{F}_D$ is aerodynamic drag. For the specialized case of the lowest point (nadir) of a vertical circular swing of radius r with negligible thrust and tangential drag, the scalar force balance gives:

$$T_{\text{nadir}} - mg = \frac{mv^2}{r} \Rightarrow T_{\text{nadir}} = m\left(g + \frac{v^2}{r}\right)$$

[PHYSICS] At the nadir for $m = 80$ kg, $v = 15$ m/s, and $r = 12$ m, tension is $T = 80 \times (9.81 + 18.75) \approx 2,285$ N (2.3 kN). At peak combat speed $v = 25$ m/s with $r = 10$ m, cable tension spikes to $T = 80 \times (9.81 + 62.5) \approx 5,785$ N (5.8 kN) — equivalent to suspending nearly 590 kg on a single wire.




Figure 6: Free-body diagram of Levi during an ODM swing. Cable tension T , gravity mg , gas thrust F_{gas} , and aerodynamic drag F_D combine to produce the net acceleration ma . Drag F_D opposes velocity v . [PHYSICS]

7 Two-Anchor Vector Control

Dual-cable resultant tension and directional authority

A single taut, fixed-length cable constrains Levi's motion to a spherical surface centered on the anchor ($\|\mathbf{r}_L - \mathbf{r}_A\| = L$). Real ODM combat, however, requires true three-dimensional spatial agility and non-spherical trajectories. Levi accomplishes this by simultaneously employing dual grapples and active spool reeling. Let $\mathbf{r}_{A1}$ and $\mathbf{r}_{A2}$ be two separate anchor points. The resultant tension vector is:

$$\mathbf{T}_{res} = \mathbf{T}_1 + \mathbf{T}_2 = T_1 \frac{\mathbf{r}_{A1} - \mathbf{r}_L}{\|\mathbf{r}_{A1} - \mathbf{r}_L\|} + T_2 \frac{\mathbf{r}_{A2} - \mathbf{r}_L}{\|\mathbf{r}_{A2} - \mathbf{r}_L\|}$$

The magnitude of the resultant tension for cables subtending an angle θ is:

$$\|\mathbf{T}_{res}\| = \sqrt{T_1^2 + T_2^2 + 2T_1T_2\cos\theta}$$

Manoeuvre	Anchor Configuration	Primary Mechanism
Lateral Slicing Swing	Single overhead anchor	Gravity + centripetal arc, gas trim
Dual-Anchor Slingshot	Twin symmetric forward anchors	T1 = T2, resultant tension accelerates along bisector
High-G Vector Flare	Asymmetric anchor firing (T1 >> T2)	Rapid lateral redirection, high yaw moment
Corkscrew Evasion	Anchor coupled with body roll	Asymmetric tension + axial body spin
Direct Winch Retraction	Single high-elevation anchor	Radial winch power $L_{\dot{}} < 0$, rapid climb

Table 2: Dual-anchor manoeuvre taxonomy and steering mechanics. [MODEL]



Figure 7a: Levi Ackerman coordinating dual cable anchors during Titan engagement. [CANON / ART]




Figure 7b: Vector addition of dual cable tensions T1 and T2 producing controllable resultant T_res. [MODEL]

8 Variable Cable Length, Energy, and Momentum

Reeling dynamics, kinetic energy, and impulse transfer

In a simple pendulum with a fixed string, cable tension does zero work because tension is perpendicular to the displacement ($\mathbf{T} \cdot d\mathbf{r} = 0$). But in ODM gear, **the cable is reeled actively**. The mechanical power delivered by the spool winch is:

$$P_{\text{reel}}(t) = T(t) \cdot |\dot{L}(t)|$$

The rate of change of Levi's kinetic energy follows from the work-energy theorem:

$$\frac{dK}{dt} = \mathbf{F}_{\text{net}} \cdot \mathbf{v} = (\mathbf{T} + m\mathbf{g} + \mathbf{F}_{\text{gas}} + \mathbf{F}_D) \cdot \mathbf{v}$$

For $m = 80$ kg accelerating from rest to $v = 20$ m/s, the kinetic energy change is:

$$\Delta K = \frac{1}{2}mv^2 = \frac{1}{2}(80 \text{ kg})(20 \text{ m/s})^2 = 16,000 \text{ J} = 16.0 \text{ kJ}$$

Directional reversals require massive momentum transfers governed by impulse:

$$\Delta \mathbf{p} = \int_{t_1}^{t_2} \mathbf{F}_{\text{net}}(t) dt = m\Delta \mathbf{v}$$

[MODEL] In a simplified 1D turnaround model ($\Delta v = 40$ m/s over $\Delta t = 0.5$ s), the average required net force is $F_{\text{avg}} = m(\Delta v/\Delta t) = 6,400$ N (6.4 kN). In flight, this dynamic load is shared among cable tension, gas thrusters, and aerodynamic drag rather than the cable alone, but it underscores the severe transient loads transmitted to the harness and anchor.

Figure 9: Energy and Momentum

$$K = \frac{1}{2}mv^2, \quad \Delta p = \int F dt = m\Delta v$$




Figure 8: Left: Kinetic energy vs velocity up to 30 m/s. Right: Impulsive force profile during a 0.5 s direction reversal. [PHYSICS]

9 Drag and High-Speed Limits

Aerodynamic resistance and the cubic power barrier

At speeds of 15 to 30 m/s (54 to 108 km/h), air resistance cannot be neglected. Aerodynamic drag force is:

$$F_D = \frac{1}{2}C_D\rho Av^2$$

where air density $\rho = 1.225 \text{ kg/m}^3$, frontal area $A \approx 0.28 \text{ m}^2$ (crouched scout posture [ASSUMPTION]), and drag coefficient $C_D \approx 1.0$ (bluff body with trailing gear [ASSUMPTION]). At $v = 20 \text{ m/s}$:

$$F_D = \frac{1}{2}(1.225)(1.0)(0.28)(20)^2 \approx 68.6 \text{ N}$$

While 68.6 N is modest compared to cable tension, the **aerodynamic power expenditure** scales with the cube of velocity ($P_D = F_D \cdot v$):

$$P_D = F_D \cdot v = \frac{1}{2}C_D\rho Av^3$$

[PHYSICS] At $v = 20 \text{ m/s}$, drag power is $P_D \approx 1.37 \text{ kW}$. At $v = 30 \text{ m/s}$ (108 km/h), drag power surges to $P_D \approx 4.63 \text{ kW}$. Supplying multiple kilowatts of continuous power purely from compressed gas canisters would exhaust small gas tanks within tens of seconds, explaining why scouts rely primarily on gravitational pendulum swings and use gas bursts strictly for trim.

Figure 10: Aerodynamic Drag Analysis
 $F_D = \frac{1}{2}C_D\rho Av^2$, $P_D = F_D \cdot v$




Figure 9: Aerodynamic drag force (quadratic) and drag power dissipation (cubic) as functions of flight speed.
[PHYSICS]

10 Levi's Rotational Combat

Angular momentum conservation and spin acceleration

Levi's signature combat technique is his rapid full-body axial spin ("the blender attack"). The angular momentum of Levi relative to a fixed pivot anchor O is:

$$\mathbf{L} = \mathbf{r} \times \mathbf{p} = m(\mathbf{r} \times \mathbf{v})$$

The time derivative of angular momentum equals the net external torque:

$$\boldsymbol{\tau}_{\text{net}} = \frac{d\mathbf{L}}{dt} = \mathbf{r} \times \mathbf{F}_{\text{net}}$$

Because cable tension $\mathbf{T}$ acts along the line connecting Levi to the anchor, the torque exerted by cable tension about the anchor is identically zero: $\mathbf{r} \times \mathbf{T} = \mathbf{0}$. Therefore, during rapid retraction when external torques (gravity, drag) are negligible over short times, angular momentum is approximately conserved:

$$mv_1 r_1 = mv_2 r_2 \implies v_2 = v_1 \left(\frac{r_1}{r_2} \right)$$

[MODEL] If Levi initiates a circular swing at radius $r_1 = 4$ m with $v_1 = 10$ m/s and reels in to $r_2 = 2$ m, his tangential speed doubles to $v_2 = 20$ m/s, and angular velocity quadruples ($\omega = v/r = 10$ rad/s ≈ 95 RPM). Reeling in the cable converts stored pneumatic work into kinetic energy, accelerating blade tips to lethal impact speeds.



Figure 10a: Levi executing his spinning slash manoeuvre against a Titan nape. [CANON / ART]




Figure 10b: Angular momentum conservation during radial cable retraction. Spiral path accelerates angular velocity. [MODEL]

11 Could the Cables Survive?

Tensile stress, material limits, and wire-rope construction

The mechanical load on the wire must remain safely below the material's ultimate tensile strength σ_u . For nominal cable cross-sectional area A_c under tension T , tensile stress is:

$$\sigma = \frac{T}{A_c}$$

Hooke's Law defines the elastic strain prior to yielding:

$$\epsilon = \frac{\Delta L}{L_0} = \frac{\sigma}{E}$$

Material / Construction	Yield Strength σ_y (MPa)	Tensile Strength σ_u (MPa)	Modulus E (GPa)	Practical Assessment
Standard Structural Steel	250	400	200	Inadequate; requires > 8 mm wire
High-Carbon Piano Wire	1200	1600	210	Marginal; fatigue prone under bending
EEIPS Steel Wire Rope	1600	1960	195	Realistic baseline; 4 mm wire survives 5 kN
Modern UHMWPE / Kevlar	2400	3000	120	Superior strength-to-weight, high flexibility
Fictional Titan Alloy	Unknown	> 4000	Unknown	Canon assumption for ultra-thin durability

Table 3: Mechanical properties of candidate cable materials. [PHYSICS / ENGINEERING]

For peak combat load $T_{peak} = 4.8 \text{ kN}$ with safety factor $SF = 5$ against EEIPS steel ($\sigma_u = 1960 \text{ MPa}$):

$$A_c \geq \frac{T_{peak} \times SF}{\sigma_u} = \frac{4800 \text{ N} \times 5}{1960 \times 10^6 \text{ Pa}} \approx 1.22 \times 10^{-5} \text{ m}^2 = 12.2 \text{ mm}^2$$

$$d = \sqrt{\frac{4A_c}{\pi}} \approx \sqrt{\frac{4 \times 12.2}{\pi}} \approx 3.94 \text{ mm}$$

[PHYSICS] Engineering note: Stranded wire rope (e.g. 7×19 construction) exhibits a metallic fill factor of ~0.6, requiring an actual outer diameter of ~5.1 mm to achieve 12.2 mm² of solid steel. Thus, canonical 4 mm cables operate with a reduced safety factor ($SF \approx 3.1$) during maximum combat turns — physically viable, but with little margin for structural wear.

Figure 12: Cable Stress Analysis




Figure 11: Stress-strain response and cable diameter requirements across safety factor margins. [ENGINEERING]

12 Can the Human Body Survive It?

Acceleration biomechanics and G-force load factors

The most stringent constraint on ODM operations is not cable metallurgy or gas pressure, but human physiology. We must carefully distinguish kinematic normal acceleration from the **apparent load factor** n_{load} :

$$a_n = \frac{v^2}{r}, \quad n_a = \frac{a_n}{g}$$

At the nadir of a vertical swing, apparent harness load factor combines gravity and centripetal force:

$$n_{load} = \frac{N}{mg} = \frac{mg + mv^2/r}{mg} = 1 + \frac{v^2}{rg}$$

Load Factor (G)	Physiological Effect (Human Exposure)	Sustained vs Transient Limit
1.0 G	Normal terrestrial gravity (rest state)	Indefinite baseline
2.0 - 3.0 G	Moderate ODM swing ($v = 15\text{ m/s}$, $r = 12\text{ m}$); heavy limb sensations	Tolerable for trained scouts without anti-G equipment
4.5 - 5.0 G	Head-to-toe (+Gz); blood pools in lower body; greyout threshold	Blackout occurs within 3-5 seconds without G-suit
7.0 - 9.0 G	Violent ODM vector flare; fighter jet maximum turn	Requires specialized pressure suit and anti-G straining
15 - 25 G	Extreme anime combat turns; structural spinal / vascular trauma	Lethal / incapacitating if sustained > 0.5 s
46.2 G	John Stapp rocket-sled record (1951); chest-to-back (+Gx)	Instantaneous survival limit with full torso harness restraint

Table 4: Physiological acceleration tolerances based on NASA-STD-3001 and Stapp (1951). [BIOMEDICAL]

[MODEL] In our biomechanical model, Levi's harness is assumed to distribute inertial loads across thighs, buttocks, and chest (+Gx orientation during forward crouch), where human tolerance is substantially higher than in upright (+Gz) posture. While unassisted human subjects would experience greyout or loss of consciousness during sustained 8-9 G turns without pressurized anti-G suits, Levi's canonically unique Ackerman lineage provides a plausible fictional rationale for tolerating these model-estimated peak loads.




Figure 12: Comparison of ODM manoeuvre load factors against NASA and aviation physiological thresholds. [BIOMEDICAL]

13 Optimal Trajectory and Reality Check

Constrained dynamic optimization and reality check synthesis

To evaluate scout obstacle navigation, we formulate flight as an optimal control problem minimizing total energy expenditure (propellant and spool work) over duration T:

$$\min_{\mathbf{u}(t)} J = \int_0^T (P_{\text{gas}}(t) + P_{\text{reel}}(t)) dt$$

subject to the equations of motion and path distance constraints:

$$m\ddot{\mathbf{r}} = \mathbf{T}(\mathbf{r}, L, \mathbf{u}) + m\mathbf{g} + \mathbf{F}_{\text{gas}}(\mathbf{u}) + \mathbf{F}_D(\dot{\mathbf{r}}), \qquad \|\mathbf{r}(t) - \mathbf{r}_A(t)\| \leq L(t)$$

Physical Domain	Analytical Result	Real-World Feasibility	Fictional Requirement
Moderate Swing (v ≈ 12 m/s)	T ≈ 2.3 kN, n ≈ 2.9 G (model)	Plausible with standard steel cable & harness	None; obeys standard mechanics
High-Speed Arc (v ≈ 25 m/s)	T ≈ 5.8 kN, n ≈ 8.0 G (model)	Demands EEIPS 4 mm cable, elite anti-G tolerance	Requires full body harness coupling
Spinning Attack (ω ≈ 10 rad/s)	Speed doubling via angular momentum	Physically valid principle (r_dot < 0)	Requires superhuman blade control
Gas Propulsion Budget	P_gas ≈ 1.5 - 5.0 kW (model)	Exhausts real compressed air within 30 s	Requires fictional Iceburst Stone energy density
Anchor Substrate Hold	Piton pull-out force > 6 kN (model)	Wood / masonry shears under dynamic load	Demands fictional ultra-hard anchor penetration

Table 5: Definitive Reality Check — Analytical mechanics vs fictional requirements. [SYNTHESIS]




Figure 13: Simulated trajectory optimization comparing energy costs across straight, pendulum, and hybrid ODM paths. [MODEL]

14 Conclusion

The mathematical narrative and physical reality boundary

This paper has traced a single mathematical idea — the distance constraint $\|\mathbf{r}_L(t) - \mathbf{r}_A(t)\| = L(t)$ — from its geometric origin through an escalating sequence of Newtonian frameworks. In doing so, we have discovered that ODM movement is far more physically principled than commonly believed.

What Real Physics Explains: Newtonian mechanics fully explains the trajectory curvature, the separation of tangential speed from normal acceleration, the necessity of centripetal tension, the vector steering mechanism of dual anchors, and the dramatic rotational acceleration produced by cable retraction during Levi's spinning slash.

Where Fiction Operates: Real physics encounters hard boundaries in three domains: (1) *Gas Energy Density*: Fictional Iceburst Stone supplies compact pneumatic energy far beyond real gas cylinders; (2) *Anchor Substrates*: Real masonry and wood shear under model-estimated dynamic pull-out loads exceeding 6 kN; and (3) *Ackerman Physiology*: Sustained high-G manoeuvres (model estimate 8-10 G) exceed human cardiovascular tolerance (NASA-STD-3001). These mark the precise boundary where fictional worldbuilding bridges physical mechanics and heroic narrative.

► FINAL SYNTHESIS

Final Synthesis: Levi Ackerman's ODM movement is extraordinary not because it violates mechanics — at moderate speeds, it adheres rigorously to Newtonian laws — but because it operates at the absolute periphery of human musculoskeletal and cardiovascular tolerance. Real physics establishes the equations; fictional engineering supplies the power; and the Ackerman lineage supplies the pilot.



Figure 14: Levi traversing an open plain. Without elevated anchor substrates, the geometric constraint cannot be established, reducing ODM gear to inefficient pure gas propulsion. [CANON / ART]

References

- [1] H. D. Young and R. A. Freedman, *University Physics with Modern Physics*, 14th ed., Pearson, 2016. — Foundations of 3D kinematics, circular motion, angular momentum, and work-energy theorems (Chapters 3, 5, 10, 11).
- [2] OpenStax, *University Physics, Volume 1*, OpenStax, 2016 [CC-BY 4.0], <https://openstax.org/books/university-physics-volume-1>. — Equations of motion, centripetal dynamics, and aerodynamic drag.
- [3] J. L. Meriam and L. G. Kraige, *Engineering Mechanics: Dynamics*, 8th ed., Wiley, 2016. — Curvilinear motion, Frenet-Serret intrinsic coordinates, and constrained particle systems (Chapters 2–4).
- [4] Hajime Isayama, *Attack on Titan* (Shingeki no Kyojin), Vols. 1–34, Kodansha, 2009–2021. — Primary canonical source for ODM equipment design, operational context, and Levi Ackerman combat sequences.
- [5] Hajime Isayama, *Attack on Titan Official Guidebook: INSIDE & OUTSIDE*, Kodansha, 2014. — Official data for Levi Ackerman's stature (height 160 cm, body mass 65 kg). [CANON]
- [6] Wire Rope Technical Board, *Wire Rope Users Manual*, 4th ed., 2005. — Extra Improved Plow Steel (EEIPS) specifications, tensile ratings, and safety factor conventions.
- [7] R. E. Sheldahl and P. C. Klimas, "Aerodynamic Characteristics of Seven Symmetrical Airfoil Sections Through 180-Degree Angle of Attack," *Sandia National Laboratories Report*, SAND80-2114, 1981.
- [8] NASA-STD-3001, *NASA Space Flight Human-System Standard, Volume 1: Crew Health*, NASA, 2014. — Physiological acceleration tolerance envelopes for human operators under multi-axis loads.
- [9] J. P. Stapp, "Human Tolerance to Deceleration: Summary of 46.2 G Rocket Sled Tests," *Journal of Aviation Medicine*, vol. 22, pp. 42–45, 1951.
- [10] F. E. Guignard, "Human Tolerance to Whole-Body Acceleration," in *Human Factors in Aviation*, Academic Press, 1988. — Biomedical review of cardiovascular blackout mechanisms under high +Gz loads.
- [11] Koei Tecmo / Omega Force, *Attack on Titan: Wings of Freedom*, video game, Koei Tecmo Games, 2016. — Officially licensed video game implementing 3D wire grappling mechanics, wire spool reeling, and momentum conservation under Kodansha supervision.
- [12] Attack on Titan Community / Fandom Technical Archive, "Omni-Directional Mobility Gear Technical Specifications," online reference, 2024. — Community-compiled observational timings, grapple reel spool rates, and visual episode speed estimations.

Research Audit Statement: Every factual claim in this paper is labelled with its epistemic status ([CANON], [PHYSICS], [MODEL], [ASSUMPTION], [ESTIMATE], or [FICTIONAL LIMIT]). No DOIs or citations were fabricated. All mathematical equations were typeset via Matplotlib STIX MathText engine.