Resource-Bounded CTF Agents — Phase 1 Baseline

Team: Steven Zhang, Benjamin Yu, Jackie Liu · **Option 7** · **Repo:** https://github.com/StrawberrysAdvanture/cse291-ctf-agent

> **Research question.** How well does a *small, self-hosted* model (7B, 4-bit, on a single mid-range GPU) solve CTF challenges under a fixed step and token budget, and **what limits it** — model capability, the tool interface, lost intermediate findings, or unproductive loops? We establish a reproducible baseline, measure its execution behavior, and use the failure breakdown to justify a Phase 2 direction.

1. Setup

A tool-using agent with a **fixed** model, instructions, tool set, and step budget, on NYU CTF Bench.

- **Model:** Qwen2.5-7B-Instruct-AWQ (INT4 weights, FP16 compute/KV cache), served with vLLM 0.7.3 on one AWS g6.xlarge (NVIDIA L4, 24 GB); 32,768-token context, temperature 0.6, max_tokens 1024.
- **Agent:** NYU CTF harness. Tools: `run_command`, `create_file`, `decompile_function`, `disassemble_function` (Ghidra), `check_flag`, `give_up`. No native tool-calling — calls are emitted/parsed as XML in a `<function_calls>` block.
- **Budget / isolation:** 20 model calls and 900 s per attempt; the agent container runs on an internal Docker network (no internet) with only the challenge server reachable; answer keys are never mounted or shown.
- **Workloads:** 10 development + 20 held-out challenges across 6 categories (crypto, forensics, misc, pwn, rev, web); development is used to design/instrument the method, held-out only to assess. 3 attempts per challenge.
- **Reproducibility:** model, vLLM, and dataset (NYU CTF Bench v20250206) are pinned; each attempt runs in a **fresh container** with deterministic seeds; no failed run or timeout is silently dropped. Versions, exclusions, and the reproduce command are in Appendix A.

2. Verification

Each attempt is re-scored **outside the harness** (`analysis/score.py`) against the answer key read from the host — not the agent's own verdict — and checked for **flag origin** (earned only if the flag appeared in a tool output before submission) and **suspicious access** (dataset metadata, `challenge.json`, Docker socket, network). The 1 held-out solve was **earned** from tool output; 0 possibly-memorized; 0 suspicious accesses; the re-score **agreed with the harness on all 90 attempts**.

3. Results

Set	Attempts	Solved (att.)	Challenges ≥1	Mean rounds	Mean wall (s)	Mean tokens/att.	Peak ctx (tok)
Development	30	0 (0.0%)	0/10	18.2	586	189.7k	17,568
Held-out	60	1 (1.7%)	1/20	18.4	544	169.4k	16,294
Pilot	3	1 (33%)	1/3	14.0	284	131.2k	11,572

- **Solve rate: held-out 1.7% of attempts, 1/20 challenges** (`2023q-rev-baby_s_third`, rev); **development 0%, 0/10**; pilot 1/3. Every category is 0 except held-out **rev 1/4**.
- **Not reliable:** the one solve occurred on only **1 of its 3 attempts** (solved in 7 rounds; `max_rounds` on the other two) — expected at temperature 0.6, and a reminder that a single success is within run-to-run noise rather than a stable capability.
- **Cost / effort:** ~**$9.4** total GPU (~11 g6-hours), well under the $20/day, $200 caps; ~540–590 s and ~170–190k cumulative tokens per attempt; peak single-call context ~16–18k of 32k.
- **Tool vs. model time, cold vs. steady:** tool-call latency is negligible (median **0.05 s**), so wall time is almost entirely model generation; the only slow tool is Ghidra (up to **30 s**, a cold-start cost on the first decompile/disassemble of a binary). The ~30 s vLLM load is a one-time server cost excluded from per-attempt timing.
- **Execution pathologies (previewing §4):** across 1,647 model rounds, **57%** produced no executed tool call, **~50%** of replies hit the 1,024-token cap, and ~**1,160** tool calls repeated an earlier action. Full per-category

tables, timeout/invalid-command breakdowns, and the outcome/context figures are in Appendices B–C.

4. Failure analysis

89 of 90 attempts failed (77 `max_rounds`, 11 `context_length`, 1 `give_up`). Hand-inspecting traces (1,647 model rounds, 1,849 tool calls across dev + held-out), we sort causes into the four prescribed categories:

1. **Poor tool interface — the largest mechanical loss. 57%** of rounds produced **no executed tool call**. Many are **format slips**: the model emits a well-formed `<invoke>` *without* the `<function_calls>` wrapper the parser requires, so the harness drops it (191 such rounds in a seed-matched run); an unwrapped invoke also has no stop sequence, so **~50%** of replies run to the 1,024-token cap. It also calls programs (`cat`, `python3`) as if they were tools (~23 rejected); 52–67% of commands returned an error.
2. **Unproductive execution loops. ~1,160 ineffective repeats** (re-issuing commands whose output was already seen) — the dominant pattern in `max_rounds` traces.
3. **Lost intermediate findings.** Tied to (2): with no memory of verified outputs, earlier results fall out of attention; large outputs are also the ones causing the 11 `context_length` overflows (a *symptom* of unmanaged history, not steady growth — peaks averaged only ~16–18k of 32k).
4. **Missing model knowledge — the binding constraint.** Even on clean rounds, a 7B model rarely produces the multi-step exploitation these challenges need. `check_flag` was called 213 times, so the agent *attempts* solutions; capability, not budget, is the ceiling.

Cross-validation. A parallel harness-hardening effort (teammate branch) ran a paired A/B over the **full 57-challenge** set: a clean baseline **0/57** and a version with *every* mechanical fix applied (lenient parsing, output caps, repeat detection, nudges) **also 0/57** (McNemar p = 1.0), despite driving no-tool replies from 56% to **0%**. This independently confirms category (4) is binding — fixing the interface alone yields no solves — and both efforts converged on the same two low-level fixes (treat overflow as `context_length`; cap oversized outputs).

5. Phase 2 direction

Category (4) is capability-bound, but (1)–(3) show **half the budget is wasted before capability is tested**. Phase 2 targets that waste and tests whether recovering it helps, with controlled comparisons against the simple agent **and** fixed retries at equal budget, plus an ablation, on held-out challenges only.

- **Primary — output budgeting / tool-feedback compaction:** cap each tool result (head + tail + re-read note) so one large output cannot overflow context. *Preliminary (branch `phase2-outputcap`):* a seed-matched held-out A/B (8k-char cap) **cut `context_length` failures 7 → 3** with **no lost solves**; dev blowouts fell 3 → 1. No blowout converted to a solve — consistent with §4.
- **Secondary — lenient tool-call parsing:** recover the ~57% dead rounds from format slips, making the budget productive and the baseline fairer.
- **Open question:** whether a *capability*-side aid (verified-findings memory to cut repeats, or targeted tool/prompt scaffolding) moves the needle where interface fixes alone did not.

Appendix A — Reproducibility

- **Pinned versions:** Qwen2.5-7B-Instruct-AWQ; vLLM 0.7.3; NYU CTF Bench dataset v20250206; agent code at the tagged Phase 1 commit.
- **Fresh state:** every attempt recreates the challenge container (`docker compose … --force-recreate`); no state carries across attempts. Deterministic seeds `1000 + attempt_index`.
- **Exclusions** (documented in `experiments/phase1/challenges.yaml`): challenges with unbuildable environments are listed with reasons and replaced to preserve category coverage; nothing is dropped silently. All finish reasons (incl. timeouts/overflows) are logged.
- **Reproduce:** `experiments/phase1/run_batch.py --set {dev,heldout} --attempts 3 --config experiments/phase1/qwen_phase1.yaml`; score with `analysis/score.py logs/phase1 <dataset_dir>`.

Appendix B — Results by category

Solves by category: held-out **rev 1/4**; crypto (0/4), forensics (0/3), misc (0/2), pwn (0/4), web (0/3) all 0. Development: all 0 across crypto, forensics, misc, pwn, rev. The per-set summary table is in §3; full per-category means (rounds, wall time, tokens, invalid commands, repeats, finish reasons) are in `results/phase1/by_category.csv`. The hardest categories by wasted budget were pwn and crypto (most invalid commands and repeats per attempt); rev produced the only solve.

Appendix C — Execution measurements

- **Tool-call latency:** median **0.05 s**, p90 0.11 s, max **30 s** (Ghidra). Tool latency is negligible; model latency dominates wall time.
- **Invalid commands:** 67% (dev) / 52% (held-out) of tool calls returned an error or non-zero exit (1,066 of 1,849).
- **Timeouts:** 0 attempt-level (none hit the 900 s wall as finish reason); 60 command-level, all held-out (47 crypto, 13 pwn) — interactive binaries blocking on stdin.
- **No-tool rounds / truncation:** 938/1,647 (57%) rounds made no executed tool call; 816/1,647 (~50%) replies hit the 1,024-token cap.
- **Repeats:** ~1,160 ineffective repeated actions (424 dev + 736 held-out).
- **Finish reasons:** 77 `max_rounds`, 11 `context_length` (4 dev, 7 held-out), 1 `give_up`, 1 solved.




Fig 1. Outcome spread per challenge over 3 attempts — almost all end in `max_rounds` or `context_length`; one solve, on one of three attempts.




Fig 2. Prompt tokens vs. round; a few attempts spike into the 32k ceiling (`context_length`).

Appendix D — Timeline and milestones

- **Phase 1 (done, Nov 4):** harness instrumentation, network isolation, independent scoring, reproducible dev + held-out runs (3 attempts each, fixed commit), execution measurements, failure analysis. Code, configs, results, and logs: see the repository above.
- **Nov 4:** output-capping experiment complete (dev + held-out); results in §5.
- **~Nov 20:** Phase 2 mechanism finalized + ablation + fixed-retries baseline on held-out.
- **~Dec 5:** full held-out evaluation and variability runs; write-up.
- **Dec 10:** Phase 2 code and final report.