Fall 2018 Mid Term Solution

Chen Wang* 11/8/2019

Contents

| 1 | OS Interfaces | 1 |
|---|--|----------|
| 2 | Basic page tables 2.1 (5 points) Draw page table structure | 1 |
| 3 | Stack and calling conventions3.1 Explain Stack3.2 Analyze output | 3 3 |
| 4 | Xv6 process organization. 4.1 (3 points) Virtual address 0x0 | 4 |
| 5 | Protection and isolation 5.1 Kernel Memory Protection Explanation | 4 |
| 6 | System calls | 4 |
| 7 | Physical and virtual memory allocation 7.1 V2P macro usage explanation | 5 |
| | Initial page tables 8.1 (5 points) Explain what will go wrong with Bob's change? | 5 |

1 OS Interfaces

This question is not covered in this midterm

2 Basic page tables

2.1 (5 points) Draw page table structure

Alice wants to construct a page table that maps virtual addresses 0x0, 0x1000and 0x2000 into physical addresses 0x1000, 0x2000, and 0x3000. Assume that the Page Directory Page is at physical address 0x0, and the Page Table Page is at physical address0x00001000 (which is PPN 0x00001).

Draw a picture of the page table Alice will construct (or alternatively simply write it down in the format similar to the one below):

Page Directory Page:

 $[*]Undergraduate in Computer Engineering, Samueli School of Engineering, University of California, Irvine. \ (chenw23@uci.edu)$

```
PDE 0: PPN=0x1, PTE_P, PTE_U, PTE_W
... all other PDEs are zero
The Page Table Page:
PTE 0: PPN=0x1, PTE_P, PTE_U, PTE_W
PTE 1: PPN=0x2, PTE P, PTE U, PTE W
PTE 2: PPN=0x3, PTE_P, PTE_U, PTE_W
... all other PTEs are zero
Reference Solution:
Page Directory Page:
PDE 0: PPN=0x1, PTE_P, PTE_U, PTE_W
... all other PDEs are zero
The Page Table Page:
PTE 0: PPN=0x1, PTE_P, PTE_U, PTE_W
PTE 1: PPN=0x2, PTE_P, PTE_U, PTE_W
PTE 2: PPN=0x3, PTE_P, PTE_U, PTE_W
... all other PTEs are zero
```

3 Stack and calling conventions

Alice developed a program that has a function foo() that is called from two other functions bar() and baz():

```
int foo(int a) {
    ...
}

int bar(int a, int b)
    ...
    foo(x);
    printf("bar:%d\n", x);
    ...
}

int baz(int a, int b, int c) {
    ...
    foo(x);
    printf("baz:%d\n", x);
    ...
}
```

While debugging her program Alice observes the following state when she hits a break point of the program inside foo() (assume that the compiler does not inline invocations of foo(), bar(), and baz(), and follows the calling conventions that we've covered in the class)

```
The bottom of the stack:
```

0x8010b5b0: 0x00000003

0x8010b5b4: ...

```
      0x8010b5ac:
      0x00000002

      0x8010b5a8
      0x80102e80

      0x8010b5a4:
      0x8010b5b4

      0x8010b5a0:
      0x80112780

      0x8010b59c:
      0x00000001

      0x8010b598:
      0x80102e32

      0x8010b594:
      0x8010b5a4
      <--- ebp</td>

      0x8010b590:
      0x00000000
      <--- esp</td>
```

3.1 Explain Stack

(a) (5 points) Provide a short explanation for each line of the stack dump above (you can annotate the printout above).

Reference Solution

The bottom of the stack:

3.2 Analyze output

(b) (5 points) If Alice continues execution of her program what output will she see on the screen (justify your answer).

Reference Solution

We know that foo() can be called from bar() or baz(), but we also know that the caller of foo()'s caller i.e., either bar() or baz(), got two arguments. Hence, it's bar(). And since we know that foo() got 0x1 as argument the string Alice will see on the screen should be bar:1

4 Xv6 process organization.

In xv6, in the address space of the process, what does the following virtual addresses contain?

4.1 (3 points) Virtual address 0x0

Reference Solution

The memory at virtual address 0x0 contains the text section (code) of the user process.

4.2 (3 points) Virtual address 0x80100000

Reference Solution:

The memory at virtual address 0x80100000 contains the text section (code) of the kernel. During the boot the kernel was loaded at physical address 0x100000 (1MB) and then later this address was mapped at 2GBs + 1MB or (0x80000000 + 0x100000).

4.3 (3 points) What physical address is mapped at virtual address 0x80000000

Reference Solution:

Physical address 0x0.

4.4 Physical address mapping look-up

(7 points) Is there a way for the kernel to find out what physical address is mapped at a specific virtual address? Provide an explanation and a code sketch (pseudo-code is OK, no need to worry about correct C syntax). Your code should take a virtual address as an input and resolve it into the physical address that is mapped into that virtual address by the process page table (in your code feel free to re-use functions that are already implemented in the xv6 kernel).

Reference Solution:

In xv6 we can access the entire page table and the page tables contain information about how a virtual address maps to the physical address. Therefore, we only need to go though the table to find out where the physical page lie in the page table and then we will be able to find out the virtual addresses that are directing to this physical address.

Please see the C file at https://github.com/StrayBird-ATSH/OperatingSystemCourseMidTermExams/blob/master/Fall%202018/Fall2018Mid-Virtual2Physical.c

5 Protection and isolation

5.1 Kernel Memory Protection Explanation

(5 points) In xv6 all segments are configured to have the base of 0 and limit of 4GBs, which means that segmentation does not prevent user programs from accessing kernel memory. Nevertheless, user programs can't read and write kernel memory. How (through what mechanisms) such isolation is achieved?

Reference Solution:

Above all, xv6 adopts page tables. That is, the kernel memory and user memory will reside in different pages. Also, each page has a flag indicating whether this page is for kernel or for user. Therefore, when a user program wants to access kernel program, it will access the kernel pages, and visiting a page with a kernel flag will trigger a fault. So achieved.

6 System calls

This question is not covered in this midterm

7 Physical and virtual memory allocation

7.1 V2P macro usage explanation

(5 points) What is the purpose of the V2P macro? Specifically, the allocuvm() function(see the listing below) uses kalloc() to allocate and map a region of memory into the address space of a process. Explain, why the V2P macro is used in line 1946 below?

```
1926 int
1927 allocuvm(pde_t *pgdir, uint oldsz, uint newsz)
1928 {
1929
       char *mem;
1930
       uint a;
1931
1932
       if(newsz >= KERNBASE)
1933
         return 0;
       if(newsz < oldsz)</pre>
1934
1935
         return oldsz;
1936
1937
       a = PGROUNDUP(oldsz);
1938
       for(; a < newsz; a += PGSIZE){</pre>
1939
         mem = kalloc();
1940
         if(mem == 0){
1941
           cprintf("allocuvm out of memory\n");
1942
           deallocuvm(pgdir, newsz, oldsz);
1943
           return 0;
         }
1944
1945
         memset(mem, 0, PGSIZE);
         if(mappages(pgdir, (char*)a, PGSIZE, V2P(mem), PTE W|PTE U) < 0){
1946
           cprintf("allocuvm out of memory (2)\n");
1947
1948
           deallocuvm(pgdir, newsz, oldsz);
1949
           kfree(mem)
1950
           return 0;
         }
1951
       }
1952
1953
       return newsz;
1954 }
```

Reference Solution:

It translates a virtual address into physical address.

Because the mappages needs to check whether a physical page is mapped or not, or whether it is available. This translations gives the mappages function the location of the physical page needed and this function will do the mapping work.

8 Initial page tables

Bob looks at the piece of code in entry.S where the initial page tables are set and thinks he doesn't need the entry that maps the 0-4MB of virtual page to 0-4MB of physical page. Accordingly he modifies the entry pgdir as below.

```
__attribute__((__aligned__(PGSIZE)))
pde_t entrypgdir[NPDENTRIES] = {
```

```
// Map VA's [KERNBASE, KERNBASE+4MB) to PA's [0, 4MB)
[KERNBASE>>PDXSHIFT] = (0) | PTE_P | PTE_W | PTE_PS,
};
```

8.1 (5 points) Explain what will go wrong with Bob's change?

Reference Solution:

Because when the system initially boots, there was no kernel section in the upper 2GB and the codes are in the first 4MB space. Therefore, before the new page table is successfully mapped, we still need the mapping of the first 4MB to keep the code running smoothly.