

Deep Links Configuration for Moody

This document explains how to set up deep links for password reset and other authentication flows.

Overview

Moody uses deep links to handle password reset flows. When a user requests a password reset, Supabase sends an email with a link that opens the app directly.

URL Scheme

The app uses the `moody://` URL scheme for deep links.

Supported Deep Links

- `moody://reset-password` - Password reset callback
- `moody://auth/callback` - General auth callback

Configuration

app.json Configuration

The `scheme` is already configured in `app.json`:

```
{
  "expo": {
    "scheme": "moody"
  }
}
```

Android Configuration

For Android App Links (verified deep links), add intent filters to `android/app/src/main/AndroidManifest.xml`:

```
<intent-filter android:autoVerify="true">
  <action android:name="android.intent.action.VIEW" />
  <category android:name="android.intent.category.DEFAULT" />
  <category android:name="android.intent.category.BROWSABLE" />
  <data android:scheme="moody" />
</intent-filter>

<!-- For HTTPS links (optional, for web fallback) -->
<intent-filter android:autoVerify="true">
  <action android:name="android.intent.action.VIEW" />
  <category android:name="android.intent.category.DEFAULT" />
  <category android:name="android.intent.category.BROWSABLE" />
  <data android:scheme="https" android:host="your-domain.com" android:pathPrefix="/auth" />
</intent-filter>
```

iOS Configuration

For iOS Universal Links, you need to:

1. **Add Associated Domains capability** in Xcode:
 - Open your project in Xcode
 - Go to Signing & Capabilities
 - Add "Associated Domains"
 - Add `applinks:your-domain.com`
2. **Create apple-app-site-association file** on your server:

```
{
  "applinks": {
    "apps": [],
    "details": [
      {
        "appID": "TEAM_ID.com.tonorga.moody",
        "paths": ["/auth/*", "/reset-password"]
      }
    ]
  }
}
```

Host this file at `https://your-domain.com/.well-known/apple-app-site-association`

Supabase Configuration

1. Go to your Supabase Dashboard
2. Navigate to Authentication > URL Configuration
3. Add `moody://reset-password` to the Redirect URLs
4. For production, also add your web domain URLs

Handling Deep Links in the App

The app uses `expo-linking` to handle incoming deep links. The password reset flow:

1. User requests password reset
2. Supabase sends email with `moody://reset-password?token=...` link
3. User clicks link, app opens
4. App extracts token and allows user to set new password

Example Deep Link Handler

```
import * as Linking from 'expo-linking';
import { useEffect } from 'react';
import { supabase } from '../lib/supabase';

export function useDeepLinkHandler() {
  useEffect(() => {
    const handleDeepLink = async (event: { url: string }) => {
      const { path, queryParams } = Linking.parse(event.url);

      if (path === 'reset-password') {
        // Handle password reset
        // The token is automatically handled by Supabase
      }
    };

    // Handle initial URL
    Linking.getInitialURL().then((url) => {
      if (url) handleDeepLink({ url });
    });

    // Listen for URL changes
    const subscription = Linking.addEventListener('url', handleDeepLink);

    return () => subscription.remove();
  }, []);
}
```

Testing Deep Links

Android

```
# Test with adb
adb shell am start -W -a android.intent.action.VIEW -d "moody://reset-password" com.to
norga.moody
```

iOS

```
# Test with xcrun
xcrun simctl openurl booted "moody://reset-password"
```

Expo Go

In development with Expo Go, use:

```
exp://127.0.0.1:8081/--/reset-password
```

Troubleshooting

1. **Link not opening app:** Ensure the scheme is correctly configured in app.json
2. **Android not verifying:** Check that assetlinks.json is properly hosted
3. **iOS not working:** Verify apple-app-site-association file and Associated Domains

4. **Supabase redirect failing:** Ensure the redirect URL is added to Supabase dashboard