



Moon Deception - Unity Setup Guide

Prerequisites

- **Unity 2022.3 LTS** or newer
 - **Universal Render Pipeline (URP)** — already configured
 - Basic Unity knowledge
-



Quick Start

Option A: Automatic Setup

1. Open the project in Unity
2. Go to menu: **Moon Deception > Setup Phase 1**
3. Press **Play** to test

Option B: Manual Setup

Follow the detailed steps below.



Manual Setup Steps

Step 1: Player Setup

1. Create Player GameObject

- GameObject > Create Empty → name it Player
- **! IMPORTANT: Position: (0, 2, 0)** — Player must spawn ABOVE ground, not inside it!
- The CharacterController center is at (0, 1, 0), so total player center will be at Y=3

2. Add Components to Player

- Add Component > Character Controller
 - Height: 2
 - Radius: 0.5
 - Center: (0, 1, 0)
 - **Skin Width: 0.08** **! Critical for ground collision!**
 - **Step Offset: 0.3**
 - Slope Limit: 45
 - Min Move Distance: 0.001
 - Add Component > PlayerMovement
 - Add Component > PlayerShooting
 - Add Component > StressSystem
 - Add Component > SimpleCrosshair (for visible crosshair)

3. Setup Camera

- Drag Main Camera as child of Player

- Camera Position: `(0, 1.6, 0)` (eye level)
 - Camera Rotation: `(0, 0, 0)`
 - In `PlayerMovement`, assign the camera to `cameraTransform`
-

Step 2: Layer Configuration

1. **Create Layers** (Edit > Project Settings > Tags and Layers)
 - Layer 8: `NPC`
 - Layer 9: `Alien`
 - Layer 10: `Environment`
 2. **Configure PlayerShooting**
 - Set `hitLayers` to include: `NPC`, `Alien`, `Environment`
-

Step 3: Test Environment

1. **Create Ground**
 - `GameObject > 3D Object > Plane`
 - Scale: `(10, 1, 10)`
 - Add a material for visibility
 - Layer: `Environment`
 2. **Create Test NPC**
 - `GameObject > 3D Object > Capsule` → name it `TestNPC`
 - Add `NPCBehavior` script
 - Layer: `NPC`
 - Duplicate a few times and spread around
-

Step 4: GameManager Setup

1. **Create GameManager**
 - `GameObject > Create Empty` → name it `GameManager`
 - Add `GameManager` script
 - Assign player reference
-

Step 5: UI Setup (Stress Bar)

1. **Create Canvas**
 - `GameObject > UI > Canvas`
 - Render Mode: `Screen Space - Overlay`
2. **Create Stress Bar**
 - Under Canvas: `UI > Slider` → name it `StressBar`
 - Anchor: Top-left
 - Position: `(120, -30, 0)`
 - Width: `200`, Height: `20`
 - Uncheck `Interactable`

3. Style the Bar

- Background: Dark gray
- Fill: Red gradient (low=green, high=red)
- Delete Handle

4. Connect to StressSystem

- Select Player
- In `StressSystem` , assign the Slider to `stressSlider`

Testing Checklist

Movement Tests

- ☐ WASD moves player correctly
- ☐ Mouse look works (horizontal + vertical)
- ☐ Vertical look is clamped (-90° to 90°)
- ☐ Space bar makes player jump
- ☐ Gravity pulls player down
- ☐ Cursor is locked and hidden

Shooting Tests

- ☐ Left-click fires raycast
- ☐ Debug rays visible in Scene view (yellow=miss, red=hit)
- ☐ Console shows hit messages with target name
- ☐ Hitting NPC triggers damage (if IDamageable)

Stress System Tests

- ☐ Stress bar visible in UI
- ☐ `AddStress(float)` increases bar
- ☐ `ReduceStress(float)` decreases bar
- ☐ Stress clamped between 0-100
- ☐ Reaching 100 triggers `OnStressMaxed` event
- ☐ Passive recovery works when below threshold

NPC Tests

- ☐ NPCs patrol between waypoints
- ☐ NPCs are on correct layer
- ☐ NPCs can receive damage

GameManager Tests

- ☐ Game starts in `Playing` state
- ☐ Stress max triggers `Chaos` phase
- ☐ Win/Lose conditions trigger correctly

Common Issues

Player falls through floor / feels inside ground

- Ensure ground has a `Collider` component
- Check `CharacterController` height and center
- **⚠️ Set Player Y position to 2 or higher** — The `CharacterController` center is offset by (0, 1, 0), so if Player is at Y=0, the feet will be at Y=0 (inside ground)
- **CRITICAL: Set Skin Width to 0.08** — Default 0.01 is too small and causes clipping!
- **Set Step Offset to 0.3** — Must be less than Height/2
- If using the scene from the repo, select Player in hierarchy and set Transform Position Y = 2

Camera feels like TPS / orbits around player

- Camera must be a **child** of the Player GameObject
- Camera local position should be `(0, 1.6, 0)` — at eye level
- Camera local rotation must be `(0, 0, 0)` initially
- **Camera should NOT have any rotation scripts** — only `PlayerMovement` controls it
- In `PlayerMovement`, the camera only rotates on LOCAL X axis (pitch), never Y
- The player body rotates on Y axis (yaw) for horizontal mouse movement

No crosshair visible

- Add the `SimpleCrosshair` script to any GameObject (e.g., Player or MainCamera)
- The script draws a crosshair using OnGUI, no Canvas needed

Mouse look not working

- Verify `cameraTransform` is assigned in `PlayerMovement`
- Check if another script is controlling cursor

Shooting doesn't hit anything

- Verify `hitLayers` includes target layers
- Ensure targets have `Collider` components
- Check raycast range in `PlayerShooting`

Stress bar not updating

- Ensure `stressSlider` is assigned in `StressSystem`
- Check Slider min/max values (should be 0-1 for normalized)
- The updated `StressSystem.cs` auto-finds the slider by name "StressBar" if not assigned
- Check console for "[StressSystem] Initialized. Slider found: true/false"

NPCs don't move/patrol

- NPCs now have **Auto Patrol** enabled by default (no waypoints needed)
 - They patrol randomly within `patrolRadius` (default 5m) from start position
 - Check console for "[NPC] name state: Idle -> Walking" logs
 - Verify NPCs have `NPCBehavior` script attached
 - If adding waypoints manually, ensure waypoint Transforms are assigned in inspector
-

Play Test Procedure

1. **Enter Play Mode** (Ctrl+P)
2. **Test Movement:** Walk around, jump on objects
3. **Test Shooting:** Aim at NPCs, check console for hits
4. **Test Stress:** Call `player.GetComponent<StressSystem>().AddStress(20)` in console
5. **Test Stress Max:** Add stress until 100, verify chaos phase triggers

Script Dependencies

```

GameManager
├── StressSystem (listens to OnStressMaxed)

PlayerMovement
├── CharacterController (required)
├── Camera (child transform)

PlayerShooting
├── Camera.main
├── IDamageable targets

StressSystem
├── UI Slider (optional)

NPCBehavior
├── NavMeshAgent (optional, for advanced AI)
├── IDamageable interface

```

Phase 2: Alien Setup

Alien Player Setup

1. **Create Alien GameObject**
 - GameObject > 3D Object > Capsule → name it Alien
 - Position: (5, 2, 5) — away from astronaut spawn
 - Tag: Alien
 - Layer: Alien
2. **Add Components to Alien**
 - Add Component > AlienController (TPS movement + camera)
 - Add Component > HungerSystem (hunger mechanics)
 - Add Component > AlienEatSystem (eating NPCs/aliens)
3. **Camera Setup for Alien**
 - Create a NEW camera for the Alien (or disable Main Camera when testing alien)
 - Assign camera to AlienController > cameraTransform
 - The TPS camera follows behind automatically — NO need to parent it
4. **Configure AlienEatSystem**
 - Edible Tags : NPC , Alien

- `Player Tag` : `Player` (NEVER edible)
- `Detect Range` : 3
- `Detect Radius` : 1

Hunger Bar UI Setup

1. Create Hunger Slider

- Under Canvas: `UI > Slider` → name it `HungerBar`
- Anchor: Top-left
- Position: `(120, -60, 0)` — below stress bar
- Width: `200` , Height: `20`
- Uncheck `Interactable`

2. Style the Hunger Bar

- Background: Dark gray
- Fill: Green (full) → Red (empty) gradient
- Delete Handle

3. Auto-connection

- `HungerSystem` auto-finds `HungerBar` by name

Eat Prompt UI

- `EatPromptUI` auto-creates the prompt panel if not found
- Shows “Press E to EAT” when looking at valid target

Target Highlighting

- `TargetHighlight` auto-applies red emission glow to edible targets
- No manual setup needed — added dynamically

Important Tags Setup

1. Go to `Edit > Project Settings > Tags and Layers`
2. Add Tag: `NPC` (for edible civilians)
3. Add Tag: `Alien` (for other alien players)
4. Add Tag: `Player` (astronaut — NEVER edible)

Testing Alien Mechanics

- [] TPS camera follows behind alien
 - [] WASD moves alien relative to camera direction
 - [] Mouse rotates camera smoothly
 - [] Hunger bar visible and decreasing over time
 - [] Looking at NPC shows red highlight
 - [] “Press E to EAT” prompt appears
 - [] Pressing E destroys NPC and restores hunger
 - [] Blood decal spawns at eat location
 - [] CANNOT eat player (no highlight, no prompt)
-

Next Steps (Phase 3)

1. Multiplayer networking setup
 2. Voting system implementation
 3. Emergency meeting mechanics
 4. Map expansion and tasks
 5. Win/lose conditions refinement
-

Happy developing! 