


DATA STRUCTURE AND PROGRAMMING II

Pointer

Write program in C++ using pointer

Remark: Pointer is a variable that store address of another variable of the same data type.

Pointers in C++



Lecture overview

□ Overall lectures

1. Introduction to algorithm
2. Basic data types and statements
3. Control structures and Loop
4. Array
5. Data structure
6. Sub-programs

7. Recursive
8. File IO
- 9. Pointers*
10. Linked Lists
11. Stacks and Queues
12. Sorting algorithms
13. Trees



C++

Outline

- What is pointer?
- What are the advantages of using pointer?
- How to use pointer
- Examples

Introduction

❑ Computer Memory

- To understand pointers, you should have knowledge about address in computer memory

- A computer memory location has an address and holds a content (value)
- The address is a numerical number (expressed in hexadecimal)
- An integer value consumes 4 bytes of memory

Memory	
Address	Value
0045FFCBI89	abc
0276GGHBC00	abcd

Introduction


❑ Computer Memory

- Each variable we create in the program has a location in the computer's memory
- The value of the variable is stored in the assigned location
- To know where the data of normal variable is stored, we use operator **&**
 - **&** gives the address occupied by a variable

- Example:

- If *num* is a variable, then *&num* gives the address of that variable

Variable Name	num
Value of Variable	10
Address of Variable	1000





num = 10
&num = 1000

Introduction

❑ What is pointer?

- A pointer is a variable that holds the memory address of another variable of the same type.
- Pointers are used to access the memory address and values at that address.




An example of a pointer variable pointing to a normal variable

Pointer Vs. Normal variable

□ Remark

- A normal variable is used to store value, while *a pointer variable is used to store address (reference) of another variable*
- Pointers are representation of addresses
- We can have a pointer to any variable type



Advantages of using pointer?


□ Some main advantages

1. Use less memory
 - Dynamic memory allocation
2. Program runs faster
 - Increase execution speed and reduce execution time
3. Efficient when work with array, structure, list, stack, queue, ...
4. Provide another way to access array element
5. Instead of copying data, pointer just point to an existing data
6. A function can return more than one value by passing via function argument

Pointer Operator

□ What?

- Two operators when work with pointer
 - Address operator (**reference operator**)
 - It uses &
 - It returns memory address
 - Indirection operator (**deference operator or value operator**)
 - It uses *
 - It returns value



Pointer Declaration

□ Syntax

A pointer is a variable that must be defined by specifying the type of variable pointed, as follows

```
var *nameOfPointer : type
```

The type of variable pointed can be a primary type (such as integer, character ...) or a complex type (such as structured type ...)

```
structure students
    name: string
    age: integer
end structure
```

```
var *a: integer
    *c: character
    *s: string
    *stu: students
```

Pointer Initialization

□ Syntax

```
var *a: integer
```

```
  a ← NULL
```

```
var *c, d: character
```

```
  c ← &d
```

Access to Pointer Variable

□ Syntax

- After (and only after) having declared and initialized a pointer, it is possible to **access the contents of the memory address pointed by the pointer** by the operator **'*'**
- Syntax: ***nameOfPointer**

```
var *a, b: integer  
a ← &b  
b ← 10  
*a ← *a + b  
write(*a, b)
```

- a: pointer (stores an address)
- * a: pointer variable (as integer variable or in this case it is equivalent to variable **b**)

Example 1

❑ Not using pointer

- A function that exchanges the values of two variables (How does it work?)

```
function exchange(v1: integer, v2: integer)
begin
  var tmp: integer
    tmp ← v1
    v1 ← v2
    v2 ← tmp
end
```

```
main program
begin
  var a,b: integer
    a ← 1
    b ← 2
    exchange(a,b)
    write(a,b)
end
```

What are the values of **a** and **b** here?

a is 1, b is 2


Example 2:

□ Using pointer

- A function that exchanges the values of two variables (How does it work?)

```
function exchange(*v1: integer, *v2: integer)
begin
  var tmp: integer
    tmp ← *v1
    *v1 ← *v2
    *v2 ← tmp
end
```

```
main program
begin
  var a,b: integer
    a ← 1
    b ← 2
    exchange (&a, &b)
    write(a, b)
end
```




What are the values of **a** and **b** here?

a is 2, b is 1

Pointer and Array

- The name of an array represents the address of its first element **&array [0]**



- If `P` points to any element of an array, then `P + 1` points to the next element
- More generally:
 - $(P+i)$ points to the i^{th} element behind `P` and
 - $(P-i)$ point to the i^{th} element before `P`

Pointer and Array

□ Remark

- Suppose we have variables

- `Var arr[10]: integer`

- `Var *p:integer`

- Array name `arr` represents the address of the first elements of this array (`&arr[0]`)

- We can say

- `p = arr;` `// p` point to the first element (`arr[0]`) in the array

- When a pointer points to an array, the value of the pointer is the first array element

- `write(*p)`

NOTE

❑ Reference (&) Vs. Deference (*) operator

- &: to get address of any variable
- *: to get value at the address that the point stores

Example:

- If an integer variable, say n, is stored in memory address 0xf1bd23, and n contains a value of 5.

Then:

Reference operator **&n** gives the value of 0xf1bd23
Deference operator ***n** gives the value of 5

Q&A

Example 1: Using C++

- Suppose we have program as follows

```
#include<iostream>
using namespace std;
int main(){
    int num=10;
    int *ptr;
    ptr = &num;

    cout<<"num="<<num<<endl;
    cout<<"Address of variable num is: "<<&num<<endl;
    cout<<"Value in variable pointer ptr is: "<<ptr<<endl;
    cout<<"*ptr="<<*ptr<<endl;    //Value in that address
}
```

Example 2: Using C++

```
#include<iostream>
using namespace std;
int main(){
    int *pc, c;
    c=5;

    cout<<"Address of c: "<<&c<<endl;
    cout<<"Value of c: "<<c<<endl;
    pc = &c;
    cout<<"Address that pc holds: "<<pc<<endl;
    cout<<"Value of address that pc holds: "<<*pc<<endl;
    c = 11;
    cout<<"Address that pc holds: "<<pc<<endl;
    cout<<"Value of address that pc holds: "<<*pc<<endl;
    *pc = 2;
    cout<<"Address of c: "<<&c<<endl;
    cout<<"Value of c: "<<c<<endl;
}
```



Output

```
{ Address of c: 0x6dfef8
  Value of c: 5
{ Address that pc holds: 0x6dfef8
  Value of address that pc holds: 5
{ Address that pc holds: 0x6dfef8
  Value of address that pc holds: 11
{ Address of c: 0x6dfef8
  Value of c: 2
```

Pointer Examples

Write program in C++ using pointer

Remark: Pointer is a variable that store address of another variable of the same data type.

```
1  #include<iostream>
2  using namespace std;
3
4  main() {
5      int num;
6      int n,p,q;
7
8      num = 20;
9      n = 1;
10     p = 2;
11     q = 3;
12
13     cout<<&num<<endl;
14     cout<<&n<<endl;
15     cout<<&p<<endl;
16     cout<<&q<<endl;
17 }
```

```
1  #include<iostream>
2  using namespace std;
3
4  main() {
5      int a[5];
6      a[0] = 2;
7      a[1] = 8;
8      int *p1;
9
10     p1 = &a[0];
11
12     cout<<&a[0]<<endl;
13     cout<<&a[1]<<endl;
14
15     cout<<p1<<endl;
16 }
```

```
1  #include<iostream>
2  using namespace std;
3
4  main() {
5      int *a;
6      int b=10;
7
8      a = &b;
9
10     cout<<b<<endl;
11     *a = 15**a;
12     cout<<b<<endl;
13 }
```

Q&A