

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : Bronze Alloys

Other means of identification : RBCuZn-A, RBCuZn-B, RBCuZn-C, RBCuZn-D, ERCuSi-A, ERCu, ERCuSn-A, ERCuSn-C, ERCuAl-A1, ERCuAl-A2, ERCuAl-A3, ERCuNiAl, ERCuMnNiAl, ECuSn-C, ECu, ECuAl-A2, ECuSi, BCuP-2, BCuP-3, BCuP-4, BCuP-5, ECuP-6

AWS Specifications : A5.6, A5.7, A5.8

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : For welding consumables and related products

1.3. Details of the supplier of the safety data sheet

Oxford Alloys, Inc.
2632 Tee Dr.
Baton Rouge, LA 70814
technical@oxfordalloys.com

1.4. Emergency telephone number

Emergency number : 225-273-4800

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Skin Sens. 1 H317
Carc. 1B H350
STOT RE 1 H372
Aquatic Acute 1 H400
Aquatic Chronic 2 H411

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) : Danger

Hazard statements (GHS-US) :

- H317 - May cause an allergic skin reaction
- H350 - May cause cancer
- H372 - Causes damage to organs through prolonged or repeated exposure
- H400 - Very toxic to aquatic life
- H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (GHS-US) :

- P201 - Obtain special instructions before use
- P202 - Do not handle until all safety precautions have been read and understood
- P260 - Do not breathe dust/fume/gas/mist/vapors/spray
- P261 - Avoid breathing dust/fume/gas/mist/vapors/spray
- P264 - Wash thoroughly after handling
- P270 - Do not eat, drink or smoke when using this product
- P272 - Contaminated work clothing should not be allowed out of the workplace
- P273 - Avoid release to the environment
- P280 - Wear protective gloves/protective clothing/eye protection/face protection
- P302+P352 - IF ON SKIN: Wash with plenty of soap and water
- P308+P313 - IF exposed or concerned: Get medical advice/attention
- P314 - Get medical advice and attention if you feel unwell
- P333+P313 - If skin irritation or rash occurs: Get medical advice/attention
- P362+P364 - Take off contaminated clothing and wash it before reuse
- P391 - Collect spillage
- P405 - Store locked up
- P501 - Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

Full text of H-phrases: see section 16

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Copper (Cu)	(CAS No) 7440-50-8	69.73 - 95.7	Not classified
Silver (Ag)	(CAS No) 7440-22-4	<= 15.5	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Manganese (Mn)	(CAS No) 7439-96-5	<= 14	Not classified
Aluminum (Al)	(CAS No) 7429-90-5	0.01 - 11.5	Not classified
Tin (Sn)	(CAS No) 7440-31-5	<= 9	Not classified
Iron (Fe)	(CAS No) 7439-89-6	<= 6	Acute Tox. 4 (Oral), H302
Nickel (Ni)	(CAS No) 7440-02-0	<= 6	Skin Sens. 1, H317 Carc. 1B, H350 STOT RE 1, H372
Silicon (Si)	(CAS No) 7440-21-3	<= 4	Not classified
Lead (Pb)	(CAS No) 7439-92-1	<= 0.02	Carc. 1B, H350

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
- First-aid measures after skin contact : Flush with water for at least 15 minutes. Seek medical attention if irritation develops or persists.
- First-aid measures after eye contact : Immediately flush eyes with water and continue washing for at least 15 minutes. Obtain medical attention if discomfort persists.
- First-aid measures after ingestion : Do NOT induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : Short-term (acute) overexposure to the gases, fumes, and dusts may include irritation of the eyes, lungs, nose, and throat. Some toxic gases associated with welding may cause pulmonary edema, asphyxiation, and death.
Acute overexposure may include signs and symptoms such as watery eyes, nose and throat irritation, headache, dizziness, difficulty in breathing, frequent coughing, or chest pain. The presence of chromium/chromate in fume can cause irritation of nasal membranes and skin. The presence of nickel compounds in fume can cause metallic taste, nausea, tightness of chest, fever, and allergic reaction. Excessive inhalation or ingestion of manganese can produce manganese poisoning. Overexposure to manganese compounds may affect the central nervous system, symptoms of which are languor, sleepiness, muscular weakness, emotional disturbances, and spastic gait resembling Parkinsonism. These symptoms can become progressive and permanent if not treated. Excessive inhalation of fumes may cause "Metal Fume Fever" with flu-like symptoms such as chills, fever, body aches, vomiting, sweating, etc.
- Symptoms/injuries after skin contact : Dusts may cause irritation.
- Symptoms/injuries after eye contact : Causes eye irritation.
- Symptoms/injuries after ingestion : Not an anticipated route of exposure during normal product handling. May be harmful if ingested.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.
- Unsuitable extinguishing media : None.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Not flammable.
Explosion hazard : None known.

5.3. Advice for firefighters

Protection during firefighting : Firefighters should wear full protective gear.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : No special measures required.
Methods for cleaning up : Attempt to reclaim the product, if this is possible.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid generating dust and inhaling fumes.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : No special storage necessary.

7.3. Specific end use(s)

For welding consumables and related products

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Aluminum (7429-90-5)		
USA ACGIH	ACGIH TWA (mg/m ³)	1 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³
Nickel (7440-02-0)		
USA ACGIH	ACGIH TWA (mg/m ³)	1.5 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	1 mg/m ³
Silver (7440-22-4)		
USA ACGIH	ACGIH TWA (mg/m ³)	0.1 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	0.01 mg/m ³
Tin (7440-31-5)		
USA ACGIH	ACGIH TWA (mg/m ³)	2 mg/m ³
Lead (7439-92-1)		
USA ACGIH	ACGIH TWA (mg/m ³)	0.05 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	50 µg/m ³
Copper (7440-50-8)		
USA ACGIH	ACGIH TWA (mg/m ³)	0.2 mg/m ³

Copper (7440-50-8)		
USA OSHA	OSHA PEL (TWA) (mg/m ³)	1 mg/m ³
Manganese (7439-96-5)		
USA ACGIH	ACGIH TWA (mg/m ³)	0.1 mg/m ³
USA OSHA	OSHA PEL (Ceiling) (mg/m ³)	5 mg/m ³
Silicon (7440-21-3)		
USA OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³

8.2. Exposure controls

Appropriate engineering controls	: Local exhaust and general ventilation must be adequate to meet exposure standards.
Hand protection	: Wear welding gloves.
Eye protection	: Wear helmet or face shield with filter lens of appropriate shade number. See ANSI/ASC Z49.1 Section 4.2. Provide protective screens and flash goggles, if necessary, to shield others.
Skin and body protection	: Wear head and body protection, which help to prevent injury from radiation, sparks, flame and electrical shock. See ANSI Z49.1. At a minimum this includes welder's gloves and a protective face shield, and may include arm protectors, aprons, hats, shoulder protection, as well as dark substantial clothing. Train the employee not to touch live electrical parts and to insulate him/herself from work and ground. Welders should not wear short sleeve shirts or short pants.
Respiratory protection	: If exposure limits are exceeded or irritation is experienced, NIOSH approved respiratory protection should be worn.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Rods or wire
Color	: Silver or yellow to red. Flux coating is white or blue-green
Odor	: No data available
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Self ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

Will not occur.

10.4. Conditions to avoid

None.

10.5. Incompatible materials

None.

10.6. Hazardous decomposition products

Welding fumes and gases cannot be classified simply. The composition and quantity of both are dependent upon the metal being welded, the process, procedure and welding consumables used. Other conditions which also influence the composition and quantity of the fumes and gases to which workers may be exposed include: coating on the metal being welded (i.e. paint, painting, galvanizing), the number of welders, the volume of the work area, the quality and the amount of ventilation, the position of the welders head with respect to the fume plume, as well as the presence of contaminants in the atmosphere (such as chlorinated hydrocarbon vapors from the cleaning and degreasing activities).

When an electrode is consumed, the fume and gas decomposition products generated are different in percent and form from the ingredients listed in Section 3. Fume and gas decomposition, and not the ingredients in the electrode, are important. The concentration of a given fume or gas component may decrease or increase by many times the original concentration. Also, new compounds not in the electrodes may form. Decomposition products of normal operation include those originating from the volatilization, reaction or oxidation of the materials shown in Section 3, plus those from the base metal coating, etc., as noted above. Reasonable expected fume constituents of this product would include: Complex oxides of iron, manganese, silicon, nickel, copper, carbon dioxide, and some products will also contain aluminum, magnesium, and or zirconium. Fume limit for nickel or manganese may be reached before limit of 5 mg/m3 of general welding fumes is reached.

Gaseous reaction products may include carbon monoxide and carbon dioxide. Ozone and nitrogen oxides may be formed by the radiation from the arc. Determine the composition and quantity of fumes and gases to which workers are exposed by taking an air sample from inside the welder's helmet if worn or in the worker's breathing zone. Improve ventilation if exposures are not below limits. See ANSI/AWS F1.1, F1.3 and F1.5, available from the American Welding Society, 550 N.W. LeJeune Road, Miami, FL 33126.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Iron (7439-89-6)	
LD50 oral rat	984 mg/kg
ATE (oral)	984.000 mg/kg
Nickel (7440-02-0)	
LD50 oral rat	> 9000 mg/kg
Silver (7440-22-4)	
LD50 oral rat	> 2000 mg/kg
Tin (7440-31-5)	
LD50 oral rat	700 mg/kg
Manganese (7439-96-5)	
ATE (oral)	9000000.000 mg/kg
Silicon (7440-21-3)	
ATE (oral)	3160.000 mg/kg

Skin corrosion/irritation : Not classified
 Serious eye damage/irritation : Not classified
 Respiratory or skin sensitisation : May cause an allergic skin reaction.
 Germ cell mutagenicity : Not classified
 Carcinogenicity : May cause cancer.

Nickel (7440-02-0)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	3 - Reasonably anticipated to be Human Carcinogen

Lead (7439-92-1)	
IARC group	2A - Probably carcinogenic to humans
National Toxicology Program (NTP) Status	3 - Reasonably anticipated to be Human Carcinogen

Reproductive toxicity : Not classified
 Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Nickel (7440-02-0)	
LC50 fishes 1	> 100 mg/l (Exposure time: 96 h - Species: Brachydanio rerio)
EC50 Daphnia 1	> 100 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 other aquatic organisms 1	0.18 mg/l (Exposure time: 72 h - Species: Pseudokirchneriella subcapitata)
LC50 fish 2	1.3 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [semi-static])
EC50 Daphnia 2	1 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 other aquatic organisms 2	0.174 - 0.311 mg/l (Exposure time: 96 h - Species: Pseudokirchneriella subcapitata [static])

Silver (7440-22-4)	
LC50 fishes 1	0.00155 - 0.00293 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	0.00024 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC50 fish 2	0.0062 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])

Lead (7439-92-1)	
LC50 fishes 1	0.44 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [semi-static])
EC50 Daphnia 1	600 µg/l (Exposure time: 48 h - Species: water flea)
LC50 fish 2	1.17 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])

Copper (7440-50-8)	
LC50 fishes 1	0.0068 - 0.0156 mg/l (Exposure time: 96 h - Species: Pimephales promelas)
EC50 Daphnia 1	0.03 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 other aquatic organisms 1	0.0426 - 0.0535 mg/l (Exposure time: 72 h - Species: Pseudokirchneriella subcapitata [static])
LC50 fish 2	< 0.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 other aquatic organisms 2	0.031 - 0.054 mg/l (Exposure time: 96 h - Species: Pseudokirchneriella subcapitata [static])

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose of contents/container in accordance with local/regional/national/international regulations.

SECTION 14: Transport information

In accordance with DOT / ADR / RID / ADNR / IMDG / ICAO / IATA

14.1. UN number

Not a dangerous good in sense of transport regulations

14.2. UN proper shipping name

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

Aluminum (7429-90-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on SARA Section 313 (Specific toxic chemical listings)

SARA Section 313 - Emission Reporting	1.0 % (dust or fume only)
---------------------------------------	---------------------------

Iron (7439-89-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Nickel (7440-02-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on SARA Section 313 (Specific toxic chemical listings)

SARA Section 313 - Emission Reporting	0.1 %
---------------------------------------	-------

Silver (7440-22-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on SARA Section 313 (Specific toxic chemical listings)

SARA Section 313 - Emission Reporting	1.0 %
---------------------------------------	-------

Tin (7440-31-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Lead (7439-92-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on SARA Section 313 (Specific toxic chemical listings)

SARA Section 313 - Emission Reporting	0.1 %
---------------------------------------	-------

Copper (7440-50-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on SARA Section 313 (Specific toxic chemical listings)

SARA Section 313 - Emission Reporting	1.0 %
---------------------------------------	-------

Manganese (7439-96-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on SARA Section 313 (Specific toxic chemical listings)

SARA Section 313 - Emission Reporting	1.0 %
---------------------------------------	-------

Silicon (7440-21-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. US State regulations

Nickel (7440-02-0)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes				

Lead (7439-92-1)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)

Lead (7439-92-1)				
Yes	Yes	Yes	Yes	

Aluminum (7429-90-5)
U.S. - Massachusetts - Right To Know List U.S. - Minnesota - Hazardous Substance List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

Nickel (7440-02-0)
U.S. - Massachusetts - Right To Know List U.S. - Minnesota - Hazardous Substance List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

Silver (7440-22-4)
U.S. - Massachusetts - Right To Know List U.S. - Minnesota - Hazardous Substance List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

Tin (7440-31-5)
U.S. - Massachusetts - Right To Know List U.S. - Minnesota - Hazardous Substance List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

Lead (7439-92-1)
U.S. - Massachusetts - Right To Know List U.S. - Minnesota - Hazardous Substance List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

Copper (7440-50-8)
U.S. - Massachusetts - Right To Know List U.S. - Minnesota - Hazardous Substance List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

Manganese (7439-96-5)
U.S. - Massachusetts - Right To Know List U.S. - Minnesota - Hazardous Substance List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

Silicon (7440-21-3)
U.S. - Massachusetts - Right To Know List U.S. - Minnesota - Hazardous Substance List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Other information

: We believe that the information contained herein is current as of the date of this SDS. As the condition or methods of use are beyond Oxford Alloys, Inc. control, Oxford Alloys, Inc. does not assume any responsibility and expressly disclaim any liability for any use of this material. Information contained herein is believed to be true and accurate but all statements or suggestions are made without any warranty, expressed or implied, regarding the accuracy of the information, the hazard connected with the use of this material or the results to be obtained for use thereof. It is the user's obligation to determine the conditions of safe use of these products.

Full text of H-phrases:

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — AcuteHazard, Category 1


Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Carc. 1B	Carcinogenicity, Category 1B
Skin Sens. 1	Sensitisation — Skin, category 1
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1
H302	Harmful if swallowed
H317	May cause an allergic skin reaction
H350	May cause cancer
H372	Causes damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects

NFPA health hazard

NFPA fire hazard

NFPA reactivity

- : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.
- : 0 - Materials that will not burn.
- : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health

Flammability

Physical

- : 2 Moderate Hazard - Temporary or minor injury may occur
- : 0 Minimal Hazard
- : 0 Minimal Hazard