

SAFETY DATA SHEET

SECTION 1: IDENTIFICATION

Product identifier used on the label:

Product Name: Coated Abrasive

 $\underline{\hbox{Other means of identification:}}$

 $\underline{\textit{Recommended use of the chemical and restrictions on use:}}\\$

 $\underline{\hbox{Chemical manufacturer address and telephone number:}}$

Manufacturer Name: Saint-Gobain Abrasives, Inc.

Address: 1 New Bond Street Worcester, MA 01615

www.Nortonabrasives.com

508-795-5000 General Phone Number:

Emergency phone number:

Website:

Emergency Phone Number: 508-795-5000

SECTION 2: HAZARD(S) IDENTIFICATION

Classification of the chemical in accordance with CFR 1910.1200(d)(f):

 $\underline{\textbf{Hazards not otherwise classified that have been identified during the classification process:}$

Potential Health Effects:

Eve: Dust may cause slight irritation.

Skin: Dust from this product may cause temporary mechanical irritation.

Inhalation: $Dusts \ from \ this \ product \ may \ cause \ mechanical \ irritation \ of \ the \ nose, \ throat \ and \ respiratory \ tract.$

Ingestion: Ingestion of this product is unlikely. However, ingestion of product may produce gastrointestinal irritation and disturbances.

Chronic Health Effects: Chronic health effects are not expected as long as good hygiene and proper safety precautions are

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures:

Inhalation:

Chemical Name	CAS#	Ingredient Percent	EC Num.
Aluminum Oxide, Non-fibrous	1344-28-1	60 - 100 by weight	215-691-6
Paper - Processed Cellulose	9004-34-6	1 - 5 by weight	232-674-9

SECTION 4: FIRST AID MEASURES

Description of necessary measures:

Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers.

Get medical attention, if irritation or symptoms of overexposure persists. Eye Contact:

Immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists. Skin Contact:

If dust from cutting or drilling is inhaled, remove the affected person to fresh air. If symptoms persist,

get medical attention.

Accidental ingestion of this material is unlikely. If this does occur, watch person for several days to make sure intestinal blockage does not occur. If symptoms persist, call a physician. Ingestion:

Coated Abrasive Revision: 07/01/2013 Note to Physicians: No information available.

SECTION 5: FIRE FIGHTING MEASURES

Suitable and unsuitable extinguishing media:

Suitable Extinguishing Media: Use any extinguishing media appropriate for the surrounding fires.

Unsuitable extinguishing media:

Special protective equipment and precautions for fire-fighters:

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Protective Equipment:

NFPA Ratings:

NFPA Health: NFPA Flammability: 0 NFPA Reactivity: NFPA Other:



SECTION 6: ACCIDENTAL RELEASE MEASURES

Methods and materials for containment and cleaning up:

Containment of this material should not be necessary. Methods for containment:

Methods for cleanup:

Shovel or sweep up for re-use or disposal. Avoid creating dusty conditions. Evaluate residue to determine if it is a hazardous waste by characteristic. Dispose of in accordance with Local, State, Federal and Provincial regulations.

SECTION 7: HANDLING and STORAGE

Precautions for safe handling:

Handling: Handle with adequate ventilation for nuisance dust. Hygiene Practices: Wear suitable gloves and eye/face protection.

 $\underline{\text{Conditions for safe storage, including any incompatibilities:}}\\$

Storage: No special storage conditions required.

SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION

EXPOSURE GUIDELINES:

Ingredient	Guideline OSHA	Guideline NIOSH	Guideline ACGIH	Quebec Canada	Ontario Canada
Aluminum Oxide, Non- fibrous	PEL-TWA: 5 mg/m3 Respirable fraction (R) PEL-TWA: 15 mg/m3 Total particulate/dust (T)		TLV-TWA: 10 mg/m3	VEMP-TWA: 10 mg/m3 Total particulate/dust (T)	OEL-TWAEV: 10 mg/m3 Total particulate/dust (T)
Paper - Processed Cellulose	PEL-TWA: 15 mg/m3 Total particulate/dust (T) PEL-TWA: 5 mg/m3 Respirable fraction (R)	REL-TWA: 10 mg/m3 Total particulate/dust (T) REL-TWA: 5 mg/m3 Respirable fraction (R)	TLV-TWA: 10 mg/m3	VEMP-TWA: 10 ppm Total particulate/dust (T)	OEL-TWAEV: 10 mg/m3 Total particulate/dust (T)
Ingredient	Alberta Canada	Mexico	British Columbia Canada		
Aluminum Oxide, Non- fibrous	OEL-TWA: 10 mg/m3	MPE-PPT: 0.1 mg/m3 Respirable fraction (R)	OEL-TWA: 3 mg/m3 Respirable fraction (R) OEL-TWA: 10 mg/m3 OEL-TWA: 10 mg/m3 Total particulate/dust (T) OEL-STEL: 20 mg/m3 Total particulate/dust (T)		
Paper - Processed Cellulose	OEL-TWA: 10 mg/m3	LMPE-PPT: 10 mg/m3 LMPE-CT: 20 mg/m3	OEL-TWA: 3 mg/m3 Respirable fraction (R) OEL-TWA: 10 mg/m3 Total particulate/dust (T)		

Appropriate engineering controls:

General dilution ventilation and/or local exhaust ventilation should be provided as necessary to Engineering Controls:

maintain exposures below occupational exposure limits.

 $\underline{Individual\ protection\ measures:}$

Eye/Face Protection: Always WEAR SAFETY GLASSES or some type of eye protection when grinding.

Skin Protection Description: Protective gloves.

> Coated Abrasive Revision: 07/01/2013

UPC Number: 66261086318 1047337_CA_AI

Long sleeved shirt and long pants.

When workers are facing airborne particulate/dust concentrations above the exposure limit they must use appropriate certified respirators. Respiratory Protection:

A properly fitted NIOSH approved disposable N 95 type dust respirator or better is recommended.

Use of this product may create elevated sound levels. Hearing protection should be worn where required (see OSHA 29 CFR 1910.134 and other applicable regulations). Other Protective:

General Hygiene Considerations: Handle in accordance with good industrial hygiene and safety practice.

Remove and wash contaminated clothing before re-use. Avoid getting dust into boots and gloves through wrist bands and pant tucks.

SECTION 9: PHYSICAL and CHEMICAL PROPERTIES

PHYSICAL AND CHEMICAL PROPERTIES:

Physical State Appearance: Solid article. Odor: Odorless. Flash Point: Does not apply. Not available.

Lower Flammable/Explosive Limit: Upper Flammable/Explosive Limit: Not available. Auto Ignition Temperature: Not determined

SECTION 10: STABILITY and REACTIVITY

Chemical Stability:

Chemical Stability: Stable under normal conditions.

Possibility of hazardous reactions:

Hazardous Polymerization: Hazardous polymerization does not occur.

Conditions To Avoid:

Conditions to Avoid: Keep away from heat, sparks, or open flame.

Hazardous Decomposition Products:

In use, dust and decomposing odors may be generated. In most cases, the material removed from the workplace will be significantly greater than the sandpaper components. Special Decomposition Products:

Coolants may produce other decomposition products.
Thermal decomposition may produce trace amounts of ammonia and formaldehyde.

SECTION 11: TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION:

Acute Toxicity: This product has not been tested for its toxicity.

Aluminum Oxide, Non-fibrous:

RTECS Number: BD1200000

Inhalation - Rat TCLo: 200 mg/m3/5H/28W (Intermittent) [Lungs, Thorax, or Respiration - Structural or functional change in trachea or bronchi; Lungs, Thorax, or Respiration - Chronic pulmonary edema; Inhalation:

Related to Chronic Data - death] (RTECS)

Paper - Processed Cellulose:

RTECS Number: F15691460

Inhalation: Inhalation - Rat LC50: >5800 mg/m3/4H [Details of toxic effects not reported other than lethal dose

value] (RTECS)

Ingestion: Oral - Rat LD50: >5 gm/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity:

Ecotoxicity: No ecotoxicity data was found for the product

SECTION 13: DISPOSAL CONSIDERATIONS

<u>Description of waste:</u>

Waste Disposal: Use standard landfill methods consistent with applicable Federal, State, Provincial and local laws.

SECTION 14: TRANSPORT INFORMATION

DOT Shipping Name: Not regulated as hazardous material for transportation.

DOT UN Number: Not regulated as hazardous material for transportation.

IATA Shipping Name: Not regulated as hazardous material for transportation.

Canadian Shipping Name: This product is Not Regulated under the Transportation of Dangerous Goods Act. (CAN).

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations specific for the product:

Inventory Status

	EINECS Number	Canada DSL	TSCA Inventory	
			Status	
Aluminum Oxide, Non-fibrous		Listed	Listed	
Paper - Processed Cellulose	232-674-9	Listed	Listed	

Aluminum Oxide, Non-fibrous:

Canada IDL: Identified under the Canadian Hazardous Products Act Ingredient Disclosure List: 0.1%.50(1298)

<u>Aluminum Oxide, Non-fibrous</u>:

EC Number: 215-691-6

<u>Paper - Processed Cellulose</u>:

EC Number: 232-674-9

State Right To Know

	PA	MA	NJ	
Aluminum Oxide, Non-fibrous	Listed	Listed	Listed: NJ Hazardous List; Substance Number: 2891	
Paper - Processed Cellulose	Listed	Listed		

SECTION 16: ADDITIONAL INFORMATION

HMIS Ratings:

HMIS Health Hazard: 1
HMIS Fire Hazard: 0
HMIS Reactivity: 0
HMIS Personal Protection: X

Health Hazard	1
Fire Hazard	0
Reactivity	0
Personal Protection	х

SDS Creation Date: August 15, 2009
SDS Revision Date: July 01, 2013