

Sundries Shelf Shelves -14-3/4" [375] REF MasterFormat Section 10 28 13 12-13/16" [325] 4-1/2" [114] Scan for Information Sustainability/LEED MR 4.1 (1) MR 6 (1) EQ 4.2 (1) ALL DIM'S INCH [MM]

PRODUCT OVERVIEW

MR 4.2 (1) EQ 4.1 (1) EQ 4.4 (1)

Shelf has open spaces between wires to allow excess water to drain away from items loaded and promote drying. Properly installed basket will support up to 11 lbs [5 kg] of bath products. Support side posts are 3/4" Dia [Ø19] tubular bar with polished cast mounting flanges bolted on. Finish on all visible stainless steel surfaces is satin.

ILLUSTRATION FOR REF ONLY AND NTS

FOR CLEANING INSTRUCTIONS SEE APPROPRIATE SECTIONS IN PRODUCT CARE & MAINTENANCE BULLETIN (PCM) ON ASI WEBSITE

KEY FEATURES & SPECIFICATIONS

- Type 304 Stainless Steel Satin Finish
- Surface Mounted

American Specialties, Inc. | 441 Saw Mill River Road, Yonkers, NY 10701 | (914) 476-9000 | www.americanspecialties.com

Model:#7381 Revision: R2 Issued: 11/1/2021 Revised: 12/6/2024



OPERATION & MAINTENANCE

Shelf has open spaces between wires to allow excess water to drain away from items loaded and promote drying. Properly installed basket will support up to 11 lbs [5 kg] of bath products.

TECHNICAL INFORMATION / PRODUCT PROPERTIES

Property	Value
Dimensions	12-3/4" W x 4-17/32" H x 4-1/2" D [375 x 115 x 114]
Construction	Type 304 Stainless Steel - Satin Finish
Mounting	Surface Mounted

INSTALLATION

Surface mount unit on wall using four (4) #6 x 1-3/8" [M4x35] self-threading screws (supplied) through holes provided in mounting plates into anchors (supplied) in suitably prepared walls (by others) or other suitable mounting hardware (by others) to suit wall conditions. Waterproof screw penetrations through tiles in wet area installations. Hang shelf post and flange assemblies on mounting plates and tighten setscrews to lock unit to plates with hex key provided. For compliance with 2010 ADA Accessibility Standards install unit with top of shelf 48" [1219] maximum Above Finished Floor (AFF) if clear floor reach access is provided. For general utility mount unit with top rim of shelf 55" [1397] to 65" [1651] above shower floor.

SCHEDULE OF AVAILABILITY

No Options Available

WARRANTY

One (1) Year from date of Invoice

American Specialties, Inc. | 441 Saw Mill River Road, Yonkers, NY 10701 | (914) 476-9000 | www.americanspecialties.com

Model: #7381 Revision: R2 Issued: 11/1/2021 Revised: 12/6/2024