

### MATERIAL SAFETY DATA SHEET

# Novablend 7650 KRL03-KHAKI 3626

Version Number 1.2 Page 1 of 8
Revision Date 03/12/2014 Print Date 3/19/2014

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION

33587 Walker Road, Avon Lake, OH 44012

Telephone : 1 (440) 930-1000 or 1 (866) POLYONE

Emergency telephone : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure

number or accident).

Product name : Novablend 7650 KRL03-KHAKI 3626

Product code : VC10003775 Chemical Name : Mixture CAS-No. : Mixture

Product Use : Industrial Applications

# 2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
8-Oxa-3,5-dithia-4-stannatetradecanoic acid, 10-ethyl-4,4-dimethyl-7-oxo-, 2-ethylhexyl	57583-35-4	1 - 5
ester		
Stannane, methyltris(2-	57583-34-3	1 - 5
ethylhexyloxycarbonylmethylthio)-		
Rutile, antimony chromium buff	68186-90-3	1 - 5
Titanium dioxide	13463-67-7	5 - 10

### 3. HAZARDS IDENTIFICATION

### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating or processing. The end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.

#### POTENTIAL HEALTH EFFECTS

Routes of Exposure: : Inhalation, Ingestion, Skin contact

Acute exposure

Inhalation : Resin particles, like other inert materials, can be mechanically

irritating.

Ingestion : May be harmful if swallowed.



# MATERIAL SAFETY DATA SHEET

# Novablend 7650 KRL03-KHAKI 3626

Version Number 1.2 Page 2 of 8 Revision Date 03/12/2014 Print Date 3/19/2014

> Eyes : Resin particles, like other inert materials, are mechanically irritating to

Skin : Experience shows no unusual dermatitis hazard from routine handling.

: Refer to Section 11 for Toxicological Information. Chronic exposure

**Medical Conditions** 

Aggravated by Exposure:

: None known.

4. FIRST AID MEASURES

Inhalation Move to fresh air in case of accidental inhalation of fumes from

overheating or combustion. When symptoms persist or in all cases of

doubt seek medical advice.

Ingestion Do not induce vomiting without medical advice. When symptoms

persist or in all cases of doubt seek medical advice.

Rinse immediately with plenty of water, also under the eyelids, for at Eyes

least 15 minutes. If eye irritation persists, seek medical attention.

Skin Wash off with soap and plenty of water. If skin irritation persists

seek medical attention.

5. FIREFIGHTING MEASURES

Flash point not applicable

Flammable Limits

Upper explosion limit not applicable Lower explosion limit not applicable Auto-ignition temperature Not applicable

Suitable extinguishing media Carbon dioxide blanket, Water spray, Dry powder, Foam.

Special Fire Fighting

Procedures

Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne

Unusual Fire/Explosion

Hazards

contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under

fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are

all possible.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions Wear appropriate personal protection during cleanup, such as

impervious gloves, boots and coveralls.

Environmental precautions Should not be released into the environment. The product should not

be allowed to enter drains, water courses or the soil.



### MATERIAL SAFETY DATA SHEET

# Novablend 7650 KRL03-KHAKI 3626

Version Number 1.2 Page 3 of 8
Revision Date 03/12/2014 Print Date 3/19/2014

Methods for cleaning up : Clean up promptly by sweeping or vacuum. Package all material in

plastic, cardboard or metal containers for disposal.

7. HANDLING AND STORAGE

Handling : Take measures to prevent the build up of electrostatic charge. Heat

only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of

these materials.

Storage : Keep containers dry and tightly closed to avoid moisture absorption

and contamination. Keep in a dry, cool place.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection : No personal respiratory protective equipment normally required. If

dusty conditions occur wear appropriate respiratory protection.

Eye/Face Protection : Safety glasses with side-shields

Hand protection : Protective gloves

Skin and body protection : Long sleeved clothing

Additional Protective

Measures

Safety shoes

General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. This product may contain residual vinyl chloride monomer (VCM) (CAS number 75-01-4) below 8.5 ppm (0.00085%). It is unlikely, under normal working conditions with adequate ventilation, that the exposure limits will be exceeded for residual VCM. However, the user should take the necessary precautions (e.g. mechanical ventilation, local exhaust ventilation, air-monitoring, respiratory protection, etc.) to ensure airborne levels of any vapors including VCM or dusts that may be released during heating or processing are

below regulated levels.

Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide

appropriate exhaust ventilation at machinery.

Exposure limit(s)



# MATERIAL SAFETY DATA SHEET

# Novablend 7650 KRL03-KHAKI 3626

Version Number 1.2 Page 4 of 8
Revision Date 03/12/2014 Print Date 3/19/2014

Components	Value	Exposure time	Exposure type	List:
Rutile, antimony chromium buff	0.5 mg/m3	Recommended exposure limit (REL):	as Cr	NIOSH
	0.5 mg/m3	PEL:	as Cr	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	ACGIH
	0.5 mg/m3	Recommended exposure limit (REL):	as Sb	NIOSH
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	OSHA Z1A
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	MX OEL
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Form : solid Evapouration rate Not applicable Appearance : pellets, powder Specific Gravity Not determined Colour TAN Bulk density Not established Vapour pressure Odour : very faint not applicable Melting point/range : Not determined Vapour density not applicable Boiling Point: not applicable not applicable pН

Water solubility : insoluble

# 10. STABILITY AND REACTIVITY

Stability : The product is stable if stored and handled as prescribed.

Hazardous Polymerization : Will not occur.

Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thermal

decomposition, do not overheat.

Incompatible Materials : Incompatible with strong acids and oxidizing agents., Avoid contact

with acetal homopolymers and acetal copolymers during processing.

Hazardous decomposition

products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

Prolonged heating (approximately 30 minutes or more) above 392 °F

(200 °C) or short term heating at 482 °F (250 °C) may result in



### MATERIAL SAFETY DATA SHEET

# Novablend 7650 KRL03-KHAKI 3626

Version Number 1.2 Revision Date 03/12/2014 Page 5 of 8 Print Date 3/19/2014

product decomposition and evolution of carbon monoxide and hydrogen chloride.

#### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
57583-35-4	8-Oxa-3,5-dithia-4-	Irritant	Eyes, Skin.
	stannatetradecanoic acid,		
	10-ethyl-4,4-dimethyl-7-		
	oxo-, 2-ethylhexyl ester		
57583-34-3	Stannane, methyltris(2-	Irritant	Eyes, Skin.
	ethylhexyloxycarbonylmet		
	hylthio)-		
68186-90-3	Rutile, antimony	Irritant	Eyes, Skin, Respiratory
	chromium buff		system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

#### LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
57583-34-3	Stannane, methyltris(2-	Oral LD50	920 mg/kg	rat
	ethylhexyloxycarbonylmet			
	hylthio)-			

#### Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

### IARC Carcinogen Classifications:

- 1 The component is carcinogenic to humans.
- 2A The component is probably carcinogenic to humans.
- 2B The component is possibly carcinogenic to humans.

#### NTP Carcinogen Classifications:

- 1 The component is known to be a human carcinogen.
- 2 The component is reasonably anticipated to be a human carcinogen.

#### 12. ECOLOGICAL INFORMATION

Persistence and degradability : Not readily biodegradable.



# MATERIAL SAFETY DATA SHEET

# Novablend 7650 KRL03-KHAKI 3626

 Version Number 1.2
 Page 6 of 8

 Revision Date 03/12/2014
 Print Date 3/19/2014

Environmental Toxicity : Adverse ecological impact is not known or expected under normal

use.

Bioaccumulation Potential : no data available

Additional advice : not applicable

13. DISPOSAL CONSIDERATIONS

Product : Like most thermoplastic plastics the product can be recycled. Where

possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

upprocess reasons, some proximinal and result regulations.

Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal,

state/provincial and local regulations.

14. TRANSPORT INFORMATION

U.S. DOT Classification : Not regulated for transportation.

ICAO/IATA : Not regulated for transportation.

IMO/IMDG (maritime) : Not regulated for transportation.

15. REGULATORY INFORMATION

US Regulations:

Contaminated packaging

OSHA Status : Classified as hazardous based on components.

TSCA Status : All components of this product are listed on or exempt from the

TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

California Proposition : Not applicable

65

SARA Title III Section 302 Extremely Hazardous Substance



# MATERIAL SAFETY DATA SHEET

# Novablend 7650 KRL03-KHAKI 3626

 Version Number 1.2
 Page 7 of 8

 Revision Date 03/12/2014
 Print Date 3/19/2014

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

#### SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Chemical Name	CAS-No.	Weight percent
MANGANESE COMPOUNDSMANGANESE	68412-38-4	0.10 - 1.00
COMPOUNDS ANTIMONY COMPOUNDS		
CHROMIUM III COMPOUNDSCHROMIUM III	68186-90-3	1.00 - 5.00
COMPOUNDSANTIMONY		
COMPOUNDSCHROMIUM COMPOUNDS		
CHROMIUM III COMPOUNDSCHROMIUM	12737-27-8	0.10 - 1.00
COMPOUNDS		

# Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight	NPRI ID#
		percent	
Manganese antimony titanium brown rutile (C.I.	68412-38-4	0.10 - 1.00	
Pigment Yellow 164)			
		0.10 - 1.00	
Rutile, antimony chromium buff	68186-90-3	1.00 - 5.00	
Iron chromite brown spinel	12737-27-8	0.10 - 1.00	

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.	
68186-90-3	
57583-34-3	

DSL : All components of this product are on the Canadian Domestic

Substances List (DSL) or are exempt.

National Inventories:

Australia AICS : Not determined

China IECS : Not determined

Europe EINECS : Not determined

Japan ENCS : Not determined



# MATERIAL SAFETY DATA SHEET

# Novablend 7650 KRL03-KHAKI 3626

Version Number 1.2 Page 8 of 8 Revision Date 03/12/2014 Print Date 3/19/2014

Korea KECI : Not determined

Philippines PICCS : Not determined

#### 16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.