

OPQ YELLOW

Version Number 1.4 Revision Date 04/02/2024 Page 1 of 17 Print Date 04/05/2024

SAFETY DATA SHEET

OPQ YELLOW

Section 1. Identification

GHS product identifier : OPQ YELLOW

Chemical name: MixtureCAS number: MixtureOther means of identification: CC01054336Product type: liquid

Relevant identified uses of the substance or mixture and uses advised against

Product use : Industrial applications. Plastics.

Supplier's details : AVIENT CORPORATION

ColorMatrix Group Inc.

680 North Rocky River Drive, Berea, Ohio, 44017-1628, USA

+1 216 622 0100

Emergency telephone number

(with hours of operation)

CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or

accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard

Communication Standard (29 CFR 1910.1200).

Classification of the substance or

mixture

SKIN IRRITATION - Category 2

GHS label elements



OPQ YELLOW

Version Number 1.4 Revision Date 04/02/2024 Page 2 of 17 Print Date 04/05/2024

Hazard pictograms

 \bigcirc

Signal word : Warning

Hazard statements : Causes skin irritation.

Precautionary statements

Not applicable.

Prevention: Wear protective gloves. Wash thoroughly after handling.

Response: Take off contaminated clothing and wash it before reuse. IF ON

SKIN: Wash with plenty of water. If skin irritation occurs: Get

medical advice or attention.

Storage:Not applicable.Disposal:Not applicable.Supplemental label elements:None known.Hazards not otherwise classified:None known.

Not available.

Section 3. Composition/information on ingredients

Substance/mixture: MixtureChemical name: MixtureOther means of identification: CC01054336

CAS number/other identifiers

Ingredient name	%	CAS number
Titanium dioxide	>= 25 - <= 50	13463-67-7
Nickel antimony yellow rutile (C.I. Pigment Yellow 53)	>= 10 - <= 25	8007-18-9
Miscellaneous Compounds Distillates, petroleum, hydrotreated middle	>= 10 - <= 25	Not available.
Silica, amorphous	>= 1 - <= 3	7631-86-9

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.



OPQ YELLOW

Version Number 1.4 Revision Date 04/02/2024 Page 3 of 17 Print Date 04/05/2024

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact: Immediately flush eyes with plenty of water, occasionally lifting the

upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable

for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical

surveillance for 48 hours.

Skin contact : Flush contaminated skin with plenty of water. Remove contaminated

clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly

before reuse.

Ingestion: Wash out mouth with water. Remove dentures if any. If material has

been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact: No known significant effects or critical hazards.Inhalation: No known significant effects or critical hazards.

Skin contact : Causes skin irritation.

Ingestion : No known significant effects or critical hazards.

Over-exposure signs/symptoms



Page 4 of 17

OPQ YELLOW

Version Number 1.4 Print Date 04/05/2024 Revision Date 04/02/2024

Eye contact Adverse symptoms may include the following:

pain or irritation

watering

redness

Inhalation No specific data.

Skin contact Adverse symptoms may include the following:

> irritation redness

No specific data. **Ingestion**

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician In case of inhalation of decomposition products in a fire, symptoms

may be delayed. The exposed person may need to be kept under

medical surveillance for 48 hours.

Specific treatments No specific treatment.

Protection of first-aiders No action shall be taken involving any personal risk or without

suitable training. It may be dangerous to the person providing aid to

give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media In case of fire, use water spray (fog), foam, dry chemical or CO₂.

None known.

Specific hazards arising from the

chemical

In a fire or if heated, a pressure increase will occur and the container

may burst.

Hazardous thermal decomposition products Decomposition products may include the following materials:

carbon dioxide carbon monoxide nitrogen oxides sulfur oxides

halogenated compounds metal oxide/oxides

Special protective actions for firefighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any

personal risk or without suitable training.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece operated

in positive pressure mode.



OPQ YELLOW

Version Number 1.4 Revision Date 04/02/2024 Page 5 of 17 Print Date 04/05/2024

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without

suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is

inadequate. Put on appropriate personal protective equipment.

For emergency responders

: If specialized clothing is required to deal with the spillage, take

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

See also the information in "For non-emergency personnel".

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil,

waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil

or air).

Methods and materials for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Dilute with

water and mop up if water-soluble. Alternatively, or if waterinsoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal

contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Approach

release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency

contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures: Put on appropriate personal protective equipment (see Section 8). Do

not ingest. Avoid contact with eyes, skin and clothing. Avoid

breathing vapor or mist. Keep in the original container or an approved



OPQ YELLOW

Version Number 1.4 Revision Date 04/02/2024 Page 6 of 17 Print Date 04/05/2024

Advice on general occupational hygiene

alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Titanium dioxide	OSHA PEL 1989 (1989-03-01) TWA 10 mg/m3 Form: Total dust OSHA PEL (1993-06-30) TWA 15 mg/m3 Form: Total dust ACGIH TLV (2022-01-06) TWA 0.2 mg/m3 Form: respirable fraction, nanoscale particles TWA 2.5 mg/m3 Form: respirable fraction, finescale particles
Nickel antimony yellow rutile (C.I. Pigment Yellow 53)	OSHA PEL 1989 (1989-03-01) TWA 1 mg/m3 (as Ni) OSHA PEL (1993-06-30) TWA 1 mg/m3 (as Ni)
Miscellaneous Compounds Distillates, petroleum, hydrotreated middle	None.
Silica, amorphous	NIOSH REL (1994-06-01) TWA 6 mg/m3



OPQ YELLOW

Version Number 1.4
Revision Date 04/02/2024

Page 7 of 17 Print Date 04/05/2024

Appropriate engineering controls

Good general ventilation should be sufficient to control worker

exposure to airborne contaminants.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.



OPQ YELLOW

Version Number 1.4 Revision Date 04/02/2024

Page 8 of 17 Print Date 04/05/2024

Section 9. Physical and chemical properties

Appearance

Physical state liquid [liquid] Color YELLOW Odor Faint odor. **Odor threshold** Not available. Not available. pН **Melting point** Not available. **Boiling point** Not available. Flash point Not available. **Burning time** Not available. **Burning rate** Not available. **Evaporation rate** Not available. Flammability (solid, gas) Not available.

Lower and upper explosive Lower: Not available. (flammable) limits **Upper:** Not available.

Vapor pressure Not available. Vapor density Not available. **Relative density** Not available. **Solubility** Not available. Solubility in water insoluble in water.

Partition coefficient: n-

octanol/water

Not applicable.

Auto-ignition temperature Not available. **Decomposition temperature** Not available. Not available. **SADT**

Dynamic: Not available. Viscosity

Kinematic: Not available.

Aerosol product

Heat of combustion Not available.

Not available. **Ignition distance Enclosed space ignition - Time** Not available.

equivalent

Enclosed space ignition -Not available.

Deflagration density

Flame height Not available. Flame duration Not available.

Section 10. Stability and reactivity



OPQ YELLOW

Version Number 1.4 Page 9 of 17 Revision Date 04/02/2024 Print Date 04/05/2024

Reactivity: No specific test data related to reactivity available for this product or

its ingredients.

Chemical stability : Stable under recommended storage and handling conditions (see

Section 7).

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will

not occur.

Conditions to avoid : Keep away from extreme heat and oxidizing agents.

Incompatible materials : Keep away from strong acids.

Oxidizer.

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition

products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Titanium oxide (TiO2)				
	LC50 Inhalation	Rat - Male	6.82 Mg/l	4 h
	Dusts and mists		_	
	LD50 Dermal	Rabbit	> 5,000 mg/kg	-

Conclusion/Summary : Mixture.Not fully tested.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Silica	Eyes - Mild irritant	Rabbit	_	24 hrs	-

Conclusion/Summary

Skin: Mixture.Not fully tested.Eyes: Mixture.Not fully tested.Respiratory: Mixture.Not fully tested.

Sensitization

Conclusion/Summary

Skin: Mixture.Not fully tested.Respiratory: Mixture.Not fully tested.

Mutagenicity

Conclusion/Summary : Mixture.Not fully tested.



OPQ YELLOW

Version Number 1.4 Page 10 of 17 Revision Date 04/02/2024 Print Date 04/05/2024

Carcinogenicity

Conclusion/Summary : Mixture. Not fully tested.

Classification

Product/ingredient name	OSHA	IARC	NTP
Titanium oxide (TiO2)	-	2B	-
Nickel antimony titanium vellow rutile	-	1	Known to be a human carcinogen.
Silica	-	3	-

Reproductive toxicity

Conclusion/Summary : Mixture.Not fully tested.

Teratogenicity

Conclusion/Summary : Mixture.Not fully tested.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Name	Result
Miscellaneous Compounds Distillates, petroleum,	ASPIRATION HAZARD - Category 1
hydrotreated middle	

Information on the likely routes of :

Not available.

exposure

Potential acute health effects

Eye contact: No known significant effects or critical hazards.Inhalation: No known significant effects or critical hazards.

Skin contact : Causes skin irritation.

Ingestion: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following: pain or irritation,

watering, redness



OPQ YELLOW

Version Number 1.4 Revision Date 04/02/2024

Page 11 of 17 Print Date 04/05/2024

Inhalation : No specific data.

Skin contact: Adverse symptoms may include the following: irritation, redness

Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Potential chronic health effects

Conclusion/Summary : Mixture.Not fully tested.

GeneralNo known significant effects or critical hazards.CarcinogenicityNo known significant effects or critical hazards.MutagenicityNo known significant effects or critical hazards.TeratogenicityNo known significant effects or critical hazards.Developmental effectsNo known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards. No known significant

effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral	Dermal	Inhalation (gases)	Inhalation (vapors)	Inhalation (dusts and mists)
OPQ YELLOW	N/A	N/A	N/A	81.8 Mg/l	N/A
Titanium oxide (TiO2)	N/A	N/A	N/A	N/A	6.82 Mg/l
Miscellaneous Compounds Distillates, petroleum, hydrotreated middle	N/A	N/A	N/A	11 Mg/l	N/A

Other information : This mixture has not been evaluated as a whole for health effects.

Exposure effects listed are based on existing health data for the



OPQ YELLOW

Version Number 1.4 Revision Date 04/02/2024 Page 12 of 17 Print Date 04/05/2024

individual components which comprise the mixture.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Titanium oxide (TiO2)			
	Acute LC50 > 1,000 Mg/l	Fish - Fundulus heteroclitus	96 h
	Marine water		
	Acute LC50 3 Mg/l Fresh water	Crustaceans - Ceriodaphnia	48 h
		dubia	
	Acute LC50 6.5 Mg/l Fresh	Daphnia - Daphnia pulex	48 h
	water		

Conclusion/Summary : Not available.

Persistence and degradability

Conclusion/Summary : Not available.

Bioaccumulative potential

Not available.

Mobility in soil

Soil/water partition coefficient

(KOC)

Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the



OPQ YELLOW

Version Number 1.4 Revision Date 04/02/2024 Page 13 of 17 Print Date 04/05/2024

requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

Section 14. Transport information

U.S.DOT 49CFR Ground/Air/Water : Not regulated for transportation.

International Air ICAO/IATA

: Not classified as dangerous goods under transport regulations.

International Water IMO/IMDG

: Not classified as dangerous goods under transport regulations.

Section 15. Regulatory information

U.S. Federal regulations

United States - TSCA 12(b) - Chemical export notification: None

of the components are listed.

United States - TSCA 4(a) - Final Test Rules: Not listed United States - TSCA 4(a) - ITC Priority list: Not listed United States - TSCA 4(a) - Proposed test rules: Not listed United States - TSCA 4(f) - Priority risk review: Not listed United States - TSCA 5(a)2 - Proposed significant new use rules:

Not listed

United States - TSCA 5(e) - Substances consent order: Not listed United States - TSCA 6 - Final risk management: Listed 1,1'-

Biphenyl, chloro derivs.

United States - TSCA 6 - Proposed risk management: Not listed United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not

determined

United States - TSCA 8(a) - Preliminary assessment report



OPQ YELLOW

Version Number 1.4 Revision Date 04/02/2024 Page 14 of 17 Print Date 04/05/2024

(PAIR): Not listed

United States - TSCA 8(c) - Significant adverse reaction (SAR):

Not listed

United States - TSCA 8(d) - Health and safety studies: Not listed United States - TSCA 5(a)2 - Final significant new use rules: Not

listed

United States - EPA Clean water act (CWA) section 307 - Priority pollutants: Listed Nickel antimony yellow rutile (C.I. Pigment

Yellow 53)

1,1'-Biphenyl, chloro derivs.

United States - EPA Clean water act (CWA) section 311 -

Hazardous substances: Listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Flammable substances: Not listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Toxic substances: Not listed

 $\label{lem:commerce-Precursor} \textbf{United States-Department of commerce-Precursor chemical:}$

Not listed

Clean Air Act Section 112(b)

Hazardous Air Pollutants (HAPs)

Clean Air Act Section 602 Class I

Substances

Clean Air Act Section 602 Class II

Substances

DEA List I Chemicals (Precursor

Chemicals)

DEA List II Chemicals (Essential

Chemicals)

Listed

Not listed

Not listed

Not listed

Not listed

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

SARA 311/312

Classification : SKIN IRRITATION - Category 2

Composition/information on ingredients

Name	%	Classification
Titanium oxide (TiO2)	>= 25 - <= 50	CARCINOGENICITY - Category 2
Nickel antimony titanium yellow rutile	>= 10 - <= 25	CARCINOGENICITY - Category 1A
Miscellaneous Compounds	>= 10 - <= 25	ACUTE TOXICITY - inhalation - Category 4



OPQ YELLOW

Version Number 1.4 Revision Date 04/02/2024 Page 15 of 17 Print Date 04/05/2024

Distillates, petroleum, hydrotreated middle		SKIN IRRITATION - Category 2 ASPIRATION HAZARD - Category 1
Silica	>= 1 - <= 3	EYE IRRITATION - Category 2B

SARA 313

Form R - Reporting requirements

Product name	CAS number	%
Nickel antimony yellow rutile (C.I. Pigment Yellow 53)	8007-18-9	>= 10 - < 30
1,1'-Biphenyl, chloro derivs.	-	>= 0 - < 0.1

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts : The following components are listed:

Titanium dioxide Silica, amorphous

New York : None of the components are listed.
New Jersey : The following components are listed:

Titanium dioxide

Nickel antimony yellow rutile (C.I. Pigment Yellow 53)

Pennsylvania: The following components are listed:

Titanium dioxide

Nickel antimony yellow rutile (C.I. Pigment Yellow 53)

Silica, amorphous

California Prop. 65

WARNING: This product can expose you to chemicals including Titanium dioxide, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable
		dosage level
Titanium dioxide	-	-
Nickel antimony yellow rutile (C.I. Pigment	-	-
Yellow 53)		



OPQ YELLOW

Version Number 1.4 Page 16 of 17 Print Date 04/05/2024 Revision Date 04/02/2024

United States inventory (TSCA 8b) All components are active or exempted.

Canada inventory All components are listed or exempted.

International regulations

Inventory list

Not determined. Australia

Canada All components are listed or exempted. China All components are listed or exempted.

Russian Federation inventory: Not determined. **Eurasian Economic Union** Japan Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined.

New Zealand Not determined. **Philippines** Not determined.

Republic of Korea All components are listed or exempted. Not determined. Not determined. **Taiwan**

Thailand Not determined. Not determined. **Turkey**

United States All components are active or exempted.

Viet Nam Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	/	2
Flammability		0
Physical hazards		0
	•	•

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

History

Date of printing 04/05/2024 Date of issue/Date of revision 04/02/2024 Date of previous issue 05/06/2021

Version

ATE = Acute Toxicity Estimate **Key to abbreviations**

BCF = Bioconcentration Factor



OPQ YELLOW

Version Number 1.4 Revision Date 04/02/2024 Page 17 of 17 Print Date 04/05/2024

GHS = Globally Harmonized System of Classification and Labelling of

Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine

pollution)

UN = United Nations

References : Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.