

Geon™ A55-56D Black Oil Filter End Cap

Version Number 1.3 Revision Date 08/29/2016 Page 1 of 18 Print Date 08/30/2016

SAFETY DATA SHEET

Geon™ A55-56D Black Oil Filter End Cap

Section 1. Identification

GHS product identifier : Geon™ A55-56D Black Oil Filter End Cap

Chemical name: MixtureCAS number: MixtureOther means of identification: FO20036384Product type: liquid

Relevant identified uses of the substance or mixture and uses advised against

Product use : Industrial applications. Plastics.

Supplier's details : POLYONE CORPORATION

33587 Walker Road, Avon Lake, OH 44012

1 (440) 930-1000 or 1 (866) POLYONE

Emergency telephone number (with hours of operation)

CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or

accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard

Communication Standard (29 CFR 1910.1200).

Classification of the substance or

mixture

SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1

GHS label elements



Geon™ A55-56D Black Oil Filter End Cap

Version Number 1.3 Page 2 of 18 Revision Date 08/29/2016 Print Date 08/30/2016

Hazard pictograms

Signal word : Danger

Hazard statements : Causes serious eye damage.

Precautionary statements

General : Not applicable.

Prevention : Wear eye or face protection.

Response : IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or physician.

Storage:Not applicable.Disposal:Not applicable.Supplemental label elements:None known.Hazards not otherwise classified:None known.

Section 3. Composition/information on ingredients

Substance/mixture: MixtureChemical name: MixtureOther means of identification: FO20036384

CAS number/other identifiers

Ingredient name	%	CAS number
Chlorinated Paraffins	10 - 25	63449-39-8
Calcium oxide	5 - 10	1305-78-8
Polypropylene glycol	3 - 5	25322-69-4
Quartz	0.1 - 0.3	14808-60-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.



Geon™ A55-56D Black Oil Filter End Cap

Version Number 1.3 Revision Date 08/29/2016

Page 3 of 18 Print Date 08/30/2016

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Get medical attention immediately. Call a poison center or physician. Eve contact Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be

treated promptly by a physician.

Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under

medical surveillance for 48 hours.

Get medical attention immediately. Call a poison center or physician. Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an

Skin contact

Inhalation

Ingestion



Geon™ A55-56D Black Oil Filter End Cap

Version Number 1.3 Page 4 of 18 Revision Date 08/29/2016 Print Date 08/30/2016

open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:

watering redness

Inhalation : No specific data.

Skin contact: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

Ingestion : Adverse symptoms may include the following:

stomach pains

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms

may be delayed. The exposed person may need to be kept under

medical surveillance for 48 hours.

Specific treatments : No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without

suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media



Geon™ A55-56D Black Oil Filter End Cap

Version Number 1.3 Revision Date 08/29/2016 Page 5 of 18 Print Date 08/30/2016

Suitable extinguishing media Unsuitable extinguishing media In case of fire, use water spray (fog), foam, dry chemical or CO_2 .

None known.

Specific hazards arising from the chemical

In a fire or if heated, a pressure increase will occur and the container may burst. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway,

sewer or drain.

Hazardous thermal decomposition products

May emit Hydrogen Chloride (HCl).

Decomposition products may include the following materials:

carbon dioxide carbon monoxide nitrogen oxides phosphorus oxides halogenated compounds carbonyl halides metal oxide/oxides

Special protective actions for firefighters Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any

personal risk or without suitable training.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece operated

in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without

suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialised clothing is required to deal with the spillage, take note of

any information in Section 8 on suitable and unsuitable materials. See

also the information in "For non-emergency personnel".

Environmental precautions: Avoid dispersal of spilled material and runoff and contact with soil,

waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment

if released in large quantities.



Geon™ A55-56D Black Oil Filter End Cap

Version Number 1.3 Revision Date 08/29/2016

Page 6 of 18 Print Date 08/30/2016

Methods and materials for containment and cleaning up

Stop leak if without risk. Move containers from spill area. Dilute with Small spill

> water and mop up if water-soluble. Alternatively, or if waterinsoluble, absorb with an inert dry material and place in an appropriate

waste disposal container. Dispose of via a licensed waste disposal

contractor.

Large spill Stop leak if without risk. Move containers from spill area. Approach

release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency

contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Put on appropriate personal protective equipment (see Section 8). Do **Protective measures**

> not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product

residue and can be hazardous. Do not reuse container.

Advice on general occupational

hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See

also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a well-ventilated place. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid

environmental contamination.



Geon™ A55-56D Black Oil Filter End Cap

Version Number 1.3 Revision Date 08/29/2016 Page 7 of 18 Print Date 08/30/2016

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Quartz	OSHA PEL 1989 (1989-03-01) Calculated as Quartz
	PEL: Permissible Exposure Level 0.1 mg/m3 Form: Respirable dust
	OSHA - PEL Z3 (1997-09-03) Time Weighted Average (TWA) Form: Respirable
	Time Weighted Average (TWA) 10 mg/m3 Form: Respirable
	Time Weighted Average (TWA) 30 mg/m3 Form: Total dust
	NIOSH REL (1994-06-01)
	Time Weighted Average (TWA) 0.05 mg/m3 Form: Respirable dust ACGIH TLV (2005-12-09)
	TLV-TWA: Threshold Limit Value - Time weighted average PEL:
	Permissible Exposure Level 0.025 mg/m3 Form: Respirable fraction
Chlorinated Paraffins	
Calcium oxide	OSHA PEL 1989 (1989-03-01)
	PEL: Permissible Exposure Level 5 mg/m3
	OSHA PEL (1993-06-30)
	PEL: Permissible Exposure Level 5 mg/m3
	NIOSH REL (1994-06-01)
	Time Weighted Average (TWA) 2 mg/m3 ACGIH TLV (1994-09-01)
	TLV-TWA: Threshold Limit Value - Time weighted average PEL:
	Permissible Exposure Level 2 mg/m3
Polypropylene glycol	AIHA WEEL (1999-01-01)
	Time Weighted Average (TWA) 10 mg/m3 Form: Aerosol
Appropriate engineering controls	: If user operations generate dust, fumes, gas, vapor or mist, use process
	enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any
	recommended or statutory limits.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of
	7/10



Geon™ A55-56D Black Oil Filter End Cap

Version Number 1.3 Revision Date 08/29/2016 Page 8 of 18 Print Date 08/30/2016

environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section 9. Physical and chemical properties



Geon™ A55-56D Black Oil Filter End Cap

 Version Number 1.3
 Page 9 of 18

 Revision Date 08/29/2016
 Print Date 08/30/2016

Appearance

Physical state liquid [liquid] Color **BLACK** Odor Not available. **Odor threshold** Not available. Not available. pН **Melting point** Not available. **Boiling point** Not available. Flash point Not available. **Burning time** Not available. **Burning rate** Not available. **Evaporation rate** Not available. Flammability (solid, gas) Not available.

Lower and upper explosive : Lower: Not available. (flammable) limits : Upper: Not available.

Vapor pressureNot available.Vapor densityNot available.Relative densityNot available.SolubilityNot available.Solubility in waterNot available.Partition coefficient: n-Not available.

octanol/water

Auto-ignition temperature: Not available.Decomposition temperature: Not available.SADT: Not available.

Viscosity : Dynamic: Not available.

Kinematic: Not available.

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or

its ingredients.

Chemical stability : Stable under recommended storage and handling conditions (see

Section 7).

Possibility of hazardous reactions: Under normal conditions of storage and use, hazardous reactions will

not occur.

Conditions to avoid : Keep away from extreme heat and oxidizing agents.

Incompatible materials : Avoid contact with acetal homopolymers and acetyl homopolymers

during processing.

Hazardous decomposition

products

Under normal conditions of storage and use, hazardous decomposition

products should not be produced.



Geon™ A55-56D Black Oil Filter End Cap

Version Number 1.3 Revision Date 08/29/2016 Page 10 of 18 Print Date 08/30/2016

Section 11. Toxicological information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Polypropylene glycol				
	LD50 Oral	Rat	3,750 mg/kg	=
	LD50 Oral	Rat	15,000 mg/kg	=
	LD50 Oral	Rat	9,760 mg/kg	=
	LD50 Oral	Rat	10,334 mg/kg	=
	LD50 Oral	Rat	7,250 mg/kg	=
	LD50 Oral	Rat	2,150 mg/kg	=
	LD50 Oral	Rat	4,190 mg/kg	=
	LD50 Oral	Rat	5,840 mg/kg	=
	LD50 Oral	Rat	2,410 mg/kg	=
	LD50 Oral	Rat	5,840 mg/kg	=
	LD50 Oral	Rat	14,800 mg/kg	=
	LD50 Dermal	Rabbit	10,000 mg/kg	=
	LD50 Dermal	Rabbit	30,000 mg/kg	=
Quartz	·	·	·	·
Chlorinated Paraffins			·	·
	LD50 Oral	Rat	26,100 mg/kg	-

Conclusion/Summary

Mixture.Not fully tested.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Polypropylene glycol	Eyes - Mild	Rabbit			-
	irritant				
	Skin - Mild	Rabbit			-
	irritant				
	Skin - Mild	Rabbit			-
	irritant				
	Skin - Mild	Rabbit			-
	irritant				
	Skin - Mild	Rabbit		24 hrs	-
	irritant				
	Eyes - Mild	Rabbit		24 hrs	-
	irritant				



Geon™ A55-56D Black Oil Filter End Cap

Version Number 1.3 Revision Date 08/29/2016 Page 11 of 18 Print Date 08/30/2016

	Skin - Mild irritant	Rabbit	24 hrs	-
	Eyes - Mild irritant	Rabbit	24 hrs	-
	Skin - Mild irritant	Rabbit		-
	Eyes - Mild irritant	Rabbit	24 hrs	-
	Skin - Mild irritant	Rabbit		-
Chlorinated Paraffins	Eyes - Mild irritant	Rabbit		-
	Skin - Mild irritant	Rat	24 hrs	-

Conclusion/Summary

Skin: Mixture.Not fully tested.Eyes: Mixture.Not fully tested.Respiratory: Mixture.Not fully tested.

Sensitization

Conclusion/Summary

Skin: Mixture.Not fully tested.Respiratory: Mixture.Not fully tested.

Mutagenicity

Conclusion/Summary : Mixture. Not fully tested.

Carcinogenicity

Conclusion/Summary : Mixture.Not fully tested.

Classification

Product/ingredient	OSHA	IARC	NTP
name			
Quartz		1	Known to be a human carcinogen.

Reproductive toxicity

Conclusion/Summary: Mixture.Not fully tested.

Teratogenicity

Conclusion/Summary : Mixture.Not fully tested.



Geon™ A55-56D Black Oil Filter End Cap

Version Number 1.3 Page 12 of 18 Revision Date 08/29/2016 Print Date 08/30/2016

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Calcium oxide	Category 3		Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely routes of

exposure

Not available.

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:

pain watering redness

Inhalation : No specific data.

Skin contact : Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

Ingestion : Adverse symptoms may include the following:

stomach pains

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available. **Potential delayed effects** : Not available.

12/18



Geon™ A55-56D Black Oil Filter End Cap

Version Number 1.3 Revision Date 08/29/2016 Page 13 of 18 Print Date 08/30/2016

Potential chronic health effects

Conclusion/Summary : Mixture.Not fully tested.

General:No known significant effects or critical hazards.Carcinogenicity:No known significant effects or critical hazards.Mutagenicity:No known significant effects or critical hazards.Teratogenicity:No known significant effects or critical hazards.Developmental effects:No known significant effects or critical hazards.Fertility effects:No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value		
Oral	15,275.1 mg/kg		
Route	ATE value	ATE value	
Dermal	8,733 mg/kg		

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Calcium oxide			
	Chronic NOEC 100 mg/l Fresh	Fish - Fish	46 d
	water		
	Chronic NOEC 100 mg/l Fresh	Fish - Fish	46 d
	water		
	Chronic NOEC 100 mg/l Fresh	Fish - Fish	46 d
	water		
	Chronic NOEC 100 mg/l Fresh	Fish - Fish	46 d
	water		
	Chronic NOEC 100 mg/l Fresh	Fish - Fish	46 d
	water		
Polypropylene glycol	•		
	Acute LC50 1,700,000 μg/l Fresh	Fish - Fish	96 h
	water		
	Acute LC50 650,000 µg/l Marine	Fish - Fish	96 h
	water		



Geon™ A55-56D Black Oil Filter End Cap

Version Number 1.3 Revision Date 08/29/2016 Page 14 of 18 Print Date 08/30/2016

Chlorinated Paraffins			
	Acute LC50 > $5,000,000 \mu g/l$	Fish - Fish	96 h
	Marine water		
	Acute LC50 > 5,000,000 μg/l	Fish - Fish	96 h
	Marine water		
	Acute LC50 > 10,000,000 μg/l	Fish - Fish	96 h
	Marine water		

Conclusion/Summary : Not available.

Persistence and degradability

Conclusion/Summary : Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Calcium oxide		2.34	low
Polypropylene glycol	-0.68 - 0.01	-	low
Chlorinated Paraffins	7.46 - 11.48	•	high

Mobility in soil

Soil/water partition coefficient

(KOC)

Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.



Geon™ A55-56D Black Oil Filter End Cap

Version Number 1.3 Revision Date 08/29/2016 Page 15 of 18 Print Date 08/30/2016

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

Section 14. Transport information

U.S. DOT Classification : Not regulated for transportation.

ICAO/IATA : Consult mode specific transport rules

IMO/IMDG (maritime) : Consult mode specific transport rules

Section 15. Regulatory information

U.S. Federal regulations : United States - TSCA 12(b) - Chemical export notification: None

of the components are listed.

United States - TSCA 4(a) - Final Test Rules: Not listed United States - TSCA 4(a) - ITC Priority list: Not listed United States - TSCA 4(a) - Proposed test rules: Not listed United States - TSCA 4(f) - Priority risk review: Not listed

United States - TSCA 5(a)2 - Final significant new use rules: Not

listed

United States - TSCA 5(a)2 - Proposed significant new use rules:

Not listed

United States - TSCA 5(e) - Substances consent order: Not listed United States - TSCA 6 - Final risk management: Not listed United States - TSCA 6 - Proposed risk management: Not listed United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not

determined

United States - TSCA 8(a) - Preliminary assessment report

(PAIR): Not listed

United States - TSCA 8(c) - Significant adverse reaction (SAR):

Not listed

United States - TSCA 8(d) - Health and safety studies: Not listed **United States - EPA Clean water act (CWA) section 307 - Priority**

pollutants: Listed Vinyl chloride monomer

United States - EPA Clean water act (CWA) section 311 -

Hazardous substances: Not listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Flammable substances: Not listed

United States - EPA Clean air act (CAA) section 112 - Accidental



Geon™ A55-56D Black Oil Filter End Cap

Version Number 1.3 Revision Date 08/29/2016 Page 16 of 18 Print Date 08/30/2016

release prevention - Toxic substances: Not listed

United States - Department of commerce - Precursor chemical:

Not listed

Clean Air Act Section 112(b)

Hazardous Air Pollutants (HAPs)

Clean Air Act Section 602 Class I

Substances

Clean Air Act Section 602 Class II

Substances

DEA List I Chemicals (Precursor

Chemicals)

DEA List II Chemicals (Essential

Chemicals)

Not listed

Not listed

Not listed

Not listed

Not listed

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

SARA 311/312

Classification : Immediate (acute) health hazard

Composition/information on ingredients

Name	0/0	Classification
Calcium oxide	5 - 10	AH
Polypropylene glycol	3 - 5	AH
Quartz	0.1 - 0.3	СН
Chlorinated Paraffins	10 - 25	АН

SARA 313

Not applicable.

State regulations

Massachusetts : The following components are listed:

Calcium carbonate Calcium oxide

New York: None of the components are listed.New Jersey: The following components are listed:

Ethene, chloro-, homopolymer

Calcium oxide



Geon™ A55-56D Black Oil Filter End Cap

Version Number 1.3 Revision Date 08/29/2016 Page 17 of 18 Print Date 08/30/2016

Calcium carbonate

Ouartz

Pennsylvania : The following components are listed:

Quartz

Calcium carbonate

Calcium oxide

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

United States inventory (TSCA 8b) : All components are listed or exempted.

Canada inventory : All components are listed or exempted.

International regulations

International lists : Australia inventory (AICS): Not determined.

Taiwan inventory (CSNN): Not determined.

Malaysia Inventory (EHS Register): Not determined.

EINECS: Not determined.

Japan inventory: Not determined.

China inventory (IECSC): All components are listed or exempted.

Korea inventory: Not determined.

New Zealand Inventory of Chemicals (NZIoC): Not determined.

Philippines inventory (PICCS): Not determined.

Chemical Weapons Convention

List Schedule I Chemicals

Chemical Weapons Convention

List Schedule II Chemicals

Chemical Weapons Convention

List Schedule III Chemicals

Not listed

Not listed

: Not listed

Section 16. Other information

History

Date of printing: 08/30/2016Date of issue/Date of revision: 08/29/2016Date of previous issue: 05/31/2016

Version : 1.3

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of



Geon™ A55-56D Black Oil Filter End Cap

Version Number 1.3 Revision Date 08/29/2016 Page 18 of 18 Print Date 08/30/2016

Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine

pollution)

UN = United Nations

References : Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.