

KEN AM100G DARK GREEN #1

Version Number 1.2 Page 1 of 18 Print Date 09/26/2015 Revision Date 09/25/2015

SAFETY DATA SHEET

KEN AM100G DARK GREEN #1

Section 1. Identification

KEN AM100G DARK GREEN #1 **GHS** product identifier

Chemical name Mixture CAS number Mixture Other means of identification FO00005333 **Product type** liquid

Relevant identified uses of the substance or mixture and uses advised against

Product use Industrial applications. Plastics.

Supplier's details POLYONE CORPORATION

33587 Walker Road, Avon Lake, OH 44012

1 (440) 930-1000 or 1 (866) POLYONE

Emergency telephone number (with hours of operation)

CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident). CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire,

exposure or accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status This material is considered hazardous by the OSHA Hazard

Communication Standard (29 CFR 1910.1200).

Classification of the substance or

mixture

FLAMMABLE LIQUIDS - Category 2

SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) -

Category 3

GHS label elements



KEN AM100G DARK GREEN #1

Version Number 1.2 Revision Date 09/25/2015 Page 2 of 18 Print Date 09/26/2015

Hazard pictograms



 \diamondsuit

Signal word : Danger

Hazard statements : Highly flammable liquid and vapour.

Causes serious eye irritation. May cause drowsiness or dizziness.

Precautionary statements

General : Not applicable.

Prevention: Wear protective gloves. Wear eye or face protection. Keep away from

heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Use only outdoors or in a well-ventilated area. Avoid

breathing vapor. Wash hands thoroughly after handling.

Response: IF INHALED: Remove victim to fresh air and keep at rest in a

position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If

eye irritation persists: Get medical attention.

Storage : Store in a well-ventilated place. Keep cool.

Disposal: Dispose of contents and container in accordance with all local,

regional, national and international regulations.

Supplemental label elements : None known. **Hazards not otherwise classified** : None known.

Section 3. Composition/information on ingredients

Substance/mixture: MixtureChemical name: MixtureOther means of identification: FO00005333

CAS number/other identifiers



KEN AM100G DARK GREEN #1

Version Number 1.2 Page 3 of 18 Revision Date 09/25/2015 Print Date 09/26/2015

Ingredient name	%	CAS number
Methyl ethyl ketone	60 - 100	78-93-3
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters,	1 - 5	68515-48-0
C9-rich		
Titanium dioxide	0.1 - 1	13463-67-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	:	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get



KEN AM100G DARK GREEN #1

Version Number 1.2 Page 4 of 18 Revision Date 09/25/2015 Print Date 09/26/2015

medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : Can cause central nervous system (CNS) depression. May cause

drowsiness or dizziness.

Skin contact : No known significant effects or critical hazards.

Ingestion: Can cause central nervous system (CNS) depression. Irritating to

mouth, throat and stomach.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:

pain or irritation

watering redness

Inhalation : Adverse symptoms may include the following:

nausea or vomiting

headache

drowsiness/fatigue dizziness/vertigo unconsciousness

Skin contact: No specific data.Ingestion: No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist

immediately if large quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

Protection of first-aiders: No action shall be taken involving any personal risk or without

suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give

mouth-to-mouth resuscitation.

See toxicological information (Section 11)



KEN AM100G DARK GREEN #1

Version Number 1.2 Revision Date 09/25/2015 Page 5 of 18 Print Date 09/26/2015

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media Use dry chemical, CO₂, water spray (fog) or foam.

Do not use water jet.

Specific hazards arising from the chemical

Highly flammable liquid and vapour. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion

hazard.

Hazardous thermal decomposition products

: May emit Hydrogen Chloride (HCl).

Decomposition products may include the following materials:

carbon dioxide carbon monoxide halogenated compounds

Special protective actions for firefighters Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-

exposed containers cool.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece operated

in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See

also the information in "For non-emergency personnel".

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the



KEN AM100G DARK GREEN #1

Version Number 1.2 Revision Date 09/25/2015 Page 6 of 18 Print Date 09/26/2015

product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

Stop leak if without risk. Move containers from spill area. Use sparkproof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.



KEN AM100G DARK GREEN #1

Version Number 1.2 Revision Date 09/25/2015 Page 7 of 18 Print Date 09/26/2015

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a well-ventilated place. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Methyl ethyl ketone	OSHA PEL 1989 (1989-03-01) PEL: Permissible Exposure Level 590 mg/m3 200 ppm Short Term Exposure Limit value for a 15-minute reference period expressed in parts per million or in mg/m3. 885 mg/m3 300 ppm OSHA PEL (1993-06-30) PEL: Permissible Exposure Level 590 mg/m3 200 ppm NIOSH REL (1994-06-01) Time Weighted Average (TWA) 590 mg/m3 200 ppm Short Term Exposure Limit value for a 15-minute reference period expressed in parts per million or in mg/m3. 885 mg/m3 300 ppm ACGIH TLV (1994-09-01) TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 590 mg/m3 200 ppm TLV-STEL: Threshold Limit Value - Short Time Exposure Level 885 mg/m3 300 ppm
Titanium dioxide	OSHA PEL 1989 (1989-03-01) PEL: Permissible Exposure Level 10 mg/m3 Form: Total dust OSHA PEL (1993-06-30) PEL: Permissible Exposure Level 15 mg/m3 Form: Total dust ACGIH TLV (1996-05-18) TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 10 mg/m3



KEN AM100G DARK GREEN #1

Version Number 1.2 Revision Date 09/25/2015 Page 8 of 18 Print Date 09/26/2015

Appropriate engineering controls

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product., When there is a risk of ignition from static electricity, wear anti-static protective clothing., For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other skin protection

Appropriate footwear and any additional skin protection measures



KEN AM100G DARK GREEN #1

Version Number 1.2 Revision Date 09/25/2015

Page 9 of 18 Print Date 09/26/2015

should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this

product.

Use a properly fitted, air-purifying or air-fed respirator complying **Respiratory protection**

with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits

of the selected respirator.

Section 9. Physical and chemical properties

Appearance

Physical state liquid [liquid] Color **GREEN** Odor Not available. Odor threshold Not available. pН Not available. **Melting point** Not available. **Boiling point** Not available.

Closed cup: -9 °C (15.80 °F) Flash point

Burning time Not available. Not available. **Burning** rate **Evaporation rate** Not available. Flammability (solid, gas) Not available.

Lower and upper explosive Lower: Not available. (flammable) limits **Upper:** Not available.

Vapor pressure Not available. Vapor density Not available. Not available. Relative density Not available. **Solubility** Solubility in water Not available. Partition coefficient: n-Not available.

octanol/water

Auto-ignition temperature Not available. **Decomposition temperature** Not available. Not available. **SADT**

Viscosity **Dynamic:** Not available.

Kinematic: Not available.

Section 10. Stability and reactivity

No specific test data related to reactivity available for this product or Reactivity



KEN AM100G DARK GREEN #1

Version Number 1.2 Page 10 of 18 Revision Date 09/25/2015 Print Date 09/26/2015

its ingredients.

Chemical stability : Stable under recommended storage and handling conditions (see

Section 7).

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will

not occur.

Conditions to avoid : Avoid all possible sources of ignition (spark or flame). Do not

pressurize, cut, weld, braze, solder, drill, grind or expose containers to

heat or sources of ignition.

Incompatible materials : Avoid contact with acetal homopolymers and acetyl homopolymers

during processing.

Reactive or incompatible with the following materials:

oxidizing materials

Hazardous decomposition

products

Under normal conditions of storage and use, hazardous decomposition

products should not be produced.

Section 11. Toxicological information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure		
Methyl ethyl ketone	Methyl ethyl ketone					
	LD50 Oral	Rat	2,737 mg/kg	=		
	LC50 Inhalation	Rat	24 mg/l	8 h		
	LD50 Dermal	Rabbit	6,480 mg/kg	=		
1,2-Benzenedicarboxylic acid,	di-C8-10-branched	alkyl esters, C9-rich				
	LD50 Oral	Rat	10,000 mg/kg	=		
Titanium dioxide						
	LC50 Inhalation	Rat - Male	6.82 Mg/l	4 h		
	LD50 Dermal	Rabbit	> 5,000 mg/kg	-		

Conclusion/Summary : Mixture.Not fully tested.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Methyl ethyl ketone	Skin - Moderate irritant	Rabbit		24 hrs	-
1,2-Benzenedicarboxylic acid, di-C8-10-branched	Eyes - Mild irritant	Rabbit			-



KEN AM100G DARK GREEN #1

Version Number 1.2 Page 11 of 18 Revision Date 09/25/2015 Print Date 09/26/2015

alkyl esters, C9-rich

Conclusion/Summary

Skin:Mixture.Not fully tested.Eyes:Mixture.Not fully tested.Respiratory:Mixture.Not fully tested.

Sensitization

Conclusion/Summary

Skin: Mixture.Not fully tested.Respiratory: Mixture.Not fully tested.

Mutagenicity

Conclusion/Summary : Mixture.Not fully tested.

Carcinogenicity

Conclusion/Summary : Mixture.Not fully tested.

Classification

Product/ingredient	OSHA	IARC	NTP
name			
Titanium dioxide		2B	

Reproductive toxicity

Conclusion/Summary : Mixture.Not fully tested.

Teratogenicity

Conclusion/Summary: Mixture.Not fully tested.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Methyl ethyl ketone	Category 3		Narcotic effects

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely routes of : Not available.

exposure



KEN AM100G DARK GREEN #1

Version Number 1.2 Page 12 of 18 Revision Date 09/25/2015 Print Date 09/26/2015

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : Can cause central nervous system (CNS) depression. May cause

drowsiness or dizziness.

Skin contact: No known significant effects or critical hazards.

Ingestion : Can cause central nervous system (CNS) depression., Irritating to

mouth, throat and stomach.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:

pain or irritation

watering redness

Inhalation : Adverse symptoms may include the following:

nausea or vomiting

headache

drowsiness/fatigue dizziness/vertigo unconsciousness

Skin contact: No specific data.Ingestion: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Potential chronic health effects

Conclusion/Summary : Mixture.Not fully tested.

General: No known significant effects or critical hazards.Carcinogenicity: No known significant effects or critical hazards.Mutagenicity: No known significant effects or critical hazards.Teratogenicity: No known significant effects or critical hazards.



KEN AM100G DARK GREEN #1

Version Number 1.2 Page 13 of 18 Revision Date 09/25/2015 Print Date 09/26/2015

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	4,535.1 mg/kg

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Methyl ethyl ketone			
	Acute LC50 3,220,000 µg/l Fresh	Fish - Fathead minnow	96 h
	water		
	Acute LC50 5,600 mg/l Fresh	Fish - Western	96 h
	water	mosquitofish	
	Acute EC50 5,091,000 μg/l Fresh	Aquatic invertebrates.	48 h
	water	Water flea	
	Acute EC50 > 500,000 μg/l Marine	Aquatic plants - Diatom	96 h
	water		
	Acute EC50 > 500 mg/l Fresh	Aquatic plants - Green	96 h
	water	algae	

Conclusion/Summary : Not available.

Persistence and degradability

Conclusion/Summary : Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Methyl ethyl ketone	0.29	-	low
1,2-Benzenedicarboxylic	8.8	3.00	low
acid, di-C8-10-branched			
alkyl esters, C9-rich			
Titanium dioxide		352.00	low



KEN AM100G DARK GREEN #1

Version Number 1.2 Page 14 of 18 Revision Date 09/25/2015 Print Date 09/26/2015

Mobility in soil

Soil/water partition coefficient

(KOC)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

<u>United States - RCRA Acute hazardous waste "P" List:</u> Not listed

United States - RCRA Toxic hazardous waste "U" List: Listed

Ingredient	CAS#	Status	Reference number
Methyl ethyl ketone	78-93-3	Listed	

Section 14. Transport information

U.S. DOT Classification

Proper Shipping Name: Resin solution

Technical Name:

Hazard Class / Division 3 UN Number UN1866 Packing Group II Label Required 3



KEN AM100G DARK GREEN #1

Version Number 1.2 Revision Date 09/25/2015 Page 15 of 18 Print Date 09/26/2015

ICAO/IATA Consult mode specific transport rules

IMO/IMDG (maritime) Consult mode specific transport rules

Section 15. Regulatory information

U.S. Federal regulations

United States - TSCA 12(b) - Chemical export notification: None of the components are listed.

United States - TSCA 4(a) - Final Test Rules: Listed 1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich Diisononyl phthalate
Diisodecyl phthalate

United States - TSCA 4(a) - Proposed test rules: Not listed United States - TSCA 4(f) - Priority risk review: Not listed United States - TSCA 5(a)2 - Final significant new use rules: Not listed

United States - TSCA 5(a)2 - Proposed significant new use rules: Not listed

United States - TSCA 5(e) - Substances consent order: Not listed United States - TSCA 6 - Final risk management: Not listed United States - TSCA 6 - Proposed risk management: Not listed United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined

United States - TSCA 8(a) - Preliminary assessment report (PAIR): Not listed

United States - TSCA 8(c) - Significant adverse reaction (SAR): Not listed

United States - TSCA 8(d) - Health and safety studies: Not listed United States - TSCA 4(a) - ITC Priority list: Not listed

United States - EPA Clean water act (CWA) section 307 - Priority

pollutants: Listed C.I. Pigment Green 36

Diisodecyl phthalate

United States - EPA Clean water act (CWA) section 311 -

Hazardous substances: Listed

United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Flammable substances: Not listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Toxic substances: Not listed

United States - Department of commerce - Precursor chemical:

Not listed



KEN AM100G DARK GREEN #1

Version Number 1.2 Page 16 of 18 Revision Date 09/25/2015 Print Date 09/26/2015

Not listed

Clean Air Act Section 112(b) :

Hazardous Air Pollutants (HAPs)

Clean Air Act Section 602 Class I : Not listed

Substances

Clean Air Act Section 602 Class II : Not listed

Substances

DEA List I Chemicals (Precursor: Not listed

Chemicals)

DEA List II Chemicals (Essential: Listed

Chemicals)

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Chemical Name	CAS-No.	RQ for component
Methyl ethyl ketone	78-93-3	5,000 lb(s)
		2,270 kg
		2,270 kg
		5,000 lb(s)

SARA 311/312

Classification : Fire hazard

Immediate (acute) health hazard

Composition/information on ingredients

Name	%	Classification
Methyl ethyl ketone	60 - 100	F, AH
100 11 11 11 11	1 7	A T T
1,2-Benzenedicarboxylic acid, di- C8-10-branched alkyl esters, C9- rich	1 - 5	АН
Titanium dioxide	0.1 - 1	СН

SARA 313

Not applicable.

State regulations

Massachusetts: The following components are listed:

Methyl ethyl ketone

New York : The following components are listed:

Methyl ethyl ketone



KEN AM100G DARK GREEN #1

Version Number 1.2 Page 17 of 18 Revision Date 09/25/2015 Print Date 09/26/2015

New Jersey The following components are listed:

Methyl ethyl ketone

Ethene, chloro-, homopolymer

Isopropanol Titanium dioxide

The following components are listed: Pennsylvania

Methyl ethyl ketone

Isopropanol

Titanium dioxide

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer., WARNING: This product contains less than 1% of a chemical known to the State of California to cause birth defects or other reproductive harm.

All components are listed or exempted. **United States inventory (TSCA 8b)**:

Canada inventory All components are listed or exempted.

International regulations

International lists Australia inventory (AICS): Not determined.

Taiwan inventory (CSNN): Not determined.

Malaysia Inventory (EHS Register): Not determined. **EINECS:** All components are listed or exempted.

Japan inventory: Not determined.

China inventory (IECSC): Not determined.

Korea inventory: Not determined.

New Zealand Inventory of Chemicals (NZIoC): Not determined.

Philippines inventory (PICCS): Not determined.

Chemical Weapons Convention

List Schedule I Chemicals

Chemical Weapons Convention

List Schedule II Chemicals

Chemical Weapons Convention

List Schedule III Chemicals

Not listed

Not listed

Not listed

Section 16. Other information

History

Date of printing 09/26/2015 Date of issue/Date of revision 09/25/2015



KEN AM100G DARK GREEN #1

Version Number 1.2 Revision Date 09/25/2015 Page 18 of 18 Print Date 09/26/2015

Date of previous issue : 10/18/2004

Version : 1.2

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of

Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine

pollution)

UN = United Nations

References : Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.