

# Geon™ MM555 CUFFING PLASTISOL 17-OZ

Version Number 1.5 Revision Date 05/25/2018

Page 1 of 19 Print Date 06/08/2018

# SAFETY DATA SHEET

#### Geon<sup>TM</sup> MM555 CUFFING PLASTISOL 17-OZ

# **Section 1. Identification**

**GHS** product identifier Geon™ MM555 CUFFING PLASTISOL 17-OZ

Chemical name Mixture CAS number Mixture Other means of identification FO20032976 **Product type** liquid

Relevant identified uses of the substance or mixture and uses advised against

Product use Industrial applications. Plastics.

POLYONE CORPORATION Supplier's details

33587 Walker Road, Avon Lake, OH 44012

CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or

1 (440) 930-1000 or 1 (866) POLYONE

**Emergency telephone number** (with hours of operation)

accident).

# Section 2. Hazards identification

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

This material is considered hazardous by the OSHA Hazard **OSHA/HCS** status

Communication Standard (29 CFR 1910.1200).

Classification of the substance or

mixture

EYE IRRITATION - Category 2A

SKIN SENSITIZATION - Category 1

#### **GHS** label elements



# Geon™ MM555 CUFFING PLASTISOL 17-OZ

 Version Number 1.5
 Page 2 of 19

 Revision Date 05/25/2018
 Print Date 06/08/2018

Hazard pictograms

❖

Signal word : Warning

**Hazard statements** : Causes serious eye irritation.

May cause an allergic skin reaction.

**Precautionary statements** 

**General** : Not applicable.

Prevention : Wear protective gloves. Wear eye or face protection. Avoid breathing

vapor. Wash hands thoroughly after handling. Contaminated work

clothing must not be allowed out of the workplace.

**Response** : IF ON SKIN: Wash with plenty of soap and water. Wash

contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

**Storage** : Not applicable.

**Disposal** : Dispose of contents and container in accordance with all local,

regional, national and international regulations.

**Supplemental label elements** : None known. **Hazards not otherwise classified** : None known.

# Section 3. Composition/information on ingredients

Substance/mixture: MixtureChemical name: MixtureOther means of identification: FO20032976

#### CAS number/other identifiers

Ingredient name	<b>%</b>	CAS number
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters,	5 - 10	68515-48-0
C9-rich		
Distillates (petroleum), hydrotreated light	1 - 3	64742-47-8
Naphtha, petroleum, hydrotreated heavy	1 - 3	64742-48-9



# Geon™ MM555 CUFFING PLASTISOL 17-OZ

 Version Number 1.5
 Page 3 of 19

 Revision Date 05/25/2018
 Print Date 06/08/2018

Calcium oxide	1 - 2.9	1305-78-8
Titanium dioxide	0.3 - 1	13463-67-7
Proprietary Hazardous Compounds	0 - 0.3	Not available.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

# Section 4. First aid measures

### Description of necessary first aid measures

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	:	Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting



# Geon™ MM555 CUFFING PLASTISOL 17-OZ

Version Number 1.5 Page 4 of 19 Revision Date 05/25/2018 Print Date 06/08/2018

unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact**: May cause an allergic skin reaction.

**Ingestion**: No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

**Eye contact** : Adverse symptoms may include the following:

pain or irritation

watering

redness

**Inhalation** : No specific data.

**Skin contact** : Adverse symptoms may include the following:

irritation redness

**Ingestion** : No specific data.

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist

immediately if large quantities have been ingested or inhaled.

**Specific treatments** : No specific treatment.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without

suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

# **Section 5. Firefighting measures**



# Geon™ MM555 CUFFING PLASTISOL 17-OZ

Version Number 1.5 Revision Date 05/25/2018 Page 5 of 19 Print Date 06/08/2018

#### **Extinguishing media**

Suitable extinguishing media Unsuitable extinguishing media In case of fire, use water spray (fog), foam, dry chemical or  $CO_2$ .

: None known.

Specific hazards arising from the chemical

In a fire or if heated, a pressure increase will occur and the container

may burst.

Hazardous thermal decomposition products

: May emit Hydrogen Chloride (HCl).

Decomposition products may include the following materials:

carbon dioxide carbon monoxide sulfur oxides

halogenated compounds metal oxide/oxides

Special protective actions for firefighters Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any

personal risk or without suitable training.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece operated

in positive pressure mode.

# Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without

suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note

of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

See also the information in For non-emergency personner.

**Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil,

waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil

or air).

#### Methods and materials for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Dilute with

water and mop up if water-soluble. Alternatively, or if water-



# Geon™ MM555 CUFFING PLASTISOL 17-OZ

Version Number 1.5 Revision Date 05/25/2018

Page 6 of 19 Print Date 06/08/2018

Large spill

insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

# Precautions for safe handling

**Protective measures** 

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

# Section 8. Exposure controls/personal protection

#### Control parameters



# Geon™ MM555 CUFFING PLASTISOL 17-OZ

Version Number 1.5 Revision Date 05/25/2018 Page 7 of 19 Print Date 06/08/2018

#### **Occupational exposure limits**

Appropriate engineering controls

**Environmental exposure controls** 

Ingredient name	Exposure limits
1,2-Benzenedicarboxylic acid, di-C8-10-	
branched alkyl esters, C9-rich	
Calcium oxide	OSHA PEL 1989 (1989-03-01)
	PEL: Permissible Exposure Level 5 mg/m3
	OSHA PEL (1993-06-30)
	PEL: Permissible Exposure Level 5 mg/m3
	NIOSH REL (1994-06-01)
	Time Weighted Average (TWA) 2 mg/m3
	ACGIH TLV (1994-09-01)
	TLV-TWA: Threshold Limit Value - Time weighted average PEL:
	Permissible Exposure Level 2 mg/m3
Naphtha, petroleum, hydrotreated heavy	
rvapitula, peu oleum, nyurotreateu neav y	
Proprietary Hazardous Compounds	
Titanium dioxide	OSHA PEL 1989 (1989-03-01)
Trainin dioxide	PEL: Permissible Exposure Level 10 mg/m3 Form: Total dust
	OSHA PEL (1993-06-30)
	PEL: Permissible Exposure Level 15 mg/m3 Form: Total dust
	NIOSH REL (1994-06-01)
	ACGIH TLV (1996-05-18)
	TLV-TWA: Threshold Limit Value - Time weighted average PEL:
	Permissible Exposure Level 10 mg/m3
Distillates (petroleum), hydrotreated light	ACGIH TLV (2003-01-01) Calculated as total hydrocarbon vapor
215thates (perforcing), flydronedied fight	TLV-TWA: Threshold Limit Value - Time weighted average PEL:
	Permissible Exposure Level 200 mg/m3

environmental protection legislation. In some cases, fume scrubbers, 7/19

exposure to airborne contaminants.

Good general ventilation should be sufficient to control worker

Emissions from ventilation or work process equipment should be

checked to ensure they comply with the requirements of



# Geon™ MM555 CUFFING PLASTISOL 17-OZ

Version Number 1.5 Revision Date 05/25/2018 Page 8 of 19 Print Date 06/08/2018

filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

### **Skin protection**

**Hand protection** 

chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Body protection** 

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** 

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

# Section 9. Physical and chemical properties

#### **Appearance**



# Geon™ MM555 CUFFING PLASTISOL 17-OZ

Version Number 1.5 Page 9 of 19 Revision Date 05/25/2018 Print Date 06/08/2018

liquid [liquid] Physical state

TAN Color

Not available. Odor **Odor threshold** Not available. Not available. рH **Melting point** Not available. **Boiling point** Not available. Flash point Not available. **Burning time** Not available. **Burning rate** Not available. **Evaporation rate** Not available. Flammability (solid, gas) Not available.

Lower and upper explosive Lower: Not available. **Upper:** Not available. (flammable) limits

Not available. Vapor pressure Not available. Vapor density **Relative density** Not available. Not available. **Solubility** Solubility in water Not available. Partition coefficient: n-Not available.

octanol/water

products

**Auto-ignition temperature** Not available. **Decomposition temperature** Not available. **SADT** Not available.

**Dynamic:** Not available. Viscosity

**Kinematic:** Not available.

# Section 10. Stability and reactivity

Reactivity No specific test data related to reactivity available for this product or

its ingredients.

**Chemical stability** Stable under recommended storage and handling conditions (see

Section 7).

Under normal conditions of storage and use, hazardous reactions will Possibility of hazardous reactions

not occur.

Conditions to avoid Keep away from extreme heat and oxidizing agents.

Avoid contact with acetal homopolymers and acetyl homopolymers **Incompatible materials** 

during processing.

Under normal conditions of storage and use, hazardous decomposition **Hazardous decomposition** 

products should not be produced.

# Section 11. Toxicological information



# Geon™ MM555 CUFFING PLASTISOL 17-OZ

Version Number 1.5 Revision Date 05/25/2018 Page 10 of 19 Print Date 06/08/2018

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

### **Information on toxicological effects**

#### **Acute toxicity**

Result	Species	Dose	Exposure		
No applicable toxicity data					
No applicable toxic	city data				
No applicable toxic	city data				
ted heavy					
LD50 Oral	Rat	6,000 mg/kg	-		
LC50 Inhalation	Rat	8.5 Mg/l	4 h		
No applicable toxic	city data				
No applicable toxic					
LC50 Inhalation	LC50 Inhalation Rat - Male 6.82 Mg/l 4 h				
LD50 Dermal	Rabbit	> 5,000 mg/kg	-		
unds					
No applicable toxic	city data				
No applicable toxic	No applicable toxicity data				
No applicable toxic	No applicable toxicity data				
No applicable toxic	city data				
No applicable toxicity data					
No applicable toxicity data					
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich					
LD50 Oral Rat 10,000 mg/kg -					
No applicable toxic	No applicable toxicity data				
	No applicable toxicity data				
	No applicable toxic No applicable toxic No applicable toxic ted heavy LD50 Oral LC50 Inhalation No applicable toxic LC50 Inhalation LD50 Dermal unds No applicable toxic	No applicable toxicity data No applicable toxicity data ted heavy LD50 Oral Rat LC50 Inhalation Rat No applicable toxicity data  No applicable toxicity data LC50 Inhalation Rat - Male LD50 Dermal Rabbit unds No applicable toxicity data	No applicable toxicity data No applicable toxicity data ted heavy  LD50 Oral Rat 6,000 mg/kg LC50 Inhalation Rat 8.5 Mg/l  No applicable toxicity data  No applicable toxicity data  LC50 Inhalation Rat - Male 6.82 Mg/l  LD50 Dermal Rabbit > 5,000 mg/kg  unds  No applicable toxicity data  No applicable toxicity data		

**Conclusion/Summary**: Mixture.Not fully tested.

### **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
Titanium dioxide	Skin - Mild irritant	Human		72 hrs	-
1,2-Benzenedicarboxylic	Eyes - Mild	Rabbit			
acid, di-C8-10-branched	irritant				
alkyl esters, C9-rich					

Conclusion/Summary

Skin: Mixture.Not fully tested.Eyes: Mixture.Not fully tested.



# Geon™ MM555 CUFFING PLASTISOL 17-OZ

Version Number 1.5 Page 11 of 19 Revision Date 05/25/2018 Print Date 06/08/2018

**Respiratory**: Mixture.Not fully tested.

**Sensitization** 

Conclusion/Summary

SkinMixture.Not fully tested.RespiratoryMixture.Not fully tested.

**Mutagenicity** 

Conclusion/Summary : Mixture.Not fully tested.

Carcinogenicity

Conclusion/Summary : Mixture. Not fully tested.

Classification

Product/ingredient name	OSHA	IARC	NTP
Titanium dioxide		2B	

#### **Reproductive toxicity**

**Conclusion/Summary** : Mixture. Not fully tested.

**Teratogenicity** 

**Conclusion/Summary**: Mixture.Not fully tested.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Calcium oxide	Category 3		Respiratory tract irritation

# **Specific target organ toxicity (repeated exposure)**

Not available.

**Aspiration hazard** 

Product/ingredient name	Result
Distillates (petroleum), hydrotreated light	ASPIRATION HAZARD - Category 1
Naphtha, petroleum, hydrotreated heavy	ASPIRATION HAZARD - Category 1

Information on likely routes of

exposure

Not available.

#### Potential acute health effects



# Geon™ MM555 CUFFING PLASTISOL 17-OZ

Version Number 1.5 Page 12 of 19 Revision Date 05/25/2018 Print Date 06/08/2018

**Eye contact** : Causes serious eye irritation.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact** : May cause an allergic skin reaction.

**Ingestion**: No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:

pain or irritation

watering

redness

**Inhalation** : No specific data.

**Skin contact** : Adverse symptoms may include the following:

irritation redness

reditess

**Ingestion** : No specific data.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

**Long term exposure** 

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Potential chronic health effects

**Conclusion/Summary** : Mixture.Not fully tested.

**General**: Once sensitized, a severe allergic reaction may occur when

subsequently exposed to very low levels.

Carcinogenicity: No known significant effects or critical hazards.Mutagenicity: No known significant effects or critical hazards.Teratogenicity: No known significant effects or critical hazards.Developmental effects: No known significant effects or critical hazards.Fertility effects: No known significant effects or critical hazards.

#### Numerical measures of toxicity

#### **Acute toxicity estimates**



# Geon™ MM555 CUFFING PLASTISOL 17-OZ

Version Number 1.5 Revision Date 05/25/2018 Page 13 of 19 Print Date 06/08/2018

Route	ATE value
Inhalation (vapors)	321.2 mg/l

# Section 12. Ecological information

# **Toxicity**

Product/ingredient name	Result	Species	Exposure			
Distillates (petroleum), hydroti	treated light					
	Acute LC50 2.2 Mg/l Fresh water Fish - Fish 96 h					
Remarks - Acute - Fish:	Acute					
Remarks - Acute - Aquatic	No applicable toxicity data					
invertebrates.:						
Remarks - Acute - Aquatic	No applicable toxicity data					
plants:						
Remarks - Chronic - Fish:	No applicable toxicity data					
Remarks - Chronic -	No applicable toxicity data					
Aquatic invertebrates.:						
Naphtha, petroleum, hydrotrea						
Remarks - Acute - Fish:	No applicable toxicity data					
Remarks - Acute - Aquatic	No applicable toxicity data					
invertebrates.:						
Remarks - Acute - Aquatic	No applicable toxicity data	No applicable toxicity data				
plants:						
Remarks - Chronic - Fish:	No applicable toxicity data					
Remarks - Chronic -	No applicable toxicity data					
Aquatic invertebrates.:						
Titanium dioxide		T				
	Acute LC50 > 1,000 Mg/l Marine water	Fish - Fish	96 h			
Remarks - Acute - Fish:	Acute					
	Acute LC50 3 Mg/l Fresh water	Aquatic invertebrates. Crustaceans	48 h			
Remarks - Acute - Aquatic invertebrates.:	Acute					
	Acute LC50 6.5 Mg/l Fresh water	Aquatic invertebrates. Daphnia	48 h			
Remarks - Acute - Aquatic invertebrates.:	Acute					
Remarks - Acute - Aquatic plants:	No applicable toxicity data					



# Geon™ MM555 CUFFING PLASTISOL 17-OZ

Version Number 1.5 Revision Date 05/25/2018 Page 14 of 19 Print Date 06/08/2018

Remarks - Chronic - Fish:	No applicable toxicity data				
Remarks - Chronic -	No applicable toxicity data	** v			
Aquatic invertebrates.:	No applicable toxicity data				
Proprietary Hazardous Compo	l unde				
Remarks - Acute - Fish:	No applicable toxicity data				
	11				
Remarks - Acute - Aquatic invertebrates.:	No applicable toxicity data				
	No appliachla tovicity data				
Remarks - Acute - Aquatic	No applicable toxicity data				
plants:	No applicable topicite data				
Remarks - Chronic - Fish:	No applicable toxicity data				
Remarks - Chronic -	No applicable toxicity data				
Aquatic invertebrates.: Calcium oxide					
	NT 1' 11 . ' ' . 1 .				
Remarks - Acute - Fish:	No applicable toxicity data				
Remarks - Acute - Aquatic	No applicable toxicity data				
invertebrates.:	N. 1. 11				
Remarks - Acute - Aquatic	No applicable toxicity data				
plants:					
	Chronic NOEC 100 Mg/l Fresh	Fish - Fish	46 d		
	water				
Remarks - Chronic - Fish:	Chronic				
Remarks - Chronic -	No applicable toxicity data				
Aquatic invertebrates.:	1. 00 10 1 1 1 1 1	• 1			
	1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich				
Remarks - Acute - Fish:	No applicable toxicity data				
Remarks - Acute - Aquatic	No applicable toxicity data				
invertebrates.:					
Remarks - Acute - Aquatic	No applicable toxicity data				
plants:					
Remarks - Chronic - Fish:	No applicable toxicity data				
Remarks - Chronic -	No applicable toxicity data				
Aquatic invertebrates.:					
Conclusion/Summary	: Not available.				

Persistence and degradability

**Conclusion/Summary** : Not available.

# **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Naphtha (petroleum), hydrotreated	-	10.00 - 2,500.00	high



# Geon™ MM555 CUFFING PLASTISOL 17-OZ

Version Number 1.5 Page 15 of 19 Revision Date 05/25/2018 Print Date 06/08/2018

heavy			
Calcium oxide	-	2.34	low
1,2-Benzenedicarboxylic acid, di-C8-	8.8	3.00	low
10-branched alkyl esters, C9-rich			

#### **Mobility in soil**

Soil/water partition coefficient

(KOC)

Other adverse effects

Not available.

No known significant effects or critical hazards.

# **Section 13. Disposal considerations**

**Disposal methods** 

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

<u>United States - RCRA Acute hazardous waste "P" List:</u> Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

# **Section 14. Transport information**

U.S.DOT 49CFR Ground/Air/Water : Not regulated for transportation.

International Air

: Consult mode specific transport rules

ICAO/IATA

International Water : Consult mode specific transport rules



### Geon™ MM555 CUFFING PLASTISOL 17-OZ

Version Number 1.5 Revision Date 05/25/2018 Page 16 of 19 Print Date 06/08/2018

IMO/IMDG

# Section 15. Regulatory information

U.S. Federal regulations

United States - TSCA 12(b) - Chemical export notification: None of the components are listed.

United States - TSCA 4(a) - ITC Priority list: Not listed United States - TSCA 4(f) - Priority risk review: Not listed United States - TSCA 5(a)2 - Final significant new use rules: Listed 4-Nonylphenol, branched

United States - TSCA 5(a)2 - Proposed significant new use rules: Not listed

United States - TSCA 5(e) - Substances consent order: Not listed United States - TSCA 6 - Final risk management: Not listed United States - TSCA 6 - Proposed risk management: Not listed United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined

United States - TSCA 8(a) - Preliminary assessment report (PAIR): Listed 4-Nonylphenol, branched

United States - TSCA 8(d) - Health and safety studies: Not listed United States - TSCA 4(a) - Final Test Rules: Listed Diisononyl phthalate

1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich

United States - TSCA 4(a) - Proposed test rules: Not listed United States - TSCA 8(c) - Significant adverse reaction (SAR): Not listed

United States - EPA Clean water act (CWA) section 307 - Priority pollutants: Listed 2-Ethylhexanoic acid zinc salt
Phenol

Vinyl chloride monomer

United States - EPA Clean water act (CWA) section 311 -

Hazardous substances: Listed

United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Flammable substances: Not listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Toxic substances: Not listed

**United States - Department of commerce - Precursor chemical:** 



# Geon™ MM555 CUFFING PLASTISOL 17-OZ

Version Number 1.5 Revision Date 05/25/2018 Page 17 of 19 Print Date 06/08/2018

Not listed

Clean Air Act Section 112(b)

Hazardous Air Pollutants (HAPs)

Listed

Not listed

Clean Air Act Section 602 Class I Substances

Clean Air Act Section 602 Class II

Not listed

**Substances** 

**DEA List I Chemicals (Precursor** 

Not listed

**Chemicals**)

**DEA List II Chemicals (Essential** 

Not listed

Chemicals)

#### US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

**SARA 311/312** 

Classification : Immediate (acute) health hazard

# **Composition/information on ingredients**

Name	%	Classification
Distillates (petroleum),	1 - 3	F, AH
hydrotreated light		
Naphtha, petroleum, hydrotreated	1 - 3	F, AH
heavy		
Titanium dioxide	0.3 - 1	СН
Proprietary Hazardous	0 - 0.3	F, AH, CH
Compounds		
Calcium oxide	1 - 2.9	AH
1,2-Benzenedicarboxylic acid, di-	5 - 10	AH
C8-10-branched alkyl esters, C9-		
rich		

#### **SARA 313**

Not applicable.

**State regulations** 

Massachusetts: None of the components are listed.New York: None of the components are listed.New Jersey: The following components are listed:

Titanium dioxide



# Geon™ MM555 CUFFING PLASTISOL 17-OZ

Version Number 1.5 Revision Date 05/25/2018 Page 18 of 19 Print Date 06/08/2018

Calcium oxide Barium sulfate

Ethene, chloro-, homopolymer
The following components are list.

**Pennsylvania**: The following components are listed:

Barium sulfate

Calcium oxide

Titanium dioxide

#### California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

United States inventory (TSCA 8b) : All components are listed or exempted.

**Canada inventory** : All components are listed or exempted.

# **International regulations**

#### **Inventory list**

Australia : Not determined.

**Canada** : All components are listed or exempted.

China Not determined. **Europe inventory** Not determined. Japan Not determined. **New Zealand** Not determined. **Philippines** Not determined. Republic of Korea Not determined. Not determined. **Taiwan** Turkey Not determined.

**United States** : All components are listed or exempted.

# Section 16. Other information

### **Hazardous Material Information System (U.S.A.)**

Flammability	0
Physical hazards	0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required



# Geon™ MM555 CUFFING PLASTISOL 17-OZ

Version Number 1.5 Revision Date 05/25/2018

Page 19 of 19 Print Date 06/08/2018

on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

#### **History**

**Date of printing** 06/08/2018 Date of issue/Date of revision 05/25/2018 Date of previous issue 05/17/2017

Version 1.5

**Key to abbreviations** ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine

pollution)

UN = United Nations

References Not available.

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.