

# X GT-17268-3B

Version Number 1.0 Revision Date 07/27/2016 Page 1 of 16 Print Date 07/28/2016

# SAFETY DATA SHEET

#### X GT-17268-3B

# **Section 1. Identification**

**GHS** product identifier : X GT-17268-3B

Chemical name: MixtureCAS number: MixtureOther means of identification: EM10039326

**Product type** : solid

Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Industrial applications. Plastics.

Supplier's details : POLYONE CORPORATION

33587 Walker Road, Avon Lake, OH 44012

1 (440) 930-1000 or 1 (866) POLYONE

Emergency telephone number

(with hours of operation)

CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or

accident).

# Section 2. Hazards identification

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status : While this material is not considered hazardous by the OSHA Hazard

Communication Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available for employees and

other users of this product.

Classification of the substance or

mixture

Not classified.

**GHS** label elements

Signal word : No signal word.

1/16



# X GT-17268-3B

Version Number 1.0 Page 2 of 16 Revision Date 07/27/2016 Print Date 07/28/2016

**Hazard statements**: No known significant effects or critical hazards.

#### **Precautionary statements**

General : Not applicable.
Prevention : Not applicable.
Response : Not applicable.
Storage : Not applicable.
Disposal : Not applicable.
Supplemental label elements : None known.
Hazards not otherwise classified : None known.

# Section 3. Composition/information on ingredients

Substance/mixture: MixtureChemical name: MixtureOther means of identification: EM10039326

### **CAS** number/other identifiers

Ingredient name	9/	<mark>%</mark>	CAS number
Copper	7.	75 - 90	7440-50-8
Tungsten	1	10 - 25	7440-33-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

# Section 4. First aid measures

#### Description of necessary first aid measures

**Eye contact**: Immediately flush eyes with plenty of water, occasionally lifting the

upper and lower eyelids. Check for and remove any contact lenses.



# X GT-17268-3B

Version Number 1.0 Page 3 of 16 Revision Date 07/27/2016 Print Date 07/28/2016

Get medical attention if irritation occurs.

**Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable

for breathing. Get medical attention if symptoms occur. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical

surveillance for 48 hours.

**Skin contact**: Flush contaminated skin with plenty of water. Remove contaminated

clothing and shoes. Get medical attention if symptoms occur.

**Ingestion** : Wash out mouth with water. Remove victim to fresh air and keep at

rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by

medical personnel. Get medical attention if symptoms occur.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

Eye contact: No known significant effects or critical hazards.Inhalation: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

Eye contact: No specific data.Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms

may be delayed. The exposed person may need to be kept under

medical surveillance for 48 hours.

**Specific treatments** : No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without

suitable training.

See toxicological information (Section 11)

# Section 5. Fire-fighting measures



# X GT-17268-3B

Version Number 1.0 Revision Date 07/27/2016

Page 4 of 16 Print Date 07/28/2016

### Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media In case of fire, use water spray (fog), foam, dry chemical or CO<sub>2</sub>.

None known.

Specific hazards arising from the chemical

**Hazardous thermal** decomposition products Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Decomposition products may include the following materials:

carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides

Special protective actions for firefighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any

personal risk or without suitable training.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece operated

in positive pressure mode.

# Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

No action shall be taken involving any personal risk or without For non-emergency personnel

> suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.

If specialised clothing is required to deal with the spillage, take note of For emergency responders any information in Section 8 on suitable and unsuitable materials. See

also the information in "For non-emergency personnel".

Avoid dispersal of spilled material and runoff and contact with soil, **Environmental precautions** 

> waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment

if released in large quantities.

### Methods and materials for containment and cleaning up

Small spill Move containers from spill area. Vacuum or sweep up material and

place in a designated, labeled waste container. Dispose of via a

licensed waste disposal contractor.

Move containers from spill area. Prevent entry into sewers, water Large spill

courses, basements or confined areas. Vacuum or sweep up material



# X GT-17268-3B

Version Number 1.0 Revision Date 07/27/2016 Page 5 of 16 Print Date 07/28/2016

and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

### Precautions for safe handling

**Protective measures** 

Put on appropriate personal protective equipment (see Section 8).

Avoid release to the environment.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

# Section 8. Exposure controls/personal protection

#### **Control parameters**

### Occupational exposure limits

Ingredient name	Exposure limits	
Copper	OSHA PEL 1989 (1989-03-01) expressed as Cu	
	PEL: Permissible Exposure Level 0.1 mg/m3 Form: Fume	
	<b>PEL: Permissible Exposure Level</b> 1 mg/m3 Form: Dusts and mists	
	OSHA PEL (1993-06-30)	
	PEL: Permissible Exposure Level 0.1 mg/m3 Form: Fume	
	<b>PEL: Permissible Exposure Level</b> 1 mg/m3 Form: Dusts and mists	
	NIOSH REL (1994-06-01) expressed as Cu	
	Time Weighted Average (TWA) 1 mg/m3 Form: Dusts and mists	
	ACGIH TLV (1994-09-01)	
	TLV-TWA: Threshold Limit Value - Time weighted average PEL:	
	Permissible Exposure Level 0.2 mg/m3 Form: Fume	
	ACGIH TLV (1994-09-01) expressed as Cu	



# X GT-17268-3B

Version Number 1.0 Revision Date 07/27/2016 Page 6 of 16 Print Date 07/28/2016

Tungsten    NIOSH REL (1994-06-01) expressed as W   Time Weighted Average (TWA) 5 mg/m3   Short Term Exposure Limit value for a 15-minute reference period expressed in parts per million or in mg/m3. 10 mg/m3   ACGIH TLV (1994-09-01) expressed as W   TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 5 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3    Appropriate engineering controls   Good general ventilation should be sufficient to control worker exposure to airborne contaminants.   Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.  Individual protection measures   Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.   Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.  Skin protection   Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.			TLV-TWA: Threshold Limit Value - Time weighted average PEL:
Time Weighted Average (TWA) 5 mg/m3   Short Term Exposure Limit value for a 15-minute reference period expressed in parts per million or in mg/m3. 10 mg/m3   ACGIH TLV (1994-09-01) expressed as W   TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 5 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3      Appropriate engineering controls   Good general ventilation should be sufficient to control worker exposure to airborne contaminants.   Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.			
Time Weighted Average (TWA) 5 mg/m3   Short Term Exposure Limit value for a 15-minute reference period expressed in parts per million or in mg/m3. 10 mg/m3   ACGIH TLV (1994-09-01) expressed as W   TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 5 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3      Appropriate engineering controls   Good general ventilation should be sufficient to control worker exposure to airborne contaminants.   Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.			
Time Weighted Average (TWA) 5 mg/m3   Short Term Exposure Limit value for a 15-minute reference period expressed in parts per million or in mg/m3. 10 mg/m3   ACGIH TLV (1994-09-01) expressed as W   TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 5 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3      Appropriate engineering controls   Good general ventilation should be sufficient to control worker exposure to airborne contaminants.   Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.	Typegeton		NIOCH DEL (1004 04 01) armyogod og W
Short Term Exposure Limit value for a 15-minute reference period expressed in parts per million or in mg/m3. 10 mg/m3   ACGHI TLV (1994-09-01) expressed as W   TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 5 mg/m3   TLV-TWEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3    Appropriate engineering controls   Good general ventilation should be sufficient to control worker exposure to airborne contaminants.   Emvironmental exposure controls   Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.  Individual protection measures   Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.  Eye/face protection   Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.  Skin protection   Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.  Body protection   Personal protective equipment for the body should be selected based	Tungsten		
Period expressed in parts per million or in mg/m3. 10 mg/m3   ACGIH TLV (1994-09-01) expressed as W   TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 5 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3			
Appropriate engineering controls  Individual protection measures  Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewear complying with an approved standard should be used when a risk assessment indicates a higher degree of protection:  Skin protection  Hand protection  Eversonal Protection  Chemical-resistant, impervious gloves complying with an approved standard should be ween the little is necessary.  Personal protective equipment for the body should be selected based personal protective equipment for the body should be selected based personal protective equipment for the body should be selected based personal protective equipment for the body should be selected based personal protective equipment for the body should be selected based personal protective equipment for the body should be selected based personal protective equipment for the body should be selected based personal protective equipment for the body should be selected based personal protective equipment for the body should be selected based personal protective equipment for the body should be selected based personal protective equipment for the body should be selected based personal protective equipment for the body should be selected based personal protective equipment for the body should be selected based personal protective equipment for the body should be selected based personal protective equipment for the body should be selected based personal protective equipment for the body should be selected based personal protective equipment for the body should be selected based personal protective equipment for the body should be selected based personal protective equipment for the body should be selected based personal protective equipment for the body should be selected based personal protective equipmen			
TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 5 mg/m3 TLV-TWA: Threshold Limit Value - Short Time Exposure Level 10 mg/m3  Environmental exposure controls  Cood general ventilation should be sufficient to control worker exposure to airborne contaminants.  Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.  Individual protection measures  Hygiene measures  Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.  Eye/face protection  Eye/face protection  Safety eyeware complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.  Skin protection  Hand protection  : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.  Body protection  : Personal protective equipment for the body should be selected based			
Permissible Exposure Level 5 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure Level 10 mg/m3   TLV-STEL: Threshold Limit Value - Short Time Exposure to literation on work process equipment should be used, unless the lavess full be checked to ensure the reposure to my literation on some cases, fume scrubbers, filters or engineering modifications to the process equipment should be used to ensure the products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Before eating, smoking and using the handling chemical products in should be used. The should be used to remove potentially			
Appropriate engineering controls  Environmental exposure controls  Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.  Individual protection measures  Hygiene measures  : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.  Eye/face protection  : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.  Skin protection  Hand protection  : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.  Body protection  : Personal protective equipment for the body should be selected based			
Appropriate engineering controls  Environmental exposure controls  Environmental exposure controls  Environmental exposure controls  Environmental exposure controls  Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.  Individual protection measures  Hygiene measures  : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.  Eye/face protection  Eye/face protection  Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.  Skin protection  Hand protection  : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.  Personal protective equipment for the body should be selected based			TLV-STEL: Threshold Limit Value - Short Time Exposure Level
exposure to airborne contaminants.  Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.  Individual protection measures  Hygiene measures  : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.  Eye/face protection  : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.  Skin protection  Hand protection  : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.  Body protection  : Personal protective equipment for the body should be selected based			10 mg/m3
exposure to airborne contaminants.  Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.  Individual protection measures  Hygiene measures  : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.  Eye/face protection  : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.  Skin protection  Hand protection  : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.  Body protection  : Personal protective equipment for the body should be selected based			
Environmental exposure controls  Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.  Individual protection measures  Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.  Eye/face protection  Eye/face protection  Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.  Skin protection  Hand protection  Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.  Personal protective equipment for the body should be selected based	Appropriate engineering controls	:	
checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.  Individual protection measures  : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.  Eye/face protection  : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.  Skin protection  Hand protection  : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.  Body protection  : Personal protective equipment for the body should be selected based			
environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.    Individual protection measures	Environmental exposure controls	:	
filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.  Individual protection measures  Hygiene measures  : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.  Eye/face protection  : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.  Skin protection  : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.  Body protection  : Personal protective equipment for the body should be selected based			
Individual protection measures  Hygiene measures  : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.  Eye/face protection  : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.  Skin protection  Hand protection  : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.  Body protection  : Personal protective equipment for the body should be selected based			
Hygiene measures   Section 1			
Hygiene measures  : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.  Eye/face protection  : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.  Skin protection  : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.  Body protection : Personal protective equipment for the body should be selected based			necessary to reduce emissions to acceptable levels.
products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.  Eye/face protection  : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.  Skin protection  : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.  Body protection : Personal protective equipment for the body should be selected based	Individual protection measures		
products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.  Eye/face protection  : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.  Skin protection  : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.  Body protection : Personal protective equipment for the body should be selected based	Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical
of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.  Eye/face protection  : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.  Skin protection  Hand protection  : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.  Body protection  : Personal protective equipment for the body should be selected based	, g		
clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.  Eye/face protection:  Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.  Skin protection:  Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.  Body protection:  Personal protective equipment for the body should be selected based			
showers are close to the workstation location.  Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.  Skin protection  : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.  Body protection: Personal protective equipment for the body should be selected based			
<ul> <li>Eye/face protection         <ul> <li>Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.</li> </ul> </li> <li>Skin protection         <ul> <li>Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.</li> </ul> </li> <li>Body protection         <ul> <li>Personal protective equipment for the body should be selected based</li> </ul> </li> </ul>			
when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.  Skin protection  : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.  Body protection: Personal protective equipment for the body should be selected based			
liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.  Skin protection  : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.  Body protection: Personal protective equipment for the body should be selected based	Eye/face protection	:	
following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.  Skin protection  : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.  Body protection : Personal protective equipment for the body should be selected based			
higher degree of protection: safety glasses with side-shields.  Skin protection  Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.  Body protection: Personal protective equipment for the body should be selected based			
Skin protection         Hand protection       : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.         Body protection       : Personal protective equipment for the body should be selected based			
Hand protection  : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.  Body protection  : Personal protective equipment for the body should be selected based			nigher degree or protection, safety grasses with side-shields.
standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.  Body protection:  Personal protective equipment for the body should be selected based	Skin protection		
standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.  Body protection:  Personal protective equipment for the body should be selected based	Hand protection	•	Chemical-resistant impervious gloves complying with an approved
if a risk assessment indicates this is necessary.  Body protection: Personal protective equipment for the body should be selected based	Tuna processi	•	
Body protection : Personal protective equipment for the body should be selected based			· · · · · · · · · · · · · · · · · · ·
	<b>Body protection</b>	:	
6 L 1111 1111 1111 1111 1111 1111 11			on the task being performed and the risks involved and should be
approved by a specialist before handling this product.			
Other skin protection : Appropriate footwear and any additional skin protection measures	Other skin protection	:	Appropriate footwear and any additional skin protection measures



# X GT-17268-3B

Version Number 1.0 Revision Date 07/27/2016 Page 7 of 16 Print Date 07/28/2016

should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this

product.

**Respiratory protection**: Use a properly fitted, particulate filter respirator complying with an

approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the

selected respirator.

# Section 9. Physical and chemical properties

#### **Appearance**

**Physical state** solid [Pellets.] Color **BLACK** Odor Faint odor. **Odor threshold** Not available. pН Not available. Not available. **Melting point Boiling** point Not available. Flash point Not available. **Burning time** Not available. **Burning rate** Not available. **Evaporation rate** Not available. Flammability (solid, gas) Not available.

Lower and upper explosive : Lower: Not available. (flammable) limits : Upper: Not available.

Vapor pressure

Vapor density

Relative density

Solubility

Solubility in water

Not available.

Not available.

Not available.

insoluble in water.

**Partition coefficient: n-** : Not available.

octanol/water

Auto-ignition temperature: Not available.Decomposition temperature: Not available.SADT: Not available.

Viscosity : Dynamic: Not available.

Kinematic: Not available.

# Section 10. Stability and reactivity

**Reactivity**: No specific test data related to reactivity available for this product or



X GT-17268-3B

Version Number 1.0 Page 8 of 16 Revision Date 07/27/2016 Print Date 07/28/2016

its ingredients.

Chemical stability : Stable under recommended storage and handling conditions (see

Section 7).

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will

not occur

**Conditions to avoid** : Keep away from extreme heat and oxidizing agents.

**Incompatible materials** : Keep away from strong acids.

Oxidizer.

**Hazardous decomposition** : Under normal conditions of storage and use, hazardous decomposition

products should not be produced.

# Section 11. Toxicological information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### **Information on toxicological effects**

#### **Acute toxicity**

products

Product/ingredient name	Result	Species	Dose	Exposure
Copper	_			
	LD50 Oral	Rat	482 mg/kg	-

**Conclusion/Summary** : Mixture. Not fully tested.

#### **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
Tungsten	Eyes - Mild irritant	Rabbit		24 hrs	-
	Skin - Mild irritant	Rabbit		24 hrs	-

**Conclusion/Summary** 

Skin: Mixture.Not fully tested.Eyes: Mixture.Not fully tested.Respiratory: Mixture.Not fully tested.

Sensitization

**Conclusion/Summary** 

Skin: Mixture.Not fully tested.Respiratory: Mixture.Not fully tested.

**Mutagenicity** 



# X GT-17268-3B

Version Number 1.0 Page 9 of 16 Print Date 07/28/2016 Revision Date 07/27/2016

Mixture.Not fully tested. **Conclusion/Summary** 

**Carcinogenicity** 

**Conclusion/Summary** Mixture. Not fully tested.

**Reproductive toxicity** 

Mixture.Not fully tested. **Conclusion/Summary** 

**Teratogenicity** 

Mixture.Not fully tested. **Conclusion/Summary** 

Specific target organ toxicity (single exposure)

Not available.

**Specific target organ toxicity (repeated exposure)** 

Not available.

**Aspiration hazard** 

Not available.

exposure

Information on the likely routes of

Not available.

Potential acute health effects

Eye contact No known significant effects or critical hazards. Inhalation No known significant effects or critical hazards. No known significant effects or critical hazards. **Skin contact** No known significant effects or critical hazards. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact No specific data. Inhalation No specific data. No specific data. Skin contact **Ingestion** No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Not available. **Potential immediate effects** 



# X GT-17268-3B

 Version Number 1.0
 Page 10 of 16

 Revision Date 07/27/2016
 Print Date 07/28/2016

**Potential delayed effects** : Not available.

**Long term exposure** 

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

**Conclusion/Summary**: Mixture.Not fully tested.

General:No known significant effects or critical hazards.Carcinogenicity:No known significant effects or critical hazards.Mutagenicity:No known significant effects or critical hazards.Teratogenicity:No known significant effects or critical hazards.Developmental effects:No known significant effects or critical hazards.Fertility effects:No known significant effects or critical hazards.

# Numerical measures of toxicity

#### **Acute toxicity estimates**

Not available.

# Section 12. Ecological information

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
Copper			
	Acute LC50 16 μg/l Fresh water	Fish - Fish	96 h
	Acute LC50 9.4 µg/l Fresh water	Fish - Fish	96 h
	Acute LC50 10.3 µg/l Fresh water	Fish - Fish	96 h
	Acute LC50 7.56 μg/l Marine	Fish - Fish	96 h
	water		
	Acute LC50 8.7 µg/l Fresh water	Fish - Fish	96 h
	Acute EC50 3.1 µg/l Fresh water	Aquatic invertebrates.	48 h
		Daphnia	
	Acute EC50 2.1 µg/l Fresh water	Aquatic invertebrates.	48 h
		Daphnia	
	Acute EC50 2.5 µg/l Fresh water	Aquatic invertebrates.	48 h
		Daphnia	



# X GT-17268-3B

Version Number 1.0 Revision Date 07/27/2016 Page 11 of 16 Print Date 07/28/2016

Acute EC50 3.2 μg/l Fresh water	Aquatic invertebrates.	48 h
Neute Le30 3.2 μg/11 resii watei	Daphnia	40 II
Acute EC50 1.6 µg/l Fresh water	Aquatic invertebrates.	48 h
	Crustaceans	
Acute LC50 0.072 μg/l Marine	Aquatic invertebrates.	48 h
water	Crustaceans	
Acute EC50 1 µg/l Fresh water	Aquatic invertebrates.	48 h
	Crustaceans	40.1
Acute EC50 1.6 μg/l Fresh water	Aquatic invertebrates.	48 h
A FO50 1 6 // For all	Crustaceans	40.1
Acute EC50 1.6 μg/l Fresh water	Aquatic invertebrates. Crustaceans	48 h
Acute LC50 3.1 μg/l Fresh water	Aquatic invertebrates.	48 h
Acute LC30 3.1 µg/1 Fresh water	Daphnia	46 11
Acute EC50 18 µg/l Marine water	Aquatic plants - Algae	72 h
Acute IC50 16 µg/l Fresh water	Aquatic plants - Algae  Aquatic plants - Algae	72 h
Acute EC50 18 µg/1 Fresh water	Aquatic plants - Algae  Aquatic plants - Algae	72 h
Acute IC50 13 µg/l Fresh water	Aquatic plants - Algae  Aquatic plants - Algae	72 h
Acute IC50 18 μg/l Hesh water  Acute IC50 18 μg/l Marine water	Aquatic plants - Algae  Aquatic plants - Algae	72 h
Acute EC50 1,100 μg/l Fresh water	Aquatic plants - Aigac  Aquatic plants -	96 h
Acute Le30 1,100 μg/111esh water	Aquatic plants  Aquatic plants	70 II
Acute IC50 5.4 mg/l Marine water	Aquatic plants -	72 h
ricute 1050 5.1 mg/1 Marine water	Aquatic plants	7211
Acute NOEC 2.5 μg/l Marine water	Aquatic plants - Algae	3 d
Acute NOEC 3 μg/l Marine water	Aquatic plants - Algae	3 d
Acute NOEC 3.2 μg/l Fresh water	Aquatic plants - Algae	3 d
Acute NOEC 0.013 mg/l Marine	Aquatic plants - Algae	4 d
water	7 · · · · · · · · · · · · · · · · · · ·	
Acute NOEC 7 mg/l Fresh water	Aquatic plants -	3 d
	Aquatic plants	
Acute EC10 0.032 mg/l Marine	Aquatic plants - Algae	4 d
water		
Chronic NOEC 1.7 µg/l Fresh	Fish - Fish	28 d
water		
Chronic NOEC 0.8 µg/l Fresh	Fish - Fish	42 d
water		
Chronic NOEC 1.2 µg/l Fresh	Fish - Fish	42 d
water		
Chronic NOEC 0.8 µg/l Fresh	Fish - Fish	42 d
water	D' 1 D' 1	42.1
Chronic NOEC 0.8 µg/l Fresh	Fish - Fish	42 d
water	A	21.1
Chronic NOEC 30.3 µg/l Fresh	Aquatic invertebrates.	21 d
water Chronic NOEC 15 µg/l Fresh water	Daphnia Aquatic invertebrates.	21 d
 Chronic NOEC 15 µg/1 Fresh water	Aquatic invertebrates.	21 U



# X GT-17268-3B

Version Number 1.0 Revision Date 07/27/2016 Page 12 of 16 Print Date 07/28/2016

		Daphnia	
	Chronic NOEC 2 µg/l Fresh water	Aquatic invertebrates.	21 d
		Daphnia	
	Chronic NOEC 29.4 µg/l Fresh	Aquatic invertebrates.	21 d
	water	Daphnia	
	Chronic NOEC 31.8 µg/l Fresh	Aquatic invertebrates.	21 d
	water	Daphnia	
	Chronic NOEC 0.02 mg/l Fresh	Aquatic invertebrates.	21 d
	water	Crustaceans	
X GT-17268-3B			
Remarks - Acute - Aquatic	Chemicals are not readily available a	s they are bound within the	polymer matrix.
invertebrates.:	-	-	

Conclusion/Summary

: Chemicals are not readily available as they are bound within the

polymer matrix.

Persistence and degradability

**Conclusion/Summary**: Chemicals are not readily available as they are bound within the

polymer matrix.

**Conclusion/Summary**: Chemicals are not readily available as they are bound within the

polymer matrix.

Bioaccumulative potential Mobility in soil

Soil/water partition coefficient (KOC)

Other adverse effects

Not available.

No known significant effects or critical hazards.

# Section 13. Disposal considerations

Disposal methods :

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and



### X GT-17268-3B

Version Number 1.0 Revision Date 07/27/2016 Page 13 of 16 Print Date 07/28/2016

contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

# **Section 14. Transport information**

U.S. DOT Classification : Not regulated for transportation.

ICAO/IATA : Not classified as dangerous good under transport regulations.

IMO/IMDG (maritime) : Not classified as dangerous good under transport regulations.

# Section 15. Regulatory information

**U.S. Federal regulations** 

: United States - TSCA 12(b) - Chemical export notification: None

of the components are listed.

United States - TSCA 4(a) - Final Test Rules: Listed C.I. Solvent

Black 7

United States - TSCA 4(a) - ITC Priority list: Not listed United States - TSCA 4(a) - Proposed test rules: Not listed United States - TSCA 4(f) - Priority risk review: Not listed United States - TSCA 5(a)2 - Final significant new use rules: Not

listed

United States - TSCA 5(a)2 - Proposed significant new use rules:

Not listed

United States - TSCA 5(e) - Substances consent order: Not listed United States - TSCA 6 - Final risk management: Not listed United States - TSCA 6 - Proposed risk management: Not listed United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not

determined

United States - TSCA 8(a) - Preliminary assessment report

(PAIR): Listed Tungsten

**United States - TSCA 8(c) - Significant adverse reaction (SAR):** 

Not listed

United States - TSCA 8(d) - Health and safety studies: Not listed United States - EPA Clean water act (CWA) section 307 - Priority

pollutants: Listed Copper



X GT-17268-3B

Version Number 1.0 Revision Date 07/27/2016 Page 14 of 16 Print Date 07/28/2016

United States - EPA Clean water act (CWA) section 311 -

Hazardous substances: Listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Flammable substances: Not listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Toxic substances: Not listed

**United States - Department of commerce - Precursor chemical:** 

Not listed

Clean Air Act Section 112(b)

Hazardous Air Pollutants (HAPs)

Clean Air Act Section 602 Class I

**Substances** 

Clean Air Act Section 602 Class II

**Substances** 

**DEA List I Chemicals (Precursor** 

Chemicals)

**DEA List II Chemicals (Essential** 

**Chemicals**)

Listed

Not listed

Not listed

Not listed

: Not listed

### US. EPA CERCLA Hazardous Substances (40 CFR 302)

Chemical Name	CAS-No.	RQ for component
Copper	7440-50-8	5,000 lb(s)
		2,270 kg

# SARA 311/312

**Classification** : Not applicable.

### **Composition/information on ingredients**

Name	%	Classification
Tungsten	10 - 25	АН
Copper	75 - 90	АН

#### **SARA 313**

	Product name	CAS number	%
Form R - Reporting	Copper	7440-50-8	75 - 90
requirements			
Supplier notification	Copper	7440-50-8	75 - 90



# X GT-17268-3B

Version Number 1.0 Revision Date 07/27/2016 Page 15 of 16 Print Date 07/28/2016

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

**State regulations** 

Massachusetts : The following components are listed:

Tungsten Copper

**New York** : The following components are listed:

Copper

**New Jersey** : The following components are listed:

Copper Tungsten

**Pennsylvania** : The following components are listed:

Copper

Tungsten

### California Prop. 65

This PolyOne product does not contain any chemical known to the State of California to cause cancer, or birth defects or other reproductive harm, in concentrations that require a warning notice under California's Proposition 65. This statement relies in part on information provided by the buyer of this PolyOne product. PolyOne does not control or have complete knowledge of the end uses to which that buyer or any other entity in the chain of distribution and marketing may put this PolyOne product. Therefore, the buyer of this PolyOne product, each entity that uses this PolyOne product in formulating another product, and each entity in the chain of distribution and marketing of any product that includes the material in this PolyOne product must make its own decision as to giving a Proposition 65 warning.

**United States inventory (TSCA 8b)** : All components are listed or exempted.

**Canada inventory** : All components are listed or exempted.

### **International regulations**

International lists : Australia inventory (AICS): Not determined.

Taiwan inventory (CSNN): All components are listed or exempted.

Malaysia Inventory (EHS Register): Not determined. EINECS: All components are listed or exempted.

Japan inventory: Not determined.

**China inventory (IECSC):** All components are listed or exempted.

**Korea inventory:** All components are listed or exempted.

New Zealand Inventory of Chemicals (NZIoC): All components

are listed or exempted.

Philippines inventory (PICCS): Not determined.

**Chemical Weapons Convention** : Not listed



# X GT-17268-3B

Version Number 1.0 Page 16 of 16 Revision Date 07/27/2016 Print Date 07/28/2016

**List Schedule I Chemicals** 

**Chemical Weapons Convention** : Not listed

List Schedule II Chemicals

**Chemical Weapons Convention** : Not listed

List Schedule III Chemicals

# Section 16. Other information

**History** 

Date of printing: 07/28/2016Date of issue/Date of revision: 07/27/2016Date of previous issue: 00/00/0000

Version : 1.0

**Key to abbreviations** : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of

Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine

pollution)

UN = United Nations

**References** : Not available.

# Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.