

13000WHB WILFLEX OASIS HYDRATE NEUTRAL.

Version Number 1.7 Page 1 of 19 Revision Date 12/04/2017 Print Date 11/28/2018

SAFETY DATA SHEET

13000WHB WILFLEX OASIS HYDRATE NEUTRAL.

Section 1. Identification

GHS product identifier : 13000WHB WILFLEX OASIS HYDRATE NEUTRAL.

Chemical name: MixtureCAS number: MixtureOther means of identification: FO20030419Product type: liquid

Relevant identified uses of the substance or mixture and uses advised against

Product use : Industrial applications. Plastics.

Supplier's details : POLYONE CORPORATION

33587 Walker Road, Avon Lake, OH 44012

1 (440) 930-1000 or 1 (866) POLYONE

Emergency telephone number

(with hours of operation)

CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or

accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard

Communication Standard (29 CFR 1910.1200).

Classification of the substance or

mixture

SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A

GHS label elements



13000WHB WILFLEX OASIS HYDRATE NEUTRAL.

Version Number 1.7 Page 2 of 19 Revision Date 12/04/2017 Print Date 11/28/2018

Hazard pictograms

❖

Signal word : Warning

Hazard statements : Causes serious eye irritation.

Causes skin irritation.

Precautionary statements

General : Not applicable.

Prevention: Wear protective gloves. Wear eye or face protection. Wash hands

thoroughly after handling.

Response : IF ON SKIN: Wash with plenty of soap and water. Take off

contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. If eye irritation persists: Get medical

attention.

Storage:Not applicable.Disposal:Not applicable.Supplemental label elements:None known.Hazards not otherwise classified:None known.

Section 3. Composition/information on ingredients

Substance/mixture:MixtureChemical name:MixtureOther means of identification:FO20030419

CAS number/other identifiers

Ingredient name	%	CAS number
Distillates (petroleum), hydrotreated light	10 - 25	64742-47-8
1,2-Propanediol	0 - 10	57-55-6
Urea	0 - 5	57-13-6



13000WHB WILFLEX OASIS HYDRATE NEUTRAL.

Version Number 1.7 Page 3 of 19 Revision Date 12/04/2017 Print Date 11/28/2018

Paraffin waxes and Hydrocarbon waxes	0 - 3	8002-74-2

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Immediately flush eyes with plenty of water, occasionally lifting the Eye contact upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention. Remove victim to fresh air and keep at rest in a position comfortable Inhalation for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. Skin contact Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse. Ingestion Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If

Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.



13000WHB WILFLEX OASIS HYDRATE NEUTRAL.

Version Number 1.7 Page 4 of 19 Revision Date 12/04/2017 Print Date 11/28/2018

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : No known significant effects or critical hazards.

Skin contact : Causes skin irritation.

Ingestion: No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:

pain or irritation

watering redness

Inhalation : No specific data.

Skin contact: Adverse symptoms may include the following:

irritation redness

Ingestion : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms

may be delayed. The exposed person may need to be kept under

medical surveillance for 48 hours.

Specific treatments : No specific treatment.

Protection of first-aiders: No action shall be taken involving any personal risk or without

suitable training. It may be dangerous to the person providing aid to

give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media

Suitable extinguishing media

In case of fire, use water spray (fog), foam, dry chemical or CO₂.

Unsuitable extinguishing media : None known.

Specific hazards arising from the

chemical

In a fire or if heated, a pressure increase will occur and the container

may burst. Fire water contaminated with this material must be



13000WHB WILFLEX OASIS HYDRATE NEUTRAL.

Version Number 1.7 Revision Date 12/04/2017 Page 5 of 19 Print Date 11/28/2018

contained and prevented from being discharged to any waterway,

sewer or drain.

Hazardous thermal decomposition products

Decomposition products may include the following materials:

carbon dioxide carbon monoxide nitrogen oxides sulfur oxides metal oxide/oxides

Special protective actions for firefighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any

personal risk or without suitable training.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece operated

in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without

suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

See also the information in "For non-emergency personnel".

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil,

waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment

if released in large quantities.

Methods and materials for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Dilute with

water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate

waste disposal container. Dispose of via a licensed waste disposal

contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Approach

release from upwind. Prevent entry into sewers, water courses,



13000WHB WILFLEX OASIS HYDRATE NEUTRAL.

Version Number 1.7 Revision Date 12/04/2017 Page 6 of 19 Print Date 11/28/2018

basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
8	



13000WHB WILFLEX OASIS HYDRATE NEUTRAL.

Version Number 1.7 Revision Date 12/04/2017 Page 7 of 19 Print Date 11/28/2018

Distillates (petroleum), hydrotreated light	ACGIH TLV (2003-01-01) Calculated as total hydrocarbon vapor TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 200 mg/m3
1,2-Propanediol	AIHA WEEL (1999-01-01) Time Weighted Average (TWA) 10 mg/m3
Paraffin waxes and Hydrocarbon waxes	OSHA PEL 1989 (1989-03-01) PEL: Permissible Exposure Level 2 mg/m3 NIOSH REL (1994-06-01) Time Weighted Average (TWA) 2 mg/m3 Form: Fume ACGIH TLV (1994-09-01) TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 2 mg/m3 Form: Fume
Urea	AIHA WEEL (1999-01-01) Time Weighted Average (TWA) 10 mg/m3
Appropriate engineering controls :	Good general ventilation should be sufficient to control worker

exposure to airborne contaminants.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures: Wash hands, forearms and face thoroughly after handling chemical

products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety

showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used

when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a

higher degree of protection: chemical splash goggles.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved



13000WHB WILFLEX OASIS HYDRATE NEUTRAL.

Version Number 1.7 Revision Date 12/04/2017

Page 8 of 19 Print Date 11/28/2018

standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves

cannot be accurately estimated.

Body protection Personal protective equipment for the body should be selected based

on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

Appropriate footwear and any additional skin protection measures Other skin protection

should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this

product.

Respiratory protection Based on the hazard and potential for exposure, select a respirator that

> meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper

fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

Vapor pressure

Physical state liquid [liquid] Color NO PIGMENT Odor Not available. **Odor threshold** Not available. 4.0 - 7.5pН

Melting point Not available. **Boiling point** Not available. Flash point Not applicable

Burning time Not available. **Burning rate** Not available. **Evaporation rate** Not available. Flammability (solid, gas) Not available.

Lower and upper explosive Lower: Not applicable **Upper:** Not applicable (flammable) limits

Vapor density Not available.

Relative density 1.12

8/19

< 1 mmHg



13000WHB WILFLEX OASIS HYDRATE NEUTRAL.

Version Number 1.7 Page 9 of 19 Revision Date 12/04/2017 Print Date 11/28/2018

Not available. **Solubility** Solubility in water Not available. Partition coefficient: n-Not available.

octanol/water

Auto-ignition temperature not applicable

Decomposition temperature Not available. Not available. **SADT**

Dynamic: Not available. Viscosity

Kinematic: Not available.

Section 10. Stability and reactivity

Reactivity No specific test data related to reactivity available for this product or

its ingredients.

Chemical stability Stable under recommended storage and handling conditions (see

Section 7).

Possibility of hazardous reactions Under normal conditions of storage and use, hazardous reactions will

Keep away from extreme heat and oxidizing agents. Conditions to avoid

Incompatible materials Keep away from strong acids.

Oxidizer.

Hazardous decomposition Under normal conditions of storage and use, hazardous decomposition products

products should not be produced.

Section 11. Toxicological information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure		
Remarks - Oral:	No applicable toxi	No applicable toxicity data				
Remarks - Inhalation:	No applicable toxi	No applicable toxicity data				
Remarks - Dermal:	No applicable toxicity data					
1,2-Propanediol						
	LD50 Oral	Rat	20,000 mg/kg	-		
Remarks - Inhalation:	No applicable toxicity data					
	LD50 Dermal	Rabbit	20,800 mg/kg	-		



13000WHB WILFLEX OASIS HYDRATE NEUTRAL.

Version Number 1.7 Revision Date 12/04/2017 Page 10 of 19 Print Date 11/28/2018

Urea				
	LD50 Oral	Rat	8,471 mg/kg	=
Remarks - Inhalation:	No applicable toxicity data			
Remarks - Dermal:	No applicable toxicity data			
Paraffin waxes and Hydrocarbon waxes				
	LD50 Oral Rat 2,000 mg/kg -			
Remarks - Inhalation:	No applicable toxicity data			
Remarks - Dermal:	No applicable toxicity data			

Conclusion/Summary : Mixture.Not fully tested.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
1,2-Propanediol	Skin - Mild irritant	Woman		96 hrs	-
	Skin - Mild irritant	Human		168 hrs	-
	Skin - Moderate irritant	Human		72 hrs	-
	Eyes - Mild irritant	Rabbit			-
	Eyes - Mild irritant	Rabbit		24 hrs	-
	Skin - Moderate irritant	Child		96 hrs	-
Urea	Skin - Moderate irritant	Human		24 hrs	-
	Skin - Mild irritant	Human		72 hrs	-
Paraffin waxes and Hydrocarbon waxes	Skin - Moderate irritant	Rabbit			-
	Eyes - Mild irritant	Rabbit			-
	Skin - Mild irritant	Rabbit		24 hrs	-
	Eyes - Mild irritant	Rabbit		24 hrs	-

Conclusion/Summary

SkinMixture.Not fully tested.EyesMixture.Not fully tested.



13000WHB WILFLEX OASIS HYDRATE NEUTRAL.

Version Number 1.7 Page 11 of 19 Revision Date 12/04/2017 Print Date 11/28/2018

Respiratory : Mixture. Not fully tested.

Sensitization

Conclusion/Summary

SkinMixture.Not fully tested.RespiratoryMixture.Not fully tested.

Mutagenicity

Conclusion/Summary : Mixture.Not fully tested.

Carcinogenicity

Conclusion/Summary: Mixture.Not fully tested.

Reproductive toxicity

Conclusion/Summary : Mixture.Not fully tested.

Teratogenicity

Conclusion/Summary : Mixture.Not fully tested.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

115 511 441 511 1141241 4	
Product/ingredient name	Result
Distillates (petroleum), hydrotreated light	ASPIRATION HAZARD - Category 1

Information on likely routes of

exposure

Not available.

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : No known significant effects or critical hazards.

Skin contact : Causes skin irritation.

Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics



13000WHB WILFLEX OASIS HYDRATE NEUTRAL.

Version Number 1.7 Page 12 of 19 Revision Date 12/04/2017 Print Date 11/28/2018

Eye contact : Adverse symptoms may include the following:

pain or irritation

watering redness

Inhalation : No specific data.

Skin contact : Adverse symptoms may include the following:

irritation redness

Ingestion : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Conclusion/Summary : Mixture.Not fully tested.

General:No known significant effects or critical hazards.Carcinogenicity:No known significant effects or critical hazards.Mutagenicity:No known significant effects or critical hazards.Teratogenicity:No known significant effects or critical hazards.Developmental effects:No known significant effects or critical hazards.Fertility effects:No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	82,304.6 mg/kg
Route	ATE value
Inhalation (vapors)	103.8 mg/l

Section 12. Ecological information



13000WHB WILFLEX OASIS HYDRATE NEUTRAL.

Version Number 1.7 Revision Date 12/04/2017 Page 13 of 19 Print Date 11/28/2018

Toxicity

Product/ingredient name	Result	Species	Exposure		
Distillates (petroleum), hydrot	eated light				
	Acute LC50 2.2 Mg/l Fresh water Fish - Fish 96 h				
Remarks - Acute - Fish:	Acute				
Remarks - Acute - Aquatic	No applicable toxicity data				
invertebrates.:					
Remarks - Acute - Aquatic	No applicable toxicity data				
plants:					
Remarks - Chronic - Fish:	No applicable toxicity data				
Remarks - Chronic -	No applicable toxicity data				
Aquatic invertebrates.:					
1,2-Propanediol					
	Acute LC50 710 Mg/l Fresh water	Fish - Fish	96 h		
Remarks - Acute - Fish:	Acute				
	Acute EC50 > 110 Mg/l Fresh	Aquatic invertebrates.	48 h		
	water	Daphnia			
Remarks - Acute - Aquatic	Acute				
invertebrates.:					
	Acute LC50 1,020 Mg/l Fresh	Aquatic invertebrates.	48 h		
	water	Crustaceans			
Remarks - Acute - Aquatic	Acute				
invertebrates.:					
Remarks - Acute - Aquatic	No applicable toxicity data	No applicable toxicity data			
plants:					
Remarks - Chronic - Fish:	No applicable toxicity data				
Remarks - Chronic -	No applicable toxicity data				
Aquatic invertebrates.:					
Urea	L	F: 1 F: 1	0.61		
	Acute LC50 0.000023 Mg/l Fresh	Fish - Fish	96 h		
Domoules Asside Fig.	water				
Remarks - Acute - Fish:	Acute	A quotio investalmete	40 h		
	Acute EC50 6,573.1 Mg/l Fresh water	Aquatic invertebrates. Crustaceans	48 h		
Remarks - Acute - Aquatic		Crustaceans			
invertebrates.:	Acute				
mver tenrates.:	Acute EC50 3,910 Mg/l Fresh	Aquatic invertebrates.	48 h		
	water	Daphnia	70 11		
Remarks - Acute - Aquatic	Acute	Dapiniu	L		
invertebrates.:	11000				
Remarks - Acute - Aquatic	No applicable toxicity data				
plants:					
piants.	<u> </u>				



13000WHB WILFLEX OASIS HYDRATE NEUTRAL.

Version Number 1.7 Page 14 of 19 Revision Date 12/04/2017 Print Date 11/28/2018

	Chronic NOEC 2,000 Mg/l Fresh	Fish - Fish	30 d
	water		
Remarks - Chronic - Fish:	Chronic		
Remarks - Chronic -	No applicable toxicity data		
Aquatic invertebrates.:			
Paraffin waxes and Hydrocarb	on waxes		
Remarks - Acute - Fish:	No applicable toxicity data		
Remarks - Acute - Aquatic	No applicable toxicity data		
invertebrates.:			
Remarks - Acute - Aquatic	No applicable toxicity data		
plants:			
Remarks - Chronic - Fish:	No applicable toxicity data		
Remarks - Chronic -	No applicable toxicity data		
Aquatic invertebrates.:			
Conclusion/Summary	: Not available.		

Persistence and degradability

Conclusion/Summary Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
1,2-Propanediol	-1.070.085	-	low
Urea	-1.73	-	low

Mobility in soil

Soil/water partition coefficient

(KOC)

Not available.

Other adverse effects No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods The generation of waste should be avoided or minimized wherever

possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the



13000WHB WILFLEX OASIS HYDRATE NEUTRAL.

Version Number 1.7 Revision Date 12/04/2017 Page 15 of 19 Print Date 11/28/2018

requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

Section 14. Transport information

U.S.DOT 49CFR : Not regulated for transportation.

Ground/Air/Water

International Air ICAO/IATA

: Consult mode specific transport rules

International Water

IMO/IMDG

: Consult mode specific transport rules

Section 15. Regulatory information

U.S. Federal regulations : United States - TSCA 12(b) - Chemical export notification: None

of the components are listed.

United States - TSCA 4(a) - Final Test Rules: Not listed
United States - TSCA 4(a) - ITC Priority list: Not listed
United States - TSCA 4(a) - Proposed test rules: Not listed
United States - TSCA 4(f) - Priority risk review: Not listed
United States - TSCA 5(a)2 - Final significant new use rules: Not

listed

United States - TSCA 5(a)2 - Proposed significant new use rules:

Not listed

United States - TSCA 5(e) - Substances consent order: Not listed United States - TSCA 6 - Final risk management: Not listed United States - TSCA 6 - Proposed risk management: Not listed United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not

determined



13000WHB WILFLEX OASIS HYDRATE NEUTRAL.

Version Number 1.7 Revision Date 12/04/2017 Page 16 of 19 Print Date 11/28/2018

United States - TSCA 8(a) - Preliminary assessment report

(PAIR): Not listed

United States - TSCA 8(c) - Significant adverse reaction (SAR):

Not listed

United States - TSCA 8(d) - Health and safety studies: Not listed United States - TSCA 8(a) - Chemical risk rules: Not listed

United States - EPA Clean water act (CWA) section 307 - Priority

pollutants: Not listed

United States - EPA Clean water act (CWA) section 311 -

Hazardous substances: Not listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Flammable substances: Not listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Toxic substances: Not listed

United States - Department of commerce - Precursor chemical:

Not listed

Clean Air Act Section 112(b)

Hazardous Air Pollutants (HAPs)

Clean Air Act Section 602 Class I

Substances

Clean Air Act Section 602 Class II

Substances

DEA List I Chemicals (Precursor

Chemicals)

DEA List II Chemicals (Essential

Chemicals)

Not listed

Not listed

Not listed

Not listed

tial : Not listed

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

SARA 311/312

Classification : Immediate (acute) health hazard

Composition/information on ingredients

Name	9/0	Classification
Distillates (petroleum),	10 - 25	F, AH
hydrotreated light		
1,2-Propanediol	0 - 10	AH
Urea	0 - 5	AH
Paraffin waxes and Hydrocarbon	0 - 3	AH



13000WHB WILFLEX OASIS HYDRATE NEUTRAL.

Version Number 1.7 Revision Date 12/04/2017 Page 17 of 19 Print Date 11/28/2018

waxes

SARA 313

Not applicable.

State regulations

Massachusetts: None of the components are listed.New York: None of the components are listed.New Jersey: The following components are listed:Paraffin waxes and Hydrocarbon waxes

1,2-Propanediol Barium sulfate

Pennsylvania : The following components are listed:

Paraffin waxes and Hydrocarbon waxes

1,2-Propanediol

Barium sulfate

California Prop. 65

This PolyOne product does not contain any chemical known to the State of California to cause cancer, or birth defects or other reproductive harm, in concentrations that require a warning notice under California's Proposition 65. This statement relies in part on information provided by the buyer of this PolyOne product. PolyOne does not control or have complete knowledge of the end uses to which that buyer or any other entity in the chain of distribution and marketing may put this PolyOne product. Therefore, the buyer of this PolyOne product, each entity that uses this PolyOne product in formulating another product, and each entity in the chain of distribution and marketing of any product that includes the material in this PolyOne product must make its own decision as to giving a Proposition 65 warning.

United States inventory (TSCA 8b) : All components are listed or exempted.

Canada inventory : Not determined.

International regulations

Inventory list

Not determined. Australia Canada Not determined. Not determined. China **Europe inventory** Not determined. Japan Not determined. **New Zealand** Not determined. **Philippines** Not determined. Republic of Korea Not determined. Taiwan Not determined. **Turkey** Not determined.



13000WHB WILFLEX OASIS HYDRATE NEUTRAL.

Version Number 1.7 Page 18 of 19 Revision Date 12/04/2017 Print Date 11/28/2018

United States : All components are listed or exempted.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	/	2
Flammability		0
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

History

Date of printing: 11/28/2018Date of issue/Date of revision: 12/04/2017Date of previous issue: 08/23/2017

Version : 1.7

Key to abbreviations: ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of

Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

 $MARPOL = International \ Convention \ for \ the \ Prevention \ of \ Pollution \ From$

Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine

pollution)

UN = United Nations

References : Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that



13000WHB WILFLEX OASIS HYDRATE NEUTRAL.

 Version Number 1.7
 Page 19 of 19

 Revision Date 12/04/2017
 Print Date 11/28/2018

exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.