

### DK GRAY UV

Version Number 1.0 Revision Date 12/01/2017

Page 1 of 19 Print Date 11/19/2018

# SAFETY DATA SHEET

### **DK GRAY UV**

## **Section 1. Identification**

DK GRAY UV **GHS** product identifier Chemical name Mixture **CAS** number Mixture Other means of identification CC10273766 **Product type** solid

Relevant identified uses of the substance or mixture and uses advised against

Product use Industrial applications. Plastics.

Supplier's details POLYONE CORPORATION

33587 Walker Road, Avon Lake, OH 44012

1 (440) 930-1000 or 1 (866) POLYONE

**Emergency telephone number** (with hours of operation)

CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or

accident).

## Section 2. Hazards identification

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. After handling, always wash hands thoroughly with soap and water.

**OSHA/HCS** status While this material is not considered hazardous by the OSHA Hazard

> Communication Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available for employees and

other users of this product.

Classification of the substance or

mixture

Not classified.

**GHS** label elements

No signal word. Signal word

1/19



## DK GRAY UV

Version Number 1.0 Page 2 of 19 Revision Date 12/01/2017 Print Date 11/19/2018

**Hazard statements** : No known significant effects or critical hazards.

#### **Precautionary statements**

General:Not applicable.Prevention:Not applicable.Response:Not applicable.Storage:Not applicable.Disposal:Not applicable.Supplemental label elements:None known.Hazards not otherwise classified:None known.

# Section 3. Composition/information on ingredients

Substance/mixture: MixtureChemical name: MixtureOther means of identification: CC10273766

#### **CAS** number/other identifiers

Ingredient name	%	CAS number
2-Propenenitrile, polymer with Ethenylbenzene	50 - 75	9003-54-7
Titanium dioxide	10 - 25	13463-67-7
2-(2-Hydroxy-5-tert-octylphenyl)benzotriazole	5 - 10	3147-75-9
1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetramethyl-4-piperidinyl)-, polymer with 2,4-dichloro-6-(4-morpholinyl)-1,3,5-triazine	5 - 10	82451-48-7
Carbon black	0 - 3	1333-86-4
Styrene	0 - 0.3	100-42-5

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require



## DK GRAY UV

Version Number 1.0 Page 3 of 19 Revision Date 12/01/2017 Print Date 11/19/2018

reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

#### **Description of necessary first aid measures**

**Eye contact**: Immediately flush eyes with plenty of water, occasionally lifting the

upper and lower eyelids. Check for and remove any contact lenses.

Get medical attention if irritation occurs.

**Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable

for breathing. Get medical attention if symptoms occur. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical

surveillance for 48 hours.

**Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated

clothing and shoes. Get medical attention if symptoms occur.

**Ingestion**: Wash out mouth with water. Remove victim to fresh air and keep at

rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by

medical personnel. Get medical attention if symptoms occur.

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

Eye contact: No known significant effects or critical hazards.Inhalation: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

Eye contact: No specific data.Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

#### Indication of immediate medical attention and special treatment needed, if necessary

**Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms

may be delayed. The exposed person may need to be kept under



DK GRAY UV

Version Number 1.0 Page 4 of 19 Revision Date 12/01/2017 Print Date 11/19/2018

medical surveillance for 48 hours.

**Specific treatments** : No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without

suitable training.

See toxicological information (Section 11)

## Section 5. Firefighting measures

#### **Extinguishing media**

Suitable extinguishing media Unsuitable extinguishing media In case of fire, use water spray (fog), foam, dry chemical or CO<sub>2</sub>.

None known.

Specific hazards arising from the chemical

No specific fire or explosion hazard.

Hazardous thermal decomposition products

: Decomposition products may include the following materials: carbon dioxide

carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides

Special protective actions for fire-

fighters

: Promptly isolate the scene by removing all persons from the vicinity

of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece operated

in positive pressure mode.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without

suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.

**For emergency responders**: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

See also the information in "For non-emergency personnel".

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil,

waterways, drains and sewers. Inform the relevant authorities if the



### DK GRAY UV

Version Number 1.0 Revision Date 12/01/2017 Page 5 of 19 Print Date 11/19/2018

product has caused environmental pollution (sewers, waterways, soil or air).

#### Methods and materials for containment and cleaning up

Small spill : Move containers from spill area. Vacuum or sweep up material and

place in a designated, labeled waste container. Dispose of via a

licensed waste disposal contractor.

Large spill : Move containers from spill area. Prevent entry into sewers, water

courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency

contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

#### Precautions for safe handling

**Protective measures** 

Advice on general occupational

hygiene

Put on appropriate personal protective equipment (see Section 8).

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use

appropriate containment to avoid environmental contamination.

# Section 8. Exposure controls/personal protection

#### **Control parameters**

#### Occupational exposure limits

	Ingredient name	Exposure limits
--	-----------------	-----------------



# DK GRAY UV

Version Number 1.0 Revision Date 12/01/2017 Page 6 of 19 Print Date 11/19/2018

minutes, unless otherwise stated. 425 mg/m3 100 ppm OSHA PEL Z2 (1993-06-30) PEL: Permissible Exposure Level 100 ppm Ceiling-A concentration that should not be exceeded at any tinduring any part of the working day. 200 ppm Acceptable Maximum Peak (AMP) 600 ppm NIOSH REL (1994-06-01) Time Weighted Average (TWA) 215 mg/m3 50 ppm Short-term exposure limit (STEL). A limit beyond which there should be no exposure and which refers to a period of fininutes, unless otherwise stated. 425 mg/m3 100 ppm ACGH TLV (1997-05-21) TLV-TWA: Threshold Limit Value - Time weighted average PEI Permissible Exposure Level 85 mg/m3 20 ppm TLV-STEL: Threshold Limit Value - Short Time Exposure L 170 mg/m3 40 ppm  Carbon black  OSHA PEL 1989 (1989-03-01) PEL: Permissible Exposure Level 3.5 mg/m3 OSHA PEL (1993-06-30) PEL: Permissible Exposure Level 3.5 mg/m3 NIOSH REL (1993-06-01) Time Weighted Average (TWA) 3.5 mg/m3 Time Weighted Average (TWA) ACGH TLV (2010-12-06) TLV-TWA: Threshold Limit Value - Time weighted average PEI Permissible Exposure Level 3 mg/m3 Form: Inhalable fraction  2-(2-Hydroxy-5-tert-octylphenyl)benzotriazole  1,6-Hexanediamine, N,N'-bis(2,2,6,6-teramethyl-4-piperidinyl)-, polymer with 2,4-dichloro-6-(4-morpholinyl)-1,3,5-triazine  Titanium dioxide  OSHA PEL 1989 (1989-03-01)		
Short-term exposure limit (STEL). A limit value beyond whic there should be no exposure and which refers to a period of fininutes, unless otherwise stated. 425 mg/m3 100 ppm OSHA PEL 72 (1993-06-30) PEL: Permissible Exposure Level 100 ppm Ceiling-A concentration that should not be exceeded at any finduring any part of the working day. 200 ppm Acceptable Maximum Peak (AMP) 600 ppm NIOSH REL (1994-06-01) Time Weighted Average (TWA) 215 mg/m3 50 ppm Short-term exposure limit (STEL). A limit value beyond which there should be no exposure and which refers to a period of fininutes, unless otherwise stated. 425 mg/m3 100 ppm ACGH TLV (1997-05-21) TLV-TWA: Threshold Limit Value - Time weighted average PEL Permissible Exposure Level 85 mg/m3 20 ppm TLV-STEL: Threshold Limit Value - Short Time Exposure L 170 mg/m3 40 ppm  Carbon black  OSHA PEL 1989 (1989-03-01) PEL: Permissible Exposure Level 3.5 mg/m3 OSHA PEL (1993-06-30) PEL: Permissible Exposure Level 3.5 mg/m3 NIOSH REL (1994-06-01) Time Weighted Average (TWA) 3.5 mg/m3 Time Weighted Average (TWA) ACGHH TLV (2010-12-06) TLV-TWA: Threshold Limit Value - Time weighted average PEL Permissible Exposure Level 3 mg/m3 Form: Inhalable fraction  2-(2-Hydroxy-5-tert-octylphenyl)benzotriazole  1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetramethyl-4-piperidinyl)-, polymer with 2,4-dichloro-6-(4-morpholinyl)-1,3,5-triazine  Titanium dioxide  OSHA PEL 1989 (1989-03-01)	Styrene	
there should be no exposure and which refers to a period of fiminutes, unless otherwise stated. 425 mg/m3 100 ppm OSHA PEL Z2 (1993-06-30) PEL: Permissible Exposure Level 100 ppm Ceiling-A concentration that should not be exceeded at any tiduring any part of the working day. 200 ppm Acceptable Maximum Peak (AMP) 600 ppm NIOSH REL (1994-06-01) Time Weighted Average (TWA) 215 mg/m3 50 ppm Short-term exposure limit (STEL). A limit value beyond whice there should be no exposure and which refers to a period of fiminutes, unless otherwise stated. 425 mg/m3 100 ppm ACGIH TLV (1997-05-21) TLV-TWA: Threshold Limit Value - Time weighted average PEL Permissible Exposure Level 85 mg/m3 20 ppm TLV-STEL: Threshold Limit Value - Short Time Exposure L 170 mg/m3 40 ppm  Carbon black  OSHA PEL 1989 (1989-03-01) PEL: Permissible Exposure Level 3.5 mg/m3 OSHA PEL (1993-06-30) PEL: Permissible Exposure Level 3.5 mg/m3 NIOSH REL (1994-06-01) Time Weighted Average (TWA) ACGIH TLV (2010-12-06) TLV-TWA: Threshold Limit Value - Time weighted average PEL Permissible Exposure Level 3 mg/m3 Form: Inhalable fraction  2-(2-Hydroxy-5-tert-octylphenyl)benzotriazole  1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetramethyl-4-piperidinyl)-, polymer with 2,4-dichloro-6-(4-morpholinyl)-1,3,5-triazine  Titanium dioxide  OSHA PEL 1989 (1989-03-01)		
minutes, unless otherwise stated. 425 mg/m3 100 ppm OSHA PEL Z2 (1993-06-30) PEL: Permissible Exposure Level 100 ppm Ceiling-A concentration that should not be exceeded at any tinduring any part of the working day. 200 ppm Acceptable Maximum Peak (AMP) 600 ppm NIOSH REL (1994-06-01) Time Weighted Average (TWA) 215 mg/m3 50 ppm Short-term exposure limit (STEL). A limit value beyond which there should be no exposure and which refers to a period of fininutes, unless otherwise stated. 425 mg/m3 100 ppm ACGH TLV (1997-05-21) TLV-TWA: Threshold Limit Value - Time weighted average PEI Permissible Exposure Level 85 mg/m3 20 ppm TLV-STEL: Threshold Limit Value - Short Time Exposure L 170 mg/m3 40 ppm ACGH TLV (1993-06-30) PEL: Permissible Exposure Level 3.5 mg/m3 OSHA PEL (1993-06-30) PEL: Permissible Exposure Level 3.5 mg/m3 NIOSH REL (1993-06-01) Time Weighted Average (TWA) 3.5 mg/m3 Time Weighted Average (TWA) ACGH TLV (2010-12-06) TLV-TWA: Threshold Limit Value - Time weighted average PEI Permissible Exposure Level 3 mg/m3 Form: Inhalable fraction  2-(2-Hydroxy-5-tert-octylphenyl)benzotriazole  1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetramethyl-4-piperidinyl)-, polymer with 2,4-dichloro-6-(4-morpholinyl)-1,3,5-triazine Titanium dioxide  OSHA PEL 1989 (1989-03-01)		
OSHA PEL Z2 (1993-06-30) PEL: Permissible Exposure Level 100 ppm Ceiling-A concentration that should not be exceeded at any tinduring any part of the working day. 200 ppm Acceptable Maximum Peak (AMP) 600 ppm NIOSH REL (1994-06-01) Time Weighted Average (TWA) 215 mg/m3 50 ppm Short-term exposure limit (STEL). A limit value beyond whice there should be no exposure and which refers to a period of fininutes, unless otherwise stated. 425 mg/m3 100 ppm ACGH TLV (1997-05-21) TLV-TWA: Threshold Limit Value - Time weighted average PEI Permissible Exposure Level 85 mg/m3 20 ppm TLV-STEL: Threshold Limit Value - Short Time Exposure L 170 mg/m3 40 ppm  Carbon black  OSHA PEL 1989 (1989-03-01) PEL: Permissible Exposure Level 3.5 mg/m3 OSHA PEL (1993-06-30) PEL: Permissible Exposure Level 3.5 mg/m3 NIOSH REL (1994-06-01) Time Weighted Average (TWA) ACGH TLV (2010-12-06) TLV-TWA: Threshold Limit Value - Time weighted average PEI Permissible Exposure Level 3 mg/m3 Form: Inhalable fraction  2-(2-Hydroxy-5-tert-octylphenyl)benzotriazole  1,6-Hexanediamine, N,N-bis(2,2,6,6-tetramethyl-4-piperidinyl)-, polymer with 2,4-dichloro-6-(4-morpholinyl)-1,3,5-triazine  Titanium dioxide  OSHA PEL 1989 (1989-03-01)		there should be no exposure and which refers to a period of fifteen
PEL: Permissible Exposure Level 100 ppm Ceiling-A concentration that should not be exceeded at any tiduring any part of the working day. 200 ppm Acceptable Maximum Peak (AMP) 600 ppm NIOSH REL (1994-06-01) Time Weighted Average (TWA) 215 mg/m3 50 ppm Short-term exposure limit (STEL). A limit value beyond which there should be no exposure and which refers to a period of fininutes, unless otherwise stated. 425 mg/m3 100 ppm ACGH TLV (1997-05-21) TLV-TWA: Threshold Limit Value - Time weighted average PEL Permissible Exposure Level 85 mg/m3 20 ppm TLV-STEL: Threshold Limit Value - Short Time Exposure L 170 mg/m3 40 ppm  Carbon black  OSHA PEL 1989 (1989-03-01) PEL: Permissible Exposure Level 3.5 mg/m3 OSHA PEL (1993-06-30) PEL: Permissible Exposure Level 3.5 mg/m3 NIOSH REL (1994-06-01) Time Weighted Average (TWA) ACGIH TLV (2010-12-06) TLV-TWA: Threshold Limit Value - Time weighted average PEL Permissible Exposure Level 3 mg/m3 Form: Inhalable fraction  2-(2-Hydroxy-5-tert-octylphenyl)benzotriazole  1,6-Hexanediamine, N.N'-bis(2,2,6,6-tetramethyl-4-piperidinyl)-, polymer with 2,4-dichloro-6-(4-morpholinyl)-1,3,5-triazine  Titanium dioxide  OSHA PEL 1989 (1989-03-01)		minutes, unless otherwise stated. 425 mg/m3 100 ppm
Ceiling-A concentration that should not be exceeded at any tin during any part of the working day. 200 ppm Acceptable Maximum Peak (AMP) 600 ppm NIOSH REL (1994-06-01) Time Weighted Average (TWA) 215 mg/m3 50 ppm Short-term exposure limit (STEL). A limit value beyond which there should be no exposure and which refers to a period of fin minutes, unless otherwise stated. 425 mg/m3 100 ppm ACGH TLV (1997-05-21) TLV-TWA: Threshold Limit Value - Time weighted average PEI Permissible Exposure Level 85 mg/m3 20 ppm TLV-STEL: Threshold Limit Value - Short Time Exposure L 170 mg/m3 40 ppm  Carbon black  OSHA PEL 1989 (1989-03-01) PEL: Permissible Exposure Level 3.5 mg/m3 OSHA PEL (1993-06-30) PEL: Permissible Exposure Level 3.5 mg/m3 NIOSH REL (1994-06-01) Time Weighted Average (TWA) ACGH TLV (2010-12-06) TLV-TWA: Threshold Limit Value - Time weighted average PEI Permissible Exposure Level 3 mg/m3 Form: Inhalable fraction  2-(2-Hydroxy-5-tert-octylphenyl)benzotriazole  1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetramethyl-4-piperidinyl)-, polymer with 2,4-dichloro-6-(4-morpholinyl)-1,3,5-triazine  Titanium dioxide  OSHA PEL 1989 (1989-03-01)		OSHA PEL Z2 (1993-06-30)
during any part of the working day. 200 ppm Acceptable Maximum Peak (AMP) 600 ppm NIOSH REL (1994-06-01) Time Weighted Average (TWA) 215 mg/m3 50 ppm Short-term exposure limit (STEL). A limit value beyond whice there should be no exposure and which refers to a period of fininutes, unless otherwise stated. 425 mg/m3 100 ppm ACGH TLV (1997-05-21) TLV-TWA: Threshold Limit Value - Time weighted average PEI Permissible Exposure Level 85 mg/m3 20 ppm TLV-STEL: Threshold Limit Value - Short Time Exposure L 170 mg/m3 40 ppm  Carbon black  OSHA PEL 1989 (1989-03-01) PEL: Permissible Exposure Level 3.5 mg/m3 OSHA PEL (1993-06-30) PEL: Permissible Exposure Level 3.5 mg/m3 NIOSH REL (1994-06-01) Time Weighted Average (TWA) 3.5 mg/m3 Time Weighted Average (TWA) ACGH TLV (2010-12-06) TLV-TWA: Threshold Limit Value - Time weighted average PEI Permissible Exposure Level 3 mg/m3 Form: Inhalable fraction  2-(2-Hydroxy-5-tert-octylphenyl)benzotriazole  1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetramethyl-4-piperidinyl)-, polymer with 2,4-dichloro-6-(4-morpholinyl)-1,3,5-triazine  Titanium dioxide  OSHA PEL 1989 (1989-03-01)		PEL: Permissible Exposure Level 100 ppm
during any part of the working day. 200 ppm Acceptable Maximum Peak (AMP) 600 ppm NIOSH REL (1994-06-01) Time Weighted Average (TWA) 215 mg/m3 50 ppm Short-term exposure limit (STEL). A limit value beyond whice there should be no exposure and which refers to a period of fininutes, unless otherwise stated. 425 mg/m3 100 ppm ACGH TLV (1997-05-21) TLV-TWA: Threshold Limit Value - Time weighted average PEI Permissible Exposure Level 85 mg/m3 20 ppm TLV-STEL: Threshold Limit Value - Short Time Exposure L 170 mg/m3 40 ppm  Carbon black  OSHA PEL 1989 (1989-03-01) PEL: Permissible Exposure Level 3.5 mg/m3 OSHA PEL (1993-06-30) PEL: Permissible Exposure Level 3.5 mg/m3 NIOSH REL (1994-06-01) Time Weighted Average (TWA) 3.5 mg/m3 Time Weighted Average (TWA) ACGH TLV (2010-12-06) TLV-TWA: Threshold Limit Value - Time weighted average PEI Permissible Exposure Level 3 mg/m3 Form: Inhalable fraction  2-(2-Hydroxy-5-tert-octylphenyl)benzotriazole  1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetramethyl-4-piperidinyl)-, polymer with 2,4-dichloro-6-(4-morpholinyl)-1,3,5-triazine Titanium dioxide  OSHA PEL 1989 (1989-03-01)		Ceiling-A concentration that should not be exceeded at any time
Acceptable Maximum Peak (AMP) 600 ppm NIOSH REL (1994-06-01) Time Weighted Average (TWA) 215 mg/m3 50 ppm Short-term exposure limit (STEL). A limit value beyond whice there should be no exposure and which refers to a period of fininutes, unless otherwise stated. 425 mg/m3 100 ppm ACGHI TLV (1997-05-21) TLV-TWA: Threshold Limit Value - Time weighted average PEI Permissible Exposure Level 85 mg/m3 20 ppm TLV-STEL: Threshold Limit Value - Short Time Exposure L 170 mg/m3 40 ppm  Carbon black  OSHA PEL 1989 (1989-03-01) PEL: Permissible Exposure Level 3.5 mg/m3 OSHA PEL (1993-06-30) PEL: Permissible Exposure Level 3.5 mg/m3 NIOSH REL (1994-06-01) Time Weighted Average (TWA) 3.5 mg/m3 Time Weighted Average (TWA) ACGHI TLV (2010-12-06) TLV-TWA: Threshold Limit Value - Time weighted average PEI Permissible Exposure Level 3 mg/m3 Form: Inhalable fraction  2-(2-Hydroxy-5-tert-octylphenyl)benzotriazole  1,6-Hexanediamine, N,N'-bis(2,2,6,6-terramethyl-4-piperidinyl)-, polymer with 2,4-dichloro-6-(4-morpholinyl)-1,3,5-triazine Titanium dioxide  OSHA PEL 1989 (1989-03-01)		
NIOSH REL (1994-06-01) Time Weighted Average (TWA) 215 mg/m3 50 ppm Short-term exposure limit (STEL). A limit value beyond which there should be no exposure and which refers to a period of fininutes, unless otherwise stated. 425 mg/m3 100 ppm ACGH TLV (1997-05-21) TLV-TWA: Threshold Limit Value - Time weighted average PEL Permissible Exposure Level 85 mg/m3 20 ppm TLV-STEL: Threshold Limit Value - Short Time Exposure L 170 mg/m3 40 ppm  Carbon black  OSHA PEL 1989 (1989-03-01) PEL: Permissible Exposure Level 3.5 mg/m3 OSHA PEL (1993-06-30) PEL: Permissible Exposure Level 3.5 mg/m3 NIOSH REL (1994-06-01) Time Weighted Average (TWA) 3.5 mg/m3 Time Weighted Average (TWA) ACGH TLV (2010-12-06) TLV-TWA: Threshold Limit Value - Time weighted average PEL Permissible Exposure Level 3 mg/m3 Form: Inhalable fraction  2-(2-Hydroxy-5-tert-octylphenyl)benzotriazole  1,6-Hexanediamine, N,N'-bis(2,2,6,6-terramethyl-4-piperidinyl)-, polymer with 2,4-dichloro-6-(4-morpholinyl)-1,3,5-triazine  Titanium dioxide  OSHA PEL 1989 (1989-03-01)		
Time Weighted Average (TWA) 215 mg/m3 50 ppm Short-term exposure limit (STEL). A limit value beyond which there should be no exposure and which refers to a period of fininutes, unless otherwise stated. 425 mg/m3 100 ppm ACGIH TLV (1997-05-21) TLV-TWA: Threshold Limit Value - Time weighted average PEI Permissible Exposure Level 85 mg/m3 20 ppm TLV-STEL: Threshold Limit Value - Short Time Exposure L 170 mg/m3 40 ppm  Carbon black  OSHA PEL 1989 (1989-03-01) PEL: Permissible Exposure Level 3.5 mg/m3 OSHA PEL (1993-06-30) PEL: Permissible Exposure Level 3.5 mg/m3 NIOSH REL (1994-06-01) Time Weighted Average (TWA) 3.5 mg/m3 Time Weighted Average (TWA) ACGIH TLV (2010-12-06) TLV-TWA: Threshold Limit Value - Time weighted average PEI Permissible Exposure Level 3 mg/m3 Form: Inhalable fraction  2-(2-Hydroxy-5-tert-octylphenyl)benzotriazole  1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetramethyl-4-piperidinyl)-, polymer with 2,4-dichloro-6-(4-morpholinyl)-1,3,5-triazine  Titanium dioxide  OSHA PEL 1989 (1989-03-01)		
Short-term exposure limit (STEL). A limit value beyond which there should be no exposure and which refers to a period of fininutes, unless otherwise stated. 425 mg/m3 100 ppm  ACGH TLV (1997-05-21)  TLV-TWA: Threshold Limit Value - Time weighted average PEL Permissible Exposure Level 85 mg/m3 20 ppm  TLV-STEL: Threshold Limit Value - Short Time Exposure L 170 mg/m3 40 ppm  Carbon black  OSHA PEL 1989 (1989-03-01)  PEL: Permissible Exposure Level 3.5 mg/m3  OSHA PEL (1993-06-30)  PEL: Permissible Exposure Level 3.5 mg/m3  NIOSH REL (1994-06-01)  Time Weighted Average (TWA) 3.5 mg/m3  Time Weighted Average (TWA)  ACGH TLV (2010-12-06)  TLV-TWA: Threshold Limit Value - Time weighted average PEL Permissible Exposure Level 3 mg/m3 Form: Inhalable fraction  2-(2-Hydroxy-5-tert-octylphenyl)benzotriazole  1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetramethyl-4-piperidinyl)-, polymer with 2,4-dichloro-6-(4-morpholinyl)-1,3,5-triazine  Titanium dioxide  OSHA PEL 1989 (1989-03-01)		
there should be no exposure and which refers to a period of fininutes, unless otherwise stated. 425 mg/m3 100 ppm  ACGIH TLV (1997-05-21)  TLV-TWA: Threshold Limit Value - Time weighted average PEI Permissible Exposure Level 85 mg/m3 20 ppm  TLV-STEL: Threshold Limit Value - Short Time Exposure L 170 mg/m3 40 ppm  Carbon black  OSHA PEL 1989 (1989-03-01)  PEL: Permissible Exposure Level 3.5 mg/m3  OSHA PEL (1993-06-30)  PEL: Permissible Exposure Level 3.5 mg/m3  NIOSH REL (1994-06-01)  Time Weighted Average (TWA)  ACGIH TLV (2010-12-06)  TLV-TWA: Threshold Limit Value - Time weighted average PEI Permissible Exposure Level 3 mg/m3 Form: Inhalable fraction  2-(2-Hydroxy-5-tert-octylphenyl)benzotriazole  1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetramethyl-4-piperidinyl)-, polymer with 2,4-dichloro-6-(4-morpholinyl)-1,3,5-triazine  Titanium dioxide  OSHA PEL 1989 (1989-03-01)		
minutes, unless otherwise stated. 425 mg/m3 100 ppm ACGIH TLV (1997-05-21) TLV-TWA: Threshold Limit Value - Time weighted average PEI Permissible Exposure Level 85 mg/m3 20 ppm TLV-STEL: Threshold Limit Value - Short Time Exposure L 170 mg/m3 40 ppm  OSHA PEL 1989 (1989-03-01) PEL: Permissible Exposure Level 3.5 mg/m3 OSHA PEL (1993-06-30) PEL: Permissible Exposure Level 3.5 mg/m3 NIOSH REL (1994-06-01) Time Weighted Average (TWA) ACGIH TLV (2010-12-06) TLV-TWA: Threshold Limit Value - Time weighted average PEI Permissible Exposure Level 3 mg/m3 Form: Inhalable fraction  2-(2-Hydroxy-5-tert- octylphenyl)benzotriazole  1,6-Hexanediamine, N,N'-bis(2,2,6,6- tetramethyl-4-piperidinyl)-, polymer with 2,4-dichloro-6-(4-morpholinyl)-1,3,5- triazine  Titanium dioxide  OSHA PEL 1989 (1989-03-01)		
ACGIH TLV (1997-05-21) TLV-TWA: Threshold Limit Value - Time weighted average PEI Permissible Exposure Level 85 mg/m3 20 ppm TLV-STEL: Threshold Limit Value - Short Time Exposure L 170 mg/m3 40 ppm  Carbon black  OSHA PEL 1989 (1989-03-01) PEL: Permissible Exposure Level 3.5 mg/m3 OSHA PEL (1993-06-30) PEL: Permissible Exposure Level 3.5 mg/m3 NIOSH REL (1994-06-01) Time Weighted Average (TWA) 3.5 mg/m3 Time Weighted Average (TWA) ACGIH TLV (2010-12-06) TLV-TWA: Threshold Limit Value - Time weighted average PEI Permissible Exposure Level 3 mg/m3 Form: Inhalable fraction  2-(2-Hydroxy-5-tert-octylphenyl)benzotriazole  1,6-Hexanediamine, N,N'-bis(2,2,6,6-tertamethyl-4-piperidinyl)-, polymer with 2,4-dichloro-6-(4-morpholinyl)-1,3,5-triazine  Titanium dioxide  OSHA PEL 1989 (1989-03-01)		
TLV-TWA: Threshold Limit Value - Time weighted average PEI Permissible Exposure Level 85 mg/m3 20 ppm  TLV-STEL: Threshold Limit Value - Short Time Exposure L 170 mg/m3 40 ppm  Carbon black  OSHA PEL 1989 (1989-03-01)  PEL: Permissible Exposure Level 3.5 mg/m3  OSHA PEL (1993-06-30)  PEL: Permissible Exposure Level 3.5 mg/m3  NIOSH REL (1994-06-01)  Time Weighted Average (TWA) 3.5 mg/m3  Time Weighted Average (TWA)  ACGIH TLV (2010-12-06)  TLV-TWA: Threshold Limit Value - Time weighted average PEI Permissible Exposure Level 3 mg/m3 Form: Inhalable fraction  2-(2-Hydroxy-5-tert-octylphenyl)benzotriazole  1,6-Hexanediamine, N,N'-bis(2,2,6,6-teramethyl-4-piperidinyl)-, polymer with 2,4-dichloro-6-(4-morpholinyl)-1,3,5-triazine  Titanium dioxide  OSHA PEL 1989 (1989-03-01)		
Permissible Exposure Level 85 mg/m3 20 ppm  TLV-STEL: Threshold Limit Value - Short Time Exposure L 170 mg/m3 40 ppm  OSHA PEL 1989 (1989-03-01) PEL: Permissible Exposure Level 3.5 mg/m3 OSHA PEL (1993-06-30) PEL: Permissible Exposure Level 3.5 mg/m3 NIOSH REL (1994-06-01) Time Weighted Average (TWA) 3.5 mg/m3 Time Weighted Average (TWA) ACGH TLV (2010-12-06) TLV-TWA: Threshold Limit Value - Time weighted average PEL Permissible Exposure Level 3 mg/m3 Form: Inhalable fraction  2-(2-Hydroxy-5-tert- octylphenyl)benzotriazole  1,6-Hexanediamine, N,N'-bis(2,2,6,6- tetramethyl-4-piperidinyl)-, polymer with 2,4-dichloro-6-(4-morpholinyl)-1,3,5- triazine  Titanium dioxide  OSHA PEL 1989 (1989-03-01)		
TLV-STEL: Threshold Limit Value - Short Time Exposure L 170 mg/m3 40 ppm  OSHA PEL 1989 (1989-03-01) PEL: Permissible Exposure Level 3.5 mg/m3 OSHA PEL (1993-06-30) PEL: Permissible Exposure Level 3.5 mg/m3 NIOSH REL (1994-06-01) Time Weighted Average (TWA) 3.5 mg/m3 Time Weighted Average (TWA) ACGIH TLV (2010-12-06) TLV-TWA: Threshold Limit Value - Time weighted average PEI Permissible Exposure Level 3 mg/m3 Form: Inhalable fraction  2-(2-Hydroxy-5-tert- octylphenyl)benzotriazole  1,6-Hexanediamine, N,N'-bis(2,2,6,6- tetramethyl-4-piperidinyl)-, polymer with 2,4-dichloro-6-(4-morpholinyl)-1,3,5- triazine  Titanium dioxide  OSHA PEL 1989 (1989-03-01)		
Carbon black  OSHA PEL 1989 (1989-03-01) PEL: Permissible Exposure Level 3.5 mg/m3 OSHA PEL (1993-06-30) PEL: Permissible Exposure Level 3.5 mg/m3 NIOSH REL (1994-06-01) Time Weighted Average (TWA) 3.5 mg/m3 Time Weighted Average (TWA) ACGIH TLV (2010-12-06) TLV-TWA: Threshold Limit Value - Time weighted average PEI Permissible Exposure Level 3 mg/m3 Form: Inhalable fraction  2-(2-Hydroxy-5-tert- octylphenyl)benzotriazole  1,6-Hexanediamine, N,N'-bis(2,2,6,6- tetramethyl-4-piperidinyl)-, polymer with 2,4-dichloro-6-(4-morpholinyl)-1,3,5- triazine  Titanium dioxide  OSHA PEL 1989 (1989-03-01)		
Carbon black  OSHA PEL 1989 (1989-03-01) PEL: Permissible Exposure Level 3.5 mg/m3 OSHA PEL (1993-06-30) PEL: Permissible Exposure Level 3.5 mg/m3 NIOSH REL (1994-06-01) Time Weighted Average (TWA) 3.5 mg/m3 Time Weighted Average (TWA) ACGIH TLV (2010-12-06) TLV-TWA: Threshold Limit Value - Time weighted average PEL Permissible Exposure Level 3 mg/m3 Form: Inhalable fraction  2-(2-Hydroxy-5-tert-octylphenyl)benzotriazole  1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetramethyl-4-piperidinyl)-, polymer with 2,4-dichloro-6-(4-morpholinyl)-1,3,5-triazine  Titanium dioxide  OSHA PEL 1989 (1989-03-01)		
PEL: Permissible Exposure Level 3.5 mg/m3 OSHA PEL (1993-06-30) PEL: Permissible Exposure Level 3.5 mg/m3 NIOSH REL (1994-06-01) Time Weighted Average (TWA) 3.5 mg/m3 Time Weighted Average (TWA) ACGIH TLV (2010-12-06) TLV-TWA: Threshold Limit Value - Time weighted average PEI Permissible Exposure Level 3 mg/m3 Form: Inhalable fraction  2-(2-Hydroxy-5-tert- octylphenyl)benzotriazole  1,6-Hexanediamine, N,N'-bis(2,2,6,6- tetramethyl-4-piperidinyl)-, polymer with 2,4-dichloro-6-(4-morpholinyl)-1,3,5- triazine  Titanium dioxide  OSHA PEL 1989 (1989-03-01)		170 mg/m3 40 ppm
PEL: Permissible Exposure Level 3.5 mg/m3 OSHA PEL (1993-06-30) PEL: Permissible Exposure Level 3.5 mg/m3 NIOSH REL (1994-06-01) Time Weighted Average (TWA) 3.5 mg/m3 Time Weighted Average (TWA) ACGIH TLV (2010-12-06) TLV-TWA: Threshold Limit Value - Time weighted average PEI Permissible Exposure Level 3 mg/m3 Form: Inhalable fraction  2-(2-Hydroxy-5-tert- octylphenyl)benzotriazole  1,6-Hexanediamine, N,N'-bis(2,2,6,6- tetramethyl-4-piperidinyl)-, polymer with 2,4-dichloro-6-(4-morpholinyl)-1,3,5- triazine  Titanium dioxide  OSHA PEL 1989 (1989-03-01)	Carbon black	OCH A DEL 1080 (1080 03 01)
OSHA PEL (1993-06-30) PEL: Permissible Exposure Level 3.5 mg/m3 NIOSH REL (1994-06-01) Time Weighted Average (TWA) 3.5 mg/m3 Time Weighted Average (TWA) ACGIH TLV (2010-12-06) TLV-TWA: Threshold Limit Value - Time weighted average PEI Permissible Exposure Level 3 mg/m3 Form: Inhalable fraction  2-(2-Hydroxy-5-tert- octylphenyl)benzotriazole  1,6-Hexanediamine, N,N'-bis(2,2,6,6- tetramethyl-4-piperidinyl)-, polymer with 2,4-dichloro-6-(4-morpholinyl)-1,3,5- triazine  Titanium dioxide  OSHA PEL 1989 (1989-03-01)	Carbon black	
PEL: Permissible Exposure Level 3.5 mg/m3 NIOSH REL (1994-06-01) Time Weighted Average (TWA) 3.5 mg/m3 Time Weighted Average (TWA) ACGIH TLV (2010-12-06) TLV-TWA: Threshold Limit Value - Time weighted average PEI Permissible Exposure Level 3 mg/m3 Form: Inhalable fraction  2-(2-Hydroxy-5-tert- octylphenyl)benzotriazole  1,6-Hexanediamine, N,N'-bis(2,2,6,6- tetramethyl-4-piperidinyl)-, polymer with 2,4-dichloro-6-(4-morpholinyl)-1,3,5- triazine  Titanium dioxide  OSHA PEL 1989 (1989-03-01)		
NIOSH REL (1994-06-01) Time Weighted Average (TWA) 3.5 mg/m3 Time Weighted Average (TWA) ACGIH TLV (2010-12-06) TLV-TWA: Threshold Limit Value - Time weighted average PEI Permissible Exposure Level 3 mg/m3 Form: Inhalable fraction  2-(2-Hydroxy-5-tert- octylphenyl)benzotriazole  1,6-Hexanediamine, N,N'-bis(2,2,6,6- tetramethyl-4-piperidinyl)-, polymer with 2,4-dichloro-6-(4-morpholinyl)-1,3,5- triazine  Titanium dioxide  OSHA PEL 1989 (1989-03-01)		
Time Weighted Average (TWA) 3.5 mg/m3 Time Weighted Average (TWA) ACGIH TLV (2010-12-06) TLV-TWA: Threshold Limit Value - Time weighted average PEI Permissible Exposure Level 3 mg/m3 Form: Inhalable fraction  2-(2-Hydroxy-5-tert- octylphenyl)benzotriazole  1,6-Hexanediamine, N,N'-bis(2,2,6,6- tetramethyl-4-piperidinyl)-, polymer with 2,4-dichloro-6-(4-morpholinyl)-1,3,5- triazine  Titanium dioxide  OSHA PEL 1989 (1989-03-01)		
Time Weighted Average (TWA) ACGIH TLV (2010-12-06) TLV-TWA: Threshold Limit Value - Time weighted average PEI Permissible Exposure Level 3 mg/m3 Form: Inhalable fraction  2-(2-Hydroxy-5-tert- octylphenyl)benzotriazole  1,6-Hexanediamine, N,N'-bis(2,2,6,6- tetramethyl-4-piperidinyl)-, polymer with 2,4-dichloro-6-(4-morpholinyl)-1,3,5- triazine  Titanium dioxide  OSHA PEL 1989 (1989-03-01)		
ACGIH TLV (2010-12-06) TLV-TWA: Threshold Limit Value - Time weighted average PEI Permissible Exposure Level 3 mg/m3 Form: Inhalable fraction  2-(2-Hydroxy-5-tert-octylphenyl)benzotriazole  1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetramethyl-4-piperidinyl)-, polymer with 2,4-dichloro-6-(4-morpholinyl)-1,3,5-triazine  Titanium dioxide  OSHA PEL 1989 (1989-03-01)		
TLV-TWA: Threshold Limit Value - Time weighted average PEI Permissible Exposure Level 3 mg/m3 Form: Inhalable fraction  2-(2-Hydroxy-5-tert-octylphenyl)benzotriazole  1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetramethyl-4-piperidinyl)-, polymer with 2,4-dichloro-6-(4-morpholinyl)-1,3,5-triazine  Titanium dioxide  OSHA PEL 1989 (1989-03-01)		
Permissible Exposure Level 3 mg/m3 Form: Inhalable fraction  2-(2-Hydroxy-5-tert- octylphenyl)benzotriazole  1,6-Hexanediamine, N,N'-bis(2,2,6,6- tetramethyl-4-piperidinyl)-, polymer with 2,4-dichloro-6-(4-morpholinyl)-1,3,5- triazine  Titanium dioxide  OSHA PEL 1989 (1989-03-01)		
2-(2-Hydroxy-5-tert-octylphenyl)benzotriazole  1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetramethyl-4-piperidinyl)-, polymer with 2,4-dichloro-6-(4-morpholinyl)-1,3,5-triazine  Titanium dioxide  OSHA PEL 1989 (1989-03-01)		
1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetramethyl-4-piperidinyl)-, polymer with 2,4-dichloro-6-(4-morpholinyl)-1,3,5-triazine  Titanium dioxide  OSHA PEL 1989 (1989-03-01)		Permissible Exposure Level 3 mg/m3 Form: Inhalable fraction
1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetramethyl-4-piperidinyl)-, polymer with 2,4-dichloro-6-(4-morpholinyl)-1,3,5-triazine  Titanium dioxide  OSHA PEL 1989 (1989-03-01)	2 (2 11 1 5	
1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetramethyl-4-piperidinyl)-, polymer with 2,4-dichloro-6-(4-morpholinyl)-1,3,5-triazine  Titanium dioxide  OSHA PEL 1989 (1989-03-01)		
tetramethyl-4-piperidinyl)-, polymer with 2,4-dichloro-6-(4-morpholinyl)-1,3,5- triazine  Titanium dioxide  OSHA PEL 1989 (1989-03-01)	octylpnenyl)benzotriazole	
tetramethyl-4-piperidinyl)-, polymer with 2,4-dichloro-6-(4-morpholinyl)-1,3,5- triazine  Titanium dioxide  OSHA PEL 1989 (1989-03-01)		
tetramethyl-4-piperidinyl)-, polymer with 2,4-dichloro-6-(4-morpholinyl)-1,3,5- triazine  Titanium dioxide  OSHA PEL 1989 (1989-03-01)	1.6 Hamanadiamina NINULIA (2.2.6.6	
2,4-dichloro-6-(4-morpholinyl)-1,3,5- triazine  Titanium dioxide  OSHA PEL 1989 (1989-03-01)		
triazine Titanium dioxide OSHA PEL 1989 (1989-03-01)		
Titanium dioxide <b>OSHA PEL 1989 (1989-03-01)</b>	1 .	
		OCITA DEL 1000 (1000 03 01)
PHI: Permissible Hypositre Level III ma/m3 Horm: Total dust	I itanium dioxide	
		PEL: Permissible Exposure Level 10 mg/m3 Form: Total dust
OSHA PEL (1993-06-30)		
PEL: Permissible Exposure Level 15 mg/m3 Form: Total dust		
NIOSH REL (1994-06-01)		NIOSH REL (1994-06-01)



# DK GRAY UV

Version Number 1.0 Revision Date 12/01/2017 Page 7 of 19 Print Date 11/19/2018

		ACGIH TLV (1996-05-18) TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 10 mg/m3
2-Propenenitrile, polymer with Ethenylbenzene		
Appropriate engineering controls	:	Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
<u>Individual protection measures</u>		
Hygiene measures  Eye/face protection	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.  Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a
Skin protection		higher degree of protection: safety glasses with side-shields.
Hand protection		Chemical-resistant, impervious gloves complying with an approved
riand protection	:	standard should be worn at all times when handling chemical products
Body protection	:	if a risk assessment indicates this is necessary.  Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be
Other skin protection	:	approved by a specialist before handling this product.  Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this
Respiratory protection	:	product.  Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper

used according to a respiratory protection program to ensure proper



## DK GRAY UV

Version Number 1.0 Page 8 of 19 Revision Date 12/01/2017 Print Date 11/19/2018

fitting, training, and other important aspects of use.

# Section 9. Physical and chemical properties

#### **Appearance**

solid [Pellets.] Physical state Color **GREY** Odor Faint odor. **Odor threshold** Not available. Not available. **Melting point** Not available. **Boiling point** Not available. Not available. Flash point **Burning time** Not available. **Burning rate** Not available. **Evaporation rate** Not available. Flammability (solid, gas) Not available.

Lower and upper explosive : Lower: Not available. (flammable) limits : Upper: Not available.

Vapor pressure: Not available.Vapor density: Not available.Relative density: Not available.Solubility: Not available.Solubility in water: insoluble in water.

**Partition coefficient: n-** : Not available.

octanol/water

Auto-ignition temperature: Not available.Decomposition temperature: Not available.SADT: Not available.

Viscosity : Dynamic: Not available.

Kinematic: Not available.

# Section 10. Stability and reactivity

**Reactivity**: No specific test data related to reactivity available for this product or

its ingredients.

Chemical stability : Stable under recommended storage and handling conditions (see

Section 7).

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will

not occur

**Conditions to avoid** : Keep away from extreme heat and oxidizing agents.

**Incompatible materials** : Keep away from strong acids.



DK GRAY UV

Version Number 1.0 Revision Date 12/01/2017 Page 9 of 19 Print Date 11/19/2018

Oxidizer.

Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# Section 11. Toxicological information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

### **Information on toxicological effects**

### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure	
Styrene					
	LD50 Oral	Rat	2,650 mg/kg	=	
	LC50 Inhalation	Rat	2,770 ppm	4 h	
	LC50 Inhalation	Rat	11.8 Mg/l	4 h	
Remarks - Dermal:	No applicable toxicity data				
Carbon black					
	LD50 Oral	Rat	15,400 mg/kg	-	
Remarks - Inhalation:	No applicable toxic	city data			
Remarks - Dermal:	No applicable toxic	city data			
2-(2-Hydroxy-5-tert-octylphen	yl)benzotriazole				
	LD50 Oral	Rat	1,000 mg/kg	-	
Remarks - Inhalation:	No applicable toxicity data				
Remarks - Dermal:	No applicable toxicity data				
1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetramethyl-4-piperidinyl)-, polymer with 2,4-dichloro-6-(4-morpholinyl)-					
1,3,5-triazine					
Remarks - Oral:		No applicable toxicity data			
	LC50 Inhalation	Rat	2.79 Mg/l	4 h	
Remarks - Dermal:	- Dermal: No applicable toxicity data				
Titanium dioxide					
Remarks - Oral:	No applicable toxicity data				
	LC50 Inhalation	Rat - Male	6.82 Mg/l	4 h	
	LD50 Dermal	Rabbit	> 5,000 mg/kg	-	
2-Propenenitrile, polymer with Ethenylbenzene					
	LD50 Oral	Rat	1,800 mg/kg	-	
Remarks - Inhalation:	No applicable toxic	city data			
Remarks - Dermal:	No applicable toxic	city data	·	·	
Conclusion/Summary	• Mixtu	re Not fully tested		·	

**Conclusion/Summary** : Mixture.Not fully tested.

#### **Irritation/Corrosion**



## DK GRAY UV

Version Number 1.0 Revision Date 12/01/2017 Page 10 of 19 Print Date 11/19/2018

Product/ingredient name	Result	Species	Score	Exposure	Observation
Styrene	Eyes - Mild	Human			-
	irritant				
	Skin - Mild	Rabbit			-
	irritant				
	Skin -	Rabbit			-
	Moderate				
	irritant				
	Eyes - Severe	Rabbit			-
	irritant				
	Eyes -	Rabbit		24 hrs	-
	Moderate				
	irritant				
Titanium dioxide	Skin - Mild	Human		72 hrs	-
	irritant				

Conclusion/Summary

Skin: Mixture.Not fully tested.Eyes: Mixture.Not fully tested.Respiratory: Mixture.Not fully tested.

### **Sensitization**

Conclusion/Summary

Skin: Mixture.Not fully tested.Respiratory: Mixture.Not fully tested.

**Mutagenicity** 

**Conclusion/Summary** : Mixture.Not fully tested.

Carcinogenicity

Conclusion/Summary : Mixture.Not fully tested.

Classification

Classification			
Product/ingredient	OSHA	IARC	NTP
name			
Styrene		2B	Reasonably anticipated to be a human carcinogen.
Carbon black		2B	
Titanium dioxide		2B	
2-Propenenitrile, polymer		3	
with Ethenylbenzene			

## **Reproductive toxicity**



## DK GRAY UV

Version Number 1.0 Page 11 of 19 Revision Date 12/01/2017 Print Date 11/19/2018

**Conclusion/Summary** : Mixture.Not fully tested.

**Teratogenicity** 

**Conclusion/Summary** : Mixture.Not fully tested.

**Specific target organ toxicity (single exposure)** 

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

**Aspiration hazard** 

Not available.

Information on likely routes of

exposure

Not available.

Potential acute health effects

Eye contact: No known significant effects or critical hazards.Inhalation: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact: No specific data.Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Short term exposure** 

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

**Potential chronic health effects** 



## DK GRAY UV

Version Number 1.0 Page 12 of 19 Revision Date 12/01/2017 Print Date 11/19/2018

**Conclusion/Summary** : Mixture. Not fully tested.

General:No known significant effects or critical hazards.Carcinogenicity:No known significant effects or critical hazards.Mutagenicity:No known significant effects or critical hazards.Teratogenicity:No known significant effects or critical hazards.Developmental effects:No known significant effects or critical hazards.Fertility effects:No known significant effects or critical hazards.

#### Numerical measures of toxicity

### **Acute toxicity estimates**

Not available.

# Section 12. Ecological information

### **Toxicity**

Product/ingredient name	Result	Species	Exposure
Styrene			
	Acute LC50 4.02 Mg/l Fresh water	Fish - Fish	96 h
Remarks - Acute - Fish:	Acute		
	Acute EC50 0.0047 Mg/l Fresh water	Aquatic invertebrates.  Daphnia	48 h
Domonto Agustia		Барина	
Remarks - Acute - Aquatic invertebrates.:	Acute		
	Acute LC50 52 Mg/l Marine water	Aquatic invertebrates. Crustaceans	48 h
Remarks - Acute - Aquatic invertebrates.:	Acute		
	Acute EC50 1.4 Mg/l Fresh water	Aquatic plants - Algae	72 h
Remarks - Acute - Aquatic plants:	Acute		
•	Acute EC50 0.72 Mg/l Fresh water	Aquatic plants - Algae	96 h
Remarks - Acute - Aquatic plants:	Acute		
•	Acute NOEC 0.063 Mg/l Fresh water	Aquatic plants - Algae	96 h
Remarks - Acute - Aquatic plants:	Chronic		
Remarks - Chronic - Fish:	No applicable toxicity data		



# DK GRAY UV

Version Number 1.0 Revision Date 12/01/2017 Page 13 of 19 Print Date 11/19/2018

	NY 12 11 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			
Remarks - Chronic -	No applicable toxicity data			
Aquatic invertebrates.:				
Carbon black				
Remarks - Acute - Fish:	No applicable toxicity data	T	1	
	Acute EC50 37.563 Mg/l Fresh	Aquatic invertebrates.	48 h	
	water	Daphnia		
Remarks - Acute - Aquatic	Acute			
invertebrates.:				
Remarks - Acute - Aquatic	No applicable toxicity data			
plants:				
Remarks - Chronic - Fish:	No applicable toxicity data			
Remarks - Chronic -	No applicable toxicity data			
Aquatic invertebrates.:				
2-(2-Hydroxy-5-tert-octylphen	yl)benzotriazole			
Remarks - Acute - Fish:	No applicable toxicity data			
Remarks - Acute - Aquatic	No applicable toxicity data			
invertebrates.:	,			
Remarks - Acute - Aquatic	No applicable toxicity data			
plants:	,			
Remarks - Chronic - Fish:	No applicable toxicity data			
Remarks - Chronic -	No applicable toxicity data			
Aquatic invertebrates.:				
	2,2,6,6-tetramethyl-4-piperidinyl)-, po	lymer with 2,4-dichloro-6-	(4-morpholinyl)-	
1,3,5-triazine	3 11 3771	,	\ 1 3/	
Remarks - Acute - Fish:	No applicable toxicity data			
Remarks - Acute - Aquatic	No applicable toxicity data			
invertebrates.:	7			
Remarks - Acute - Aquatic	No applicable toxicity data			
plants:	and approximate the second second			
Remarks - Chronic - Fish:	No applicable toxicity data			
Remarks - Chronic -	No applicable toxicity data			
Aquatic invertebrates.:	The approache territory and			
Titanium dioxide				
	Acute LC50 > 1,000 Mg/l Marine	Fish - Fish	96 h	
	water			
Remarks - Acute - Fish:	Acute		1	
	Acute LC50 3 Mg/l Fresh water	Aquatic invertebrates.	48 h	
	Troute Bees e magniness water	Crustaceans	.01	
Remarks - Acute - Aquatic	Acute	Crustuceuns		
invertebrates.:	Teate			
mver testates.	Acute LC50 6.5 Mg/l Fresh water	Aquatic invertebrates.	48 h	
		Daphnia		
Remarks - Acute - Aquatic	Acute	- ap		
invertebrates.:				
AIL TO TOWN AUTON	13/19			
	12/10			



## DK GRAY UV

Version Number 1.0 Revision Date 12/01/2017 Page 14 of 19 Print Date 11/19/2018

Remarks - Acute - Aquatic	No applicable toxicity data
plants:	
Remarks - Chronic - Fish:	No applicable toxicity data
Remarks - Chronic -	No applicable toxicity data
Aquatic invertebrates.:	
2-Propenenitrile, polymer with	Ethenylbenzene
Remarks - Acute - Fish:	No applicable toxicity data
Remarks - Acute - Aquatic	No applicable toxicity data
invertebrates.:	
Remarks - Acute - Aquatic	No applicable toxicity data
plants:	
Remarks - Chronic - Fish:	No applicable toxicity data
Remarks - Chronic -	No applicable toxicity data
Aquatic invertebrates.:	
DK GRAY UV	
Remarks - Acute - Aquatic	Chemicals are not readily available as they are bound within the polymer matrix.
invertebrates.:	

**Conclusion/Summary** 

: Chemicals are not readily available as they are bound within the

polymer matrix.

#### Persistence and degradability

**Conclusion/Summary** : Chemicals are not readily available as they are bound within the

polymer matrix.

**Conclusion/Summary** : Chemicals are not readily available as they are bound within the

polymer matrix.

### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Benzene, ethenyl-	0.35	13.49	low

### **Mobility in soil**

**Soil/water partition coefficient** 

Not available.

(KOC)

Other adverse effects : No known significant effects or critical hazards.

# Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimized wherever



### DK GRAY UV

Version Number 1.0 Revision Date 12/01/2017 Page 15 of 19 Print Date 11/19/2018

possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

# Section 14. Transport information

U.S.DOT 49CFR Ground/Air/Water : Not regulated for transportation.

International Air ICAO/IATA

: Not classified as dangerous goods under transport regulations.

International Water IMO/IMDG

: Not classified as dangerous goods under transport regulations.

## **Section 15. Regulatory information**

**U.S. Federal regulations** 

United States - TSCA 12(b) - Chemical export notification: None of the components are listed

of the components are listed.

United States - TSCA 4(a) - Final Test Rules: Not listed United States - TSCA 4(a) - ITC Priority list: Not listed United States - TSCA 4(a) - Proposed test rules: Not listed United States - TSCA 4(f) - Priority risk review: Not listed United States - TSCA 5(a)? Final significant new was rules

United States - TSCA 5(a)2 - Final significant new use rules: Not

listed

United States - TSCA 5(a)2 - Proposed significant new use rules:

Not listed

**United States - TSCA 5(e) - Substances consent order:** Not listed **United States - TSCA 6 - Final risk management:** Not listed



DK GRAY UV

Version Number 1.0 Revision Date 12/01/2017

Page 16 of 19 Print Date 11/19/2018

United States - TSCA 6 - Proposed risk management: Not listed United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined

United States - TSCA 8(a) - Preliminary assessment report (PAIR): Not listed

United States - TSCA 8(c) - Significant adverse reaction (SAR): Not listed

United States - TSCA 8(d) - Health and safety studies: Not listed United States - EPA Clean water act (CWA) section 307 - Priority pollutants: Listed Rutile, antimony chromium buff

Acrylonitrile

United States - EPA Clean water act (CWA) section 311 -

Hazardous substances: Listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Flammable substances: Not listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Toxic substances: Not listed

**United States - Department of commerce - Precursor chemical:** 

Not listed

Clean Air Act Section 112(b)

Hazardous Air Pollutants (HAPs)

Clean Air Act Section 602 Class I

**Substances** 

Clean Air Act Section 602 Class II

**Substances** 

**DEA List I Chemicals (Precursor** Chemicals)

**Chemicals**)

Listed

Not listed

Not listed

Not listed

**DEA List II Chemicals (Essential** Not listed

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

**SARA 311/312** 

Classification Not applicable.

Composition/information on ingredients

Name	%	Classification
Styrene	0 - 0.3	F, AH, CH



## DK GRAY UV

Version Number 1.0 Page 17 of 19 Revision Date 12/01/2017 Print Date 11/19/2018

Carbon black	0 - 3	СН
2-(2-Hydroxy-5-tert- octylphenyl)benzotriazole	5 - 10	AH
1,6-Hexanediamine, N,N'- bis(2,2,6,6-tetramethyl-4- piperidinyl)-, polymer with 2,4- dichloro-6-(4-morpholinyl)-1,3,5- triazine	5 - 10	АН
Titanium dioxide	10 - 25	СН
2-Propenenitrile, polymer with Ethenylbenzene	50 - 75	AH

#### **SARA 313**

	Product name	CAS number	%
Form R - Reporting	Styrene	100-42-5	0 - 0.3
requirements			
	Rutile, antimony chromium	68186-90-3	0 - 3
	buff		
Supplier notification	Styrene	100-42-5	0 - 0.3
	Rutile, antimony chromium	68186-90-3	0 - 3
	buff		

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

**State regulations** 

MassachusettsNone of the components are listed.New YorkThe following components are listed:

Styrene

**New Jersey**: The following components are listed:

2-Propenenitrile, polymer with Ethenylbenzene

Titanium dioxide Carbon black

Rutile, antimony chromium buff

Iron oxide Styrene

**Pennsylvania** : The following components are listed:

Titanium dioxide

Carbon black



## DK GRAY UV

Version Number 1.0 Revision Date 12/01/2017 Page 18 of 19 Print Date 11/19/2018

Rutile, antimony chromium buff

Iron oxide

Styrene

#### California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

United States inventory (TSCA 8b) : All components are listed or exempted.

**Canada inventory** : All components are listed or exempted.

#### **International regulations**

#### **Inventory list**

AustraliaAll components are listed or exempted.CanadaAll components are listed or exempted.ChinaAll components are listed or exempted.Europe inventoryAll components are listed or exempted.

Japan : Not determined.

New Zealand
Philippines
All components are listed or exempted.
Republic of Korea
All components are listed or exempted.

Turkey : Not determined.

United States : All components are listed or exempted.

## Section 16. Other information

#### **Hazardous Material Information System (U.S.A.)**

Health	/	0
Flammability		0
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on



### DK GRAY UV

Version Number 1.0 Page 19 of 19 Revision Date 12/01/2017 Print Date 11/19/2018

HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

**History** 

Date of printing: 11/19/2018Date of issue/Date of revision: 12/01/2017Date of previous issue: 00/00/0000

Version : 1.0

**Key to abbreviations** : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of

Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine

pollution)

UN = United Nations

**References** : Not available.

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.