

FOAM ADDITIVE 72 (FA-72)

Version Number 1.1 Revision Date 02/27/2017 Page 1 of 20 Print Date 02/28/2017

SAFETY DATA SHEET

FOAM ADDITIVE 72 (FA-72)

Section 1. Identification

GHS product identifier : FOAM ADDITIVE 72 (FA-72)

Chemical name: MixtureCAS number: MixtureOther means of identification: CC10229168Product type: liquid

Relevant identified uses of the substance or mixture and uses advised against

Product use : Industrial applications. Plastics.

Supplier's details : POLYONE CORPORATION

ColorMatrix Group Inc.

680 North Rocky River Drive, Berea, Ohio, 44017-1628, USA

+1 216 622 0100

Emergency telephone number (with hours of operation)

CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or

accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard

Communication Standard (29 CFR 1910.1200).

Classification of the substance or

mixture

SKIN CORROSION/IRRITATION - Category 2

SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A

RESPIRATORY SENSITIZATION - Category 1

SKIN SENSITIZATION - Category 1

GERM CELL MUTAGENICITY - Category 2



FOAM ADDITIVE 72 (FA-72)

Version Number 1.1 Revision Date 02/27/2017

Page 2 of 20 Print Date 02/28/2017

GHS label elements

Hazard pictograms

Signal word

Hazard statements Causes serious eve irritation.

Causes skin irritation.

May cause allergy or asthma symptoms or breathing difficulties if

inhaled.

May cause an allergic skin reaction. Suspected of causing genetic defects.

Precautionary statements

General Not applicable.

Obtain special instructions before use. Do not handle until all safety **Prevention**

> precautions have been read and understood. Use personal protective equipment as required. Wear protective gloves. Wear eye or face protection. In case of inadequate ventilation wear respiratory protection. Avoid breathing vapor. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of

the workplace.

IF exposed or concerned: Get medical attention. IF INHALED: If Response

breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER or physician. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. If eye irritation persists: Get medical

attention.

Store in a well-ventilated place. Storage **Disposal**

Dispose of contents and container in accordance with all local,

regional, national and international regulations.

Supplemental label elements None known. Hazards not otherwise classified None known.

Section 3. Composition/information on ingredients



FOAM ADDITIVE 72 (FA-72)

Page 3 of 20 Version Number 1.1 Print Date 02/28/2017 Revision Date 02/27/2017

Substance/mixture Mixture Chemical name Mixture Other means of identification CC10229168

CAS number/other identifiers

Ingredient name	%	CAS number
Azodicarbonamide	10 - 30	123-77-3
Miscellaneous Compounds Distillates, petroleum, hydrotreated middle	10 - 30	Not available.
Sodium bicarbonate	10 - 30	144-55-8
Diphenyloxide-4,4'-disulfohydrazide	5 - 10	80-51-3
Zinc oxide	1 - 5	1314-13-2
Calcium oxide	1 - 5	1305-78-8

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses.
	Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable
	for breathing. If it is suspected that fumes are still present, the rescuer
	should wear an appropriate mask or self-contained breathing
	apparatus. If not breathing, if breathing is irregular or if respiratory
	arrest occurs, provide artificial respiration or oxygen by trained
_	3/20



FOAM ADDITIVE 72 (FA-72)

Version Number 1.1 Revision Date 02/27/2017

Skin contact

Page 4 of 20 Print Date 02/28/2017

personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. In the event of any complaints or

symptoms, avoid further exposure.

Wash with plenty of soap and water. Remove contaminated clothing

and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes

thoroughly before reuse.

Wash out mouth with water. Remove dentures if any. Remove victim **Ingestion**

to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing

such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact Causes serious eye irritation.

Inhalation May cause allergy or asthma symptoms or breathing difficulties if

inhaled. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Ingestion Irritating to mouth, throat and stomach.

Over-exposure signs/symptoms

Adverse symptoms may include the following: Eye contact

pain or irritation

watering redness

Inhalation Adverse symptoms may include the following:

wheezing and breathing difficulties



FOAM ADDITIVE 72 (FA-72)

Version Number 1.1 Revision Date 02/27/2017 Page 5 of 20 Print Date 02/28/2017

asthma

Skin contact: Adverse symptoms may include the following:

irritation redness

Ingestion : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms

may be delayed. The exposed person may need to be kept under

medical surveillance for 48 hours.

Specific treatments : No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without

suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media In case of fire, use water spray (fog), foam, dry chemical or CO_2 .

: None known.

Specific hazards arising from the

chemical
Hazardous thermal
decomposition products

In a fire or if heated, a pressure increase will occur and the container

may burst.

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide nitrogen oxides sulfur oxides metal oxide/oxides

Special protective actions for fire-

fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any

personal risk or without suitable training.

Special protective equipment for

fire-fighters

Fire-fighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece operated

in positive pressure mode.



FOAM ADDITIVE 72 (FA-72)

Version Number 1.1 Revision Date 02/27/2017 Page 6 of 20 Print Date 02/28/2017

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without

suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is

inadequate. Put on appropriate personal protective equipment.

For emergency responders

: If specialized clothing is required to deal with the spillage, take

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

See also the information in "For non-emergency personnel".

Environmental precautions: Avoid dispersal of spilled material and runoff and contact with soil,

waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil

or air).

Methods and materials for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Dilute with

water and mop up if water-soluble. Alternatively, or if waterinsoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal

contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Approach

release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency

contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures: Put on appropriate personal protective equipment (see Section 8).

Persons with a history of skin sensitization problems or asthma, allergies or chronic or recurrent respiratory disease should not be

6/20



FOAM ADDITIVE 72 (FA-72)

Version Number 1.1 Revision Date 02/27/2017 Page 7 of 20 Print Date 02/28/2017

Advice on general occupational hygiene

employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a well-ventilated place. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits		
Diphenyloxide-4,4'-disulfohydrazide	ACGIH TLV (2000-03-01)		
	TLV-TWA: Threshold Limit Value - Time weighted average PEL:		
	Permissible Exposure Level 0.1 mg/m3 Form: Inhalable fraction		
Zinc oxide	OSHA PEL 1989 (1989-03-01)		
Zific Oxide	,		
	PEL: Permissible Exposure Level 5 mg/m3 Form: Fume		
	Maximum permissible limit of exposure in the short term (short-		
	term exposure limit). 10 mg/m3 Form: Fume		
	PEL: Permissible Exposure Level 10 mg/m3 Form: Total dust		
	PEL: Permissible Exposure Level 5 mg/m3 Form: Respirable		
	fraction		
	OSHA PEL (1993-06-30)		
	PEL: Permissible Exposure Level 5 mg/m3 Form: Fume		



FOAM ADDITIVE 72 (FA-72)

Version Number 1.1 Revision Date 02/27/2017 Page 8 of 20 Print Date 02/28/2017

	PEL: Permissible Exposure Level 15 mg/m3 Form: Total dust
	PEL: Permissible Exposure Level 5 mg/m3 Form: Respirable fraction
	1
	NIOSH REL (1994-06-01) Time Weighted Average (TWA) 5 mg/m ² . Form: Dust and fumes
	Time Weighted Average (TWA) 5 mg/m3 Form: Dust and fumes Maximum permissible limit of exposure in the short term (short-
	term exposure limit). 10 mg/m3 Form: Fume
	Maximum permissible level of exposure peak. 15 mg/m3 Form:
	Dust
	ACGIH TLV (2003-01-01)
	TLV-TWA: Threshold Limit Value - Time weighted average PEL:
	Permissible Exposure Level 2 mg/m3 Form: Respirable fraction
	TLV-STEL: Threshold Limit Value - Short Time Exposure Level
	10 mg/m3 Form: Respirable fraction
	To mg mo Torm. Respirable fraction
Calcium oxide	OSHA PEL 1989 (1989-03-01)
	PEL: Permissible Exposure Level 5 mg/m3
	OSHA PEL (1993-06-30)
	PEL: Permissible Exposure Level 5 mg/m3
	NIOSH REL (1994-06-01)
	Time Weighted Average (TWA) 2 mg/m3
	ACGIH TLV (1994-09-01)
	TLV-TWA: Threshold Limit Value - Time weighted average PEL:
	Permissible Exposure Level 2 mg/m3
_	ı

Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end

of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations

and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used



FOAM ADDITIVE 72 (FA-72)

Version Number 1.1 Revision Date 02/27/2017 Page 9 of 20 Print Date 02/28/2017

when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section 9. Physical and chemical properties

Appearance

Physical state : liquid [liquid]
Color : NOT APPLICABLE

Odor Faint odor. **Odor threshold** Not available. Not available. pН **Melting point** Not available. **Boiling point** Not available. Flash point Not available. **Burning** time Not available. **Burning rate** Not available. **Evaporation rate** Not available. Flammability (solid, gas) Not available.



FOAM ADDITIVE 72 (FA-72)

Version Number 1.1 Page 10 of 20 Revision Date 02/27/2017 Print Date 02/28/2017

Lower and upper explosive : Lower: Not available. (flammable) limits : Upper: Not available.

Vapor pressure: Not available.Vapor density: Not available.Relative density: Not available.Solubility: Not available.Solubility in water: insoluble in water.

Partition coefficient: n-

octanol/water

: Not available.

Auto-ignition temperature: Not available.Decomposition temperature: Not available.SADT: Not available.

Viscosity : Dynamic: Not available.

Kinematic: Not available.

Section 10. Stability and reactivity

Reactivity: No specific test data related to reactivity available for this product or

its ingredients.

Chemical stability : Stable under recommended storage and handling conditions (see

Section 7).

Possibility of hazardous reactions: Under normal conditions of storage and use, hazardous reactions will

not occur.

Conditions to avoid : Keep away from extreme heat and oxidizing agents.

Incompatible materials : Keep away from strong acids.

Oxidizer.

Hazardous decomposition: Under normal conditions of storage and use, hazardous decomposition

products should not be produced.

Section 11. Toxicological information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Information on toxicological effects

Acute toxicity

products

Product/ingredient name	Result	Species	Dose	Exposure	
Azodicarbonamide					
	LD50 Oral	Rat	6,400 mg/kg	-	
Miscellaneous Compounds Distillates, petroleum, hydrotreated middle					
Sodium bicarbonate					



FOAM ADDITIVE 72 (FA-72)

Version Number 1.1 Revision Date 02/27/2017 Page 11 of 20 Print Date 02/28/2017

	LD50 Oral	Rat	4,220 mg/kg	-
Diphenyloxide-4,4'-disulfohyd	lrazide			
	LD50 Oral	Rat	2,300 mg/kg	=
Zinc oxide				
Calcium oxide				

Conclusion/Summary: Mixture.Not fully tested.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Sodium bicarbonate	Eyes - Mild irritant	Rabbit		0.008 hrs	-
	Skin - Mild irritant	Human		72 hrs	-
Zinc oxide	Eyes - Mild irritant	Rabbit		24 hrs	-
	Skin - Mild irritant	Rabbit		24 hrs	-

Conclusion/Summary

Skin: Mixture.Not fully tested.Eyes: Mixture.Not fully tested.Respiratory: Mixture.Not fully tested.

Sensitization

Conclusion/Summary

Skin: Mixture.Not fully tested.Respiratory: Mixture.Not fully tested.

Mutagenicity

Conclusion/Summary : Mixture.Not fully tested.

Carcinogenicity

Conclusion/Summary : Mixture.Not fully tested.

Reproductive toxicity

Conclusion/Summary : Mixture.Not fully tested.

Teratogenicity

Conclusion/Summary : Mixture. Not fully tested.



FOAM ADDITIVE 72 (FA-72)

Version Number 1.1 Page 12 of 20 Revision Date 02/27/2017 Print Date 02/28/2017

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Calcium oxide	Category 3		Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Product/ingredient name	Result
Miscellaneous Compounds Distillates, petroleum,	ASPIRATION HAZARD - Category 1
hydrotreated middle	

Information on likely routes of

exposure

Not available.

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : May cause allergy or asthma symptoms or breathing difficulties if

inhaled. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.

Skin contact : Causes skin irritation. May cause an allergic skin reaction.

Ingestion : Irritating to mouth, throat and stomach.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:

pain or irritation watering

redness

Inhalation : Adverse symptoms may include the following:

wheezing and breathing difficulties

asthma

Skin contact : Adverse symptoms may include the following:

irritation redness

Ingestion : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.



FOAM ADDITIVE 72 (FA-72)

Version Number 1.1 Revision Date 02/27/2017 Page 13 of 20 Print Date 02/28/2017

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Conclusion/Summary : Mixture.Not fully tested.

General : Once sensitized, a severe allergic reaction may occur when

subsequently exposed to very low levels.

Carcinogenicity: No known significant effects or critical hazards.

Mutagenicity : Suspected of causing genetic defects.

Teratogenicity : No known significant effects or critical hazards.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	6,350.7 mg/kg
Route	ATE value
Inhalation (dusts and mists)	6.185 mg/l

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure				
Sodium bicarbonate	Sodium bicarbonate						
	Acute LC50 8,600,000 μg/l Fresh	Fish - Fish	96 h				
	water						
	Acute LC50 8,600,000 μg/l Fresh	Fish - Fish	96 h				
	water						
	Acute LC50 8,600,000 μg/l Fresh	Fish - Fish	96 h				
	water						
	Acute LC50 8,250,000 μg/l Fresh	Fish - Fish	96 h				
	water						
	Acute LC50 7,550 mg/l Fresh	Fish - Fish	96 h				



FOAM ADDITIVE 72 (FA-72)

Version Number 1.1 Revision Date 02/27/2017 Page 14 of 20 Print Date 02/28/2017

	water		
	Acute LC50 767.87 mg/l Marine	Aquatic invertebrates.	48 h
	water	Crustaceans	
	Acute LC50 1,415.51 mg/l Marine	Aquatic invertebrates.	48 h
	water	Crustaceans	
	Acute EC50 650,000 μg/l Fresh	Aquatic plants - Algae	96 h
	water		
	Chronic NOEC 576 mg/l Fresh	Aquatic invertebrates.	21 d
	water	Daphnia	
	Chronic NOEC 576 mg/l Fresh	Aquatic invertebrates.	21 d
	water	Daphnia	
Zinc oxide			
	Acute LC50 2,246,000 μg/l Fresh	Fish - Fish	96 h
	water		
	Acute LC50 1.1 mg/l Fresh water	Fish - Fish	96 h
	Acute LC50 2.525 mg/l Fresh	Fish - Fish	96 h
	water		
	Acute LC50 3.969 mg/l Fresh	Fish - Fish	96 h
	water		
	Acute LC50 98 µg/l Fresh water	Aquatic invertebrates.	48 h
		Daphnia	
	Acute EC50 0.622 mg/l Fresh	Aquatic invertebrates.	48 h
	water	Daphnia	
	Acute EC50 1 mg/l Fresh water	Aquatic invertebrates. Daphnia	48 h
	Acute LC50 1.25 mg/l Fresh water	Aquatic invertebrates. Daphnia	48 h
	Acute EC50 0.481 mg/l Fresh water	Aquatic invertebrates. Daphnia	48 h
	Acute IC50 46 µg/l Fresh water	Aquatic plants - Algae	72 h
	Acute IC50 46 μg/I Fresh water Acute IC50 63 μg/I Fresh water	Aquatic plants - Algae Aquatic plants - Algae	72 h
	Acute IC50 03 µg/1 Flesh water Acute IC50 1.85 mg/l Marine water	Aquatic plants - Algae Aquatic plants - Algae	96 h
	Acute IC50 1.85 filg/1 Marine water Acute IC50 2.97 mg/l Marine water	Aquatic plants - Algae Aquatic plants - Algae	96 h
	Acute IC50 2.36 mg/l Marine water	Aquatic plants - Algae Aquatic plants - Algae	96 h
Calcium oxide	Acute 1030 2.30 mg/1 Marine Water	Aquatic plants - Aigae	70 11
Carcium Oxiue	Chronic NOEC 100 mg/l Fresh	Fish - Fish	46 d
		1 1511 - 1 1511	40 u
	Chronic NOEC 100 mg/l Fresh	Fish - Fish	46 d
	water	1 1311 - 1 1311	70 u
	Chronic NOEC 100 mg/l Fresh	Fish - Fish	46 d
	water	11011 11011	10 4
	Chronic NOEC 100 mg/l Fresh	Fish - Fish	46 d
	water	11011	100
	Chronic NOEC 100 mg/l Fresh	Fish - Fish	46 d
	water	2 2 3 1 1 1 1 1 1	1.0 %
	14/20	<u> </u>	1



FOAM ADDITIVE 72 (FA-72)

Version Number 1.1 Revision Date 02/27/2017 Page 15 of 20 Print Date 02/28/2017

FOAM ADDITIVE 72 (FA-72)

Remarks - Acute - Aquatic invertebrates.:

Dangerous for the environment: May cause long term adverse effects in the aquatic environment.

Conclusion/Summary

Dangerous for the environment: May cause long term adverse effects

in the aquatic environment.

Persistence and degradability

Conclusion/Summary : Not available.

Conclusion/Summary: Dangerous for the environment: May cause long term adverse effects

in the aquatic environment.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential		
Azodicarbonamide	1	-	low		
Diphenyloxide-4,4'-		3.00	low		
disulfohydrazide					
Zinc oxide		60,960.00	high		
Calcium oxide		2.34	low		

Mobility in soil

Soil/water partition coefficient

(KOC)

Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.



FOAM ADDITIVE 72 (FA-72)

Version Number 1.1 Revision Date 02/27/2017 Page 16 of 20 Print Date 02/28/2017

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

Section 14. Transport information

U.S. DOT Classification : Not regulated for transportation.

ICAO/IATA : UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE.

LIQUID, N.O.S. (Zinc Oxide), 9, PGIII, Marine Pollutant

IMO/IMDG (maritime) : UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE,

LIQUID, N.O.S. (Zinc Oxide), 9, PGIII, Marine Pollutant

Section 15. Regulatory information

U.S. Federal regulations : United States - TSCA 12(b) - Chemical export notification: None

of the components are listed.

United States - TSCA 4(a) - Final Test Rules: Not listed
United States - TSCA 4(a) - ITC Priority list: Not listed
United States - TSCA 4(a) - Proposed test rules: Not listed
United States - TSCA 4(f) - Priority risk review: Not listed
United States - TSCA 5(a)2 - Final significant new use rules: Not

listed

United States - TSCA 5(a)2 - Proposed significant new use rules:

Not listed

United States - TSCA 6 - Final risk management: Not listed
United States - TSCA 6 - Proposed risk management: Not listed
United States - TSCA 8(a) - Chemical risk rules: Not listed
United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed
United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not

determined

United States - TSCA 8(a) - Preliminary assessment report (PAIR): Listed Diphenyloxide-4,4'-disulfohydrazide

United States - TSCA 8(c) - Significant adverse reaction (SAR):

Not listed

United States - TSCA 8(d) - Health and safety studies: Not listed United States - TSCA 5(e) - Substances consent order: Not listed United States - EPA Clean water act (CWA) section 307 - Priority

pollutants: Listed Zinc oxide

United States - EPA Clean water act (CWA) section 311 -



FOAM ADDITIVE 72 (FA-72)

Version Number 1.1 Revision Date 02/27/2017

Page 17 of 20 Print Date 02/28/2017

Hazardous substances: Listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Flammable substances: Not listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Toxic substances: Not listed

United States - Department of commerce - Precursor chemical:

Not listed

Clean Air Act Section 112(b)

Hazardous Air Pollutants (HAPs)

Clean Air Act Section 602 Class I Not listed

Substances

Clean Air Act Section 602 Class II

Substances

DEA List I Chemicals (Precursor

Chemicals)

Chemicals)

Not listed

Not listed

Not listed

DEA List II Chemicals (Essential Not listed

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

SARA 311/312

Classification Immediate (acute) health hazard

Delayed (chronic) health hazard

Composition/information on ingredients

Name	0/0	Classification
Azodicarbonamide	10 - 30	AH
Miscellaneous Compounds	10 - 30	AH
Distillates, petroleum,		
hydrotreated middle		
Sodium bicarbonate	10 - 30	AH
Diphenyloxide-4,4'-	5 - 10	F, AH, CH
disulfohydrazide		
Zinc oxide	1 - 5	AH
Calcium oxide	1 - 5	AH

SARA 313



FOAM ADDITIVE 72 (FA-72)

Version Number 1.1 Revision Date 02/27/2017

Page 18 of 20 Print Date 02/28/2017

	Product name	CAS number	%
Form R - Reporting	Zinc oxide	1314-13-2	1 - 5
requirements			
Supplier notification	Zinc oxide	1314-13-2	1 - 5

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts The following components are listed:

Calcium carbonate

Zinc oxide Calcium oxide

New York None of the components are listed. **New Jersey**

The following components are listed:

Calcium carbonate

Diphenyloxide-4,4'-disulfohydrazide

Zinc oxide Calcium oxide

Pennsylvania The following components are listed:

Calcium carbonate

Zinc oxide

Calcium oxide

California Prop. 65

This PolyOne product does not contain any chemical known to the State of California to cause cancer, or birth defects or other reproductive harm, in concentrations that require a warning notice under California's Proposition 65. This statement relies in part on information provided by the buyer of this PolyOne product. PolyOne does not control or have complete knowledge of the end uses to which that buyer or any other entity in the chain of distribution and marketing may put this PolyOne product. Therefore, the buyer of this PolyOne product, each entity that uses this PolyOne product in formulating another product, and each entity in the chain of distribution and marketing of any product that includes the material in this PolyOne product must make its own decision as to giving a Proposition 65 warning.

United States inventory (TSCA 8b): All components are listed or exempted.

Canada inventory All components are listed or exempted.

International regulations

International lists Australia inventory (AICS): All components are listed or exempted.

Taiwan Chemical Substances Inventory (TCSI): Not determined.

Malaysia Inventory (EHS Register): Not determined.



FOAM ADDITIVE 72 (FA-72)

Version Number 1.1 Revision Date 02/27/2017 Page 19 of 20 Print Date 02/28/2017

EINECS: All components are listed or exempted.

Japan inventory: All components are listed or exempted.

China inventory (IECSC): All components are listed or exempted.

Korea inventory: All components are listed or exempted.

New Zealand Inventory of Chemicals (NZIoC): All components

are listed or exempted.

Philippines inventory (PICCS): All components are listed or

exempted.

Taiwan Chemical Substances Inventory (TCSI): Not determined.

Chemical Weapons Convention

List Schedule I Chemicals

Chemical Weapons Convention

List Schedule II Chemicals

Chemical Weapons Convention

List Schedule III Chemicals

Not listed

Not listed

Not listed

Section 16. Other information

History

Date of printing: 02/28/2017Date of issue/Date of revision: 02/27/2017Date of previous issue: 11/06/2015

Version : 1.1

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of

Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

 $\label{eq:marker} MARPOL = International \ Convention \ for \ the \ Prevention \ of \ Pollution \ From$

Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine

pollution)

UN = United Nations

References : Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other



FOAM ADDITIVE 72 (FA-72)

Version Number 1.1 Revision Date 02/27/2017 Page 20 of 20 Print Date 02/28/2017

materials or in any process, unless specified in the text.